### imageRUNNER ADVANCE C255i, C355i, C355iFC, C355P

# Intelligent, versatile Colour A4 multifunctional\* with flexible connectivity

The imageRUNNER ADVANCE C255/C355 series are A4 models but offer much of the functionality of larger departmental, A3 devices. Making them a great addition to any busy working groups who need a compact solution.

**Control costs:** 

- Technology designed to reduce total cost of print
- User activity tracking provides visibility of print behaviour
- Apply policies and restrict usage at function level by user\*
- Save on transmission costs by utilising the Fax over IP option\*
- Tight integration with output management solutions such as uniFLOW
- Remote diagnostics and assistance, help reduce costs by minimising downtime and time spent by IT resolving issues
- Remote and centralised fleet management simplifies IT management of devices and fleets

#### Support for Mobile Working:

- Connect to cloud storage to access documents online
- Secure mobile printing as standard
- Support for industry standards such as Apple Airprint<sup>®</sup> and Mopria<sup>®</sup>
- Enable guest printing with Direct Connection
- Supports a range of connection types with your smart device e.g. Optional Bluetooth
- Substitute your PC for your smart device to complete your day-to-day workflows
- Send data from your smart device to the imageRUNNER ADVANCE C255/C355 series and vice versa



PRINT

C355P is a printer only model



SCAN

Canon

Optional on all MFP Models

COPY

### Secure confidential information:

- Control who has access to the device with Award-winning, smart user authentication without impacting on user productivity or convenience
- Ability to disable functions by user to prevent unauthorised usage
- Secure Print and Mailbox enhance document confidentiality
- Ensure information privacy and security across your network with IPsec, port filtering capabilities, and SSL technology
- Prevent unauthorised distribution of sensitive information with an array of standard and optional document security features
- Industry-first Data Loss Prevention and auditing of prints, copies, scans and faxes through uniFLOW\*

#### Streamline document workflows:

- Intuitive user interface with a large, responsive colour touchscreen with smart phone-like usability
- Advanced personalisation enables a unique, personal experience tailored to meet each user's workflow needs.
- Effortless, rapid scanning captures paper-based documents with ease\*
- Scan and convert documents to Searchable PDF, Microsoft<sup>®</sup> Word, and Microsoft<sup>®</sup> PowerPoint files through a single-pass duplexing document feeder that holds up to 100 originals\*
- Time-saving automatic staple finishing option

#### Achieve stunning results:

- Robust design and engine, with up to 2,300 sheet paper capacity, perfect for handling workloads of busy workgroups
- V<sup>2</sup> (Vivid & Vibrant) imaging technology ensures documents impress time after time and stand out from the rest

\*C355P is a printer only model

### Manage devices efficiently:

- Suitable for small workgroups in either a desktop, or floor standing environment
- Supports industry and network standards i.e. PCL and Adobe PostScript for seamless integration
- Shares resources (e.g. Fax) with other imageRUNNER ADVANCE devices on the network\*
- Collaborates with business applications and external systems in the cloud
- Canon's MEAP platform provides process optimisation, by integrating with a range of powerful document, capture and output management solutions\*
- Canon's device management tools give you a centralised point of control across your entire fleet, upgrade devices, check device status and consumables, turn off devices remotely, capture meter readings, as well as manage address books and printer drivers
- Designed to achieve maximum uptime with intuitive user maintenance videos and status notifications, to help keep supplies replenished

### Environmentally responsible:

- Class leading Typical Electricity Consumption (TEC) ratings
- Consumes as little as 0.8W in sleep mode
- Incorporates sustainable design, with the use of recycled materials and bio-based plastic, and a focus on minimising environmental impact
- ENERGY STAR<sup>®</sup> qualified
- Qualifies for the stringent Blue Angel award (Not applicable for C355i/C355P model)
- Minimise waste with default 2-sided printing, secure printing, and the ability to hold print jobs, preview them and change print settings at the device, achieving the desired results at the first time of printing



# Canon

### **Main configuration options**

# Technical Specifications

### imageRUNNER ADVANCE C255i, C355i, C355iFC, C355P

Main Unit	Colour Learn Multility at 1	Operating System	UFRII: Windows Vista/Server 2008/7/Server 2008 R2/8/ Server 2012/8.1/Server 2012 R2/10/Server 2016, MAC OS X
Machine type	Colour Laser Multifunctional <sup>1</sup>		(10.6.8 or later) PCL: Windows Vista/Server 2008/7/Server 2008 R2/8/
Core functions	Print, Copy <sup>1</sup> , Scan <sup>1</sup> , Send <sup>1</sup> , Store and Fax <sup>2</sup>		Server 2012/8.1/Server 2012 R2/10/Server 2016
Processor Speed Control Panel	Canon Dual Custom Processor (Shared) 1.75 Ghz 25.6 cm (10.1 inch) TFT LCD WSVGA Colour Touch panel		PS: Windows Vista/Server 2008/7/Server 2008 R2/8/ Server 2012/8.1/Server 2012 R2/10/Server 2016, MAC OS X
Memory Standard	Standard: 3.0GB RAM		(10.6.8 or later)
Hard Disk drive	Standard: 250GB		PPD: MAC OS 9.1 or later, MAC OS X (10.3.9 or later), Windows Vista/7/8/8.1/10
Interface Connection	NETWORK Standard: 1000Base-T/100Base-TX/10Base-T, Wireless LAN (IEEE 802.11 b/g/n); Optional: NFC,		SAP Device Types are available via the SAP Market Place. Please refer to http://www.canon-europe.com/support/ business-product-support for availability of print solutions for
	Bluetooth Low Energy OTHERS Standard: USB 2.0 (Host) x1, USB 3.0 (Host) x1, USB 2.0 (Device) x1; Optional: Serial Interface, Copy Control Interface		other operating systems and environments including AS/400, UNIX, Linux and Citrix. Some of these solutions are chargeable.
Paper input (Standard)	iR-ADV C355P/C255i/C355i:	Comu Constituentional	-
	550-sheet cassettes (80gsm) 100-sheet multi-purpose tray (80gsm)	Copy Specifications <sup>1</sup> Copy Speed	iR-ADV C255i:
	iR-ADV C355iFC:		25 ppm (A4), 26 ppm (B5), 26 ppm (A5)
	4 x 550-sheet cassettes (80gsm)		<b>iR-ADV C355i/C355iFC:</b> 35 ppm (A4), 26 ppm (B5), 26 ppm (A5)
Paper input (Option for	100-sheet multi-purpose tray (80gsm) 550-sheet cassettes (80 gsm) (CASSETTE MODULE-AE1)	First-Copy-Out Time	iR-ADV C255i: Approx. 6.9/9.4 seconds or less
C255i/C355i/C355P)	550-sheet cassettes (80gsm) (CASSETTE FEEDING UNIT-AJ1) 3 x 550-sheet cassettes (80gsm) (CASSETTE FEEDING UNIT-	Copy resolution	iR-ADV C355i/C355iFC: Approx. 5.1/6.9 seconds or less Reading: 600 dpi x 600 dpi Printing: Up to 2.400 dpi equivalent x 600 dpi
Maximum paper input	AK1) 2,300 sheets (80 gsm)	Multiple Copies	Up to 999 copies
capacity		Magnification	25% - 400% (1% Increments)
Paper output capacity	Without Finisher: 250 Sheets (A4, 80 gsm) With Finisher: Max.500 sheets (A4, 80 gsm)	Preset Reductions	25%, 50%, 71%, 100%
Einishing capabilities	Collate. Group	Preset Enlargements	141%, 200%, 400%
Finishing capabilities	With External Finisher : Collate, Group, Offset, Staple	Scan Specifications <sup>1</sup>	
Supported media types	Cassette:	Standard type	Single-pass Duplexing Automatic Document Feeder
	Thin paper, Plain paper, Thick paper, Colour paper, Recycled paper, Pre-punched paper, Bond paper, Envelope*	Pull Scan Spec	Colour Network ScanGear2. For both TWAIN and WIA
	*Envelope supported via standard cassette 1 only Multi-purpose tray:	-	Supported OS: Windows Vista/7/8/8.1/10 Windows Server 2008/Server 2008 R2/Server 2012/ Server 2012 R2
	Thin paper, Plain paper, Thick paper, Colour paper, Recycled paper, Pre-punched paper, Transparency, Label, Bond paper,	Scan Resolution	100 x 100 dpi, 150 x 150 dpi, 200 x 100 dpi, 200 x 200 dpi,
	Envelope	Acceptable Originals	200 x 400 dpi, 300 x 300 dpi, 400 x 400 dpi, 600 x 600 dpi Platen media size: Sheet, Book, 3-Dimensional Objects
Supported media sizes	Cassette 1: Standard size: A4, B5, A5, Envelopes (No. 10(COM 10), Monarch,	Acceptable Originals	Document Feeder media size : A4, B5, A5, A6 Document Feeder media weight :
	ISO-C5, DL) Custom size: Min. 98 mm x 190.5 mm up to 216 mm x 355.6 mm		1-sided scanning: 50 to 128 gsm/64 to 128 gsm (BW/CL) 2-sided scanning: 50 to 128 gsm/64 to 128 gsm (BW/CL)
	Multi-purpose tray: Standard size: A4, B5, A5	Scan Method	Send functionality available on all models
	Custom Size: Min. 98 mm x 148 mm up to 216 mm x 355.6 mm		
	Envelopes: No.10 (COM10), Monarch, ISO-C5, DL Envelope custom size: 98 mm x 148 mm to 216 mm x 355.6 mm		Scan to USB Memory Key: Available on all models
	CASSETTE MODULE-AE1: Standard size: A4, B5, A5		Scan to Mobiles or internet-connected devices: A range of solutions is available to provide scanning to mobile devices or
	Custom size: Min. 98 mm x 190.5 mm up to 216 mm x 355.6 mm		internet-connected devices depending on your requirements.
	CASSETTE FEEDING UNIT-AJ1: Standard size: A4, B5, A5		Please contact your sales representative for further information Scan to cloud-based services: A range of solutions is available
	Custom size: Min. 98 mm x 190.5 mm up to 216 mm x 355.6 mm CASSETTE FEEDING UNIT-AK1: (Standard on the C355iFC model):		to provide scanning to cloud-based services depending on your requirements. Please contact your sales representative for further information
	Standard size: A4, B5, A5 Custom size: Min. 98 mm x 190.5 mm up to 216 mm x 355.6 mm		TWAIN/WIA Pull scanning available on all models
Supported media weights	Cassette:	Scan Speed (BW/CL; A4)	Single-sided Scanning (BW): 50 ipm (300 dpi x 300 dpi) /
	60 to 163 gsm		50 ipm (300 x 600 dpi) Single-sided Scanning (Colour): 50 ipm (300 dpi x 300 dpi) /
	Multi-purpose tray:		50 ipm (300 x 600 dpi)
	60 to 220 gsm		Double-sided Scanning (BW): 100 ipm (300 dpi x 300 dpi) / 100 ipm (300 x 600 dpi)
	Duplex: 60 to 163 gsm		Double-sided Scanning (Colour): 100 ipm (300 dpi x 300 dpi) / 100 ipm (300 dpi x 600 dpi)
Warm-up Time	From Power on: iR-ADV C255i 34 Seconds or Less <sup>3</sup>	Paper Capacity	100 Sheets (80 gsm)
	iR-ADV C355P/C355i/C355iFC: 30 Seconds	Double sided scanning	2-sided to 2-sided (Automatic)
	or Less <sup>3</sup>		
	From Sleep Mode: 10 Seconds or Less Quick Start-up Mode: iR-ADV C255i/C355i/C355iFC: 4 seconds	Send Specifications <sup>1</sup>	Chandrad an all MED madels
	or less <sup>4</sup>	Optional / Standard Destination	Standard on all MFP models E-mail/Internet FAX (SMTP), SMB, FTP, WebDAV, Mail Box,
Dimensions (W x D x H)	iR-ADV C355P: 511 mm x 651 mm x 541 mm iR-ADV C255i/C355i: 511 mm x 651 mm x 639 mm	Sestillation	Super G3 FAX(Optional for iR-ADV C255i/C355i),
	iR-ADV C255i/C355i: 511 mm x 651 mm x 639 mm iR-ADV C355iFC: 511 mm x 651 mm x 1,064 mm		IP Fax(Optional)
Installation Space(W x D)	852 mm x 908 mm (Basic: DADF + Multi-purpose tray extended)	Address Book/speed dials	LDAP (2,000)/Local (1,600)/Speed dial (200)
	1,407 mm x 908 mm (Fully configured: DADF + STAPLE FINISHER-Z1 + Multi-purpose tray extended)	Send resolution	100 x 100 dpi, 150 x 150 dpi, 200 x 100 dpi, 200 x 200 dpi, 200 x 400 dpi, 300 x 300 dpi, 400 x 400 dpi, 600 x 600 dpi
Weight	iR-ADV C355P: Approx. 42 kg including toner iR-ADV C255i/C355i: Approx. 49 kg including toner	Communication protocol	File: FTP, SMB v3.0, WebDAV
	iR-ADV C355iFC: Approx. 68 kg including toner		E-mail/I-Fax: SMTP, POP3, I-Fax (Simple, Full)
Print Specifications		File Format	Standard: TIFF, JPEG, PDF(Compact, Searchable, Apply policy, Optimize for Web, PDF A/1-b), XPS(Compact, Searchable),
Printing method	Colour Laser Beam Printing		Office Open XML (PowerPoint, Word)
Print Speed	iR-ADV C255i:		Optional: PDF(Trace&Smooth, Encrypted), PDF/XPS(Digital
	25ppm (A4), 26ppm (B5), 26 ppm (A5)		Signature)
	iR-ADV C355P/C355i/C355iFC: 35 ppm (A4), 26 ppm (B5), 26 ppm (A5)	Fax Specifications <sup>1</sup>	
Print Resolution	1,200 dpi x 1,200 dpi equivalent	Optional / Standard	iR-ADV C255i/C355i: Optional
Page description languages	UFR II, PCL 6, Genuine Adobe PostScript Level 3 (Standard)	Madam Crass'	iR-ADV C355iFC: Standard
Double Sided Printing	Automatic (Standard)	Modem Speed	Super G3: 33.6 kbps G3: 14.4 kbps
Direct Print	Direct printing available from USB memory key, Advanced space, Remote UI and Web Access <sup>5</sup>	<b>Compression Method</b>	MH, MR, MMR, JBIG
	Supported file types: TIFF, JPEG, PDF, EPS, and XPS.	Resolution	400 x 400 dpi, 200 x 400 dpi, 200 x 200 dpi, 200 x 100 dpi
Printing from mobile and	A range of software and MEAP-based solutions is available to	Sending/Recording Size	A4, B5*, A5* and A6*
cloud	provide printing from mobile devices or internet-connected devices and cloud-based services depending on your	FAX memory	*Sent as A4 Up to 30,000 pages
	requirements. Please contact your sales representative for further information	FAX memory Speed dials	Max. 200
Fonts	Please contact your sales representative for further information PCL fonts: 93 Roman, 10 Bitmap fonts, 2 OCR fonts,	Group dials/destinations	Max. 199 dials
	Andalé Mono WT J/K/S/T* (Japanese, Korean, Simplified and	Sequential broadcast	Max. 256 addresses
	Traditional Chinese) , Barcode fonts** PS fonts: 136 Roman	Memory backup	Yes
	*Requires optional PCL INTERNATIONAL FONT SET-A1		
	**Requires optional BARCODE PRINTING KIT-D1		



### **Technical Specifications**

Standard: Universal Login Manager (Device and Function Level Log-in), User Authentication, Department ID, Authentication, Access Management System

Standard: Trusted Platform Module (TPM), Hard Disk Password

Lock, Hard Disk Drive Erans, Mail Box Password Protection, Hard Disk Drive Encryption(FIPS140-2 Validated), Common Criteria Certification (DIN ISO 15408)<sup>10</sup> Optional: Hard Disk Drive removal, Data Loss Prevention (Requires uniFLOW)

Standard: IP/Mac Address Filtering, IPSEC, TLS Encrypted Communication, SNMP V3.0, IEEE 802.1X, IPv6, SMTP Authentication, POP Authentication before SMTP, S/MIME

Temperature: 10 to 30 °C (50 to 86 °F) Humidity: 20 to 80 % RH (no condensation)

Maximum: Approx. 1.5 kW

Sound Power Level (LwAd)9

Sound Pressure (LpAm)9

ENERGY STAR\* Qualified

Ecomark Blue Angel<sup>11</sup> RoHS

220-240 V (±10 %), 50/60 Hz (±2 Hz), 3.9 Amp

Active (CL): 66.8 dB or less<sup>6</sup>, Standby: 53 dB or less

or less iR-ADV C355i/C355iFC: Active (BW): 51.4 dB or less<sup>6</sup>, Active (CL): 52.3 dB or less<sup>6</sup>, Standby: 6 dB or less

Standard: Secure Print, Adobe LiveCycle® Rights Management ES2.5 Integration Optional: Encrypted PDF1, Encrypted Secure Print, User and Device signatures, Secure Watermarks, Document Scan locking

iR-ADV C255i: Active (BW): 63.2 dB or less<sup>6</sup>, Active (CL): 63.7 dB or less<sup>6</sup>, Standby: 43 dB or less iR-ADV C355P/C355i/C355iFC: Active (BW): 65.9 dB or less<sup>6</sup>,

Bystander's position: IR-ADV C355P: Active (BW): 51.4 dB or less<sup>6</sup>, Active (CL): 52.3 dB or less<sup>6</sup>, Standby: 7 dB or less IR-ADV C255i: Active (BW/CL): 48.7 dB or less<sup>6</sup>, Standby: 7 dB

Security Specifications

**Environmental Specifications** 

**Operating Environment** 

Power consumption

Authentication

Data

Network

Document

Power source

Noise levels

Standards

### imageRUNNER ADVANCE C255i, C355i, C355iFC, C355P

Co	nsu	ma	bl	es

Toner Cartridge/s Toner (Estimated Yield @5% Coverage)

Hardware Accessorie

C-EXV 47 TONER BK/C/M/Y C-EXV 47 TONER BK: 19,000 C-EXV 47 TONER C/M/Y: 21,500

For full information on options avilable for the iR-ADV C255/ C355 series, please refer to the spefication tables on your local Canon web site.

Footnotes

<sup>[1]</sup> Not applicable to the C355P as it is a print only model
<sup>[2]</sup> Not applicable to the C355P and optional on C255i and C355i

<sup>(3)</sup> Time between device power-on and when the start key is enabled. Quick start-up Mode ON

[4] Time until key operation can be performed on the touch panel display

<sup>[5]</sup>Only PDF print from websites is supported

<sup>[6]</sup> Data taken from Blue Angel Certification User Notes

<sup>(7]</sup> 0.8W sleep mode is not available in all circumstances due to certain settings.

<sup>(8)</sup>Typical Electricity Consumption (TEC) rating represents the typical electricity consumed by a product during 1 week, measured in kilowatt-hours (kWh). The test methodology is defined by Energy Star (http://www.eu-energystar.org).

<sup>[9]</sup> Declared noise emission in accordance with ISO 7779

<sup>[10]</sup> Common Criteria Certification (DIN ISO 15408) - Testing is scheduled to be finalised by the end of July 2017

 $^{\scriptscriptstyle [11]}{\rm Not}$  applicable to the C355i and C355P

#### **Software and Solutions**



canon.com Canon Europe canon-europe.com English edition © Canon Europa N.V.,2017

Woodhatch Reigate Surrey RH2 8BF Telephone no 01737 220000 Facsimile 01737 220022 canon.co.uk

3006 Lake Drive Citywest, Saggart Co.Dublin, Ireland Telephone No: 01 2052400 Facsimile No: 01 2052525 canon.ie

