

imagePROGRAF iPF670 MFP L24e

ACCELERATE PRODUCTIVITY WITH THIS CONVENIENT LARGE FORMAT MULTIFUNCTION PRINTER.

Introducing the iPF670 MFP L24e - an affordable, intuitive, network-compatible large format printer, compact and lightweight enough to integrate into small office environments with ease.



KEY FEATURES:

- Simplified PC-less scan-to-copy operation drives efficiency
- Flexible workflow options - scan to USB, network, or cloud
- Easy operation via touch screen control panel
- Slender 24-inch footprint requires minimal office space
- Affordable operation thanks to 5-colour dye-and-pigment ink system
- Productivity-boosting scan speeds of up to 3 inches per second
- Crisp 600-dpi optical resolution
- Support for a variety of file formats, including TIFF, PDF and JPEG

PRODUCT RANGE



Canon

TECHNICAL SPECIFICATIONS

imagePROGRAF iPF670 MFP L24e

SCANNER

Scan Technology	SingleSensor with multiple LED illumination
Optical Resolution	600dpi
Scan speed	COPY 300/300dpi Draft = 1inch/sec colour, 3inch/sec mono 300/600dpi Standard = 1inch/sec colour, 3inch/sec mono 600/600dpi Best = 0.5inch/sec colour, 1.5inch/sec mono
Scan Modes	SCAN 200dpi Draft = 1inch/sec colour, 3inch/sec mono 300dpi Standard = 0.5inch/sec colour, 1.5inch/sec mono 600dpi Best = 0.33inch/sec colour, 1inch/sec mono Scan to USB - RGB/Greyscale/BW, TIFF Scan to PC - RGB/Greyscale/BW, Tiff, Jpeg, PDF, TiffG4 Copy - RGB/Greyscale/BW Copy & Archive - RGB/Greyscale/BW, Tiff, Jpeg, PDF, TiffG4
Max scan width	24" / 609.6mm
Max document width	26" / 660.4mm
Max scan length	109" / 2768mm
Max & Min Document thickness	Min = 0.07mm Max = 0.5mm
Scan accuracy	Accuracy 0.2% +/-1 pixel
Weight of scanner	5.28kg (11.6lbs) without Doc return guide
Dimensions width	935mm
Dimensions height	131mm
Dimensions depth	Without Doc Return Guide - Paper tray folded: 146mm Without Doc Return Guide - Paper Tray flat: 193mm With Doc Return Guide - Paper tray folded: 206mm With Doc Return Guide - Paper Tray flat: 253mm
Power Supply	External PSU: Input: 100 - 240V, 50-60Hz Output: 3.42A at 19V
Max Power consumption	Standby (sleep): 0.6W Idle: 11.7W Scanning: 17.5W
Scan to USB	USB2, 128GB FAT32
Scan to Network - Scan App Le	Sets scan directory and file type. OS compatibility : Windows7,8,10(32/64bit)
Control Panel UI	3" touch screen display
Languages for Scan App Le	English/French/German/Italian/Spanish/Russian/Portuguese/Czech/Polish
Environment	Temp: 10-35C Humidity: 10-90%
Acoustic noise	48.4dB gray scan
Environment Certificates	Energy Star Europe : CE mark, Russia : EAC, Other countries : CB Certification
What's in the Box?	<ul style="list-style-type: none"> • Le scanner • Printer mounting brackets, fixings & 3mm tool • 2 feet for desktop use • 2 paper edge guides & paper refeed preventers • 1 Document return guide • Calibration target • CD for Scan App Le software (includes PDF documentation: Le Scanner User Manual and Icon Guide per language and Quick Start Guide) • User Manual and Icon Guide per language and Quick Start Guide) • Le Scanner Quick Start Guide. • Ethernet cable (2 meter) • Power Supply • Regional - Mains power cord(s) (2 meter)

Notes & recommendations

Note 1	Maximum number of supported iPF printers = 15 Maximum number of PCs running Scan App Le = 15
---------------	---

Some images are simulated for clarity of reproduction. All data is based on Canon's standard testing methods. This leaflet and the specifications of the product have been developed prior to the date of product launch. Final specifications are subject to change without notice.™ and R: All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.

Canon recommends you use Canon Media for the best results. Please check media (paper) compatibility list to see which variety of paper/media is recommended.

PRINTER

Printer Type	5 Colour - 24"/609.6 mm
Print Technology	Canon Bubblejet on Demand 6 colours integrated type (6 chips per print head x 1 print head) Total: 15,360 MBK: 5,120 nozzles C, M, Y, BK: 2,560 nozzles each colour
Number of Nozzles	2400 dpi x 1200 dpi 1200 dpi x 2 includes Non-firing nozzle detection and compensation system 0.02 mm
Print Resolution	±0.1 % or less
Nozzle Pitch	4 Picoliter per colour
Guaranteed Minimum Line Width	Bundled Starter Ink: C, M, Y, Bk, MBK 90ml Sales Ink: C, M, Y, Bk, MBK 130ml
Line Accuracy	Dye/Pigment Reactive Ink: Cyan, Magenta, Yellow, Black Pigmen ink: 2 x Matte Black
Ink Droplet Size	Windows 32 bit - XP, Vista, 7, 8, 8.1 & 10 Server 2003 / 2003R2, Server 2008
Ink Capacity	Windows 64 bit - Vista, 7, 8, 8.1 & 10 Server 2003 / 2003R2, Server 2008 / 2008R2, Server 2012 / 2012R2 Mac: OSX - 10.6.8 - 10.10.x
Ink Type	GARO (Graphic Arts language with Raster Operations), HP-GL/2, HP RTL
Printer OS Compatibility	USB 2.0 High-Speed IEEE 802.3 10base-T IEEE 802.3u 100base-TX / Auto-Negotiation IEEE 802.3ab 1000base-T / Auto-Negotiation IEEE 802.3x Full Duplex IEEE 802.3az EEE
Printer Languages	256MB
Standard Interfaces	Roll paper: 10" / 254 mm - 24" / 609.6 mm Cut sheet: 8" / 203.2 mm - 24" / 609.6 mm
Standard Memory	Roll Unit: 0.07 mm - 0.8 mm Top Loading Manual Feed: 0.07 mm - 0.8 mm
Media Width	Maximum Printable Length
Media Thickness	Roll: 18m (varies according to the OS and application) Cut Sheet: 1.6m



imagePROGRAF



Canon Inc.
canon.com
Canon Europe
canon-europe.com
English edition
© Canon Europa N.V., 2017