

# imageRUNNER ADVANCE 8500 III series

## A HIGHLY PRODUCTIVE AND RELIABLE MONO DIGITAL PRINTER FOR PROFESSIONAL AND INTEGRATED ENVIRONMENTS



Canon uniFLOW OnLine  
Outstanding Cloud Content Management Solution



### MAIN CONFIGURATION OPTIONS

#### imageRUNNER ADVANCE 8585 III\*

 <p><b>BOOKLET FINISHER-X1</b></p> <ul style="list-style-type: none"> <li>• 3-tray, 4,250-sheet capacity</li> <li>• Corner and double stapling up to 100 sheets</li> <li>• Booklet-making up to 20 sheets and saddlefolding up to 5 sheets</li> <li>• Supports optional internal 2/4 and 4-hole puncher (Puncher Unit-BG1 and BH1) and booklet trimming (Inner Booklet Trimmer-A1)</li> </ul>	 <p><b>PAPER FOLDING UNIT-J1</b></p> <ul style="list-style-type: none"> <li>• Z-fold, C-fold, Half-fold, Accordion Z-fold, Double-parallel Fold</li> </ul>  <p><b>MULTI FUNCTION PROFESSIONAL PUNCHER-B1</b></p> <ul style="list-style-type: none"> <li>• Supports various die sets</li> <li>• Up to 256 gsm</li> <li>• Supports A3, A4, A4R</li> <li>• 70,000 chip tray capacity</li> <li>• Enhanced die durability</li> </ul>  <p><b>DOCUMENT INSERTION UNIT-N1</b></p> <ul style="list-style-type: none"> <li>• Insert preprinted sheets</li> <li>• Up to A3</li> <li>• Two trays</li> <li>• 4 00-sheet total capacity</li> </ul>	 <p><b>MFP MODEL **</b>      <b>PRINTER MODEL **</b></p>	
 <p><b>STAPLE FINISHER-X1</b></p> <ul style="list-style-type: none"> <li>• 3-tray, 4,250-sheet capacity</li> <li>• Corner and double stapling up to 100 sheets</li> <li>• Supports optional internal 2/4 and 4-hole puncher (Puncher Unit- BG1 and BH1)</li> </ul>	 <p><b>BOOKLET FINISHER-V2</b></p> <ul style="list-style-type: none"> <li>• 3-tray, 3,500-sheet capacity</li> <li>• Corner and double stapling up to 65 sheets (80 gsm)</li> <li>• Booklet-making up to 20 sheets and non-staple saddle folded capacity up to 3 sheets (A3/A4R)</li> <li>• Supports Eco stapling 4 sheets (80 gsm) and Staple On Demand 65 sheets (80 gsm)</li> <li>• Supports optional 2/4 and 4 hole inner Puncher - 2/4 Hole Puncher Unit-A1 and 4 Hole Puncher Unit-A1</li> </ul>  <p><b>STAPLE FINISHER-V2</b></p> <ul style="list-style-type: none"> <li>• 3-tray, 3,500-sheet capacity</li> <li>• Corner and double stapling up to 65 sheets (80 gsm)</li> <li>• Supports Eco stapling 4 sheets (80 gsm) and Staple On Demand 65 sheets (80 gsm)</li> <li>• Supports optional 2/4 and 4 hole inner Puncher - 2/4 Hole Puncher Unit-A1 and 4 Hole Puncher Unit-A1</li> </ul>	 <p><b>PAPER DECK UNIT-E1</b></p> <ul style="list-style-type: none"> <li>• 3,500-sheet capacity</li> <li>• Supports A4</li> </ul>  <p><b>POD DECK LITE-C1</b></p> <ul style="list-style-type: none"> <li>• 3,500-sheet capacity</li> <li>• 52 to 256 gsm</li> <li>• Supports up to SRA3</li> <li>• User adjustable</li> </ul>	
			 <p><b>imagePASS-Y3</b></p> <ul style="list-style-type: none"> <li>• Delivers fast processing speed, outstanding image quality, and time-saving workflow</li> </ul>
			 <p><b>INNER TRIMMER</b>      <b>INNER PUNCHERS</b></p>

This flat configuration is for illustration purpose only. For a complete list of options and the exact compatibility relationships, please refer to the online product configurator.

III\* indicates that this model has been upgraded to new system software and includes additional security features as standard.

\*\* Standard configuration: flat touch panel; Optional: upright touch panel

# imageRUNNER ADVANCE 8500 III series

## imageRUNNER ADVANCE 8595 Pro III\* / 8505 Pro III\*

 <p><b>BOOKLET TRIMMER-F1</b> Requires BOOKLET FINISHER-W1 PRO</p>  <p><b>BOOKLET FINISHER-W1 PRO</b></p> <ul style="list-style-type: none"> <li>• 2-tray, 5,000-sheet capacity</li> <li>• Corner and double stapling up to 100 sheets</li> <li>• Booklet-making up to 25 sheets and saddle-folding up to 5 sheets</li> <li>• Supports optional internal 2/4 and 4-hole puncher (Puncher Unit-BT1 and BU1) and optional booklet trimming (Booklet Trimmer-D1)</li> <li>• Precise output stacking alignment</li> <li>• Enhanced durability for high volumes</li> </ul>  <p><b>STAPLE FINISHER-W1 PRO</b></p> <ul style="list-style-type: none"> <li>• 2-tray, 5,000-sheet capacity</li> <li>• Corner and double stapling up to 100 sheets</li> <li>• Supports optional internal 2/4 and 4-hole puncher (Puncher Unit-BT1 and BU1)</li> <li>• Precise output stacking alignment</li> <li>• Enhanced durability for high volumes</li> </ul>	 <p><b>DOCUMENT INSERTION UNIT-N1</b></p> <ul style="list-style-type: none"> <li>• Insert preprinted sheets</li> <li>• Up to A3</li> <li>• Two trays</li> <li>• 400-sheet total capacity</li> </ul>  <p><b>MULTI FUNCTION PROFESSIONAL PUNCHER-B1</b></p> <ul style="list-style-type: none"> <li>• Supports various die sets</li> <li>• Up to 256 gsm</li> <li>• Supports A3, A4, A4R</li> <li>• 70,000 chip tray capacity</li> <li>• Enhanced die durability</li> </ul>	 <p><b>MFP MODEL **</b>      <b>PRINTER MODEL **</b></p>
 <p><b>BOOKLET FINISHER-X1</b></p> <ul style="list-style-type: none"> <li>• 3-tray, 4,250-sheet capacity</li> <li>• Corner and double stapling up to 100 sheets</li> <li>• Booklet-making up to 20 sheets and saddlefolding up to 5 sheets</li> <li>• Supports optional internal 2/4 and 4-hole puncher (Puncher Unit-BG1 and BH1) and booklet trimming (Inner Booklet Trimmer-A1)</li> </ul>  <p><b>STAPLE FINISHER-X1</b></p> <ul style="list-style-type: none"> <li>• 3-tray, 4,250-sheet capacity</li> <li>• Corner and double stapling up to 100 sheets</li> <li>• Supports optional internal 2/4 and 4-hole puncher (Puncher Unit-BG1 and BH1)</li> </ul>	 <p><b>PAPER FOLDING UNIT-J1</b></p> <ul style="list-style-type: none"> <li>• Z-fold, C-fold, Half-fold, Accordion</li> <li>• Z-fold, Double-parallel Fold</li> </ul>	 <p><b>PAPER DECK UNIT-E1</b>      <b>POD DECK LITE-C1</b></p> <ul style="list-style-type: none"> <li>• 3,500-sheet capacity</li> <li>• Supports A4</li> <li>• 3,500-sheet capacity</li> <li>• 52 to 256 gsm</li> <li>• Supports up to SRA3</li> <li>• User adjustable</li> </ul>
		 <p><b>imagePASS-Y3</b></p> <ul style="list-style-type: none"> <li>• Delivers fast processing speed, outstanding image quality, and time-saving workflow</li> </ul>
		 <p><b>INNER TRIMMER</b>      <b>INNER PUNCHERS</b></p>

This flat configuration is for illustration purpose only. For a complete list of options and the exact compatibility relationships, please refer to the online product configurator.

**III\* indicates that this model has been upgraded to new system software and includes additional security features as standard.**

\*\* Standard configuration: flat touch panel; Optional: upright touch panel

# TECHNICAL SPECIFICATIONS

# imageRUNNER ADVANCE 8500 III series

## MAIN UNIT

**Type** Monochrome Laser Multifunctional  
**Core Functions** Print, Copy\*, Scan\*, Send\*, Store and Optional Fax\*  
\*Not available on 8500 III Printer model  
**Processor** Canon Dual Custom Processor (Shared)  
**Control Panel** Standard: 25.6 cm (10.1 inch) TFT LCD WSVGA Colour Flat Touch panel  
 Optional: 26.4 cm (10.4 inch) TFT LCD SVGA Colour Upright Touch panel  
**Memory** Standard: 3.0 GB RAM  
**Hard Disk Drive** Standard: 250 GB, Maximum: 1 TB  
**Mirroring Hard Disk Drive** Optional: 250 GB, 1 TB  
**Interface Connection** Network  
 Standard: 1000Base-T/100Base-TX/10Base-T, Wireless LAN (IEEE 802.11 b/g/n)  
 Optional: NFC, Bluetooth Low Energy  
 Others  
 Standard: USB 2.0 (Host) x2, USB 3.0 (Host) x1, USB 2.0 (Device) x1  
 Optional: Serial Interface, Copy Control Interface

## Paper Supply Capacity (A4, 80gsm)

Standard: 4,200 sheets  
 1,500-sheet Paper Deck x 2, 550-sheet Paper Cassette x 2, 100-sheet Multi-purpose tray  
 Maximum: 7,700 sheets (with POD Deck Lite-C1 or Paper Deck Unit-E1)

## Paper Output Capacity (A4, 80 gsm)

250 sheets (with Copy Tray-R2).  
 Maximum: 5,000 sheets (with Staple Finisher-W1 PRO or Booklet Finisher-W1 Pro)

## Finishing Capabilities

Standard: Collate, Group  
 With External finisher: Collate, Group, Offset, Staple, Staple On Demand, Staple-free Staple<sup>\*1</sup>, Saddle Stitch<sup>\*2</sup>, Trimming<sup>\*3</sup>, Hole Punch<sup>\*4</sup>, Professional Hole Punch (multiple patterns)<sup>\*5</sup>, Document Insertion<sup>\*6</sup>, Fold<sup>\*7</sup> (C-, Z-, Half-, Double-parallel, Accordion-Z fold)  
\*2 Requires Staple Finisher-V2 or Booklet Finisher-V2  
 \*3 Requires Booklet Finisher-V2, Booklet Finisher-X1 or Booklet Finisher-W1 Pro  
 \*4 Requires Inner Booklet Trimmer-A1 (with Booklet Finisher-X1) or Booklet Trimmer- F1 (with Booklet Finisher-W1 Pro)  
 \*5 Requires 2/4 Hole Puncher Unit-A1 or 4 Hole Puncher Unit-A1 (with Staple Finisher-V2 or Booklet Finisher-V2), Puncher Unit-BG1 or Puncher Unit-BH1 (with Staple Finisher-X1 or Booklet Finisher-X1), or Puncher Unit-BT1 or Puncher Unit-BU1 (with Staple Finisher-W1 Pro or Booklet Finisher-W1 Pro)  
 \*6 Requires Multifunctional Professional Puncher-B1 (with Staple Finisher-X1, Booklet Finisher-X1, Staple Finisher-W1 Pro or Booklet Finisher-W1 Pro)  
 \*7 Requires Document Insertion Unit-N1 (with Staple Finisher-X1, Booklet Finisher-X1, Staple Finisher-W1 Pro or Booklet Finisher-W1 Pro)  
 \*8 Requires Paper Folding Unit-J1 (with Staple Finisher-X1, Booklet Finisher-X1, Staple Finisher-W1 Pro or Booklet Finisher-W1 Pro)

## Supported media types

Upper Left/Right Decks (1/2):  
 Thin, Plain, Recycled, Colour, Thick, Pre-punched, Letterhead, Bond  
 Lower Cassettes (3/4):  
 Thin, Plain, Recycled, Colour, Thick, Pre-punched, Letterhead, Bond, Tab\*  
\*Requires Tab Feeding Attachment Kit-B1  
 Multi-purpose tray:  
 Thin, Plain, Recycled, Colour, Thick, Pre-punched, Bond, Transparency, Labels, Letterhead, Tab, Tracing\*  
\* Some types of tracing paper cannot be used.  
 Pod Deck Lite-C1: Thin paper, Plain paper, Recycled paper, Colour paper, Heavy paper, Pre-punched paper, Letterhead, Bond paper, Transparency, Labels, Tab paper

## Supported media sizes

Paper Deck Unit-E1: Thin paper, Plain paper, Recycled paper, Colour paper, Heavy paper, Pre-punched paper, Letterhead, Bond paper  
 Upper Left/Right Decks (1/2):  
 Standard size: A4, B5  
 Lower Cassettes (3/4):  
 Standard size: SRA3, A3, A4, A4R, A5R, B4, B5, B5R  
 Custom size: 100.0 x 148.0 mm to 330.2 x 487.7 mm  
 Free size: 100.0 x 182.0 mm to 330.2 x 487.7 mm  
 Pod Deck Lite-C1:  
 330 mm x 483 mm (13" x 19"), 320 mm x 450 mm (SRA3), 305 mm x 457 mm (12" x 18"), A3, B4, A4, A4R, A5R, B5, B5R  
 Custom size: 139.7 mm x 182 mm to 330.2 mm x 487.7 mm  
 Paper Deck Unit-E1:  
 A4, B5

## Supported media weights

Paper Decks / Paper Cassettes: 52 to 220 gsm  
 Multi-purpose tray/ Pod Deck Lite-C1/ Paper Deck Unit-E1: 52 to 256 gsm  
 Duplex: 52 to 220 gsm

## Warm-up Time

From Power On\*: 60 Seconds or Less  
\*Time from device power-on, until copy ready (not print reservation)  
 From Deep Sleep Mode: 60 Seconds or Less

## Dimensions (W x D x H)

MFP Model with optional upright touch panel:  
 1,481 x 770 x 1,252 mm  
 MFP Model with flat touch panel: 670 x 779 x 1,220 mm  
 Printer Model with flat touch panel: 670 x 779 x 1,052 mm

## Installation Space (W x D)

Basic: 1,533 x 1,353 mm (with Multi-purpose tray/ upper-right cover open + Front Cover open + Copy Tray)  
 Fully configured: 5,068 x 1,400 mm (with POD Deck Lite-C1 + Document Insertion Unit-N1 + Multifunction Professional Puncher-B1 + Paper Folding Unit-J1 + Booklet Finisher-W1 Pro + Booklet Trimmer- F1 + Main unit Front Cover open)  
 MFP Model with optional upright touch panel:  
 Approx. 240 kg<sup>\*1</sup>  
 MFP Model with flat touch panel: Approx. 236 kg<sup>\*1</sup>  
 Printer Model with flat touch panel: Approx. 206 kg<sup>\*2</sup>  
\*1 Including ADF, and the toner bottle  
 \*2 including printer cover and the toner bottle

## PRINT SPECIFICATIONS

### Print Speed

iR-ADV 8505 Pro III  
 105 ppm (A4, A5R), 54 ppm (A3), 76 ppm (A4R)

iR-ADV 8595 Pro III  
 95 ppm (A4, A5R), 50 ppm (A3), 69 ppm (A4R)

iR-ADV 8585 Pro III  
 85 ppm (A4, A5R), 44 ppm (A3), 63 ppm (A4R)

1,200 x 1,200, 600 x 600  
 Standard: UFR II (standard),  
 Optional: PCL 6, Genuine Adobe PostScript Level 3

### Print Resolution (dpi)

### Page Description Languages

Direct printing available from USB memory, Advanced space, Remote UI and Web Access\*  
 Supported file types: TIFF, JPEG, PDF, EPS, and XPS  
\*Only PDF print from websites is supported

### Direct Print

### Printing from mobile and cloud

AirPrint, Mopria, Google Cloud Print, and Canon PRINT Business, and uniFLOW Online

A range of software and MFP-based solutions is available to provide printing from mobile devices or internet-connected devices and cloud-based services depending on your requirements.  
 Please contact your sales representative for further information

### Fonts

PCL fonts: 93 Roman, 10 Bitmap fonts, 2 OCR fonts, Andalé Mono WTJ/K/S/Tr<sup>\*1</sup> (Japanese, Korean, Simplified and Traditional Chinese), Barcode fonts<sup>\*2</sup>  
 PS fonts: 136 Roman  
\*1 Requires optional PCL International Font Set-A1  
 \*2 Requires optional Barcode Printing Kit-D1

### Print Features

Suspend Job Timeout, Subset Finishing (PS only), Profile Settings, Secured Print, Watermark, Header/Footer, Page Layout, Two-sided Printing, Collating, Booklet Printing, Grouping, Mixed Paper Sizes/ Orientations, Offsetting, Front/Back Covers, Toner Reduction, Poster Printing, Forced Hold Printing

### Operating System

UFR II: Windows 7 / 8.1 / 10 / Server 2008 / Server 2008 R2 / Server 2012 / Server 2012 R2 / Server 2016, MAC OS X (10.7 or later)  
 PCL: Windows 7 / 8.1 / 10 / Server 2008 / Server 2008 R2 / Server 2012 / Server 2012 R2 / Server 2016  
 PS: Windows 7 / 8.1 / 10 / Server 2008 / Server 2008 R2 / Server 2012 / Server 2012 R2 / Server 2016, MAC OS X (10.7 or later)  
 PPD: MAC OS X (10.7 or later), Windows 7 / 8.1 / 10

## COPY SPECIFICATIONS

### Copy Speed

iR-ADV 8505 Pro III  
 105 ppm (A4), 54 ppm (A3), 76 ppm (A4R), 105 ppm (A5R)

iR-ADV 8595 Pro III  
 95 ppm (A4), 50 ppm (A3), 69 ppm (A4R), 95 ppm (A5R)

iR-ADV 8585 Pro III  
 85 ppm (A4), 44 ppm (A3), 63 ppm (A4R), 85 ppm (A5R)

Approx. 2.7 seconds or less

Reading: 600 x 600

Printing: 1,200 x 1,200

Up to 9,999 copies

Automatic or Manual (9 Levels)

Magnification  
 25% - 400% (1% Increments)

Preset Reductions  
 25%, 50%, 70%

Preset Enlargements  
 141%, 200%, 400%

## SCAN SPECIFICATIONS

### Type

Colour flatbed plus Single-pass duplex automatic document feeder\* (1-Pass duplex scan) [2-sided to 2-sided (Automatic with DADF)]  
\*Detect Feeder Multi Sheet Feed is supported.

300 Sheets

### Document Feeder Paper Capacity (80 gsm)

Platen: Sheet, Book, 3-Dimensional Objects (Height: Up to 50 mm, Weight: up to 2kg)

### Acceptable originals and weights

Document Feeder media weight:  
 1-sided scanning: 38 to 220 gsm (BW), 64 to 220 gsm (CL)  
 2-sided scanning: 50 to 220 gsm (BW), 64 to 220 gsm (CL)

### Supported media sizes

Platen: max. scanning size: 297.0 x 431.8 mm  
 Document Feeder media size: A3, A4, A4R, A5, A5R, B4, B5, B5R, B6R, Custom size: 128.0 x 139.7 mm to 304.8 x 431.8 mm

### Scan Speed (ipm: BW/CL; A4)

1-sided Scanning: 120/120 (300 dpi), 120 (BW: 600 dpi)  
 2-sided Scanning: 240/220 (300 dpi), 150 (BW: 600 dpi)

### Scan Resolution (dpi)

600 x 600, 400 x 400, 300 x 300, 200 x 400, 200 x 200, 200 x 100, 150 x 150, 100 x 100



# TECHNICAL SPECIFICATIONS

# imageRUNNER ADVANCE 8500 III series

## SEND SPECIFICATIONS

<b>Destination</b>	E-Mail/Internet FAX (SMTP), SMB v3.0, FTP, WebDAV, Mail Box, Super G3 Fax (optional), IP Fax (optional)
<b>Address Book</b>	LDAP (2000)/Local (1600)/Speed dial (200)
<b>Send resolution (dpi)</b>	600 x 600, 400 x 400, 300 x 300, 200 x 400, 200 x 200, 200 x 100, 150 x 150, 100 x 100
<b>Communication protocol</b>	File: FTP (TCP/IP), SMB v3.0, WebDAV E-mail/I-Fax: SMTP, POP3
<b>File Format</b>	Standard: TIFF, JPEG, PDF (Compact, Searchable, Apply Policy, Optimise for Web, PDF A/1-b, Encrypted), XPS (Compact, Searchable), Office Open XML (PowerPoint, Word), PDF/XPS ( Device Signature) Optional: PDF (Trace&Smooth), PDF/XPS (User Signature)

## FAX SPECIFICATIONS

<b>Maximum Number of Connection Lines</b>	2
<b>Modem Speed</b>	Super G3: 33.6 kbps G3: 14.4 kbps
<b>Compression Method</b>	MH, MR, MMR, JBIG
<b>Resolution (dpi)</b>	400 x 400, 200 x 400, 200 x 200, 200 x 100
<b>Sending/Recording Size</b>	A3, A4, A4R, A5*, A5R*, B4, B5*, B5R* *1Sent as A4 *2Sent as B4
<b>FAX memory</b>	Up to 30,000 pages
<b>Speed dials</b>	Max. 200
<b>Group dials/destinations</b>	Max. 199 dials
<b>Sequential broadcast</b>	Max. 256 addresses
<b>Memory backup</b>	Yes

## SECURITY SPECIFICATIONS

<b>Authentication</b>	Standard: Universal Login Manager (Device and Function Level Log-in), uniFLOW Online Express*, User Authentication, Department ID Authentication, Access Management System Optional: My Print Anywhere secure print (Requires uniFLOW) *No charge for this solution; however activation is required.
<b>Data</b>	Standard: Trusted Platform Module (TPM), Hard Disk Password Lock, Hard Disk Drive Erase, Mail Box Password Protection, Hard Disk Drive Encryption (FIPS140-2 Validated), Common Criteria Certification (DIN ISO 15408) Optional: Hard Disk Drive Mirroring, Hard Disk Drive removal, Data Loss Prevention (Requires uniFLOW)
<b>Network</b>	Standard: IP/Mac Address Filtering, IPSEC, TLS Encrypted Communication, SNMP V3.0, IEEE 802.1X, IPv6, SMTP Authentication, POP Authentication before SMTP, S/MIME
<b>Document</b>	Standard: Secure Print, Adobe LiveCycle® Rights Management ES2.5 Integration, Encrypted PDF, Encrypted Secure Print, Device signature, Secure Watermarks Optional: User signature, Document Scan lock

## ENVIRONMENTAL SPECIFICATIONS

<b>Operating Environment</b>	Temperature: 10 to 30 °C Humidity: 20 to 80 % RH (Relative Humidity) 220-240 V (±10%), 50/60 Hz (±2Hz), 10A CEE 7/7 (230V)
<b>Power Source</b>	Maximum: Approx. 2,400 W
<b>Plug (Main Unit)</b>	Printing: Approx. 1,611.4 W* Standby: Approx. 219.8 W* Sleep mode: Approx. 0.9 W* Plugin Off: Approx. 0.3W* *1Reference value: measured one unit *20.9W sleep mode may not be possible in all circumstances due to certain settings.
<b>Power Consumption</b>	*3Reference value, Quick startup mode OFF
<b>Noise Levels</b>	Sound Power Level (LwAd) Active: 75 dB or Less Standby: 54 dB Blue Angel
<b>Standards</b>	

## CONSUMABLES

<b>Toner Cartridge</b>	C-EXV 35 Black Toner
<b>Toner (Estimated Yield @6% Coverage)</b>	70,000 pages

## FIERY PRINT CONTROLLER SPECIFICATIONS (EXTERNAL)

<b>Optional/Standard</b>	Optional on all models imagePASS Y3 (External)
<b>Name</b>	1,200 x 1,200, 600 x 600
<b>Print Resolution (dpi)</b>	PCL6, Adobe PostScript 3
<b>Standard Page Description Language(s)</b>	
<b>Memory</b>	8GB (2 x 4GB)
<b>Hard Disk Drive</b>	500 GB SATA
<b>PROCESSOR</b>	Intel Pentium G4400 (3.3 GHz)
<b>System</b>	Fiery FS350Pro
<b>Fonts</b>	PS: 138 Fonts PCL: 113 Fonts
<b>Base OS</b>	Windows 10 IoT Enterprise 2016 LTSB

For a complete list of all Hardware accessories, please refer to our website specifications page or online product configurator.

## Software & Solutions



## Certifications and compatibility



**Canon Ireland**  
3006 Lake Drive  
Citywest, Saggart  
Co. Dublin, Ireland  
Telephone No: 01 2052400  
Facsimile No: 01 2052525  
canon.ie

**Canon (UK) Ltd**  
Woodhatch  
Reigate  
Surrey RH2 8BF  
Telephone No: 01737 220000  
Facsimile No: 01737 220022  
canon.co.uk

**Canon Inc.**  
canon.com  
**Canon Europe**  
canon-europe.com  
English edition  
© Canon Europa N.V., 2019