

imageRUNNER ADVANCE C7500 III series

EXCELLENT COLOUR QUALITY COMMUNICATION




Canon uniFLOW Online
Outstanding Cloud Output Management Solution



Canon imageRUNNER ADVANCE C7580i
Outstanding 70- to 80-ppm Colour Copier MFP




MAIN CONFIGURATION OPTIONS




STAPLE FINISHER-V2

- 3 tray, 3,500 sheet capacity
- Corner and double stapling up to 65 sheets (90 gsm)
- Supports Eco stapling 4 sheets (80 gsm) and Staple on Demand 65 sheets (90 gsm)
- Supports optional internal 2/4 and 4 hole inner punchers (2/4 Hole Puncher Unit-A1 and 4 Hole puncher unit-A1)




DOCUMENT INSERTION UNIT-G1

- Insert pre-printed sheets
- Up to A3
- 1-tray, 100 sheet capacity




DOCUMENT INSERTION/ FOLDING UNIT-K1

- Insert pre-printed sheets
- Up to A3
- 1-tray, 100-sheet capacity
- Z-fold and C-fold




STAPLE FINISHER-X1

- 3 tray, 4,250 sheet capacity
- Corner and double stapling up to 100 sheets (80 gsm)
- Supports optional internal 2/4 and 4 hole inner punchers (Puncher Unit-BG1 (2/F4H) and Puncher Unit-BH1 (S4H))




DOCUMENT INSERTION UNIT-N1

- Insert pre-printed sheets
- Up to A3
- 2-tray, 400 sheet capacity




PAPER FOLDING UNIT-J1

- Insert pre-printed sheets
- Up to A3
- Z-fold, Accordion Z-Fold, C-fold, Half-Fold and Double Parallel Fold




MULTI FUNCTION PROFESSIONAL PUNCHER-A1

- Up to A3
- Media weight 52 - 300 gsm




PAPER DECK UNIT-E1

- Supports A4
- Media weight 52 - 256 gsm
- 3,500 sheets (80gsm)




POD DECK LITE-C1

- Supports up to A3
- Media weight 52 - 300 gsm
- 3,500 sheets (80 gsm)



MULTI DRAWER PAPER DECK-C1


- Supports up to A3
- Media weight 52 - 300 gsm
- 6,000 sheets (80 gsm)



IMAGEPASS-N2

| | |
|---------------|---------------|
| PDL | • PCL/PS |
| MEMORY | • 4GB/500GB |
| SYSTEM | • Fiery FS350 |

- Delivers fast processing speed, outstanding image quality, and time-saving workflow
- Personalised printing with the built-in, entry-level Fiery FreeForm (TM) or with the supported industry-leading variable data printing (VDP) formats
- Integrates print production workflows with EFI (TM) management information systems, Web-to-Print systems, and popular prepress workflows for end-to-end automation
- Communicates with the full suite of optional uniFLOW modules



**IR-ADV C7565i III*/
IR-ADV C7570i III*/
IR-ADV C7580i III***

This flat configuration is for illustration purpose only. For a complete list of options and the exact compatibility relationships, please refer to the online product configurator.

III* indicates that this model has been upgraded to new system software and includes additional security features as standard.

TECHNICAL SPECIFICATIONS

imageRUNNER ADVANCE C7500 III series

MAIN UNIT

Machine type
Core functions
Processor
Control Panel

A3 Colour Laser Multifunctional
Print, Copy, Scan, Send, Store and Optional Fax
Canon Dual Custom Processor (Shared)
Standard: 25.6 cm (10.1 inch) TFT LCD WSVGA Colour Touch panel
Optional: 26.4 cm (10.4 inch) TFT LCD SVGA Colour Upright Touch Panel
Standard: 4.0GB RAM
Standard: 250GB, Maximum: 1TB
Optional: 250GTB, 1TB
NETWORK
Standard: 1000Base-T/100Base-TX/10Base-T, Wireless LAN (IEEE 802.11 b/g/n);
Optional: NFC, Bluetooth Low Energy
OTHERS
Standard: USB 2.0 (Host) x2, USB 3.0 (Host) x1, USB 2.0 (Device) x1;
Optional: Serial Interface, Copy Control Interface

Memory

Hard Disk drive
Mirroring Hard Disk Drive
Interface Connection

Standard: 3,550 sheets 1,100-sheet Paper Deck x 2, 550-sheet Paper Cassette x 2, 250-sheet Multi-purpose tray
Maximum: 9,300 sheets (with MULTI-DRAWER PAPER DECK-C1)

Paper Supply Capacity (A4, 80gsm)

Paper output capacity (A4, 80gsm)

Finishing capabilities

250 Sheets (with COPY TRAY-R2)
Maximum: 4,250 Sheets (with STAPLE FINISHER-X1 or BOOKLET FINISHER-X1)
Standard: Collate, Group
With External Finisher : Collate, Group, Offset, Staple, Saddle Stitch^{*1}, Hole Punch^{*2} (multiple patterns), Staple-Free Staple^{*3}, Staple on Demand^{*3}, Document Insertion^{*4}, Fold (C^{+*}, Z^{+*}, Half^{*6}, Double parallel^{*6}, Accordion-Z fold^{*6}), Trimming^{*7}
^{*1} Requires Booklet Finisher-V2 or Booklet Finisher-X1
^{*2} Requires 2/4 Hole Puncher Unit-A1 or 4 Hole Puncher Unit-A1 (with Staple Finisher-V2 or Booklet Finisher-V2) or Puncher Unit-BG1 or Puncher Unit-BH1 or Multi Function Professional Puncher-A1/B1 (with Staple Finisher-X1 or Booklet Finisher-X1)
^{*3} Requires Staple Finisher-V2 or Booklet Finisher-V2
^{*4} Requires Document Insertion Unit-Q1 or Document Insertion/Folding Unit-K1 (with Staple Finisher-V2 or Booklet Finisher-V2) or Document Insertion Unit-N1 (with Staple Finisher-X1 or Booklet Finisher-X1)
^{*5} Requires Document Insertion/Folding Unit-K1 (with Staple Finisher-V2 or Booklet Finisher-V2) or Paper Folding Unit-J1 (with Staple Finisher-X1 or Booklet Finisher-X1)
^{*6} Requires Paper Folding Unit-J1 (with Staple Finisher-X1 or Booklet Finisher-X1)
^{*7} Requires Inner Booklet Trimmer-A1 (with Booklet Finisher-X1)

Supported media types

Paper Decks (1/2): Thin, Plain, Recycled, Thick, Colour, Transparency, Pre-punched, Letterhead, Bond
Paper Cassettes (3/4): Thin, Plain, Recycled, Thick, Colour, Tab*, Transparency, Bond, Pre-punched, Letterhead, Envelope
^{*Requires Tab Feeding Attachment-F1}
Multi-purpose tray: Thin, Plain, Recycled, Thick, Colour, Transparency, Label, Tracing*, Envelope, Coated, Textured, Bond, Pre-punched, Letterhead, Tab
^{* Some types of tracing paper cannot be used.}

Supported media sizes

Paper Decks (1/2):
Standard size: A4, B5
Paper Cassettes (3/4):
Standard size: SRA3, A3, A4, A4R, A5, A5R, A6R (Simplex only), B4, B5, B5R,
Envelope [No.10 (COM10), Monarch, ISO-C5, DL]
Envelope custom size: 98.0 x 148 mm to 330.2 x 487.7 mm
Custom Size: 139.7 x 182.0 mm to 330.2 x 487.7 mm
Multi-purpose tray:
SRA3, A3, A4, A4R, A5, A5R, A6R, B4, B5, B5R, Envelope [No.10 (COM10), Monarch, ISO-C5, DL]
Envelope custom size: 90.0 x 148 mm to 330.2 x 487.7 mm
Custom size: 100.0 x 148.0 mm to 330.2 x 487.7 mm
Free size: 100.0 x 182.0 mm to 330.2 x 487.7 mm

Supported media weights

Paper Deck (1/2): 52 to 220 gsm
Paper Cassettes (3/4): 52 to 256 gsm
Multi-purpose tray: 52 to 300 gsm
Duplex: 52 to 220 gsm
From Power On: 30 Seconds or Less*
^{* Time from device power-on, until copy ready (not print reservation)}

Warm-up Time

From Sleep Mode: 30 Seconds or Less
Quick Startup Mode: 4 seconds or less*
^{*Time from device power-on to when key operations can be performed on the touch panel display.}

Dimensions (W x D x H)

Installation Space(W x D)

689 x 941 x 1,220 mm
Basic-1: 1,758 x 1,524 mm (with Front door open + Multi-purpose tray/upper-right cover open + Left cover open)
Basic-2: 2,026 x 1,524 mm (with Front door open + Multi-purpose tray/upper-right cover open + Buffer Pass-M1 + Booklet Finisher-V2/extension tray & rotary tray extended)
Fully Configured: 3,818 x 1,524 mm (with Multi-Drawer Paper Deck-C1 + Buffer Pass-M1 + Document Insertion Unit-N1 + Multi Function Professional Puncher-A1 + Paper Folding Unit-J1 + Booklet Finisher-X1)
Approx. 269 kg (including toner)

Weight

PRINT SPECIFICATIONS

Print Speed (BW/CL)

iR-ADV C7580i III: 80/70 ppm (A4, A5, A5R, A6R), 40/35 ppm (A3), 56/49 ppm (A4R)
iR-ADV C7570i III: 70/65 ppm (A4, A5, A5R, A6R), 35/32 ppm (A3), 49/46 ppm (A4R)
iR-ADV C7565i III: 65/60 ppm (A4, A5, A5R, A6R), 32/30 ppm (A3), 46/42 ppm (A4R)
Up to 2,400 x 2,400

Print Resolution (dpi)

Page description languages

Direct Print

Standard: UFR II, PCL 6, Genuine Adobe PostScript Level 3
Direct printing available from USB memory, Advanced space, Remote UI and Web Access*
Supported file types: TIFF, JPEG, PDF, EPS, and XPS
^{* Only PDF print from websites is supported}

Printing from mobile and cloud

AirPrint, Mopria, Google Cloud Print, and Canon PRINT Business, and uniFLOW Online
A range of software and MEEP-based solutions are available to provide printing from mobile devices or internet-connected devices and cloud-based services depending on your requirements.
Please contact your sales representative for further information

Fonts

PCL fonts: 93 Roman, 10 Bitmap fonts, 2 OCR fonts, Andale Mono WT J/K/S/T*1 (Japanese, Korean, Simplified and Traditional Chinese), Barcode fonts*2
PS fonts: 136 Roman
^{*1} Requires optional PCL International Font Set-A1
^{*2} Requires optional Barcode Printing Kit-D1

Print Features

Suspend Job Timeout, Subset Finishing (PS only), Profile Settings, Secured Print, Watermark, Header/Footer, Page Layout, Two-sided Printing, Collating, Booklet Printing, Grouping, Mixed Paper Sizes/Orientations, Offsetting, Front/Back Covers, Toner Reduction, Poster Printing, Forced Hold Printing

Operating System

UFR II: Windows 7 / 8.1/10 / Server 2008 / Server 2008 R2 / Server 2012 / Server 2012 R2 / Server 2016, MAC OS X (10.7 or later)
PCL: Windows 7 / 8.1 / 10 / Server 2008 / Server 2008 R2 / Server 2012 / Server 2012 R2 / Server 2016
PS: Windows 7 / 8.1 / 10 / Server 2008 / Server 2008 R2 / Server 2012 / Server 2012 R2 / Server 2016, MAC OS X (10.7 or later)
PPD: MAC OS X (10.7 or later), Windows 7 / 8.1/ 10
McAfee Embedded Control Software

SAP Device Types are available via the SAP Market Place. Please refer to <http://www.canon-europe.com/support/business-product-support> for availability of print solutions for other operating systems and environments including AS/400, UNIX, Linux and Citrix. Some of these solutions are chargeable.

COPY SPECIFICATIONS

Copy Speed (BW/CL)

iR-ADV C7580i III: 80/70 ppm (A4, A5, A5R, A6R), 40/35 ppm (A3), 56/49 ppm (A4R)
iR-ADV C7570i III: 70/65 ppm (A4, A5, A5R, A6R), 35/32 ppm (A3), 49/46 ppm (A4R)
iR-ADV C7565i III: 65/60 ppm (A4, A5, A5R, A6R), 32/30 ppm (A3), 46/42 ppm (A4R)

First-Copy-Out Time (A4) (BW/CL)

iR-ADV C7580i III: Approx. 4.4/5.4 seconds or less
iR-ADV C7570i III: Approx. 4.8/5.9 seconds or less
iR-ADV C7565i III: Approx. 4.8/5.9 seconds or less

Copy resolution (dpi)

Reading: 600 x 600
Printing: Up to 2,400 x 2,400

Multiple Copies

Copy Density

Magnification

Preset Reductions

Preset Enlargements

Basic Copy Features

Up to 9,999 copies
Automatic or Manual (9 Levels)
25% - 400% (1% Increments)
25%, 50%, 70%
141%, 200%, 400%
Preset R/E Ratios by Area, Paper Setting, Previous Setting, Favourite Setting, Finishing, Two-Sided, Density Adjustment, Original Type Selection, Interrupt Mode, Setting Confirmation/Cancel

Special Copy Features

Book to Two Pages, Two-sided Original, Finishing, Booklet, Job Build, N on 1, Add Cover, Insert Sheets, Different Size Originals, Density Adjustment, Original Type Selection, Transparency Cover Sheets, Page Numbering, Copy Set Numbering, Sharpness, Erase Frame, Secure Watermark, Print Date, Shift, Gutter, Print & Check, Negative/Positive, Repeat Images, Merge Job Blocks, Job Done Notice, Mirror Image, Print on Tab, Store in Mail Box, Superimpose Image, Copy ID Card, Skip Blank Pages, Detect Feeder Multi Sheet Feed, Free Size Original

SCAN SPECIFICATIONS

Type

Colour Platen and Single-pass Duplexing Automatic Document Feeder* [2-sided to 2-sided (Automatic)]
^{* Detect Feeder Multi Sheet Feed is supported.}
300 Sheets

Document Feeder Paper Capacity (80 gsm)

Acceptable originals and weights

Platen: Sheet, Book, 3-Dimensional Objects (Height: Up to 50 mm, Weight: up to 2kg)
Document Feeder media weight:

Supported media sizes

1-sided scanning: 38 to 220 gsm (BW), 64 to 220 gsm (CL)
2-sided scanning: 50 to 220 gsm (BW), 64 to 220 gsm (CL)
Platen: max. scanning size: 297.0 x 431.8 mm

Scan Speed (ipm: BW/CL; A4)

Document Feeder media size: A3, A4, A4R, A5, A5R, B4, B5, B5R, B6R, Custom size: 128.0 x 139.7 mm to 304.8 x 431.8 mm

Scan Resolution (dpi)

Single-sided Scanning: 120 /120 (300dpi), 120 /70 (600 dpi)
Double-sided Scanning: 240 /220 (300dpi), 150 /90 (600 dpi)
600 x 600, 400 x 400, 300 x 300, 200 x 400, 200 x 200, 200 x 100, 150 x 150, 100 x 100

Pull Scan Specifications

Colour Network ScanGear2. For both TWAIN and WIA Supported OS: Windows 7/8.1/10
Windows Server 2008/Server 2008 R2/Server 2012/Server 2012 R2/Server 2016

Scan Method

Send functionality available on all models
Scan to USB Memory Key; Available on all models
Scan to Mobile Devices and cloud-based services: A range of solutions is available to provide scanning to mobile devices or cloud-based services depending on your requirements. Please contact your sales representative for further information.
TWAIN/WIA Pull scanning available on all models

SEND SPECIFICATIONS

Destination

Address Book

Send resolution (dpi)

E-mail/Internet FAX (SMTP), SMB v3.0, FTP, WebDAV, Mail Box, Super G3 FAX (Optional), IP Fax (Optional)
LDAP (2,000)/Local (1,600)/Speed dial (200)
600 x 600, 400 x 400, 300 x 300, 200 x 400, 200 x 200, 200 x 100, 150 x 150, 100 x 100



TECHNICAL SPECIFICATIONS

imageRUNNER ADVANCE C7500 III series

| | | | |
|-------------------------------------|---|---|---|
| Communication protocol | File: FTP (TCP/IP), SMB v3.0, WebDAV | CONSUMABLES | |
| File Format | E-mail/1-Fax: SMTP, POP3 Standard: TIFF, JPEG, PDF (Limited Colour, Compact, Searchable, Apply policy, Optimize for Web, PDF A/1-b, Encrypted), XPS (Compact, Searchable), Office Open XML (PowerPoint, Word), PDF/XPS (Device Signature) Optional: PDF (Trace & Smooth), PDF/XPS (User Signature) | Toner Cartridges | C-EXV 52 TONER BK/C/M/Y |
| Universal Send Features | Original Type Selection, Two-sided Original, Book to Two Pages, Different-size Originals, Density Adjustment, Sharpness, Copy Ratio, Erase Frame, Job Build, Sender's Name (TTI), Delayed Send, Preview, Job Done Notice, File Name, Subject/Message, Reply-to, E-mail Priority, TX Report, Original Content Orientation, Skip Blank Pages, Detect Feeder Multi Sheet Feed | Toner Yield (Estimated @ 5% Coverage) | C-EXV 52 TONER BK: 82,000 pages C-EXV 52 TONER C/M/Y: 66,500 pages |
| FAX SPECIFICATIONS | | SOFTWARE AND PRINTER MANAGEMENT | |
| Maximum Number of Connection Lines | 2 | Tracking and reporting | Universal Login Manager* (ULM): Manage your costs easily by using the embedded reporting capability to identify and control costs on a user-based level by device. |
| Modem Speed | Super G3: 33.6 kbps G3: 14.4 kbps | | uniFLOW Online Express: Combining with ULM you can gain further control and highlight expenditures per users/department and pinpoint where costs can be scaled down from a central cloud based location. *Installation, activation & registration required |
| Compression Method | MH, MR, MMR, JBIG | Remote management tools | iW Management Console: Server-based software for centralised management of a fleet of devices (includes monitoring or consumables, status monitoring and alerts, distribution of address books, configuration settings, firmware and MEAP applications, meter capture and reporting, driver and resource management) |
| Resolution (dpi) | 400 x 400, 200 x 400, 200 x 200, 200 x 100 | | eMaintenance: Compatible with eMaintenance services via embedded RDS (Enables meter capture, automatic consumables management, remote diagnostics and reporting for service providers to offer efficient, fast and proactive maintenance) |
| Sending/Recording Size | A3, A4, A4R, A5*, A5R*, B4, B5*, B5R* * Sent as A4 * Sent as B4 | | Content Delivery System: Allows the Remote distribution of firmware, iR options and MEAP applications; Remote User Interface (RUI) Web based interface to each device that helps to provide remote device management and control |
| FAX memory | Up to 30,000 pages | Scanning software | Network ScanGear: TWAIN-compliant scanner driver that enables computers on a network to use the pull scan functionality of the device |
| Speed dials | Max. 200 | | |
| Group dials/destinations | Max. 199 dials | | |
| Sequential broadcast | Max. 256 addresses | | |
| Memory backup | Yes | | |
| Fax Features | Original Type Selection, Two-sided Original, Book to Two Pages, Different-size Originals, Density (for Scanning), Sharpness, Copy Ratio, Erase Frame, Job Build, Sender's Name (TTI), Selecting the Telephone Line, Direct Send, Delayed Send, Preview, Job Done Notice, TX Report, Detect Feeder Multi Sheet Feed | | |
| STORE SPECIFICATIONS | | FIERY PRINT CONTROLLER SPECIFICATIONS (EMBEDDED) | |
| Mail Box (Number supported) | 100 User Inboxes, 1 Memory RX Inbox, 50 Confidential Fax Inboxes, 30,000 Maximum Pages Stored | Optional/Standard | Optional on all models |
| Advanced Space | Communication Protocol: SMB or WebDAV Supported Client PC: Windows (Windows/7/8/10) Concurrent Connections (Max.): SMB: 64, WebDAV: 3 (Active Sessions) | Name | imagePASS N2 (Embedded) |
| Advanced Space available disc space | Approx. 16GB (Standard HDD) | Print Resolution (dpi) | 1200 x 1200, 600 x 600 |
| Advanced Space Features | Approx. 480GB (with option 1TB HDD) | Page Description Language(s) | Adobe PS3, PCL6 |
| Memory Media | Authentication for Advanced Space Log-in, Sort Function, Printing a PDF File with a Password, imageWARE Secure Audit Manager Support Standard: USB Memory | Memory | 4GB (1 x 4GB) |
| SECURITY SPECIFICATIONS | | Hard Disk Drive | 500 GB SATA |
| Authentication | Standard: Universal Login Manager (Device and Function Level Log-in), uniFLOW Online Express*, User Authentication, Department ID Authentication, Access Management System Optional: My Print Anywhere secure print (Requires uniFLOW) * No charge for this solution; however activation is required. | Processor Speed | Intel Pentium G4400 (3.3 GHz) |
| Data | Standard: Trusted Platform Module (TPM), Hard Disk Password Lock, Hard Disk Drive Erase, Mail Box Password Protection, Hard Disk Drive Encryption(FIPS140-2 Validated), Common Criteria Certification (DIN ISO 15408) Optional: Hard Disk Drive Mirroring, Hard Disk Drive removal, Data Loss Prevention (Requires uniFLOW) | System | Fiery F5350 |
| Network | Standard: IP/Mac Address Filtering, IPSEC, TLS Encrypted Communication, SNMP V3.0, IEEE 802.1X, IPv6, SMTP Authentication, POP Authentication before SMTP, S/MIME | Fonts | PS: 138 Fonts PCL: 113 Fonts |
| Document | Standard: Secure Print, Adobe LiveCycle® Rights Management ES2.5 Integration, Encrypted PDF, Encrypted Secure Print, Device signature, Secure Watermarks Optional: User signature, Document Scan lock | Supported Operating Systems | Windows 7 32 and 64 bit / Windows 8.1 32 and 64 bit / Windows10 32 and 64 bit / Windows Server 2012 64bit only / Windows Server 2012 R2 64bit only / Windows Server 2016 R2 64bit only / MAC OS (10.11, 10.12, 10.13, 10.14) 2 x Ethernet (1000Base-T/100Base-TX/10Base-T), USB3.0 x 2 (Rear), USB2.0 x 4 (Rear) |
| ENVIRONMENTAL SPECIFICATIONS | | Interface | |
| Operating Environment | Temperature: 10 to 30 °C Humidity: 20 to 80 % RH (Relative Humidity) | Network protocols | TCP/IP (FTP, SMTP, POP, HTTP, SNMP, LDAP, SLP, SMB, LPD, IPP, WS-Discovery, Bonjour, Direct Mobile Printing, Port9100, SNT, 802.1X, DHCP, DNS, NTP) PDF1.7, EPS, TIFF6, JDF1.4/JMF(OP) FreeForm v1, v2.1 |
| Power source | iR-ADV C7565i III/C7570i III: 220-240 V (±10 %), 50/60 Hz (±2 Hz), 10 Amp iR-ADV C7580i III: 220-240 V (±10 %), 50/60 Hz (±2 Hz), 11 Amp CEE 7/7 (230V) | Direct Print | |
| Plug (Main Unit) | | VDP | Fiery Command WorkStation 6 / Paper Catalog / Fiery Spot-On / Fiery Remote Scan / Fiery Hot Folders & Virtual Printers |
| Power consumption | Maximum: Approx. iR-ADV C7580i III: 2,500 W, iR-ADV C7570i III/C7565i III: 2,000 W Printing: Approx. 1,472 W* Standby: Approx. 136.6 W* Sleep mode: Approx. 0.9 W* Plug In Off: Approx. 0.3 W* * Reference value: measured one unit * 0.9W sleep mode is not available in all circumstances due to certain settings. * Reference value, Quick start mode OFF | Fiery Print Controller Standard Features | Fiery Impose / Fiery Compose / Fiery Impose and Compose / Productivity Package Web Activate (Include Fiery JDF) |
| Noise levels (BW/CL) | Sound Power Level (LwAd) iR-ADV C7580i III: Active(BW): 76.3 dB or Less* Active(CL): 75.5 dB or Less* iR-ADV C7570i III: Active(BW): 75.5 dB or Less* Active(CL): 75.1 dB or Less* iR-ADV C7565i III: Active(BW): 75.1 dB or Less* Active(CL): 74.7 dB or Less* Standby: 52 dB* Sound Pressure (LpAm) Bystander's position: (2-sided/1-sided) iR-ADV C7580i III: Active(BW): 55/56 dB* Active(CL): 55/56 dB* Standby: 34 dB* iR-ADV C7570i III: Active(BW): 55/55 dB* Active(CL): 54/55 dB* Standby: 34 dB* iR-ADV C7565i III: Active(BW): 55/55 dB* Active(CL): 54/55 dB* Standby: 34 dB* * DE-UZ205 (2017) compliant (*Data taken from Blue Angel Standard value) * Reference value: measured only one unit with ISO7779, described with ISO9296 (1988) | Fiery Print Controller Options | |
| Standards | Blue Angel | HW Platform | E400 |
| | | Base OS | Debian of Linux |
| | | Power source | AC100-240V, 50Hz/60Hz, 3.0A (100V) - 1.3A (240V) |
| | | Maximum Power consumption | 47 W |
| | | Dimensions (W x D x H) | 285 x 93 x 295 mm |
| | | Weight | Fiery unit only (with plate):4.95 kg |
| | | PAPER SUPPLY OPTIONS | |
| | | PAPER DECK UNIT-E1 | Paper Capacity: 3,500 sheets (80 gsm) Paper Type: Thin, Plain, Recycled, Thick, Colour, Pre-punched, Letterhead, Bond Paper Size: A4, B5 Paper Weight: 52 to 256 gsm Power Source: From the Main Unit Dimensions (W x D x H): 340 x 630 x 572 mm Weight: Approx. 34 kg |
| | | POD DECK LITE-C1 | Paper Capacity: 3,500 sheets (80 gsm) Paper Type: Thin, Plain, Recycled, Thick, Colour, Pre-punched, Letterhead, Bond, Tab, Transparency, Label, Coated, Textured, Tracing, Envelope* Paper Size: SRA3, A3, A4, A4R, A5R, B4, B5, B5R, Envelope [No.10(COM10), Monarch, DL, ISO-C5], Custom size: 139.7 x 148.0 mm to 330.2 to 487.7 mm Paper Weight: 52 to 300 gsm Power Source: 220-240V/1.2A 50/60Hz Dimensions (W x D x H): 633 x 686 x 574 mm Weight: Approx. 68 kg *Requires Envelope Feeder Attachment-G1 |
| | | MULTI-DRAWER PAPER DECK-C1 | Paper Capacity: 2,000 sheets x 3 drawers, total 6,000 sheets (80 gsm) Paper Type: Thin, Plain, Thick, Recycled, Colour, Pre-punched, Letterhead, Bond, Tab, Transparency, Label, Coated, Textured Paper Size: SRA3, A3, A4, A4R, A5R, B4, B5, B5R, Custom size: 139.7 x 182.0 mm to 330.2 x 487.7 mm Paper Weight: 52 to 300 gsm Power Source: 220-240V/1.7A 50/60Hz Dimensions (W x D x H): 950 x 797 x 1,040 mm Weight: Approx. 155 kg |



TECHNICAL SPECIFICATIONS

imageRUNNER ADVANCE C7500 III series

OUTPUT OPTIONS COPY TRAY-R2

Provides a simple tray for basic output needs.
Capacity: 250/100 sheets (1-sided/2-sided, 80 gsm)

STAPLE FINISHER-V2 (External)

Number of Trays: 3
Upper Tray Capacity*: A4, A5, A5R, A6R, B5: 250 sheets, A3, A4R, B4, B5R: 125 sheets
Mid Tray Capacity*: A4, A5, A5R, A6R, B5: 250 sheets, A3, A4R, B4, B5R: 125 sheets
Lower Tray Capacity*: A4, A5, A5R, B5: 3,000 sheets SRA3, A3, A4R, B4, B5R: 1,500 sheets, A6R: 250 sheets
* with 81.4 gsm paper
Paper Weight: Upper Tray 52 to 256 gsm, Mid Tray 52 to 256 gsm
Lower Tray 52 to 300 gsm
Staple Position: Corner, Double
Staple Capacity: Corner and Double Stapling:
A4/B5: 65 sheets (52 to 90 gsm)
A3/A4R/B4: 30 sheets (52 to 90 gsm)
Eco Staple:
A3/A4: 5 sheets (52 to 64 gsm)
4 sheets (65 to 81.4 gsm)
3 sheets (81.5 to 105 gsm)
Staple On Demand: 65 sheets (90 gsm)
Dimensions (W x D x H): 656 x 623 x 1,195 mm (when the extension tray and rotary tray are extended)
Weight: Approx. 35 kg

BOOKLET FINISHER-V2 (External)

(Includes the above STAPLE FINISHER-V2 basic staple specifications.)
Saddle Stitch paper size: A3, A4R, B4, Custom Size (195.0 x 270.0 mm to 304.8 x 457.2 mm)
Saddle Stitch Staple Capacity: 20 sheets x 10 sets (52 to 81.4 gsm) (including 1 cover sheet up to 256 gsm)
Non Staple Folded Bunch Capacity: up to 3 sheets (52 to 105 gsm)
Dimensions (W x D x H): 656 x 623 x 1,195 mm (when the extension tray and rotary tray are extended)
Weight: Approx. 58 kg

STAPLE FINISHER-X1 (External)

Number of Trays: 3
Upper Tray Capacity*: A4, A5R, B5: 1,500 sheets, SRA3, A3, A4R, A5, B4, B5R, 750 sheets, A6R: 250 sheets
Mid Tray Capacity*: A4, A5R, B5: 250 sheets, A3, A4R, A5, A6R, B4, B5R: 125 sheets
Lower Tray Capacity*: [Cascade-Load mode] A4, B5 2,500 sheets, [Random-Load mode] A4, A5R, B5: 1,500 sheets, SRA3, A3, A4R, A5, B4, B5R: 750 sheets, A6S: 250 sheets
* with 81.4 gsm paper
Paper Weight: Upper Tray 52 to 300 gsm
Mid Tray 52 to 300 gsm
Lower Tray 52 to 300 gsm
Staple Position: Corner, Double
Staple Capacity: Corner and Double Stapling:
A4/B5: 100 sheets (52 to 80 gsm)
A3/B4/A4R: 50 sheets (52 to 80 gsm)
Power Source: 100-240V, 50/60Hz, 2.8A
Dimensions (W x D x H): 782 x 765 x 1,040 mm (when the extension tray is extended)
Weight: Approx. 64 kg

BOOKLET FINISHER-X1 (External)

(Includes the above STAPLE FINISHER-X1 basic staple specifications.)
Saddle Stitch paper size: SRA3, A3, A4R, B4, Custom Size (210.0 x 279.4 mm to 330.2 x 487.7 mm)
Saddle Stitch Staple Capacity: 20 sheets x 5 sets (60 to 81.4 gsm) (including 1 cover sheet up to 300 gsm)
Non Staple Folded Bunch Capacity: up to 5 sheets (60 to 105 gsm)
Power Source: 100-240V, 50/60Hz, 2.8A
Dimensions (W x D x H): 896 x 765 x 1,040 mm (when the extension tray is extended)
Weight: Approx. 110 kg

2/4 HOLE PUNCHER UNIT-A1

(Requires either the STAPLE FINISHER-V2 or BOOKLET FINISHER-V2)
Two or Four Holes
Acceptable Punch Paper Weight: 52 to 300 gsm
Acceptable Punch Paper Size: Two holes A3, A4, A4R, A5, B4, B5, B5R; Four holes A3, A4
Power Source: From the Main Unit

4 HOLE PUNCHER UNIT-A1

(Requires either the STAPLE FINISHER-V2 or BOOKLET FINISHER-V2)
Four Holes
Acceptable Punch Paper Weight: 52 to 300 gsm
Acceptable Punch Paper Size: Four holes A3, A4, A4R, A5, B4, B5, B5R
Power Source: From the Main Unit

PUNCHER UNIT-BG1(2/F4H)

(Requires either the STAPLE FINISHER-X1 or BOOKLET FINISHER-X1)
Two or Four Holes
Acceptable Punch Paper Weight: 52 to 256 gsm
Acceptable Punch Paper Size: Two holes A3, A4, A4R, A5, B5R Four holes A3, A4
Power Source: From the Finisher

PUNCHER UNIT-BH(S4H)

(Requires either the STAPLE FINISHER-X1 or BOOKLET FINISHER-X1)
Four Holes
Acceptable Punch Paper Weight: 52 to 256 gsm
Acceptable Punch Paper Size: Four holes A3, A4, A4R, A5, B4, B5, B5R
Power Source: From the Finisher

MULTI FUNCTION PROFESSIONAL PUNCHER-A1 / B1

(Requires either the STAPLE FINISHER-X1 or BOOKLET FINISHER-X1)
Acceptable Punch Paper Size: SRA3, A3, A4, A4R
Acceptable Punch Paper Weight: Bypass: 52 to 300 gsm; Punch: 75 to 300 gsm
Supported Punch Dies (Optional) :
A4: Loose Leaf (2- or 4-hole), Plastic Comb (21-hole), Velo Bind (12-hole), Twin Loop (23- or 34-hole), Color Coil (47-hole)
Power Source: 230V/50Hz 1.9A
Dimensions (W x D x H): 445 x 795 x 1,040 mm
Weight: Approx. 102 kg

INNER BOOKLET TRIMMER-A1

(Requires the BOOKLET FINISHER-X1)
Waste Tray Capacity: 1,500 Sheets
Acceptable Paper Weight: 60 to 300 gsm
Trim Amount: 2 to 20 mm
Acceptable Paper Size: 210 x 279.4 mm to 330.2 x 487.7mm
Power Source: From Finisher

DOCUMENT INSERTION UNIT-Q1

(Requires either the STAPLE FINISHER-V2 or BOOKLET FINISHER-V2)
Number of trays: 1
Tray Capacity: 100 Sheets (80 gsm)
Acceptable Paper Type: Thin, Plain, Recycled, Colour, Thick, Textured, Bond, Coated, Tab, Letterhead
Acceptable Paper Sizes: SRA3, A3, A4, A4R, B4, B5, B5R, Acceptable Paper Weight: 60 to 256 gsm
Power Source: 100-240V/50/60Hz 1.0A
Dimensions (W x D x H): 247 x 679 x 1,242 mm (width excluding document tray)
Weight: Approx. 40 kg

DOCUMENT INSERTION/ FOLDING UNIT-K1

(Requires either the STAPLE FINISHER-V2 or BOOKLET FINISHER-V2)
Number of trays: 1
Tray Capacity: 100 Sheets (80 gsm)
Supported Folding Type: Z-Fold, C-Fold
Acceptable Paper Type: Z-Fold/C-Fold: Thin, Plain, Recycled, Colour, Insertion Unit: Thin, Plain, Recycled, Colour, Thick, Letterhead, Bond, Coated, Tab, Textured
Acceptable Paper Sizes: Z-Fold: A3, A4R, B4 C-Fold: A4R
Insertion Unit: SRA3, A3, A4, A4R, B4, B5, B5R
Acceptable Paper Weight: Z-Fold/C-Fold: 60 to 105 gsm, Insertion Unit: 60 to 256 gsm
Power Source: 100-240V/50/60Hz 1.0A
Dimensions (W x D x H): 247 x 679 x 1,242 mm (width excluding document tray)
Weight: Approx. 76 kg

DOCUMENT INSERTION UNIT-N1

(Requires either the STAPLE FINISHER-X1 or BOOKLET FINISHER-X1)
Number of trays: 2
Tray Capacity: Upper Tray: 200 Sheets (80 gsm), Lower Tray: 200 Sheets (80 gsm)
Acceptable Paper Type: Thin, Plain, Recycled, Colour, Thick, Pre-punched, Letterhead, Bond, Coated, Tab, Tracing, Textured
Acceptable Paper Sizes: SRA3, A3, A4, A4R, B4, B5, B5R, Custom size (182.0 x 182.0 mm to 330.2 x 487.7 mm)
Acceptable Paper Weight: 52 to 300 gsm
Power Source: 100-240V/50/60Hz 1.0A
Dimensions (W x D x H): 336 x 793 x 1,407 mm (width excluding document tray)
Weight: Approx. 61 kg

PAPER FOLDING UNIT-J1

(Requires either the STAPLE FINISHER-X1 or BOOKLET FINISHER-X1)
Supported Folding Type: Z-Fold, Accordion Z-Fold, C-Fold, Half-Fold, Double Parallel Fold
Acceptable Paper Type: Thin, Plain, Recycled, Colour, Bond
Acceptable Paper Sizes: Z-Fold: A3, A4R, B4 Accordion Z-Fold, C-Fold, Half-Fold, Double Parallel Fold: A4R
Acceptable Paper Weight: Z-Fold, Accordion Z-Fold, C-Fold, Half-Fold: 52 to 105 gsm Double Parallel Fold: 52 to 90 gsm
Power Source: From the Finisher
Dimensions (W x D x H): 336 x 793 x 1,190 mm
Weight: Approx. 71 kg

OTHER OPTIONS STAPLE CARTRIDGE

STAPLE-N1 - for Stapling (3 x 5,000 pcs) (for Staple Finisher-X1 and Booklet Finisher-X1)
STAPLE-P1 - for Saddle Stitching (2 x 5,000 pcs) (for Booklet Finisher-X1)
STAPLE CARTRIDGE-X1 - For Stapling (3 x 5,000 pcs) (Staple Finisher-V2 and Booklet Finisher-V2)
STAPLE CARTRIDGE-Y1 - For saddle stitching (2 x 2,000 pcs) (for Booklet Finisher-V2)

For a complete list of all Hardware accessories, please refer to our website specifications page or online product configurator.

Software & Solutions



Certifications and compatibility



Canon Ireland
3006 Lake Drive
Citywest, Saggart
Co. Dublin, Ireland
Telephone No: 01 2052400
2052400
Facsimile No: 01 2052525
canon.ie

Canon (UK) Ltd
Woodhatch
Reigate
Surrey RH2 8BF
Telephone No: 01737 220000
220000
Facsimile No: 01737 220022
canon.co.uk

Canon Inc.
canon.com
Canon Europe
canon-europe.com
English edition
© Canon Europa N.V., 2019

