

Reference : AT-SG-001-07

Issue Date : June. 5, 2014

Revision Date : January. 6, 2021

SAFETY DATA SHEET

1. Chemical product and company identification

Product Name : ASAHITACK SG1860G
 Supplier Name : ASAHI CHEMICAL SYNTHETIC CO. LTD.
 Address : 2-18-10 Nakachou, Toda-si, Saitama, 335-0012 Japan
 Section in its duty : Technical Development Dept.
 Telephone : +81-48-441-5835
 FAX : +81-48-441-5642

2. Hazards Information

GHS Classification

Physical and Chemical Hazards

Flammable solids : Classification not possible
 Pyrophoric solids : Classification not possible
 Self-heating substance : Classification not possible
 Corrosive to metals : Classification not possible

Health and Environmental Hazards

Acute toxicity Oral : Not classified
 Acute toxicity Dermal : Not classified
 Acute toxicity Inhalation Gasses : Not applicable
 Acute toxicity Inhalation Vapors : Not applicable
 Acute toxicity Inhalation Dusts : Classification not possible
 Acute toxicity Inhalation Mists : Classification not possible
 Skin corrosion / irritation : Classification not possible
 Serious eye damage / eye irritation : Classification not possible
 Respiratory sensitization : Classification not possible
 Skin sensitization : Classification not possible
 Germ cell mutagenicity : Classification not possible
 Carcinogenicity : Classification not possible
 Reproductive toxicity : Classification not possible
 Specific target organ systemic toxicity
 Single exposure : Classification not possible
 Repeated exposure : Not classified
 Aspiration hazard : Classification not possible
 Hazardous to the aquatic environment
 Acute toxicity : Classification not possible
 Chronic toxicity : Classification not possible
 Hazardousness to the ozone layer : Classification not possible

GHS Label Elements

Symbol : None
 Signal Word : None
 Hazard Statement : None

Precautionary statements

- Prevention : Obtain and read an instruction manual before use.
 Don't handle till read and understand all security attention.
 Avoid breathing dust / fume / mist / vapor / spray.
 Wear suitable protective gloves or personal protective tools if necessary.
 Use in well-ventilated area and ventilate the workshop enough.
 Don't take out the polluted work-clothes from workshop.
 Wash clothing when you reuse polluted clothes.
- Response : Wash hands thoroughly after handling.
 If adhering to the skin, wash thoroughly with soap and plenty of water soap.
 If skin irritation or a rash appeared, get medical advice / attention.
 If the eyes, wash carefully with water.
 Call doctor/physician if you feel unwell.
- Storage : Store in sealable containers with key in well-ventilated place.
- Disposal : Dispose in accordance with local / regional / national / international regulation.

3. Composition / information on ingredients

- Chemical substance or mixture : mixture
 Chemical name or generic name : Synthetic rubber system hot-melt adhesives
 Ingredients and contents : Styrene block copolymer etc. 100%

【Density range of constitution ingredients (Japan)】

Constitution ingredients	Density range	Public announcement reference number	CAS Number	Remarks
Styrene block copolymer	Closed	Existing	Closed	Thermoplastics
Petroleum resin	Closed	Existing	Closed	Tackifier resin
Mineral oil	60~70%	Closed	Closed	Softener
Titanium oxide	<1.0%	(1)-558	13463-67-7	Coloring agent
Carbon Black	<0.1%	(5)-3328	1333-86-4	
Additive	<1.0%	(3)-1693	6683-19-8	Antioxidant
Product (mixture)	100.0%	—	—	—

【Laws and regulations object ingredients (Japan)】

Constitution ingredients	Industrial Safety & Health Act	Pollutant Release and Transfer Regulation (PRTR)	Poisonous and Deleterious Substances Control Act
Mineral oil	Dispiay,notification object No.168	Non-correspondence	Non-correspondence
Titanium oxide	Notifiable substances No.191	Non-correspondence	Non-correspondence

(Notice : Follow all regulations and laws in your country)

4. Emergency measures

- Inhalation : Remove to fresh air and keep at rest in a position comfortable for breathing, and then get medical advice / attention immediately.
If breathing has stopped, apply artificial respiration after clothes are loosened and the respiratory airway is secured, and call the doctor immediately.
When breathing and vomiting, do a brain to the side.
Don't give anything from the mouth to the victim when not conscious.
Employ an attendant to the victim, and must not leave alone.
- Skin contact : In the case of contact of the degree without the burn, wash it away with water well and wash it with soap more, then call a doctor.
When you touched to the molten product , promptly cool off with plenty of water, and then get medical attention.
Don't peel off forcibly when the product and clothes, etc. stick in the skin.
(Don't crush the blister, and do not peel off the skin.)
Call a doctor if you feel unwell.
- Eye contact : In case of contact with eyes, rinse with plenty of water for at least 15 minutes, and get medical attention immediately.
Remove contact lenses (if worn) if easily possible, then continue rinsing.
When a molten product entered to the eyes, cool enough with plenty of water immediately, and get medical attention to the burn.
(Don't rub eyes, and open it forcibly.)
- Ingestion : If conscious, give plenty of water or milk to drink, and get immediately medical attention.(show this container or label)
- Concise information on the most important symptom
: The vapor occurring at the time of heating, stimulates eyes, a nose, a throat, respiratory organs and a mucous membrane.
The vapor occurring at the time of heating, causes symptoms such as unpleasantness, a headache, and a lacrimation.
If the molten product touched any body part, a serious burn is caused.
- Protection of a person taking a first-aid measure
: Wear appropriate protective equipment, when there are a possibility of coming in contact with the molten product and a possibility of inhaling vapor.
- Special instructions for the doctor
: Wear appropriate protective equipment, when there are a possibility of coming in contact with the molten product and a possibility of inhaling vapor.

5. Fire-fighting measures

- Fire extinguisher : Powder fire extinguishing medicine, bubble fire extinguishing medicine, CO₂, sand, water(a large quantity of water), etc.
- Fire extinguisher that are not suitable
: Don't use cylinder shape water, because it might expand a fire.
- Specific dangerous hazardous property at a fire
: Carbon dioxide, carbon monoxide, in addition, nitrogen oxide-based gas, and hazardous gases or vapors may evolve on burning.
- Specific fire extinguishing method
: Perform the fire extinguishing work from windward.

It is noted enough that cylinder shape water scatters the hot water or the molten products, and has possibility of the burn.

In this case, it is effective to intercept air by using the fire foam.

Stop the supply of combustion source immediately, and water the equipments of surroundings and it cools off.

Prohibit people except the parties concerned from entering around the fire occurrence place, and let them evacuate to the safe place.

Perform an appropriate measures so that the material which has an influence on environment should not flow out by watering for fire extinguishing.

Protection for firefighters

: On the occasion of fire extinguishing work, wear complete protective clothing, perform a step of the prevention of burn, and perform fire fighting from windward.

Because toxic gas may be generated, wear a tool for an appropriate breath protection (a gas mask for organic gas or self-contained breathing apparatus).

6. Accidental release measures

Personal precaution : Stretch a rope around leaking, and prohibit peoples other than persons concerned from entering in the zone.
Evacuate all non essential personnel from the area immediately.

Wear the appropriate protection equipment, and perform the collecting work from windward.

When the molten product leaked, allow the product to cool/ solidify and remove as a solid.

Perform enough ventilation till collection is over.

Environmental precaution : Do appropriate measures to inform the leakage to neighboring resident, because there is a possibility of feeling the smell unpleasantly according to the person.

Prevent the leaking dispersion of the material to the outside, the outflow to the river, drainage, and the drainage trench, and infiltration to the soil.

Moreover, make efforts to collect the whole quantity when flowing out.

Recovery method : If the molten product leaked, cool off and solidify.

And then collect it as a solid state in sealable containers.

Prevention of secondary hazards

: Remove all sources of ignition from the circumference immediately.

7. Handling and storage precaution

Handling

Technical measures : Fire attention.

Use special melting equipment and coating equipment.

Don't heat product directly by the fire etc..

Near a handling place, install the equipment to cool, to wash a hand, a face and a body, and to gargle in emergency.

- Wear the protective equipment when there is a possibility of inhalation or contact to the skin.
 Perform the handling at a good place of the ventilation, and also perform the ventilation of the workshop enough.
 Install a local exhaust or the total exhaust if necessary.
- Safe handling advice : Do not handle until reading and understanding all the safety attention.
 Don't treat the containers violently to lead to damage.
 Avoid breathing vapors and fumes from the molten product at heating.
 Perform the handling in the outdoors as much as possible from windward.
 After handling, wash a hand, a face and a body well, and also gargle.
 Prohibit the entry to the handling places other than the person concerned.
- Storage
- Technical measures : Keep it in the inventory location of "Designated flammable good".
 Seal it up so that garbage and water do not enter, and keep it.
 Store in a well-ventilated, cool and dark place away from fire sources and high temperature objects.
 Avoid the direct sunshine because the direct sunshine may decrease the performance of the product remarkably.
- Packaging materials : The wrapping material which prevent moisture absorption, electrostatic outbreak and the package which is hard to destroy are desirable, if possible.

8. Exposure controls / personal protection

Management density : No information is available.

Permissible Exposure Limit : (as Permissible Exposure Limit for constitution ingredients)

Constitution ingredients	Permissible Exposure Limit	
	Japan Association on Industrial Health	ACGIH
Styrene block copolymer	No information is available	TWA 10mg/ m ³
Mineral oil	3mg / m ³ (mineral oil mist)	TWA 5mg/ m ³ (mineral oil mist)
Titanium oxide	4mg/ m ³ (Total dust)	TWA 10mg/ m ³
Carbon black	4mg/ m ³ (Total dust)	TWA 3.5mg/ m ³

Note : Total dust is referred to the standard value of "the 2nd, 3rd kind dust".

Equipment measures : In mixing and molding work, it is desirable to use sealing up-type melting equipment.
 Install a local exhaust or the total exhaust, if necessary.
 Near a handling place, install the equipment to cool, to wash a hand, a face and a body, and to gargle in emergency.

Personal protection equipment

- Respiratory protection : Breathing protection when handling the molten product,
Such as gas mask for organic gas, dust protective mask and
Supply air mask, etc.
- Hand protection : Heat-insulating gloves when handling the molten product.
- Eye protection : Safety goggles when handling the molten product.
- Skin and body protection: Heat protective suits when handling the molten product.
- Hygiene measures : Wash hands and gargle after handling.

9. Physical and chemical properties

Physical state

- Shape : Solid
- Color : Gray
- Odor : It is
- PH : No data

The specific temperature/temperature range where a physical state changes

- Boiling point and : No data
- Boiling range
- Softening point : 119 °C
- Decomposition temperature : No data
- Flash point : No data
- Ignition point : No data
- Explosion range : No data
- Vapor pressure : No data
- Vapor density : No data
- Density : 0.90 (g/cm³)
- Solubility : Not soluble in water
- VOC, weight percent : 0.00% (Toluene, Xylene, Ethylbenzene, Styrene)

10. Stability and reactivity

- Stability : Stable in normal conditions.
But the performance of the product may change by heat and
Sunshine.
- Hazardous reaction potential: Stable. No self reactivity.
- Condition to avoid : Avoid all sources of ignition, direct sunshine, water and
excessive heat.
- Incompatible products : No information
- Hazardous decomposition products
: Carbon dioxide, carbon monoxide and other poisonous gas.

11. Toxicological information

(1) Acute toxicity

- (Oral) : (Styrene block copolymer) LD50 > 2000mg/kg
- (Titanium oxide) LD50 > 10000mg/kg
- (Carbon black) LD50 > 15400mg/kg
- (Additive) rat LD50 > 2000mg/kg

Because the mixture is ATEmix>2000 , it is said that it is out of division.
(Classification JIS)

(Dermal) : (Styrene block copolymer) LD50 > 2000mg/kg
 (Titanium oxide) LD50 > 10000mg/kg
 (Additive) rat LD50 > 2000mg/kg

Because the mixture is ATEmix>2000 , it is said that it is out of division.
 (Classification JIS)

(Inhalation:gas,vapor) : Because the mixture was a solid, a classification was inapplicable

(Inhalation:mist,dust) : No information

(2) Skin corrosion / stimulativeness

: No information (Classification JIS)

(3) Serious eye damage / stimulativeness to eyes

: (Titanium oxide) Category 2B
 No information

(4) Respiratory organs sensitization

: No information

(5) Skin sensitization : No information

(6) Germ cell mutagenicity : No information

(7) Carcinogenicity : (Carbon black) Category 2
 No information

(8) Reproductive toxicity : No information

(9) Specific target organ / systemic toxicology

Single exposure : (Titanium oxide) Category 3
 No information

Repetitive exposure : (Titanium oxide, Carbon black) Category 1

Content of the mixture in Category 1 because it is less than 1%, I was classified.

(10) Aspiration respiratory organs hazard

: No information

Other information : The data of this product in itself are not provided.

12. Ecological information

(1) Hazardous to the aquatic environment-acute toxicity : No information

(2) Hazardous to the aquatic environment-chronic toxicity : (Titanium oxide) Category 4
 No information

(3) Hazardousness to the ozone layer : No information

Other information : The data of this product in itself are not provided.

13. Disposal considerations

Residual waste : Dispose in accordance with the current local regulations in the own country.
 Dispose after completely cooling off, if waste is a high temperature.

Contaminated containers or packing : Dispose of an empty container after completely removing contents.
 Dispose in accordance with the current local regulations in the own country.

14. Transport information

- UN classification : Not the dangerous materials of the United Nations definition.
- Domestic regulation : Follow the mode of transportation established in applied laws and ordinances in the own country.
- Specific safety measures and a condition of the transportation (in Japan)
- : Fire attention.
 - Transport it by the container and the loading method according to regulations of "Fire Service Act", because it corresponds to "Designated flammable goods" of this law.
 - Confirm that there are not the damage, corrosion and a leak of the container before the transportation.
 - Avoid the direct sunshine, and keep the water wet, and the water getting wet and pouring water and the high temperature are assumed to be strict prohibition, and also keep dry.

15. Regulatory information

Take the application of the laws and ordinances of the own country.

In Japan :

PRTR(Pollutant Release and Transfer Regulation)

: Non-correspondence

Industrial Safety Control Act

: Article57-2 Display,notification object

Mineral oil (No. 168)

Article57-2 Notifiable substances

Titanium oxide (No. 191)

Poisonous and Deleterious Substances Control Act

: Non-correspondence

Fire Service Act

: Article9-4 Designated flammable goods (Synthetic resins)
(more than 3,000kg)

Waste Management and Public Cleaning Act

: Article 2 (Waste plastics)

16. Other information

Literature references :

"Model MSDS Creation and guidance of GHS MSDS corresponding" Japan Adhesive Industry Association

The Chemical Daily published

"Globally Harmonized System of Classification and Labelling of Chemicals (GHS)" (five revision)

JIS Z 7253: 2012 "The methods of communicating hazard information of chemicals based on GHS - labels, safety data sheets and display of workplace within"

JIS Z 7252: 2009 "Classification method of chemical substances based on the GHS"

National Institute of Technology and Evaluation HP (comprehensive chemical substance information providing system)

Raw materials supplied by the manufacturer (product) Safety Data Sheet

Others :

It has been prepared on the basis of the information available at the moment of our book, but does not guarantee, such as aptitude harmlessness accuracy of the information, credibility, product safety, for applications.

Among the information in this document, guaranteed value, the value "content", "composition and ingredient information," and "physical and chemical properties" is not a standard value.

Unknown hazards, risk, and also considered the chemical products of all, there may not be enough information necessarily dangerous, hazard, evaluation, and careful attention must be paid to the handling.

In addition, since the notes contained in this document are those intended for normal handling, as a reference to this, the responsibility of their own, your on the implement appropriate safety measures in accordance with the actual situation of the handling of individual Please use.

This document may be revised new information, the revision of the law, by reason of the review, and other content.

If you have received a revised version of the SDS, and discard the old (M) SDS.

The reference of mention contents :

Technical Development Dept. TEL +81-48-441-5835
FAX +81-48-441-5642