

Printing date 31.05.2021

Version number 32

Revision: 31.05.2021

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

· 1.1 Product identifier

- Trade name: GRF BISON/CONTACT TIX TI 5L*1 L221
- **1.2 Relevant identified uses of the substance or mixture and uses advised against** No further relevant information available.
- · Application of the substance / the mixture Adhesive

1.3 Details of the supplier of the safety data sheet Manufacturer/Supplier: Bison International Dr.A.F.Philipsstraat 9 NL-4462 EW Goes PO Box 160 NL-4460 AD Goes tel. +31 88 3235700 fax. +31 88 3235800 e mail: sds@boltonadhesives.com

· Further information obtainable from: Bison QESH

· 1.4 Emergency telephone number:

Emergency medical information: 8am-10pm (seven days) contact National Poisons Information Centre, Beaumont Hospital, Dublin 9. Tel 01 8092566

SECTION 2: Hazards identification

• 2.1 Classification of the substance or mixture • Classification according to Regulation (EC) No 1272/2008

GHS02 flame

Flam. Liq. 2 H225 Highly fl

H225 Highly flammable liquid and vapour.

GHS07

GHS02 GHS07

S	kin Irrit. 2	H315	Causes skin irritation.
-	ye Irrit. 2		Causes serious eye irritation.
S	TOT SE 3	H336	May cause drowsiness or dizziness.
A	quatic Chronic 3	H412	Harmful to aquatic life with long lasting effects.
· L T		ing to I ssified a	Regulation (EC) No 1272/2008 and labelled according to the CLP regulation.

(Contd. on page 2)



Printing date 31.05.2021

Version number 32

Revision: 31.05.2021

Trade name: GRF BISON/CONTACT TIX TI 5L*1 L221

(Contd. of page 1)

· Signal word Danger

- · Hazard-determining components of labelling:
- butanone methylcyclohexane

ethyl acetate

acetone

· Hazard statements

H225 Highly flammable liquid and vapour.

- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

• Precautionary statements

- P101 If medical advice is needed, have product container or label at hand.
- P102 Keep out of reach of children.
- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P261 Avoid breathing vapours.
- P370+P378 In case of fire: Use to extinguish: Water haze, Alcohol resistant foam, Fireextinguishing powder, Carbon dioxide.
- P403+P233 Store in a well-ventilated place. Keep container tightly closed.
- P501 Dispose of contents/container in accordance with national regulations.

Additional information:

EUH208 Contains Rosin. May produce an allergic reaction.

Product contains: Reportable explosives precursors. Making available, introduction, possession and use according to Regulation (EU) 2019/1148, Article 9.

- · Labelling of packages where the contents do not exceed 125 ml
- Hazard pictograms



· Signal word Danger

- · Hazard-determining components of labelling:
- butanone

methylcyclohexane

- ethyl acetate
- acetone
- Hazard statements

H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

· Precautionary statements

- P101 If medical advice is needed, have product container or label at hand.
- P102 Keep out of reach of children.
- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P261 Avoid breathing vapours.
- P403+P233 Store in a well-ventilated place. Keep container tightly closed.

(Contd. on page 3)



Printing date 31.05.2021

Version number 32

Revision: 31.05.2021

(Contd. of page 2)

Trade name: GRF BISON/CONTACT TIX TI 5L*1 L221

P501 Dispose of contents/container in accordance with national regulations.

2.3 Other hazards

· Results of PBT and vPvB assessment

• **PBT:** Not applicable.

vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Description: Adhesive

 Dangerous components: 		
CAS: 78-93-3 EINECS: 201-159-0 Index number: 606-002-00-3 Reg.nr.: 01-2119457290-43	butanone Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336	25-50%
CAS: 141-78-6 EINECS: 205-500-4 Index number: 607-022-00-5 Reg.nr.: 01-2119475103-46- XXXX	ethyl acetate Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336	10-25%
CAS: 108-87-2 EINECS: 203-624-3 Index number: 601-018-00-7 Reg.nr.: 01-2119556887-18	methylcyclohexane Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; Skin Irrit. 2, H315; STOT SE 3, H336	10-25%
CAS: 67-64-1 EINECS: 200-662-2 Index number: 606-001-00-8 Reg.nr.: 01-2119471330-49- XXXX	acetone Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336	2.5-109
CAS: 25085-50-1 ELINCS: 472-160-3 Reg.nr.: Exempt	Butylphenolformaldehyde resin Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	2.5-109
CAS: 8050-09-7 EINECS: 232-475-7 Index number: 650-015-00-7 Reg.nr.: 01-2119480418-32	Rosin	<1%
CAS: 123-26-2 EINECS: 204-613-6 Reg.nr.: 01-2119978265-26	N,N'-ethane-1,2-diylbis(12-hydroxyoctadecan-1-amide) Skin Sens. 1, H317; Aquatic Chronic 3, H412	<1%
CAS: 1314-13-2 EINECS: 215-222-5 Index number: 030-013-00-7 Reg.nr.: 01-2119463881-32	zinc oxide Aquatic Acute 1, H400; Aquatic Chronic 1, H410	<1%

(Contd. on page 4)



Printing date 31.05.2021

Version number 32

Revision: 31.05.2021

Trade name: GRF BISON/CONTACT TIX TI 5L*1 L221

(Contd. of page 3)

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information: No special measures required.
- · After inhalation:
- In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:
- Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- · After swallowing: If symptoms persist consult doctor.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- Suitable extinguishing agents:
- Water haze
- Alcohol resistant foam
- Fire-extinguishing powder
- Carbon dioxide
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture
- No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.
- Additional information
- Cool endangered receptacles with water spray.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
6.2 Environmental precautions: Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.
6.3 Methods and material for containment and cleaning up: Send for recovery or disposal in suitable receptacles. Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.
6.4 Reference to other sections See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment.

(Contd. on page 5)

IE-EN



Printing date 31.05.2021

Version number 32

Revision: 31.05.2021

(Contd. of page 4)

Trade name: GRF BISON/CONTACT TIX TI 5L*1 L221

See Section 13 for disposal information.

SECTION 7: Handling and storage

• 7.1 Precautions for safe handling
 Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).
 Ensure good ventilation/exhaustion at the workplace.
 Prevent formation of aerosols.
 • Information about fire - and explosion protection:
 Keep ignition sources away - Do not smoke.
 Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions:
- Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

- Storage class: 3
- 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

• Additional information about design of technical facilities: No further data; see item 7.

la ava di a ata u				
	vith limit values that require monitoring at the workplace:			
78-93-3 butar	none			
OEL (Ireland)	Short-term value: 900 mg/m³, 300 ppm Long-term value: 600 mg/m³, 200 ppm Sk, IOELV			
IOELV (EU)	Short-term value: 900 mg/m³, 300 ppm Long-term value: 600 mg/m³, 200 ppm			
141-78-6 ethy	l acetate			
OEL (Ireland)	Short-term value: 1468 mg/m³, 400 ppm Long-term value: 734 mg/m³, 200 ppm IOELV			
IOELV (EU)	Short-term value: 1468 mg/m³, 400 ppm Long-term value: 734 mg/m³, 200 ppm			
108-87-2 met	hylcyclohexane			
OEL (Ireland)	Long-term value: 1600 mg/m ³ , 400 ppm			
67-64-1 acetone				
OEL (Ireland)	Long-term value: 1210 mg/m³, 500 ppm IOELV			
IOELV (EU)	Long-term value: 1210 mg/m³, 500 ppm			
		(Contd. on page 6		
		IE-I		



Printing date 31.05.2021

Version number 32

Revision: 31.05.2021

Trade name: GRF BISON/CONTACT TIX TI 5L*1 L221

DNELs			
78-93-3 bi			
Oral	Consumer, oral, longterm exposition	31 mg/kg bw/day	
Dermal	Consumer, dermal, longterm exposition	412 mg/kg bw/day	
	Consumer, inhalation, longterm exposition	on 106 mg/m³	
	thyl acetate		
Oral	Consumer, oral, longterm exposition	4.5 mg/kg bw/day	
Dermal	Consumer, dermal, longterm exposition	37 mg/kg bw/day	
Inhalative	Consumer DNEL, acute inhalation	734 mg/m³	
	Consumer, inhalation, longterm exposition	on 367 mg/m³	
67-64-1 ac			
Oral	Consumer, oral, longterm exposition	62 mg/kg bw/day	
Dermal	Consumer, dermal, longterm exposition	62 mg/kg bw/day	
Inhalative	Consumer, inhalation, longterm exposition	on 200 mg/m³	
PNECs			
78-93-3 bi	tanone		
Fresh wate	er 55.8 mg/l		
Marine wa	er 55.8 mg/l		
Soil	22.5 mg/kg		
141-78-6 e	thyl acetate		
Fresh wate	er 0.26 mg/l		
Marine wa	er 0.026 mg/l		
Soil 0.22 mg/kg			
67-64-1 ac	etone		
Fresh wate	er 10.6 mg/l		
Marine wa	er 1.06 mg/l		
Soil	29.5 mg/kg		
Additiona	information: The lists valid during the	naking were used as basis.	
Personal p General p The usual Keep away Immediate Wash hand Do not inha Avoid cont Respirato Use suitab	ure controls protective equipment: rotective and hygienic measures: precautionary measures are to be adher from foodstuffs, beverages and feed. ly remove all soiled and contaminated cluds before breaks and at the end of work. ale gases / fumes / aerosols. act with the eyes and skin. ry protection: le respiratory protective device in case of nded filter device for short term use:	othing	
Filter AX Filter A			



Printing date 31.05.2021

Version number 32

Revision: 31.05.2021

(Contd. of page 6)

Trade name: GRF BISON/CONTACT TIX TI 5L*1 L221

Protection of hands:

Solvent resistant gloves



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- Material of gloves
- Butyl rubber, BR
- Recommended thickness of the material: > 0,7 mm
- Penetration time of glove material

For the mixture of chemicals mentioned below the penetration time has to be at least 120 minutes (Permeation according to EN 374 Part 3: Level 4).

• Eye protection:



Tightly sealed goggles

Goggles recommended during refilling • **Body protection:** Use protective suit. Solvent resistant protective clothing

SECTION 9: Physical and chemical properties

 9.1 Information on basic physical a General Information 	and chemical properties	
Appearance:		
Form:	Fluid	
Colour:	According to product specificat	tion
· Odour:	Characteristic	
· Odour threshold:	Not determined.	
· pH-value:	Not determined.	
 Change in condition Melting point/freezing point: Initial boiling point and boiling ratio 	Undetermined. ange: 55.8-56.6 °C	
· Flash point:	-4 °C	
· Flammability (solid, gas):	Not applicable.	
· Ignition temperature:	260 °C	
· Decomposition temperature:	Not determined.	
		(Contd. on page



Printing date 31.05.2021

Version number 32

Revision: 31.05.2021

Trade name: GRF BISON/CONTACT TIX TI 5L*1 L221

	(Contd. of page 7
· Auto-ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product is not explosive. However, formation o explosive air/vapour mixtures are possible.
· Explosion limits:	
Lower:	1.8 Vol %
Upper:	11.5 Vol %
· Vapour pressure at 20 °C:	105 hPa
· Density at 20 °C:	0.87 g/cm ³
Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
· Partition coefficient: n-octanol/water:	Not determined.
· Viscosity:	
Dynamic at 20 °C:	1000 mPas
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	80.4 %
Water:	0.1 %
Solids content:	19.5 %
· 9.2 Other information	All relevant physical data were determined for the
	mixture. All non-determined data are not measurable o
	not relevant for the characterization of the mixture.

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:
- No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- \cdot 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: Danger of forming toxic pyrolysis products.

SECTION 11: Toxicological information

· 11.1 Information on toxicological effects

· Acute toxicity Based on available data, the classification criteria are not met.

(Contd. on page 9)

IE-EN -



Printing date 31.05.2021

Version number 32

Revision: 31.05.2021

Trade name: GRF BISON/CONTACT TIX TI 5L*1 L221

Jes relevant for c 50 3300 mg/k 50 5000 mg/k 50 5620 mg/k 50 5620 mg/k 50 5620 mg/k 50 2250 mg/k 50 5800 mg/k 50 55000 mg 50 >50000 mg	ig (rat) ig (rabbit) ig (rabbit) (rat) ig (mouse) ig (rat) /kg (rabbit)
50 3300 mg/k 50 5000 mg/k 7 / acetate 50 5620 mg/k 50/4 h 1600 mg/l hylcyclohexane 50 2250 mg/k 50 5800 mg/k 50 5800 mg/k 50 ≥5000 mg	ig (rabbit) ig (rabbit) (rat) ig (mouse) ig (rat) /kg (rabbit)
50 5000 mg/k /I acetate 50 50 5620 mg/k 50/4 h 1600 mg/l hylcyclohexane 50 50 2250 mg/k 50 5800 mg/k 50 5800 mg/k 50 5800 mg/k 50 50000 mg 50 50000 mg	ig (rabbit) ig (rabbit) (rat) ig (mouse) ig (rat) /kg (rabbit)
/l acetate 50 5620 mg/k 50/4 h 1600 mg/l hylcyclohexane 50 2250 mg/k 50 5800 mg/k 50 20000 mg. 60 20000 mg. 50 55000 mg.	ig (rabbit) (rat) ig (mouse) ig (rat) /kg (rabbit)
50 5620 mg/k 50/4 h 1600 mg/l hylcyclohexane 50 50 2250 mg/k 50 5800 mg/k 50 5800 mg/k 50 20000 mg. 50 55000 mg/k	(rat) sg (mouse) sg (rat) /kg (rabbit)
50/4 h 1600 mg/l hylcyclohexane 50 2250 mg/k 50 5800 mg/k 50 20000 mg. 60 coxide 50	(rat) sg (mouse) sg (rat) /kg (rabbit)
hylcyclohexane 50 2250 mg/k 50 5800 mg/k 50 5800 mg/k 50 20000 mg. ic oxide 50 50 >5000 mg.	zg (mouse) zg (rat) /kg (rabbit)
50 2250 mg/k 50 5800 mg/k 50 20000 mg. 50 20000 mg. 50 >5000 mg.	g (rat) /kg (rabbit)
50 5800 mg/k 50 20000 mg. ac oxide 50 50 >5000 mg.	g (rat) /kg (rabbit)
50 5800 mg/k 50 20000 mg. ic oxide 50 >5000 mg	/kg (rabbit)
50 20000 mg. ic oxide 50 >5000 mg	/kg (rabbit)
ic oxide 50 >5000 mg	
50 >5000 mg	
5	$(1, \dots, (n-1))$
int effect:	/kg (rat)
s (acute toxicity, i Not applicable. se toxicity Not ap (carcinogenity, n utagenicity Not ap city Based on ava toxicity Based of exposure owsiness or dizzin ed exposure Bas	irritation and corrosivity) Not applicable. pplicable. nutagenicity and toxicity for reproduction) oplicable. ilable data, the classification criteria are not met. on available data, the classification criteria are not met.
I2: Ecological	information evant information available.
	n Not applicable. se toxicity Not ap (carcinogenity, n utagenicity Not ap city Based on available e toxicity Based on e toxicity Based on rowsiness or dizzir ted exposure Bas azard Based on available 12: Ecological

- \cdot 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system.

(Contd. on page 10)

IE-EN



Printing date 31.05.2021

Version number 32

Revision: 31.05.2021

(Contd. of page 9)

Trade name: GRF BISON/CONTACT TIX TI 5L*1 L221

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

12.5 Results of PBT and vPvB assessment

• **PBT:** Not applicable.

· vPvB: Not applicable.

12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Disposal must be made according to official regulations.

- · Uncleaned packaging:
- · Recommendation:

Packagings that may not be cleansed are to be disposed of in the same manner as the product.

14.1 UN-Number ADR/ADN, IMDG, IATA	UN1133	
14.2 UN proper shipping name ADR/ADN IMDG, IATA	1133 ADHESIVES ADHESIVES	
14.3 Transport hazard class(es)		
ADR/ADN		
Class Label	3 (F1) Flammable liquids. 3	
IMDG, IATA		
Class	3 Flammable liquids.	
Label	3	
14.4 Packing group ADR/ADN, IMDG, IATA	III	
	10	ontd. on pag



Printing date 31.05.2021

Version number 32

Revision: 31.05.2021

Trade name: GRF BISON/CONTACT TIX TI 5L*1 L221

	(Contd. of page 10
 14.5 Environmental hazards: Marine pollutant: 	No
 14.6 Special precautions for user Hazard identification number (Kemler code) 	Warning: Flammable liquids.
EMS Number: Stowage Category	F-E,S-D A
 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code 	Not applicable.
 Transport/Additional information: Quantity limitations 	On passenger aircraft/rail: 60 L On cargo aircraft only: 220 L
 ADR/ADN Limited quantities (LQ) Excepted quantities (EQ) 	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 100 ml
 Transport category Tunnel restriction code 	3 E
·IMDG	
 Limited quantities (LQ) Excepted quantities (EQ) 	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 100 ml
· Remarks:	Under certain conditions substances in Class : (flammable liquids) can be classified i packinggroup III. See IMDG, Part 2, Chapter 2.3, Paragraph 2.3.2.2
UN "Model Regulation":	UN 1133 ADHESIVES, 3, III

SECTION 15: Regulatory information

 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Directive 2012/18/EU

· Named dangerous substances - ANNEX I None of the ingredients is listed.

· Seveso category P5c FLAMMABLE LIQUIDS

· Qualifying quantity (tonnes) for the application of lower-tier requirements 5000 t

· Qualifying quantity (tonnes) for the application of upper-tier requirements 50000 t

• REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

 DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

(Contd. on page 12)

IE-EN



Printing date 31.05.2021

Version number 32

Revision: 31.05.2021

Trade name: GRF BISON/CONTACT TIX TI 5L*1 L221

· REGULATION (EU) 2019/1148

(Contd. of page 11)

 Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

Annex II - REPORTABLE EXPLOSIVES PRECURSORS

67-64-1 acetone

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H225 Highly flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

Classification according to Regulation (EC) No 1272/2008

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

Flammable liquids	Bridging principles
Skin corrosion/irritation Serious eye damage/eye irritation Specific target organ toxicity (single exposure) Hazardous to the aquatic environment - long- term (chronic) aquatic hazard	The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

· Department issuing SDS: Bison QESH

· Contact: Reach coordinator

· Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2

(Contd. on page 13)



Printing date 31.05.2021

Version number 32

Revision: 31.05.2021

(Contd. of page 12)

Trade name: GRF BISON/CONTACT TIX TI 5L*1 L221

Skin Irrit. 2: Skin corrosion/irritation – Category 2 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2 Skin Sens. 1: Skin sensitisation – Category 1 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 Asp. Tox. 1: Aspiration hazard – Category 1 Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3 *** Data compared to the previous version altered.**

IE-EN