# SAFETY DATA SHEET

DATE OF ISSUE/<u>LAST REVISION</u> : December 6, 2016

OUR REF No. Ⅲ-85

1. IDENTIFICATION OF THE PRO	DUCT AND OF THE SUPPLIER
[PRODUCT NAME]	HANARL FLX-2E
[USE OF THE CHEMICAL]	Lubricant
[SUPPLIER'S NAME]	Kanto Kasei Ltd.
[SUPPLIER'S ADDRESS]	1-8-1, Marunouchi, Chiyoda-ku, Tokyo JAPAN, 100-0005
[DIVISION]	Environmental quality assurance
[PHONE NUMBER]	TEL: 03(3218)7111 FAX: 03(3218)7100
[E-MAIL]	<u>info@kanto-kasei.com</u>
	<pre>c Environment (Chronic) : Category 4- Aquatic Chronic 4 2008(CLP)     : H413 : May cause long lasting harmful effects to         aquatic life. G : [Prevention]     P261 : Avoid breathing dust/fume/gas/mist/vapours/spray.     [Disposal]     P501 : Dispose of contents/container in accordance with         applicable local/regional/national/international         regulations.     : No data available</pre>

3. COMPOSITION/INFORMATION	ON INGREDIENTS	
DISTINCTION		
(SINGLE PRODUCT/MIXTURE)	: Mixture	
CHEMICAL NAME	:Dry film lubricant	
COMPOSITIION	: Fluorinated solvent	$85{\sim}95{ m wt}\%$
	: Fluoric oil, solid lubricants and others	$5\sim\!15 \mathrm{wt}\%$
CHEMICAL FORMULAE	:Not disclose, because of trade secrets	
CAS NO	:Not disclose, because of trade secrets	
UN CLASS/UN NUMBER	:Not applicable	

<ul> <li>4. FIRST-AID MEASURES IF INHALED</li> <li>IF ON SKIN IF IN EYES</li> <li>IF SWALLOWED</li> <li>MOST IMPORTANT SYMPTOM PROTECTION OF PERSON GIVE FIRST-AID SPECIAL NOTE TO DOCTOR</li> </ul>	<ul> <li>Remove victim to fresh air. Get medical advice/attention.</li> <li>Wash the affected area with soap and water.</li> <li>Flush eyes with plenty of water, and get medical advice /attention.</li> <li>Do not induce vomiting. Get medical advice/attention. If a mouth is polluted, wash it with plenty of water.</li> <li>No data available</li> <li>No data available</li> <li>No data available</li> </ul>
5. FIRE-FIGHTING MESURES EXTINGUISHING MEDIA FIRST FIRE LARGE-SCALE FIRE UNSUITABLE EXTINGUISHING MED PECULIAR HAZARD STATEMENT PECULIAR EXTINCTION METHOD PROTECTION OF THE PERSON EXTINGUISHIES FIRE	<ul> <li>: Use spray foam, foam, powder or CO<sub>2</sub> gas extinguishing media.</li> <li>: Use powder or CO<sub>2</sub> gas extinguishing media.</li> <li>: Use foam extinguishing media.</li> <li>IA : Water must not be used to extinguish.</li> <li>: May be harmful if inhaled vapor/mist produced at 260°C or more.</li> <li>: Cut off combustion source of fire.</li> <li>: Sprinkle water to equipment to cool.</li> <li>: Prohibit to enter to the scene of a fire except staff.</li> <li>: Extinguish fire on the windward side of the fire and not fail to wear protector.</li> </ul>
6. ACCIDENTAL RELEASE MEASUR PERSONAL PRECAUTIONS ENVIRONMENTAL PRECAUTIONS	<ul><li>ES</li><li>: Not fail to wear protector.</li><li>: Take care not to be drained into river and drain.</li><li>: If the medicine is used for the sea, it should be what suits the standard in the technology that provides by the transportation ministerial ordinance.</li></ul>
METHODS FOR CONTAINMENT AND CLEANING UP SMALL QUANTITY	<pre>: Remove source of a fire. : Remove with a spatula or shovel, or absorb with soil, sand or a cloth. Wipe off remainder with a cloth.</pre>
LARGE QUANTITY	: Prevent access by roping off the perimeter around the leak. Prevent the spilling grease from spreading with soil and sand. After draining off to a safety area, collect as much as possible into an empty
AT SEA PREVENTION MESURE OF SECOND DISASTER	<ul> <li>container.</li> <li>Prevent dispersion by creating an oil fence. Scoop up or use adsorption mats to soak up. When chemicals are used, these must comply with technological standards as set down in ministry of transport ordinances.</li> <li>Inform promptly a related organization to attempt prevention and the expansion prevention of the accident when leaking.</li> <li>Remove source of a fire and prepare extinguishing media.</li> </ul>

7. HANDLING AND STORAGE HANDLING	
TECHNICAL MESURES	<ul> <li>Avoid contact with flame, sparks and heated objects. Do not allow unnecessary dispersion of vapor.</li> <li>Take steps to prevent static electricity, and use conductive work clothes and shoes.</li> <li>Remove completely it in the safety area, if the mechanical equipment are repaired and are processed.</li> <li>Wear protector, if there is possibility of skin contact or eye contact.</li> <li>Avoid inhalation of vapor or mist.</li> </ul>
NOTES	: Containers must be sealed. : The vapor from petroleum products builds up easily as it is heavier than air. It is therefore necessary to ensure adequate ventilation and take care with fire.
NOTES OF SAFE HANDLING	<ul> <li>: Handling should be done at room temperature. Prevent contamination of water and impurities.</li> <li>: Avoid contact with halogens, strong acids, alkaline substances and oxidants.</li> </ul>
STORAGE	<ul> <li>: Protect from sunlight. Store in a well-ventilated place.</li> <li>: Avoid heat, sparks, flames and any build-up of static electricity.</li> <li>: Avoid contact and storing with halogens, strong acids, alkaline substances and oxidants.</li> <li>: Don't turn the heat to an empty container.</li> <li>: Don't cut, weld, heat, or make the hole the container. Traces might ignite attended with the explosion.</li> </ul>

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

o. En obene controllo/ i Enoonie	
EQUIPMENT MESURES	: If the vapor arises, ventilation equipment or closing of vapor source is needed.
	: The equipment for washing and the body washing of eyes is set up near the handling area.
MANAGEMENT CONCENTRAITON	:Not established
ALLOWABLE CONCENTRATION	:Not established
	: ACGIH Not established
PROTECTION	
RESPIRATORY PROTECTION	: If necessary, wear hazard mask.
HAND PROTECTION	:Wear the resistance to oil if coming in contact repeating for a long term.
EYE PROTECTION	:Wear safety glasses with side shields.
SKIN PROTECTION	: Wear the long sleeve work wear of the resistance to oil if handling or getting wet for a long term.
APPROPRIATE SANITARY	
REQUIREMENT	: Take off and wash the wet clothes, and use again.

9. PHYSICAL AND CHEMICAL PROPER	RTIES
APPEARANCE	:Liquid
COLOR	: Milky white
ODOR	: Slightly odor
рH	:No data
MELTING POINT/FREEZING POINT	: Approx138°C
INITIAL BOILING POINT	
AND BOILING	: 75∼80°C

FLASH POINT UPPER/LOWER FLAMMABILITY OR EXPLOSIVE LIMITS VAPOR PRESSURE VAPOR DENSITY RELATIVE DENSITY (WATER=1) SOLUBILITY AUTO-IGNITION TEMPERATURE DECOMPOSITION TEMPERATURE VISCOSITY	<pre>: Not applicable Does not flash : Not applicable : Approx. 14, 532. 1 Pa (25℃) : Approx. 9. 1 (0℃) : Approx. 1. 43 (25℃) : Water : Insoluble Other solvent : Insoluble Other solvent : Insoluble : Approx. 375 ℃ : No data : Approx. 0. 43 cSt * These data except for appearance are about main solvent.</pre>
10. STABILITY AND REACTIVITY STABILITY POSSIBILITY OF HAZARDOUS REACTIONS CONDITIONS TO AVOID INCOMPATIBLE MATERIALS HAZARDOUS DECOMPOSITION PRODUCTS OTHER	<ul> <li>: Stability at room temperature</li> <li>: No reaction with water</li> <li>: Heating, high temperature, and contact hazardous material</li> <li>: Avoid contact with halogens, strong acids, alkaline substances and oxidants.</li> <li>: Harmful thermal decomposition products may be produced such as gaseous hydrogen fluoride when heated at extremely high temperature.</li> <li>: No data available</li> </ul>
11. TOXICOLOGICAL INFORMATION ACUTE TOXICITY SKIN CORROSION/IRRITATION SERIOUS EYE DANAGE/ IRRITATION RESPIRATORY OR SKIN SENSITIZATION GERM CELL MUTAGENICITY CARCINOGENICITY REPRODUCTIVE TOXICITY STOT-single exposure STOT-repeated exposure ASPIRATION HAZARD	<pre>: Oral: No data Dermal: No data Inhalation(vapor): No data Inhalation(mist) : No data : No data available : No data available</pre>
12. ECOLOGICAL INFORMATION ACUATIC TOXICITY ACUTE CHARONIC PERSISTENCE/DEGRADABILITY BIOACCUMULATIVE POTENTIAL MOBILITY IN SOIL OTHER ADVERSE EFFECTS	: No toxicity : Category 4 : May cause toxic to aquatic life with long lasting effects. : No data available : No data available : No data available : No data available : No data available

13. DISPOSAL CONSIDERATIONS	
WASTE DISPOSAL METHOD	: Consider disposal via licensed waste disposal company. Scrap may be incinerated under properly controlled condition. Follow all regulations in your country.

#### 14. TRANSPORT INFORMATION

Not classified as dangerous in all means of transport regulations, including air, sea and land.

INTERNATIANAL REGULATIONS	
FOR TRANSPORT	:Not regulated (Not dangerous)
UN CLASS	:Not applicable
UN NUMBER	:Not applicable
PRODUCT NAME	:Not applicable
CONTAINER GRADE	:Not applicable
SEAWATER POLLUTION MATERIAL	: None
SPECIFIC SECURITY PRECAUTION	
AND CONDITION OF TRANSPORTATION	: The container is avoided direct sunlight, and it
	loads so as not to be damaged, corroded and leak.
	The collapse of cargo piles is prevented surely.
	:Don't pile the heavy load.

#### 15. REGULATORY INFORMATION

Ensure this material in compliance with nation's requirements, and ensure conformity to local regulation.

### 16. OTHER INFORMATION

Please read the SDS well before use.

SAFETY DATE SHEETS ARE ISSUED BASED ON THE LATEST INFORMATION WE HAVE KNOWN. HOWEVER, THESE ARE NOT THE ONE TO INSURE SAFETY. THESE ARE PROVIDED TO COMPANIES HANDLING THE MATERIALS AS REFERENCE INFORMATION REGARDING HAZARDOUS AND HARMFUL CHEMICALS TO ENSURE SAFE HANDLING. WE ASK THAT THESE SHEETS BE USED BY COMPANIES AS REFERENCE AND WITH THE UNDERSTANDING THAT IT IS NECESSARY FOR MESURES APPROPRIATE TO THE SPECIFIC CIRCUMSTANCES RELATED TO HANDLING THE MATERIALS TO BE TAKEN UNDER THEIR OWN RESPONSIBILITY. ACCORDINGLY, THIS DATA SHEET IN NO WAY CONSTITUTES A GUARANTEE OF SAFETY.