

VarioStream 4000 series

ROBUST CONTINUOUS FEED PRINTING FOR HIGH PRODUCTIVITY AND QUALITY

The VarioStream 4000 series is a highly flexible continuous feed monochrome printing system that offers the highest quality and productivity for heavy production environments, easy intuitive operation and seamless workflow integration.



- Speed and media choice flexibility
- Enhanced print quality
- Simplex, Duplex and Dual Simplex configurations
- Compatible with the latest standards for world languages and barcodes
- Quick Change Developer Station technology
- Seamlessly integrates into colour workflows
- Intuitive user friendly touch screen operation
- Upgradeable

Canon

VarioStream 4000 series

SPECIFICATIONS

	Print Speed meters per minute	Print Speed A4 pages per minute		Duty Cycle million A4 per month		Power Connection	Power Consumption Printing (EU) ^[3]	Power consumption idle (EU) ^[3]
		Single	Twin	Single	Twin			
VarioStream 4200	27	180	360	1-5	3-11	400/230 V ±10%	7.2 kW	1.9 kW
VarioStream 4300	39	260	520	2-8	4-16	400/230 V ±10%	7.9 kW	1.9 kW
VarioStream 4400	52	350	700	3-11	5-21	400/230 V ±10%	9.0 kW	2.0 kW
VarioStream 4450	65	440	880	3-13	7-27	400/230 V ±10%	10.3 kW	2.0 kW
VarioStream 4550	74	500	1000	4-15	7-30	400/230 V ±10%	11.5 kW	2.1 kW
VarioStream 4650	89	600	1200	4-18	9-36	400/230 V ±10%	13.0 kW	2.1 kW

TECHNICAL SPECIFICATIONS

TECHNOLOGY

Print technology	LED technology, dry toner
Fusing technology	Heat-pressure fusing
Functionality	Simplex or duplex (twin)
Operating Panel	Touch Screen Graphical User Interface
Paper transport	Pin feed or tractor ^[1]
Paper input	Stack, jumbo stack, unwinder
Paper output	Integrated stacker, rewinder or other post-processing with a Type 1 Interface
Print resolution	600×600 dpi with Super Cell Technology

PAPER

Print width	Pinless: max. 18.25" (463.5 mm), tractor: max. 17" (431.8 mm)
Page length	3"-28" (76.2 - 711.2 mm)
Paper width	Pinless: 6.5"-19" (165 - 482.6 mm), tractor: 6.5"-18" (165 - 457.2 mm)
Form length	Internal stacker: 6"-16" (152.4 - 406.4 mm)
Paper weight ^[2]	Pinless: 50 - 160 g/m ² , tractor: 70 - 160 g/m ²
Substrates	Single layer continuous forms with or without (pinless only) tractor feed margins, perforated, coloured or preprinted

ENVIRONMENTAL

Temperature	Operating range 15 - 28 °C, limited range 10 - 30 °C
Humidity	Operating range 40 - 75 %, limited range 40 - 80 %
Operating noise (with stacker)	Maximum 68.7 dB

WORKFLOW

Controller	Server based SRA Controller
Printer data formats	AFP/IPDS (IS/3), PCL 6e, PDF
Print manager (optional)	PRISMAproduction/ PRISMAproduction Host
Connectivity	Gigabit Ethernet (copper or optical)

OPTIONS

Additional Network Interface
Additional Printer Data Formats
Operator attention light
MICR Option
Power Stacker
Additional Quick Change Developer Station

PHYSICAL DATA

Dimensions (L × W × H)	2,711 mm × 1,063 mm × 1,550 mm
Weight (EU)	1,310 kg

Footnote

- ^[1] Tractor paper transport only available for VarioStream 4200, 4300, 4400 and 4450
- ^[2] Paper with higher weight could be used after testing and approval; with the Light-Weight Paper Kit, stocks as light as 35 g/m² can be used with the pinless transport
- ^[3] All values apply per engine in a twin configuration

Trademark notice:

Canon is a registered trademark of Canon Inc. Arizona is a trademarks or registered trademark of Canon Production Printing Netherlands B.V. All other trademarks are the property of their respective owners and hereby acknowledged.

Disclaimer: No part of this publication may be copied, modified, reproduced or transmitted in any form or by any means, electronic, manual, or otherwise, without the prior written permission of Canon Production Printing. Illustrations and printer output images are simulated and do not necessarily apply to products and services offered in each local market. The content of this publication should neither be construed as any guarantee or warranty with regard to specific properties or specifications nor of technical performance or suitability for particular applications. The content of this publication may be subject to changes from time to time without notice. Canon production printing shall not be liable for any direct, indirect or consequential damages of any nature, or losses or expenses resulting from the use of the contents of this publication.

