SAFETY DATA SHEET

OUR REF No. I-1

1. IDENTIFICATION OF THE PROD	UCT AND OF THE SUPPLIER
[PRODUCT NAME]	FLOIL 923
[USE OF THE CHEMICAL]	Lubricating Grease
[MANUFACTURER NAME]	Kanto Kasei Ltd.
[MANUFACTURER ADDRESS]	1-8-1, Marunouchi, Chiyoda-ku, Tokyo JAPAN, 100-0005
(DIVISION)	Environmental quality assurance
PHONE NUMBER	TEL: 03 (3218) 7111 FAX: 03 (3218) 7100
[E-MAIL]	<u>info@kanto-kasei.com</u>

2. HAZARDS IDENTIFICATION GHS CLASSIFICATION (JIS Z7253:2012)

: Not applicable Hazard identification that there is no description in the above-mentioned is Not applicable or Not possible to classify.

LABEL ELEMENTS

SYMBOLS	:No pictogram
SIGNAL WORD	: None
HAZARD STATEMENT	:Not applicable
PRECAUTIONARY STATEMENTS	[Prevention]
	: None
	Response
	: None
	[Storage]
	: None
	[Disposal]
	: None

Even if there is not a mention of the notice by the GHS classification, the information in later, making a sufficient consideration relates to prevention/response/storage/disposal.

3. COMPOSITION/INFORMATION ON INGREDIENTS DISTINCTION (SINGLE PRODUCT/MIXTURE) : Mixture CHEMICAL NAME : Lubricating oil COMPOSITIION BASE OIL : Synthetic oil 85~95wt% OTHERS : Additives 5~15wt% CHEMICAL FORMULAE : Not disclose, because of trade secrets CAS NO : Not disclose, because of trade secrets UN CLASS/UN NUMBER : Not applicable

 4. FIRST-AID MEASURES IF INHALED IF ON SKIN IF IN EYES IF SWALLOWED MOST IMPORTANT SYMPTOM PROTECTION OF PERSON GIVE FIRST-AID SPECIAL NOTE TO DOCTOR 	<pre>: Remove victim to fresh air. Get medical advice/attention. : Wash the affected area with soap and water. : Flush eyes with plenty of water, and get medical advice /attention. : Do not induce vomiting. Get medical advice/attention. If a mouth is polluted, wash it with plenty of water. : No data available : No data available : No data available</pre>
5. FIRE-FIGHTING MESURES EXTINGUISHING MEDIA FIRST FIRE LARGE-SCALE FIRE UNSUITABLE EXTINGUISHING MED PECULIAR HAZARD STATEMENT PECULIAR EXTINCTION METHOD PROTECTION OF THE PERSON EXTINGUISHIES FIRE	 : No data available : Cut off combustion source of fire. : Sprinkle water to equipment to cool. : Prohibit to enter to the scene of a fire except staff. : Extinguish fire on the windward side of the fire and
6. ACCIDENTAL RELEASE MEASUR PERSONAL PRECAUTIONS ENVIRONMENTAL PRECAUTIONS	not fail to wear protector. EES : Always wear protective equipment when working. : Take care not to be drained into river and drain. : If the medicine is used for the sea, it should be what suits the standard in the technology that provides by the transportation ministerial ordinance.
METHODS FOR CONTAINMENT AND CLEANING UP SMALL QUANTITY LARGE QUANTITY AT SEA	 : Remove source of a fire. : Remove with a spatula or shovel, or absorb with soil, sand or a cloth. Wipe off remainder with a cloth. : Prevent access by roping off the perimeter around the leak. Prevent the spilling grease from spreading with soil and sand. After draining off to a safety area, collect as much as possible into an empty container. : Prevent dispersion by creating an oil fence. Scoop up or use adsorption mats to soak up. When chemicals are used, these must comply with technological standards as set down in ministry of transport ordinances.
PREVENTION MESURE OF SECOND DISASTER	 : Inform promptly a related organization to attempt prevention and the expansion prevention of the accident when leaking. : Remove source of a fire and prepare extinguishing media.

7. HANDLING AND STORAGE HANDLING	
TECHNICAL MESURES	 Avoid contact with flame, sparks and heated objects. Do not allow unnecessary dispersion of vapor. Take steps to prevent static electricity, and use conductive work clothes and shoes. Remove completely it in the safety area, if the mechanical equipment are repaired and are processed. Wear protector, if there is possibility of skin contact or eye contact. Avoid inhalation of vapor or mist. Containers must be sealed.
NOTES	 containers must be seared. The vapor from petroleum products builds up easily as it is heavier than air. It is therefore necessary to ensure adequate ventilation and take care with fire.
NOTES OF SAFE HANDLING	 Handling should be done at room temperature. Prevent contamination of water and impurities. Avoid contact with halogens, strong acids, alkaline substances and oxidants.
STORAGE	 : Protect from sunlight. Store in a well-ventilated place. : Avoid heat, sparks, flames and any build-up of static electricity. : Electrical equipment used in the storage area must have a non-explosive structure, and devices must be earthed. : Avoid contact and storing with halogens, strong acids, alkaline substances and oxidants. : Do not apply pressure to empty containers. : Don't cut, weld, heat, or make the hole the container. Traces might ignite attended with the explosion.
8. EXPOSURE CONTROLS/PERSONA EQUIPMENT MESURES	L PROTECTION : If the vapor arises, ventilation equipment or closing of vapor source is needed. : The equipment for washing and the body washing of
MANAGEMENT CONCENTRAITON ALLOWABLE CONCENTRATION	<pre>eyes is set up near the handling area. : Not established : Japan Society for Occupational Health(2010) 3mg/m³ (as mist of mineral oil) : ACGIH(2010) TWA : 5mg/m³ (as mist of mineral oil)</pre>
PROTECTION RESPIRATORY PROTECTION HAND PROTECTION EYE PROTECTION SKIN PROTECTION APPROPRIATE SANITARY	 TWA: 5mg/m³ (as mist of mineral oil) : If necessary, wear hazard mask. : Wear the resistance to oil if coming in contact repeating for a long term. : Wear safety glasses with side shields. : When contacting for a long time or repeatedly, wear oil resistant ones.
REQUIREMENT	: Remove dirty clothes, wash completely and reuse.

9. PHYSICAL AND CHEMICAL PROPERTIES		
APPEARANCE	: Liquids	
COLOR	:Light yellow	
ODOR	: Slightly odor	
рН	:No data	
MELTING POINT/FREEZING POINT	:No data	
INITIAL BOILING POINT		
AND BOILING	:No data	
FLASH POINT	: 0ver 200°C(COC)	
UPPER/LOWER FLAMMABILITY		
OR EXPLOSIVE LIMITS	: Upper : 7wt% lower : 1wt%	
VAPOR PRESSURE	:No data	
VAPOR density	:No data	
RELATIVE DENSITY		
(WATER=1)	: Approx. 0. 83	
SOLUBILITY	:Water :Insoluble	
	Other solvent: Insoluble	
AUTO-IGNITION TEMPERATURE	:No data	
DECOMPOSITION TEMPERATURE	:No data	
VISCOSITY	:No data	
10. STABILITY AND REACTIVITY		
STABILITY	:Stability at room temperature	
POSSIBILITY OF HAZARDOUS		
REACTIONS	: Avoid contact with strong acids	
CONDITIONS TO AVOID	: Heating, high temperature, and contact hazardous	
INCOMPATIBLE MATERIALS	material : Avoid contact with halogens, strong acids, alkaline	
	substances and oxidants.	
HAZARDOUS DECOMPOSITION		
PRODUCTS	: CO	
OTHER	:No data available	
11. TOXICOLOGICAL INFORMATION	$(0, 1, \dots, 4, 1) > 5000 / 1 + 1 + 1 + 1 + 1 + 1 + 1 + 1 + 1 + 1$	
ACUTE TOXICITY	: Oral : rat LD ₅₀ ≧ 5000mg/kg : Not classified Dermal : No data	
	Inhalation(vapor) : No data	
	Inhalation(mist) : No data	
SKIN CORROSION/IRRITATION	:No data available	
SERIOUS EYE DAMAGE/		
IRRITATION	:No data available	
RESPIRATORY OR SKIN SENSITIZATION	:No data	
GERM CELL MUTAGENICITY	: No data available	
	: IARC, OSHA, NTP, EU, EPA, ACGIH Not established	
MINERAL OIL	: IARC, ACGIH : Group 3	
ADDITIVES	:No data available	
REPRODUCTIVE TOXICITY	: No data available	
STOT-single exposure STOT-repeated exposure	:No data available :No data available	
ASPIRATION HAZARD	: No data available	

12. ECOLOGICAL INFORMATION		
TOXICITY FI	ISH	:No data available
ΓΟ	THERS	:No data available
PERSISTENCE/DEGRADABILITY		:No data available
BIOACCUMULATIVE POTENTIAL		:No data available
MOBILITY IN SOIL		:No data available
OTHER ADVERSE EFFECTS		:No data available
BIOACCUMULATIVE POTENTIAL MOBILITY IN SOIL		: No data available : No data available

13. DISPOSAL CONSIDERATIONS

14. TRANSPORT INFORMATION

Not classified as dangerous in all means of transport regulations, including air, sea and land..

INTERNATIANAL REGULATIONS	
FOR TRANSPORT	:Not regulated (Not dangerous)
UN CLASS	:Not applicable
UN NUMBER	:Not applicable
PRODUCT NAME	:Not applicable
CONTAINER GRADE	:Not applicable
SEAWATER POLLUTION MATERIAL	: None
SPECIFIC SECURITY PRECAUTION	
AND CONDITION OF TRANSPORTATION	: The container is avoided direct sunlight, and it
	loads so as not to be damaged, corroded and leak.
	The collapse of cargo piles is prevented surely.
	: Don't pile the heavy load.

15. REGULATORY INFORMATION

Ensure this material in compliance with nation's requirements, and ensure conformity to local regulation.

16. OTHER INFORMATION

Please read the SDS well before use.

SAFETY DATE SHEETS ARE ISSUED BASED ON THE LATEST INFORMATION WE HAVE KNOWN. HOWEVER, THESE ARE NOT THE ONE TO INSURE SAFETY. THESE ARE PROVIDED TO COMPANIES HANDLING THE MATERIALS AS REFERENCE INFORMATION REGARDING HAZARDOUS AND HARMFUL CHEMICALS TO ENSURE SAFE HANDLING. WE ASK THAT THESE SHEETS BE USED BY COMPANIES AS REFERENCE AND WITH THE UNDERSTANDING THAT IT IS NECESSARY FOR MESURES APPROPRIATE TO THE SPECIFIC CIRCUMSTANCES RELATED TO HANDLING THE MATERIALS TO BE TAKEN UNDER THEIR OWN RESPONSIBILITY. ACCORDINGLY, THIS DATA SHEET IN NO WAY CONSTITUTES A GUARANTEE OF SAFETY.