FLOIL G-573

SAFETY DATA SHEET

OUR REF No. I-114

1. IDENTIFICATION OF THE PRODUCT AND OF THE SUPPLIER

[PRODUCT NAME] FLOIL G-573

【USE OF THE CHEMICAL】 Lubricating Grease
[MANUFACTURER NAME] Kanto Kasei Ltd.

[MANUFACTURER ADDRESS] 1-8-1, Marunouchi, Chiyoda-ku, Tokyo JAPAN, 100-0005

[DIVISION] Chemical Safety Division

[PHONE NUMBER] TEL: 03 (3218) 7111 FAX: 03 (3218) 7100

[E-MAIL] info@kanto-kasei.com

2. HAZARDS IDENTIFICATION

CLP REGULATION (EC) No 1272/2008

CLASSIFICATION:

This material is not classified as hazardous according to Regulation (EC) No. 1272/2008, as amended, on classification, labelling, and packaging of substances and mixtures.

LABEL ELEMENTS

CLP REGULATION (EC) No 1272/2008 : Not applicable

3. COMPOSITION/INFORMATION ON INGREDIENTS

DISTINCTION

(SINGLE PRODUCT/MIXTURE) : Mixture CHEMICAL NAME : Grease

COMPOSITIION BASE OIL : Synthetic oil $65\sim75 \text{wt}\%$ THICKNER : Lithium soap $10\sim20 \text{wt}\%$ OTHERS : Additives $15\sim20 \text{wt}\%$

CHEMICAL FORMULAE : Not disclose, because of trade secrets CAS NO : Not disclose, because of trade secrets

UN CLASS/UN NUMBER : Not applicable

4. FIRST-AID MEASURES

IF INHALED : Remove victim to fresh air.

Get medical advice/attention.

IF ON SKIN : Wash the affected area with soap and water.

IF IN EYES : Flush eyes with plenty of water, and get medical advice

/attention.

IF SWALLOWED : Do not induce vomiting. Get medical advice/attention.

If a mouth is polluted, wash it with plenty of water.

MOST IMPORTANT SYMPTOM : No data available

PROTECTION OF PERSON

GIVE FIRST-AID : No data available SPECIAL NOTE TO DOCTOR : No data available

5. FIRE-FIGHTING MESURES

EXTINGUISHING MEDIA : Use spray foam, foam, powder or CO_2 gas

extinguishing media.

FIRST FIRE : Use powder or CO_2 gas extinguishing media.

LARGE-SCALE FIRE : Use foam extinguishing media.

UNSUITABLE EXTINGUISHING MEDIA : Prohibit rod-shaped water injection.

PECULIAR HAZARD STATEMENT : No data available

FLOIL G-573

PECULIAR EXTINCTION METHOD

: Cut off combustion source of fire.

: Sprinkle water to equipment to cool.

: Prohibit to enter to the scene of a fire except $% \left(1\right) =\left(1\right) \left(1\right) \left($

staff.

PROTECTION OF THE PERSON EXTINGUISHIES FIRE

: Extinguish fire on the windward side of the fire and $% \left(1\right) =\left(1\right) +\left(1\right) +\left($

not fail to wear protector.

6. ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS

ENVIRONMENTAL PRECAUTIONS

: Always wear protective equipment when working.

: Take care not to be drained into river and drain.

: If the medicine is used for the sea, it should be what suits the standard in the technology that provides by the transportation ministerial ordinance.

METHODS FOR CONTAINMENT

AND CLEANING UP SMALL QUANTITY

LARGE QUANTITY

: Remove source of a fire.

 $: \ensuremath{\mathsf{Remove}}$ with a spatula or shovel, or absorb with soil,

sand or a cloth. Wipe off remainder with a cloth.

: Prevent access by roping off the perimeter around the leak. Prevent the spilling grease from spreading with soil and sand. After draining off to a safety area, collect as much as possible into an empty

container.

AT SEA

: Prevent dispersion by creating an oil fence. Scoop up or use adsorption mats to soak up. When chemicals are used, these must comply with technological standards as set down in ministry

of transport ordinances.

PREVENTION MESURE OF SECOND DISASTER

: Inform promptly a related organization to

attempt prevention and the expansion prevention

of the accident when leaking.

: Remove source of a fire and prepare extinguishing

media.

7. HANDLING AND STORAGE HANDLING

TECHNICAL MESURES

: Avoid contact with flame, sparks and heated objects. $\,$

Do not allow unnecessary dispersion of vapor.

: Take steps to prevent static electricity, and use

conductive work clothes and shoes.

: Remove completely it in the safety area, if the mechanical equipment are repaired and are processed.

: Wear protector, if there is possibility of skin

contact or eye contact.

: Avoid inhalation of vapor or mist.

: Containers must be sealed.

NOTES

: The vapor from petroleum products builds up easily as it is heavier than air. It is therefore necessary to ensure adequate ventilation and

take care with fire.

NOTES OF SAFE HANDLING

: Handling should be done at room temperature. Prevent $% \left(1,...,1\right) =\left(1,...,1\right)$

contamination of water and impurities.

: Avoid contact with halogens, strong acids, alkaline

substances and oxidants.

STORAGE

: Protect from sunlight. Store in a well-ventilated

: Avoid heat, sparks, flames and any build-up of

FLOIL G-573

static electricity.

: Electrical equipment used in the storage area must have a non-explosive structure, and devices must be earthed.

: Avoid contact and storing with halogens, strong acids, alkaline substances and oxidants.

: Do not apply pressure to empty containers. : Don't cut, weld, heat, or make the hole the

container. Traces might ignite attended with the

explosion.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

EQUIPMENT MESURES : If the vapor arises, ventilation equipment or

closing of vapor source is needed.

: The equipment for washing and the body washing of

eyes is set up near the handling area.

MANAGEMENT CONCENTRAITON : Not established

ALLOWABLE CONCENTRATION : Japan Society for Occupational Health (2010)

3mg/m³ (as mist of mineral oil)

: ACGIH(2010) TWA: 5mg/m³ (as mist of mineral oil)

PROTECTION

RESPIRATORY PROTECTION : If necessary, wear hazard mask.

HAND PROTECTION : Wear the resistance to oil if coming in contact

repeating for a long term.

EYE PROTECTION : Wear safety glasses with side shields.

SKIN PROTECTION : When contacting for a long time or repeatedly, wear

oil resistant ones.

APPROPRIATE SANITARY

REQUIREMENT : Remove dirty clothes, wash completely and reuse.

9. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE : Semisolid

COLOR : Yellow

ODOR : Slightly odor

p H : No data MELTING POINT/FREEZING POINT : No data

INITIAL BOILING POINT

AND BOILING : No data

FLASH POINT : Over 200°C (SETA)

UPPER/LOWER FLAMMABILITY

OR EXPLOSIVE LIMITS : Upper: 7wt% lower: 1wt% (Base oil)

VAPOR PRESSURE : No data VAPOR density : No data RELATIVE DENSITY (WATER=1) : $0.8 \sim 0.9$

SOLUBILITY : Water : Insoluble

Other solvent: Insoluble

AUTO-IGNITION TEMPERATURE : No data
DECOMPOSITION TEMPERATURE : No data
VISCOSITY : No data

10. STABILITY AND REACTIVITY

STABILITY : Stability at room temperature

POSSIBILITY OF HAZARDOUS

REACTIONS : Do not make contact with strong oxidizing agent.

CONDITIONS TO AVOID : Heating, high temperature, and contact hazardous

FLOIL G-573

material

INCOMPATIBLE MATERIALS : Avoid contact with halogens, strong acids, alkaline

substances and oxidants.

HAZARDOUS DECOMPOSITION

PRODUCTS : CO

OTHER : No data available

11. TOXICOLOGICAL INFORMATION

ACUTE TOXICITY : Oral : rat $LD_{50} \ge 5000 mg/kg$: Not classified

Dermal: No data

Inhalation(vapor): No data Inhalation(mist): No data

SKIN CORROSION/IRRITATION : No data available

SERIOUS EYE DAMAGE/

IRRITATION : No data available

RESPIRATORY OR SKIN

SENSITIZATION : No data

GERM CELL MUTAGENICITY : No data available

CARCINOGENICITY MINERAL OIL : IARC group3

BASE OIL : IARC, OSHA, NTP, EU, EPA, ACGIH Not established

ADDITIVE : No data available TY : No data available

REPRODUCTIVE TOXICITY : No data available STOT-single exposure : No data available STOT-repeated exposure : No data available ASPIRATION HAZARD : No data available

12. ECOLOGICAL INFORMATION

TOXICITY FISH : No data available

OTHERS : No data available

PERSISTENCE/DEGRADABILITY : No data available
BIOACCUMULATIVE POTENTIAL : No data available
MOBILITY IN SOIL : No data available
OTHER ADVERSE EFFECTS : No data available

13. DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD : Consider disposal via licensed waste disposal

company. Scrap may be incinerated under properly controlled condition. Follow all regulations in

your country.

14. TRANSPORT INFORMATION

Not classified as dangerous in all means of transport regulations, including air, sea and land.

INTERNATIANAL REGULATIONS

FOR TRANSPORT : Not regulated (Not dangerous)

UN CLASS : Not applicable
UN NUMBER : Not applicable
PRODUCT NAME : Not applicable
CONTAINER GRADE : Not applicable

SEAWATER POLLUTION MATERIAL : None

SPECIFIC SECURITY PRECAUTION

AND CONDITION OF TRANSPORTATION: The container is avoided direct sunlight, and it

loads so as not to be damaged, corroded and leak. The collapse of cargo piles is prevented surely.

: Don't pile the heavy load.

FLOIL G-573

15. REGULATORY INFORMATION

Chemical Safety Assessment

A chemical safety assessment has been carried out for this substance/mixture in accordance with Regulation (EC) No1907/2006, as amended.

16. OTHER INFORMATION

Please read the SDS well before use.

SAFETY DATE SHEETS ARE ISSUED BASED ON THE LATEST INFORMATION WE HAVE KNOWN. HOWEVER, THESE ARE NOT THE ONE TO INSURE SAFETY.

THESE ARE PROVIDED TO COMPANIES HANDLING THE MATERIALS AS REFERENCE INFORMATION REGARDING HAZARDOUS AND HARMFUL CHEMICALS TO ENSURE SAFE HANDLING.

WE ASK THAT THESE SHEETS BE USED BY COMPANIES AS REFERENCE AND WITH THE UNDERSTANDING THAT IT IS NECESSARY FOR MESURES APPROPRIATE TO THE SPECIFIC CIRCUMSTANCES RELATED TO HANDLING THE MATERIALS TO BE TAKEN UNDER THEIR OWN RESPONSIBILITY. ACCORDINGLY, THIS DATA SHEET IN NO WAY CONSTITUTES A GUARANTEE OF SAFETY.