

NA10 & WA10 Network Adapter

ENABLING SCANNING DIRECTLY OVER THE NETWORK WITH CANON'S USB SCANNERS



- Expand access by consolidating management of scanners in a workspace on to a single wired or wireless network
- Share access among multiple computers
- Streamline the scanning process via push scanning, undertaking jobs with one button press on the unit
- Perform scanning functions from mobiles and smart devices without using a computer
- Compatibility with CaptureOnTouch Job Tool, an iOS and Android application that enables control of scanning operations from a smart device
- Scan settings from previous jobs can be recalled and executed via the network
- Energy efficient – consumes as little as 4.5W in sleep mode
- Flexible installation – adapter can be stored vertically or horizontally
- Power via the AC adapter of the scanner

Productivity

Increase productivity by consolidating the management of scanners in an office on to a single wired network. No need to physically connect the scanner to a computer, then disconnect and connect to another computer

Control

The NA10/WA10 enables 'push scanning', which allows the user to start the scanning process with one button press on the unit. It also facilitates scanning directly from web applications

Connectivity

The NA10 comes with wired LAN connection interface while the WA10 comes additionally with a WiFi interface.

Ease of use

The NA10/WA10 works with six Canon DR range scanners. It is simple to set up and use

Flexibility

The NA10/WA10 has been designed to fit unobtrusively next to a scanner and can be sited either vertically or horizontally where space may be limited

PRODUCT RANGE



NA10



WA10

Canon

TECHNICAL SPECIFICATIONS

NA10 & WA10 Network Adapter

Product Name	NA10 & WA10 Network Adapter
Type	Network Adapter
Dimensions (W x D x H)	116 × 93,6 × 28.8 mm
Weight	179 g
Network Interface	IEEE802.3 10Base-T/100Base-TX/1000Base-T
Power Supply	The AC adapter supplied with the scanner is used for the power supply. Connect the AC adapter to the WA10/NA10 and connect a relay cable to the scanner to supply power to both the WA10/NA10 and the scanner.
Power Consumption	Maximum power: 7.0 W (WA10), 5.6 W (NA10) Power off: 0.1 W or less
OPERATING ENVIRONMENT	
Temperature	10°C to 35°C (50°F to 95°F)
Humidity	20% to 85% (RH)
WI-FI SPECIFICATION	
BASIC WIRELESS LAN SPECIFICATIONS (WA10 ONLY)	
Data Rate (Theoretical Values)	IEEE802.11b: Up to 11 Mbps IEEE802.11g: Up to 54 Mbps IEEE802.11n: Up to 72.2 Mbps
Frequency	2.4 GHz band
Wi-Fi Security	WPA-PSK (TKIP/AES), WPA2-PSK (TKIP/AES), WEP, open
Wireless standard	IEEE802.11b/g/n (2.4 GHz only)
Easy setting	WPS
Supported imageFORMULA scanners	DR-C230, DR-C240, DR-M140, DR-M160II, DR-M260, DR-M1060



(WA10 only)



Canon Ireland
3006 Lake Drive
Citywest, Saggart
Co. Dublin, Ireland
Tel: 01 2052400
Fax: 01 2052525
canon.ie

Canon (UK) Ltd
Woodhatch
Reigate
Surrey RH2 8BF
Tel: 01737 220000
Fax: 01737 220022
canon.co.uk

Canon Electronics Inc.
Canon.com

Canon Europe
canon-europe.com

English Edition
© Canon Europa N.V., 2018