

EASY SECURE AND INTELLIGENT

Productive monochrome large
format printing



Easy

The PlotWave series is easy to use at first glance thanks to its embedded intelligence and exceptional simplicity. Access and print your latest revisions from your home folder, cloud or local network, or use the intuitive copying and scanning features available on the user interface.

Secure

Security is critical in the modern office environment. SMARTshield protects your data in all phases of the print process, now and in the future. When data is in transit, it is protected by secure, encrypted protocols. When at rest, your data is securely encrypted.

Intelligent

The PlotWave series has intelligent automated functions, such as easy media loading, Pico Printing and Radiant Fusing technology that save time and make life easier in many ways.

PlotWave 7500

For environments where anyone may need to print a complex, large format technical document at any time, the PlotWave 7500 offers excellent quality and robust versatility, without hassle: easy printing, with intelligent automation for impressive results every time.



TECHNICAL SPECIFICATIONS

STANDARD SYSTEM CONFIGURATION

4 Roll printing system (standard)	Productive large format monochrome printer with ClearConnect multi-touch user panel.
Stacking systems (standard)	Integrated Top Delivery Tray, 100 sheets capacity.
ClearConnect multi-touch user interface (standard)	Consistent look and feel from every angle of your workflow, standard including Smart Inbox, SmartAccess and Live Preview.
Roll media switch (standard)	Fully automated roll media switch, to guide the media to the top delivery tray or back output depending on the user application.
ClearConnect workflow software (standard)	Drivers: Driver Select for Microsoft® Windows®, Driver Express PostScript 3 driver. Publishers: Publisher Mobile for IOS and Android® Publisher Express, Publisher Select 3 for Microsoft Windows.
Starter kit included	1 bottle toner 500 g, 1 bottle developer 1750 g, 1 roll 36 inch standard media 75 g/m2.
Earthquake provision¹	Secure the printer against moving or tilting during an earthquake. This provision enables the user to secure the printer to a sturdy connection of the building.

OPTIONAL SYSTEM CONFIGURATIONS

Office space saving scanning system (optional)	Scanner Express with Image Logic technology, integrated scanner positioned on top of the printer to save office space.
Standalone System scanner (optional)	Scanner Professional, productive Stand alone 48 bit color scanner with 1200x1200 dpi CCD technology (9600x9600 dpi interpolated), 22 inch flatpanel touchscreen, powerful embedded Linux controller and 23 meter / scan min speed
Stacking Systems (optional)	Stacker Select, up to 400 sheets capacity. Increase your delivery capacity up to 500 sheets
Roll media capacity upgrade (optional)	Additional 3rd drawer to increase media capacity from 4 to 6 media rolls (800 to 1200 m2).
Cutsheet tray (optional)	Capacity, 250 pages A/A4 size-C/A2-size
Removable hard disk (optional)	For secure environments, hard disk can easily removed from the printer system to secure data integrity
User attention light	For productive environments, the status of the machine is visible from a distance.

TECHNOLOGY

Imaging technology	Electrophotography (LED) with Organic photoconductor (OPC) Radiant Fusing Technology with Instant warm-up Clean toner refill system Virtually no ozone emission
Fusing technology	Instant warm-up, contactless fusing, low power consumption (heating on demand)
Toner / type	Black toner: 1000 gram per toner kit

PRODUCTIVITY

Speed (print and copy)	PlotWave 7500: 10 D/A1-sizes² per minute 5 E/A0 sizes³ per minute
First print out time⁴	< 40 sec
First copy out time⁵	< 40 sec

QUALITY

Print Resolution	600 x 1200 dpi
Minimum line width (ISO/IEC 13660:2001E)	0.06 mm; 0.00236 in
1:1 Line accuracy	< 0.3%

SIZE AND WEIGHT

Size main engine (WxDxH)	Compact design: 1563 x 803 x 1695 mm; (including Top Delivery Tray)
Shipping dimensions (WxDxH)	1470 x 850 x 1280 mm
Weight main engine	286 kg
Shipping weight main engine	335 kg

MEDIA HANDLING

Media capacity	4 or 6 rolls; Cutsheet tray
Paper cutting	Cutter included in the drawers for fast and easy roll media switching
Maximum media capacity	4 roll: 800 m1, 730 m2; 6 roll: 1200 m1, 1095 m2;
Media sizes roll	A4, A3, A2, A1, A0, B1, B2, B3, B, C, D, E, B+, C+, D+, E+, E1, 21", 15", 891 mm, 880 mm, 860 mm, 800 mm, 700 mm, 660 mm, 620 mm, 500 mm, 460 mm, 440 mm, 430 mm, 350 mm, 310 mm
Media sizes Cut sheet tray	Short edge feed (portrait): A4, A3, B4, A, B, A+, B+, Carto B4, 230x310 mm, 310x440 mm. Long edge feed (landscape): A4, A3, A2, B4, B3, B, C, B+, C+, Carto B4, Carto B3, 15x21", 310x440 mm, 440x594 mm
Media weight	60 - 110 g/m2; 16 - 29 lb; film: 3.5 - 4.0 mm
Roll length	Up to 200 m

PlotWave 7500

Roll width	297 - 914 mm; 11 - 36 inch
Minimum printed length	279 mm; 11 inch
Maximum printed length	200 m
Roll media type	Plain paper, Transparencies, Translucent, Recycled paper, Engineering Bond, Engineering Vellum, Coloured paper, Top Label Paper FSC, Red Label Paper PEFC, Black Label Paper PEFC, Green Label FSC, RecycledWhiteZero FSC, Transparent Paper, Transparent Paper FSC, Polyester film, Polyester film antistatic, Contrast Film, Clear Polyester Film, Double Matte Polyester Film, White Opaque Polyester Film, Translucent Engineering Bond, Recycled Engineering Bond, Colour Top, Recycled paper, Plain Paper recycled, Transparent, and Orika LPEX rice paper
Cut sheet media type	Plain paper, Recycled paper, and Coloured paper, films, and transparent media.
Automatic roll media handling	- Automatic width detection - Automatic roll media selection for optimised productivity and media saving, based on drawing size, media type, roll width and finishing - Automatic rotation and alignment for folding - Automatic legend detection - Automatic roll switching when end of roll is reached "
USER INTERFACE	
Description	ClearConnect multi-touch user panel
Size (WxDxH)	300 x 220 x 40 mm; 11.8 x 8.7 x 1.6 in. Touch screen: 10.4 in
Resolution	800 x 600 pixels (SVGA)
Technology	Projective capacitive touch
Operation	3 hard buttons: [Wake-up], [Stop, interrupt, abort], [Home] Multi-touch functions: tab, double tap, pinch, 2 finger pinch, swipe, flick and spread.
Interface design	Distinctive user interface with intuitive navigation and clearly defined levels of operation.
Features	View optimisation: Tilt (-4 to +45 degrees) and turn (-45 to +180 degrees) Status light (red, orange, green) USB 2.0 interface with indication light. Switch instantly between 2 languages, select from 21 languages.
CONTROLLER	
Description	High performance POWERsync controller with Windows 10 IoT LTSC, 64 bits
Processor	Dual Core, Dual Thread Celeron® G4900 @3.10Ghz
Memory	4 GB DDR4
Video	Intel HD Graphics, 1GHz
Hard Disk	500 GB, 7200 rpm (standard)
TPM	TPM2.0
Client operating system support	Windows 7 / Windows 7 64 bits / Windows 8.1 / Windows 8.1 64 bits / Windows 10 / Windows 10 64 bits / Windows Server 2008 R2 64 bits / Windows Server 2012 64 bits / Windows Server 2012 R2 64 bits Mac OS 10.10 / Mac OS 10.11 / Mac OS 10.12 (PostScript 3 driver support only for Mac OS)
Interface	2x Ethernet 100 Mbps/s, 1 Gbit/s TCP/IP: DHCP, IPv4, IPv6, HTTPS Discovery: APIPA, WS-Discovery, SNMP v3
Page description language	TIFF, JPEG, HPGL, HPGL2, DWF, C4, Calcomp 906/907/951, CALS, NIRS, NIFF, PS/PDF (optional)
Printing protocol	LPR, FTP, WebDav, WSD print LPR - FTP - Pull from SMB, FTP - Pull from cloud (retrieve from ARC Collaborate, WebDAV based clouds) - HTTP/HTTPS (used by Publisher Express) - Print from home folder (via optional access management license)
Back channel protocol	SNMP v3, Wave interface, WS-Discovery.
SECURITY	
SMARTshield	E-shredding, IPsec, IP filtering/Access Control Lists, HTTPS, SNMP v3, audit logging, AES256 Disk Encryption, 802.1x Authentication, network protocol enable/disable, LDAP integration, Active Directory Integration , User authentication on local ClearConnect user panel and via Express WebTools (LDAP/Active Directory credentials, smart card) for scan/copy/print. Configure HTTPS Certificates. Allow disabling TLS1.0 and 1.1 protocols (no response to network scan) and enable TLS 1.2 with stronger cipher. Embedded FIPS 140-2 Certified Trusted Platform Module (TPM) and BitLocker 256 AES hard disk encryption, hard disk wipe , Configurable CA certificate, Disable Network Ports and Protocols, Security Event Logging, Single Sign-on . Options: Removable hard disk, McAfee antivirus, McAfee Application control (whitelisting).
Cloud support	Unlimited user and or Administrator authenticated cloud support via WebDAV and/or third party provider: e.g. Microsoft® SharePoint®, Dropbox®, Box.com, box.net, Google® Drive®, Microsoft® OneDrive®, Amazon Cloud Drive®, Cloudsafe®, MyDisk®, PlanWell Collaborate. The cloud user authentication can either be preconfigured by the administrator or done by the user at the time of accessing the specific cloud.
Transformations	Scaling (scale-to-fit page, reduce when image too large to avoid clipping or to custom factor, scale page size to standard size), Rotation, Shift (automatic or user defined), Adding/removing trailing/leading edge, Mirror, Black intensity in poster mode, Print optimisation (standard, lines/text, poster). Colour Highlight and Dark Original. Area to erase (area of interest).

SCANNER EXPRESS (optional)		PERIPHERALS	
Description	Integrated Contact Image Sensor (CIS) Colour scanner with Image Logic technology	SCANNER PROFESSIONAL (optional)	
Scan resolution	600 x 600 dpi	Description	Charge-coupled device (CCD) colour 44" scanner with optional upgrade to 48"
Scan speed	15.2 m/min Black & white scanning 10.1 m/min Copying 5.0 m/min Colour scanning	Scan resolution	1200 x 1200 dpi (9600 x 9600 dpi interpolated)
Scan formats	TIFF, PDF, PDF/A, JPEG, CALS, multi-page PDF, multi-page PDF/A and multi-page TIFF	Scan speed	23 m/min (200 dpi) 6 m/min (600 dpi)
Scan templates	Extensive number of scan templates to standardise common scan settings and destinations	Scan formats	Multipage PDF (PDF/A) and TIFF, JPEG, JPEG 2000, PNM, PNG, BMP, TIFF (Raw, G3, G4, LZW, JPEG) AutoCAD DWF, JBIG, DjVu, DICOM, PCX, Postscript, EPS, Raw data
Scan protocol	FTP, SMB, scan to cloud (push to WebDAV based clouds)	Scan templates	unlimited
Scan destination	Local USB flash drive, FTP, SMB, Smart Inbox on Controller, Optional Local Home folder (LDAP), mobile device via Mobile WebTools, WebDAV Clouds, PlanWell Collaborate.	Original width	1270 mm; 50 inch
Scan naming	Preset naming with auto numbering for productive scanning or file name on the ClearConnect user panel.	Original length	Endless
Original width	208 mm - 914 mm; 8.2" - 36", automatic width detection	Colour depth/ colour output	48 bit colour, 16 bit greyscale / 24 bit colour, 8 bit greyscale, bitonal, enhanced halftone
Original length	208 mm - 16000 mm; 8.2" - 630", automatic length detection	Scan width	44 model: 118 mm; 44" / 48 model: max. 1220 mm; 48"
Original thickness	Maximum 0.8 mm; 0.03" (non-rigid documents)	Connections	1 USB Port 3.0 Interface 1 GBit Fast Ethernet with TCP/IP based Interface
Zoom (copy)	1:1, Scale to media size, Scale to standard format, Custom: 10 - 1000%	Embedded controller	64 bit Linux, Intel i3, quad core processor, 16 Gigabyte RAM, 320GB HDD for unfold long scans
Original types presets	Blueprint, Coloured original, Dark original, Folded lines/text, Lines/text standard, Lines/text draft, Photo, Map, Artwork	Size scanner (WxDxH)	228 x 1425 x 507 mm; 9 x 56.1 x 20" (H x W x D)
Size scanner (WxDxH)	1097 x 308 x 140 mm; 43 x 12 x 5.5".	Weight scanner	53 kg / 117 lbs
Weight scanner	25 kg; 55 lbs	FOLDER EXPRESS 3011 (optional)	
ENVIRONMENTAL		Description	Integrated automatic fullfold folder saving office space.
Sound power level	Standby and sleep: less than 26 dB Print mode: less than 52 dB	Folding speed	Folding speed 1 - 11 m/min ; 0.7 - 7.2"/sec
Ozone concentration	< 0.002365 PPM (0,25% of permitted limit value)	Dimensions folder	1748 x 852 x 1118 mm; 70 x 63 x 44"
Heat emission	Ready: 66 W; Active: 1.7 kW	Delivery capacity	80 A0/E size folded packages (80 gr/m2)
Power requirements	100 - 240 V; 50/60Hz	FOLDER PROFESSIONAL 6011/13 (optional)	
Power consumption	Sleep mode: <2 W ready mode: 66 W Active mode: 1.7 kW	Description	Integrated productive fullfold folder with automated, manual folding and unfold output.
Safety/ EMC marks & environmental labels	CE, TUV GS, CETECOM, Energy Star 3.0, FEMP, Rohs, CCC, VCCI TüV GS, c-UL-US, CB, RCM, EPEAT, EAC, FCC Class A, VCCI Class A	Folding speed	2,5 - 10 m/min ; 1.6 - 6.6"/sec (29 m/min ; 11.8"/sec with optional High Speed License)
Recyclables	Printer: made of steel or highly recyclable plastics: up to 95% of the engine can either be up cycled or recycled. Remaining 5% are non toxic waste. Prints: very good deinkability when recycled. Toner: bottles made of highly recyclable HDPE (High Density Polyethylene)	Dimensions Folder Professional 6011/6013 (WxDxH)	1837 x 1634 x 1227 mm (6011) 2157 x 1634 x 1227 mm (6013)
CLEARCONNECT WORKFLOW SOFTWARE		Delivery capacity (standard delivery belt)	150 A0/E size folded packages (80 gr/m2)
Job submission	The ClearConnect software suite consists of a variety of applications with the same user interface. Create, retrieve and/or send jobs from drivers (Driver select for Microsoft Windows, Driver Express for Adobe PostScript 3 for Microsoft Windows or Apple OS), external locations (SMB, FTP, LPR, WebDAV), Mobile devices via Express WebTools and Publisher Mobile, USB flash drive, Cloud services and optional Home folder(LDAP), Optional PlanWell Collaborate. 1-click printing from USB, 1-click printing from previous sent jobs via Print SmartAccess on ClearConnect user panel. The Smart Inbox on the ClearConnect user panel enables the job preview: swipe between your jobs for print selection and preview. Pan to view the image in detail (zoom). With the template-oriented Publisher Select 3 submitting multiple files in batches is supported. Print multiple times, and sort by page or set. Media saving automatically rotates print files to optimise media usage.	Reinforcement (tab unit)	Folder Professional 6013 only
Smart inbox	Personalised Smart Inbox with history, Manage queue, Manage history, Express WebTools, Secured controller access	STACKER SELECT	
Queue management	Spool memory provides a queuing system for print and copy jobs. This enables multiple users to send print and copy jobs at the same time. Customise priority settings for copy and print jobs in the queue. The Job Queue overview gives access to job names, owners and status including required media. Jobs can be paused, deleted, and placed on top of the queue.	Description	Integrated productive stacker with high capacity and tray full sensor
Print management & accounting	View the counter history at preferred time periods, per job or total overview in Express WebTools. View, create, edit and delete stamp templates. Optional uniFLOW support, login your personal uniFLOW Queue on the ClearConnect User interface. Supports manual authentication, card readers, and contactless card readers.	Capacity	up to 400 sheets
Device management	Express WebTools provide administrators the tools to manage the device remotely via the web: e.g. check printer status, define default settings for print, copy and scan, define access, security, accounting, remote shutdown, software update and restart, power on/off timer, system behaviour, queue management, license management, view, create, edit and delete stamp templates etc.	FOOTNOTES:	
Scan to colour inkjet	Scan directly to iPF 600/700/800/TX-2000/3000/4000/5200/5300/5400 series via Publisher Select 3 (hotfolder)	1	Excluding cable/chain and mounting material
		2	D size (34 x 22") / A1 size (841 x 594 mm)
		3	E-size (36 x 48") / A0 Size (841 x 1189 mm)
		4	1 A1 landscape print made from the smart inbox, on 64 g media, back output, lines and text mode.
		5	1 copy made with A1 original in landscape on 64 g media, back output, background compensation off, custom width 841 mm, custom length 594 mm.

© 2020 Canon Production Printing

Canon is a registered trademark of Canon Inc. All other trademarks are the property of their respective owners and hereby acknowledged.

No part of this publication may be copied, modified, reproduced or transmitted in any form or by any means, electronic, manual, or otherwise, without the prior written permission of Canon Production Printing. Illustrations and printer output images are simulated and do not necessarily apply to products and services offered in each local market. The content of this publication should neither be construed as any guarantee or warranty with regard to specific properties or specifications nor of technical performance or suitability for particular applications. The content of this publication may be subject to changes from time to time without notice. Canon production printing shall not be liable for any direct, indirect or consequential damages of any nature, or losses or expenses resulting from the use of the contents of this publication.

Canon

Canon Europe
canon-europe.com
English edition
