Page 1/9




Safety data sheet according to 1907/2006/EC, Article 31

Printing date 30.10.2017

Version number 119

Revision: 30.10.2017



Page 2/9

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 30.10.2017

Version number 119

Revision: 30.10.2017

(Contd. of page 1)

Trade name: LONGS GENERAL PURPOSE MULTI FOAM 400 ML

- · Signal word Danger
- · Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.H319 Causes serious eye irritation.

· Precautionary statements

- P102 Keep out of reach of children.
- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P211 Do not spray on an open flame or other ignition source.
- P251 Do not pierce or burn, even after use.
- P260 Do not breathe spray.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

- P501 Dispose of contents / container in accordance with regional regulations.
- · 2.3 Other hazards

· Results of PBT and vPvB assessment

- **PBT:** Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

| · Dangerous components: | | |
|--|---|-------------------|
| CAS: 67-63-0 EINECS: 200-661-7 Index number: 603-117-00-0 Reg.nr.: 01-2119457558-25 CAS: 74-98-6 | | 2.5-<5% |
| EINECS: 200-827-9 Index number: 601-003-00-2 Reg.nr.: 01-2119486944-21 | propane Flam. Gas 1, H220 Press. Gas C, H280 | |
| CAS: 106-97-8 EINECS: 203-448-7 Index number: 601-004-00-0 Reg.nr.: 01-2119474691-32 | butane Flam. Gas 1, H220 Press. Gas C, H280 | 2.5-<5% |
| CAS: 75-28-5 EINECS: 200-857-2 Index number: 601-004-00-0 Reg.nr.: 01-2119485395-27 | isobutane Flam. Gas 1, H220 Press. Gas C, H280 | 2.5-<5% |
| CAS: 107-98-2 EINECS: 203-539-1 Index number: 603-064-00-3 Reg.nr.: 01-2119457435-35 | 1-methoxy-2-propanol Flam. Liq. 3, H226 STOT SE 3, H336 | <2.5% |
| CAS: 1336-21-6 EINECS: 215-647-6 Index number: 007-001-01-2 | ammonia Acute Tox. 3, H331 Skin Corr. 1B, H314 Aquatic Acute 1, H400 Acute Tox. 4, H302 | ≤ 0.5% |
| · Regulation (EC) No 648/20 | 04 on detergents / Labelling for contents | |
| aliphatic hydrocarbons | | ≥ 5 - <15% |

(Contd. on page 3)

Page 3/9

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 30.10.2017

Version number 119

Revision: 30.10.2017

Trade name: LONGS GENERAL PURPOSE MULTI FOAM 400 ML

(Contd. of page 2)

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Generally the product does not irritate the skin.
- · After eye contact:
- Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- \cdot 4.3 Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:
- CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · 5.2 Special hazards arising from the substance or mixture
- During heating or in case of fire poisonous gases are produced.
- · 5.3 Advice for firefighters -
- · Protective equipment: Mouth respiratory protective device.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Mount respiratory protective device.
- Wear protective equipment. Keep unprotected persons away.
- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up: Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.
- 6.4 Reference to other sections
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

SECTION 7: Handling and storage

- 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace. No special measures required.
 Information about fire - and explosion protection: Do not spray onto a naked flame or any incandescent material. Keep ignition sources away - Do not smoke. Keep respiratory protective device available. Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles:
- Observe official regulations on storing packagings with pressurised containers.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 2 B

(Contd. on page 4)

Page 4/9

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 30.10.2017

Version number 119

Revision: 30.10.2017

Trade name: LONGS GENERAL PURPOSE MULTI FOAM 400 ML

(Contd. of page 3)

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

• Additional information about design of technical facilities: No further data; see item 7.

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

67-63-0 propan-2-ol

WEL Short-term value: 1250 mg/m³, 500 ppm Long-term value: 999 mg/m³, 400 ppm

106-97-8 butane

WEL Short-term value: 1810 mg/m³, 750 ppm Long-term value: 1450 mg/m³, 600 ppm Carc (if more than 0.1% of buta-1.3-diene)

107-98-2 1-methoxy-2-propanol

WEL Short-term value: 560 mg/m³, 150 ppm Long-term value: 375 mg/m³, 100 ppm Sk

· Additional information: The lists valid during the making were used as basis.

· 8.2 Exposure controls

· Personal protective equipment:

• General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Do not inhale gases / fumes / aerosols. Avoid contact with the eyes and skin. Avoid contact with the eyes.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection:



Tightly sealed goggles

(Contd. on page 5)

*

*

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 30.10.2017

Version number 119

Revision: 30.10.2017

Trade name: LONGS GENERAL PURPOSE MULTI FOAM 400 ML

(Contd. of page 4)

| 9.1 Information on basic physical and c | hemical properties |
|--|--|
| General Information Appearance: | |
| Appearance: Form: | Aerosol |
| Colour: | Clear |
| Odour: | Ammonia-like |
| Odour threshold: | Not determined. |
| pH-value: | Not determined. |
| Change in condition | |
| Melting point/freezing point: Initial boiling point and boiling range | Undetermined. |
| Flash point: | <0 °C (<32 °F) |
| rusn point. | Not applicable, as aerosol. |
| Flammability (solid, gas): | Not applicable. |
| Ignition temperature: | 425 °C (797 °F) |
| Decomposition temperature: | Not determined. |
| Auto-ignition temperature: | Product is not selfigniting. |
| Explosive properties: | <i>Product is not explosive. However, formation of explosive air/vapour mixtures are possible.</i> |
| Explosion limits: | |
| Lower: | 2 Vol % |
| Upper: | 12 Vol % |
| Vapour pressure at 20 °C (68 °F): | 8 hPa (6 mm Hg) |
| Density at 20 •C (68 •F): | 0.93 g/cm ³ (7.76 lbs/gal) |
| Relative density | Not determined. |
| Vapour density | Not determined. |
| Evaporation rate | Not applicable. |
| Solubility in / Miscibility with | Not missible on diff out to min |
| water: | Not miscible or difficult to mix. Not determined. |
| Partition coefficient: n-octanol/water: | |
| Viscosity: | |
| Dynamic: | Not determined. |
| Kinematic: | Not determined. |
| Solvent content: | 10.0.07 |
| Organic solvents: | 18.8% |
| EU-VOC: | 717.2 g/l |
| EU-VOC in %: | 21.60 % |
| Water: | 77.9 % |
| VOC (EC) | |
| VOC-EU% | 717.2 g/l 21.60 % |
| | |
| Solids content: | 0.4 % |

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

(Contd. on page 6)

GB

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 30.10.2017

Version number 119

Revision: 30.10.2017

(Contd. of page 5)

Trade name: LONGS GENERAL PURPOSE MULTI FOAM 400 ML

- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.
- Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- \cdot Serious eye damage/irritation
- Causes serious eye irritation.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- *Reproductive toxicity Based on available data, the classification criteria are not met.*
- $\cdot \textit{STOT-single exposure Based on available data, the classification criteria are not met.}$
- $\cdot \textit{STOT-repeated exposure Based on available data, the classification criteria are not met.}$
- \cdot Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · 12.5 Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

| • European | · European waste catalogue | |
|------------|---|--|
| 20 01 13* | solvents | |
| 15 01 04 | metallic packaging | |
| | metallic packaging containing a hazardous solid porous matrix (for example asbestos), including empty pressure containers | |
| | (Contd. on page 7) | |

Page 7/9

*

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 30.10.2017

Version number 119

Revision: 30.10.2017

(Contd. of page 6)

Trade name: LONGS GENERAL PURPOSE MULTI FOAM 400 ML

· Uncleaned packaging:

• Recommendation: Non contaminated packagings may be recycled.

| 14.1 UN-Number ADR, IMDG, IATA | UN1950 |
|--|---|
| 14.2 UN proper shipping name | |
| ADR | 1950 AEROSOLS |
| IMDG | AEROSOLS |
| ΙΑΤΑ | AEROSOLS, flammable |
| 14.3 Transport hazard class(es) | |
| ADR | |
| | |
| Class | 2 5F Gases. |
| Label | 2.1 |
| IMDG, IATA | |
| Class | 2.1 |
| Label | 2.1 |
| 14.4 Packing group ADR, IMDG, IATA | not regulated |
| 14.5 Environmental hazards: | Not applicable. |
| 14.6 Special precautions for user | Warning: Gases. |
| Danger code (Kemler): | - |
| EMS Number: | F-D,S-U |
| Segregation groups | Alkalis |
| Stowage Code | SW1 Protected from sources of heat. |
| | SW22 For AEROSOLS with a maximum capacity of 1 litre Category A. For AEROSOLS with a capacity above 1 litre |
| | Category B. For WASTE AEROSOLS with a capacity above 1 title Category B. For WASTE AEROSOLS: Category C, Clear |
| | of living quarters. |
| Segregation Code | SG69 For AEROSOLS with a maximum capacity of 1 litre |
| 0.0 | Segregation as for class 9. Stow "separated from" class 1 |
| | except for division 1.4. For AEROSOLS with a capacity |
| | above 1 litre: Segregation as for the appropriate |
| | subdivision of class 2. For WASTE AEROSOLS: |
| | Segregation as for the appropriate subdivision of class 2. |
| 14.7 Transport in bulk according to Ann Marpol and the IBC Code | ex II of Not applicable. |
| Transport/Additional information: | |
| ADR | |
| Limited quantities (LQ) | 1L |
| Excepted quantities (\widetilde{EQ}) | Code: E0 |
| | Not permitted as Excepted Quantity |

- GB

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 30.10.2017

Version number 119

Revision: 30.10.2017

Trade name: LONGS GENERAL PURPOSE MULTI FOAM 400 ML

| | (Contd. of pag |
|--|------------------------------------|
| | Code: E0 |
| | Not permitted as Excepted Quantity |
| Transport category | 2 |
| Tunnel restriction code | D |
| IMDG | |
| Limited quantities (LQ) | 1L |
| \cdot Excepted quantities (\widetilde{EQ}) | Code: E0 |
| | Not permitted as Excepted Quantity |
| | Code: E0 |
| | Not permitted as Excepted Quantity |
| UN "Model Regulation": | UN 1950 AEROSOLS, 2.1 |

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P3a FLAMMABLE AEROSOLS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- \cdot Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H220 Extremely flammable gas. H225 Highly flammable liquid and vapour. H226 Flammable liquid and vapour. H280 Contains gas under pressure; may explode if heated. H302 Harmful if swallowed. H314 Causes severe skin burns and eye damage. H319 Causes serious eye irritation. H331 Toxic if inhaled. H336 May cause drowsiness or dizziness. H400 Very toxic to aquatic life. · Department issuing SDS: R&D legislation and regulatory advisor · Contact: Mr. K. Smedeman · Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

- VOC: Volatile Organic Compounds (USA, EU) PBT: Persistent, Bioaccumulative and Toxic
- vPvB: very Persistent and very Bioaccumulative

Flam. Gas 1: Flammable gases – Category 1

Aerosol 1: Aerosols – Category 1

(Contd. on page 9)

- GB

Page 9/9

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 30.10.2017

Version number 119

Revision: 30.10.2017

Trade name: LONGS GENERAL PURPOSE MULTI FOAM 400 ML

(Contd. of page 8)

GB

Press. Gas C: Gases under pressure - Compressed gas Flam. Liq. 2: Flammable liquids – Category 2 Flam. Liq. 3: Flammable liquids – Category 3 Acute Tox. 4: Acute toxicity – Category 4 Acute Tox. 3: Acute toxicity – Category 3 Skin Corr. 1B: Skin corrosion/irritation – Category 1B Eye Irrit. 2: Serious eye damage/eye irritation – Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

 $\cdot *$ Data compared to the previous version altered.