- + The power of UVgel. Our unique UVgel technology creates robust, light-fast and scratch-resistant prints with a superior print quality.
- + White ink without worry. Developed for the Colorado M-series, our UVgel ink set now brings you a next-level white ink: hassle-free and with spectacular results. With a brief service visit, you can even enjoy UVgel white.
- + FLXfinish<sup>+</sup>. A game-changer in large-format graphics. Print matte, gloss or mixed matte and gloss in one print, without varnish or an additional printhead.
- + FLXture. Look no further for the magic touch. With FLXture, you can add subtle surface detail to your prints, creating a luxurious and intriguing feel for your products.

- + Impressive media range. More design freedom to impress your customers. Easily print textured, transparent, coloured, reflective, magnetic and heatsensitive media, plus many more!
- + Upgradeable without service visits. Is your business changing course or growing quickly? Easily add speed, FLXfinish<sup>+</sup>, magnetic media support and many other new functionalities to your Colorado M-series printer.
- + Rock-solid quality. The Colorado family is built to last, for high uptime and consistent print output. Reliable from print to print and from year to year.
- + Level up your Colorado into a Factory. Add a jumbo roll bulk feed system and perfectly matching finishing modules for a high throughput and overnight jobs.
- + Designed with sustainability in mind. Reduced ink usage, reduced energy usage, low emissions - reduce your costs and your environmental footprint at the same time.



No part of this publication may be copied, modified, reproduced or transmitted in any form or by any means, electronic, manual, or otherwise, without the prior written permission of Canon Production Printing. Illustrations and printer output images are simulated and do not necessarily apply to products and services offered in each local market. The content of this publication should neither be construed as any representation, guarantee or warranty with regard to specific properties or specifications nor of technical performance or suitability for particular applications. The content of this publication may be subject to changes from time to time without notice. Canon Production Printing shall not be liable for any direct, indirect or consequential damages of any nature, or losses or expenses resulting from the use of the contents of this publication.

### © 2025 Canon Production Printing

anon Inc Colorado is a registered trademark of Canon Production Printing Netherlands B.V.

## Canon

# GA MF

Colorado M-series

i I

Canon Inc. canon.com

Canon Europe canon-europe.com

English Edition © Canon Europa N.V. 2025 **Canon Europe Limited** 

4 Roundwood Avenue Stockley Park Uxbridge UB11 1AF

## Canon

Are you ready for the next level in productivity, creativity and profitability? With the Colorado M-series, you can say 'yes' to more jobs, create stunning applications and promise short turnaround times. It's field upgradeable to grow with your business, and designed for a low cost of ownership.

### **Colorado M-series**



M3

M3W

Colorado Colorado Colorado

M5



M5W



Factory

UVgel Packaging Factory

UVgel UVgel Print Wallpaper Factory



Colorado Colorado M3 M3W

Colorado M5

4

0

750 kg

0 W

5

| Printing method                    | UVgel piezoelectric inkjet |         |                     |                 |               | PRINTHEAD  |   |        |
|------------------------------------|----------------------------|---------|---------------------|-----------------|---------------|--|---|--------|
|                                    |                            |         |                     |                 | <u>^</u>      |  |   |        |
| White                              | 0                          | •       | 0                   | •               | 0             | UVgel 425  | 4 |        |
| PRINTING MODES: GLOSS              | •<br>111 m²/hr             |         | •                   |                 | •             | High frequency drop-on-demand piezo-electric printhead |   |        |
| High Key                           | 111                        | m²/hr   | 1                   | 159 m²/hr       | 159 m²/hr     | PAINT (Piezo Acoustic Integrated Nozzle                |   |        |
| Express                            | 78 m²/hr                   |         | 114 m²/hr           |                 | 114 m²/hr     | Technology)  |   |        |
| Speed                              | 55 m²/hr                   |         | 80 m²/hr            |                 | 80 m²/hr      | Automatic maintenance                                  |   |        |
| Production                         | 39                         | m²/hr   |                     | 57 m²/hr        | 57 m²/hr      | Curing   |   |        |
| High Quality                       | 29                         | m²/hr   |                     | 40 m²/hr        | 40 m²/hr      | Media  |   |        |
| Premium                            | 22                         | m²/hr   |                     | 27 m²/hr        | 27 m²/hr      |  |   |        |
| Specialty                          | 19                         | m²/hr   |                     | 20 m²/hr        | 20 m²/hr      | Roll width   |   |        |
| PRINTING MODES: MATTE              |                            | 0       |                     | 0               | 0             | Print margin   |   |        |
| Express                            | 36                         | m²/hr   |                     | 46 m²/hr        | 46 m²/hr      | Roll weight  |   |        |
| Speed                              | 27                         | m²/hr   |                     | 38 m²/hr        | 38 m²/hr      | Roll diameter  |   |        |
| Production                         | 22                         | m²/hr   |                     | 31 m²/hr        | 31 m²/hr      | Media thickness  |   |        |
| High Quality                       | 18                         | m²/hr   |                     | 27 m²/hr        | 27 m²/hr      | Media input  |   |        |
| Specialty                          | 18                         | m²/hr   |                     | 20 m²/hr        | 20 m²/hr      | Print side out   |   |        |
| Matte Density                      | 10 m²/hr                   |         | 10 m²/hr            |                 | 10 m²/hr      | Print side in/Double-sided printing                    |   |        |
| Backlit                            | 13 m²/hr                   |         | 20 m²/hr            |                 | 20 m²/hr      | 1 roll   |   |        |
| Backlit Density                    | 10                         | m²/hr   |                     | 10 m²/hr        | 10 m²/hr      | 2 rolls (automatic roll-feeding and -                  |   |        |
| Backlit High Density               | 71                         | m²/hr   |                     | 7 m²/hr         | 7 m²/hr       | switching depending on media)                          |   |        |
| PRINTING MODE: MIXED MATTE/GLOSS   |                            | 0       |                     | 0               | 0             | Magnetic media kit                                     |   |        |
| FLXfinish⁺                         | 7 m²/hr                    |         | 7 m²/hr             |                 | 7 m²/hr       | Jumbo roll interface                                   | - |        |
| PRINTING MODES: SPOT WHITE 1 LAYER |                            |         |                     |                 |               | Input/Output Interface                                 |   |        |
| Express                            | 27 m²/hr                   |         | 36 m²/hr            |                 | 36 m²/hr      | Colorado Light Tension Bar-X                           |   |        |
| Speed                              | 22 m²/hr                   |         | 30 m²/hr            |                 | 30 m²/hr      | UVGEL TECHNOLOGY                                       |   |        |
| Production                         | 18 m²/hr                   |         | 24 m²/hr            |                 | 24 m²/hr      | Instant pinning and dot gain control                   |   |        |
| High Quality                       | 13                         | m²/hr   | 18 m²/hr            |                 | 18 m²/hr      | Low temperature curing - suitable for                  |   |        |
| Specialty                          | 91                         | m²/hr   | 12 m²/hr            |                 | 12 m²/hr      | thin and heat-sensitive media                          |   |        |
| PRINTING MODES: WHITE              |                            |         |                     |                 |               | Outstanding scratch resistance                         |   |        |
| UNDERFLOOD/OVERFLOOD 2 LAYERS      |                            |         |                     |                 |               | Easy lamination, smooth ink film                       |   |        |
| Speed                              | 20                         | m²/hr   | 20 m²/hr            |                 | 20 m²/hr      | High precision colour-matching and<br>consistency      |   |        |
| Production                         | 14                         | m²/hr   |                     | 14 m²/hr        | 14 m²/hr      | Odourless and instant dry printout                     |   |        |
| High Quality                       | 10                         | m²/hr   |                     | 10 m²/hr        | 10 m²/hr      | FLXfinish*   |   |        |
| Specialty                          | 71                         | m²/hr   |                     | 7 m²/hr         | 7 m²/hr       | Certifications   |   |        |
| PRINTING MODES: WHITE 3 LAYERS     |                            |         |                     |                 |               |  |   |        |
| High Quality                       | 7 m²/hr                    |         | 7 m²/hr             |                 | 7 m²/hr       | Environmental and safe use                             |   |        |
| Specialty                          | 5 m²/hr                    |         | 5 m²/hr             |                 | 5 m²/hr       | Media  |   |        |
| PRINTING MODES: WHITE 5 LAYERS     |                            |         |                     |                 |               | Interface  |   |        |
| High Quality                       | 4 m²/hr                    |         | 4 m²/hr             |                 | 4 m²/hr       | Dimensions   |   |        |
| Specialty                          | 3 m²/hr                    |         | 3 m²/hr             |                 | 3 m²/hr       | Printer W x D x H                                      |   |        |
| PRINT RESOLUTION                   |                            |         |                     | Up to 1.800 dpi |               | Weight   |   |        |
| INK TYPES                          |                            |         | Canon UVgel 460 ink |                 |               |  |   |        |
| INK COLOR                          | СМҮК                       | CMYKW   | СМҮК                | CMYKW           | CMYK or CMYKW | Printer  |   |        |
| INK PACKAGING                      |                            |         |                     |                 |               | Working environment                                    |   |        |
| 1 x 0.7 litre ink bottle           |                            | •       |                     |                 | •             | Operation printer                                      |   | 18 - 3 |
| 2 x 1 litre ink bottle             | -                          |         | •                   |                 | •             |  |   | 20     |
| Ink reservoir per ink color        | 1,8                        | 3 litre |                     | 2,1 litre       |               | Power  |   |        |
| Refill while printing              |                            |         |                     | •               |               | Off  |   |        |





Colorado UVgel Packaging M5W Factory

UVgel Wallpaper Factory Factory

UVgel Print



Colorado

M5



UVgel Packaging

Factory

UVgel

Wallpaper Factory

Colorado

M5W

0

0

0

0



UVgel Print

Factory

5 4 or 5 ٠ ٠ • UV LED

| Up to 1.625 mm |   |
|----------------|---|
| 5,3 mm*        |   |
| Up to 50 kg    |   |
| Up to 220 mm   |   |
| Up to 1,6 mm   |   |
|                |   |
| •              |   |
| 0              |   |
| •              |   |
| 0              |   |
| 0              |   |
| 0              | • |
| Ū              | 0 |
|                | 0 |
|                | 0 |
| •              |   |
| -              |   |
| •              |   |
| •              |   |
| •              |   |
| •              |   |
| •              |   |
| 0              |   |
|                |   |
|                |   |

Indoor AgBB, GREENGUARD Gold, CE EN 15102 (decorative wall coverings) ASTM F793 Type II, M1, B-s1d0, Émissions dans l'air intérieur A+

3M<sup>™</sup> MCS<sup>™</sup> Warranty/Avery Dennison ICS Performance Guarantee



● Standard O Optional - Not available

| Standby  |   |   |                   |                       |    |   |  |  |
|--|---|---|-------------------|-----------------------|----|---|--|--|
| Ready  |   | 1.350                                     |                   |                       |    |   |  |  |
| Printing   |   | 2.000 W                                   |                   |                       |    |   |  |  |
|  |   |   |                   |                       |    |   |  |  |
| Consumption  |   | 2 inputs, each 200                        | D-240V +/- 10%,   |                       |    |   |  |  |
|  |   | 50/60 Hz,                                 |                   |                       |    |   |  |  |
| Source   | Pi  | rinter is declared und<br>Directive (RED) |                   |                       |    |   |  |  |
| Regulatory certification   |   |   |                   |                       |    |   |  |  |
| Declaration of conformity  | Compliant v   | vith EN62479, EN3014                      | 489-1, EN301 489- | 3, EN300-330          |    |   |  |  |
|  | F   | CC Part 15 and RSS-21                     |                   |                       |    |   |  |  |
| Radio  | IEC/EN/UL/CSA 62  | 2368-1 compliant App<br>RCN               |                   |                       |    |   |  |  |
| Safety   | Emission: Class A   | compliant according<br>Immunity: CISPF    |                   |                       |    |   |  |  |
|  | Applic  | able marks: CE, FCC,                      |                   |                       |    |   |  |  |
| EMC  |   |   |                   |                       |    |   |  |  |
| Environmental  | W   | EEE, RoHS directive 2                     |                   |                       |    |   |  |  |
| Software   |   |   |                   |                       |    |   |  |  |
| Factory supported RIPs   |   |   | (                 | ONYX Graphics, Calder | ra |   |  |  |
| Supported RIPs   | EFI, PrintFactory, ColorGATE, ErgoSoft, Shiraz, AGFA, SAI |   |                   |                       |    |   |  |  |
| API  | Colorado API for 3rd party vendors                        |   |                   |                       |    |   |  |  |
| PRISMAguide XL   | 0   |   |                   |                       |    |   |  |  |
| PRISMA remote app  | •   |   |                   |                       |    |   |  |  |
| PRISMAservice  | •   |   |                   |                       |    |   |  |  |
| External modules   |   |   |                   |                       |    |   |  |  |
| Jumbo Roll Loader  | -   | -   | -                 | -                     | •  | • |  |  |
| X/Y Cutter   | -   | -   | -                 | -                     | •  | • |  |  |
| Rewinder   | -   | -   | -                 | -                     | -  | 0 |  |  |
| Jumbo Roll Rewinder  | -   | -   | -                 | -                     | •  | - |  |  |
| Warranty programme <sup>1</sup>                                      |   |   |                   |                       |    |   |  |  |
| STANDARD WARRANTY  |   |   |                   |                       |    |   |  |  |
| Printer: 2 years   |   |   |                   | •                     |    |   |  |  |
| Printhead: 2 years or 20.000 sqm, whichever comes first <sup>2</sup> |   |   |                   | •                     |    |   |  |  |
| EXTENDED WARRANTY  |   |   |                   |                       |    |   |  |  |
| Extended Parts Coverage (3, 4 or 5-years)                            |   |   |                   | 0                     |    |   |  |  |
|  |   |   |                   |                       |    |   |  |  |

Extended Parts and Printhead Coverage

(3, 4 or 5-years)<sup>3</sup>

Service programme<sup>4</sup>

proCARE (3, 4 or 5-years)

proCARE+ (3, 4 or 5-years)⁵

Please be aware that there might be regional distinctions in Warranty programmes, Term and Conditions applicable.
Repair or replacement of an item does not extend the warranty period of the item repaired or replaced.
The following volume levels are applicable: Prime (3 years or 50.000 sqm, 4 years or 40.000 sqm, 5 years or 50.000 sqm)
Plus (3 years or 60.000 sqm, 4 years or 80.000 sqm, 5 years or 100.000 sqm)
Pro (3 years or 90.000 sqm, 4 years or 120.000 sqm, 5 years or 150.000 sqm)

Pro (5 years of 90:000 sqm, 4 years of 120:000 sqm, 5 years of 150:000 sqm, 6 years of 150:000 sqm, 5 years of 15

٠

٠