



Ecma/TC38-TG3/2015/025 (Rev. 1 – 15 April 2015)

Annex B1 - Product environmental attributes Imaging equipment

The declaration may be published only when all rows and/or fields marked with * are filled-in (n.a. for not applicable). Additional information regarding each item may be found under P15.

Brand *	Canon	Logo
Company name *	Canon Europa N.V.	
Contact information *	environment@canon-europe.com	Canon
e-mail address		Californ
Internet site *	www.canon-europe.com	
Additional information		

The company declares (based on product specification or test results based obtained from sample testing), that the product conforms to the statements given in this declaration.			
Type of product *	Type of product * MFD		
Commercial name *	imageRUNNER ADVANCE DX 6765i		
Model number *	imageRUNNER ADVANCE DX 6765i		
Issue date *	2019/12/20		
Intended market *	☐ Global ☐ Europe ☐ Asia, Pacific & Japan ☐ Americas ☐ Other		
Additional information			

This is an uncontrolled copy when in printed form. Please refer to the contact information for the latest version.

About Annex B1

Annex B1 reflects Product environmental attributes relevant for Imaging products. The following items from the ECMA-370 Main body are not shown in the template:

P9.1 PTEC, ETEC and display resolution P12.1-P12.2 Ergonomic requirements.

Model number *	imageRUNNER ADVANCE DX 6765i	Logo	0
Issue date *	2019/12/20		Canon

Product	Product environmental attributes - Legal requirements			met
Item		Yes	No	n.a.
P1	Hazardous substances and preparations			
P1.1*	Products do comply with the current European RoHS Directive. (See legal reference and NOTE B1)	\boxtimes		
P1.2*	Products do not contain Asbestos (see legal reference). Comment: Legal reference has no maximum concentration value.			
P1.3*	Products do not contain Ozone Depleting Substances: Chlorofluorocarbons (CFC), hydrobromofluorocarbons (HBFC), hydrochlorofluorcarbons (HCFC), Halons, carbontetrachloride, 1,1,1-trichloroethane, methyl bromide (see legal reference). Comment: Legal reference has no maximum concentration values.			
P1.4*	Products do not contain more than; 0,005% polychlorinated biphenyl (PCB), 0,005% polychlorinated terphenyl (PCT) in preparations (see legal reference).			
P1.5*	Products do not contain more than 0,1% short chain chloroparaffins (SCCP) with 10-13 carbon atoms in th chain containing at least 48% per mass of chlorine in the SCCP (see legal reference).	e 🔀		
P1.6*	Parts with direct and prolonged skin contact do not release nickel in concentrations above 0,5 μg/cm²/weel (see legal reference). Comment: Max limit in legal reference when tested according to EN1811:2011-5.	;		
P1.7*	REACH Article 33 information about substances in articles is available at (add URL or mail contact):			
P2	Batteries			
P2.1*	If the product contains a battery or an accumulator, the battery/accumulator is labeled with the disposal symbol. Information on proper disposal is provided in user manual. (See legal reference)	\boxtimes		
P2.2*	Batteries or accumulators do not contain more than 0,0005% of mercury or 0,002% of cadmium. (See lega reference)	I 🔀		
P2.3*	Batteries and accumulators are readily removable. (See legal reference)	\square		
P3	Conformity verification & Eco design (ErP)			
P3.1*	The product is CE-marked to show conformance with applicable legal requirements (see legal reference). The Declaration of Conformity can be requested at (add link or e-mail address): http://www.canon-europe.com/ce-documentation/			
P3.2*	The product complies with the Eco design requirements for energy-related products, (see legal reference).			
	Required information is; given in item P15 or added to this document, available at (add URL): http://canon-europe.com/printers/			
P4	Consumable materials			
P4.1*	If a photo conductor (drum, belt etc.) is used in the product, it does not contain cadmium max 0,01% (see legal reference and NOTE B1).			
P4.2*	If ink/toner is used in the product, it does not contain cadmium max 0,1% by weight (see legal reference).	\square		
P4.3*	If the ink/toner formulation/preparation is classified as hazardous or contains a substance for which there are Community workplace exposure limits, the product/packaging is adequately labeled according to applicable regulations and a Safety Data Sheet (SDS) in accordance with these requirements is available (see legal reference).			
P5	Product packaging	, i		
P5.1*	Packaging and packaging components do not contain more than 0,01% lead, mercury, cadmium an hexavalent chromium by weight of these together.	d 🔀		
P5.2*	The packaging materials are marked with abbreviations and numbers indicating the nature of the material(sused (see legal reference).	,		
P5.3*	The product packaging material is free from ozone depleting substances as specified in the Montre- Protocol (see legal reference). Comment: Legal reference has no maximum concentration values.	al 🔀		
P6	Treatment information			
P6.1*	Information for recyclers/treatment facilities is available (see legal reference).	\boxtimes		

NOTE B1 Restriction applies to the homogeneous material, unless other specified and expressed in weight %. Stating "Yes" means that the product is compliant with the mandatory requirements.

Model number *	imageRUNNER ADVANCE DX 6765i	Logo	0
Issue date *	2019/12/20		Canon

	environmental attributes - Market requirements (See General NOTE GN below) Environmental conscious design	Require	ement	met
Item	*=mandatory to fill in. Additional information regarding each item may be found under P14.			า.a.
P7	Design			
	Disassembly, recycling			
P7.1*	Parts that have to be treated separately are easily separable	\boxtimes		
P7.2*	Plastic materials in covers/housing have no surface coating.	\boxtimes		
P7.3*	Plastic parts > 100 g consist of one material or of easily separable materials.	\boxtimes		
P7.4*	Plastic parts > 25 g have material codes according to ISO 11469 referring ISO 1043-4.	\boxtimes		
P7.5	Plastic parts are free from metal inlays or have inlays that can be removed with commonly available tools.			
P7.6*	Labels are easily separable. (This requirement does not apply to safety/regulatory labels).	\boxtimes		
	Product lifetime			
P7.7*	Upgrading can be done e.g. with processor, memory, cards or drives	\boxtimes		
P7.8*	Upgrading can be done using commonly available tools	\boxtimes		
P7.9.	Spare parts are available after end of production for: years			
P7.10	Service is available after end of production for: years			
	Material and substance requirements		•	
P7.11*	Product cover/housing material type (e.g. plastics, metal, aluminum):			
D7.40	Material type: PC+AS Material type: PC+AS			
P7.12	Insulation materials of external electrical cables are PVC free.			-
P7.13	Insulation materials of internal electrical cables are PVC free.	<u> </u> _		Щ.
P7.14	External plastic casing/cover parts > 25 g contain no more than 0,1% weight (1000 ppm) bromine and 0,1% weight (1000 ppm) chlorine attributable to brominated flame retardants, chlorinated flame retardants, and polyvinyl chloride or 0,3% weight (3000 ppm) bromine and 0,3% weight (3000 ppm) chlorine in parts containing more than 25% post-consumer recycled content.	ı —		
P7.15	Printed circuit boards, PCBs (without components) are low halogen: all PCBs > 25 g are low halogen as defined in IEC 61249-2-21. (See NOTE B2)	<i>I</i>		
P7.16	Flame retarded plastic parts > 25 g in covers / housings are marked according ISO 1043-4: Marking:			
P7.17	Alt. 1: Chemical specifications of flame retardants in printed circuit boards > 25 g (without components): TBBPA (additive), TBBPA (reactive) (See NOTE B3), Other; chemical name: , CAS #: Alt. 2: Chemical specifications of flame retardants in printed circuit boards (without components) > 25 g			
	according ISO 1043-4:			
P7.18	Alt. 1: Flame retarded plastic parts > 25 g contain the following flame retardant substances/preparations in concentrations above 0,1%: 1. Chemical name: , CAS #: (See NOTE B4) 2. Chemical name: , CAS #: " 3. Chemical name: , CAS #: "			
	Alt. 2: Chemical specifications of flame retardants in plastic parts > 25 g according ISO 1043-4:			
P7.19	In plastic parts > 25 g, flame retardant substances/preparations above 0,1% are used which have been assigned the following Risk phrases; and Hazard statements:			
	The source(s) for these classifications is/are found at (add URL(s)): , (See NOTE B5)			
P7.20*	Postconsumer recycled plastic material content is used in the product (See NOTE B6):	\boxtimes		
	If YES; at least one of the two alternatives below shall be answered; a) Of total plastic parts' weight > 25 g, the postconsumer recycled plastic material content (calculated as a percentage of total plastic by weight) is %. or b) The weight of recycled material is 52.3 g.	ı		

GENERAL NOTE Standard references should direct to the latest version of a standard. If an older version of a standard is used, section P15 shall be used for explanation.

NOTE B2 IEC 61249-2-21 defines maximum limits of 900 ppm for each of the substances chlorine and bromine and a maximum limit of 1500ppm of these substances combined. The standard does not address fluorine, iodine and astatine which are included in the group of halogens.

NOTE B3 and B4 A Guidance document on Chemical substances is available; see http://www.ecma-international.org/publications/standards/Ecma-370.htm

NOTE B5 If a certain substance has been assigned a certain risk phrases / hazard statement in the referenced source, this does not necessarily mean the substance has been tested for all of the hazards referred to by a certain customer.

NOTE B6 Applies to a product containing plastic parts whose combined weight exceeds 100 g with the exception of printed circuit boards, cables, connectors and electronic components and bio-based plastic material.

If YES; at least one of the two alternatives below shall be answered; a) Of total plastic parts' weight > 25 g, the biobased plastic material content (calculated as a percentage of total plastic by weight) is %. or b) The weight of the biobased plastic material is g. P7.22* Light sources are free from mercury, i.e. less than 0,1 mg/lamp. If mercury is used specify. Number of lamps: and maximum mercury content per lamp: mg P8 Batteries P8.1* Battery chemical composition: Liftum P9 Energy consumption (See NOTE B8) P9.1 For the product the following power levels or energy consumptions are reported: Energy mode * Power level at 115 V AC 230 V AC modes and test method * Sleep mode for ENERGY W W W W W W STAR® Operational Mode (OM) products Sleep mode for ENERGY STAR (Derational Mode (OM) products Standby/off mode for ENERGY STAR (Wh/week kWh/week 5.7 kWh/week ENERGY STAR (US scheme), Eligibility Criteria Version 3.0 for Imaging Equipment MAX W W W 2400 W Canon's Own Standard Printing(Average) W W W 1290 W Canon's Own Standard Standby W W 256 W Canon's Own Standard Standby W W W 256 W Canon's Own Standard Standby W W W O.9 W Canon's Own Standard Standby W W W O.9 W Canon's Own Standard Steep W W W W O.9 W Canon's Own Standard Steep W W W W W W Canon's Own Standard Steep W W W W W W W	Model number *	imageRU	NNER ADVANCE DX	6765i		Logo	0	
Material and substance requirements (continued) P7.21* Biobased plastic material content is used in the product (See NOTE B7):	Issue date *	date * 2019/12/20			Canon	1		
Material and substance requirements (continued) P7.211 Biobased plastic material content is used in the product (See NOTE B7):	Product environmental attributes - Market requirements (continued)				Requirement	met		
P7.211 Biobased plastic material content is used in the product (See NOTE B7):								
P7.211 Biobased plastic material content is used in the product (See NOTE B7):		and subst	ance requirements (c	continued)				
a) Of total plastic parts' weight > 25 g, the biobased plastic material content (calculated as a percentage of total plastic by weight) is "%. or b) The weight of the biobased plastic material is g. P7.22* Light sources are free from mercury, i.e. less than 0.1 mg/lamp. If mercury is used specify. Number of lamps: and maximum mercury content per lamp: mg P8 Batteries P8.1* Battery chemical composition: Litium					NOTE B7):			
total plastic by weight) is %. or of b) The weight of the biobased plastic material is g. P7.22* Light sources are free from mercury, i.e. less than 0,1 mg/lamp. mercury is used specify. Number of lamps: and maximum mercury content per lamp: mg P8 Batteries P9.1* Battery chemical composition: Litium p9 Energy consumption (See NOTE B8) P9.1 For the product the following power levels or energy consumptions are reported: Energy mode * Power level at 100 V AC 115 V AC 230 V AC modes and test method * Sleep mode for ENERGY W W W W Granding for energy consumptions are reported: Energy mode for ENERGY W W W W W Granding for energy modes and test method * Sleep mode for ENERGY W W W W Granding for energy modes and test method * Sleep mode for ENERGY W W W W Granding for energy modes and test method * Sleep mode for ENERGY W W W W Granding for energy Max Granding for energy Granding for energy Max Granding for energy Grand	If YES;	at least one	of the two alternatives	below shall be ans	swered;			
P7.22* Light sources are free from mercury, i.e. less than 0.1 mg/tamp. If mercury is used specify: Number of lamps: and maximum mercury content per lamp: mg P8	total plastic by weight) is %.							
If mercury is used specify: Number of lamps: and maximum mercury content per lamp: mg P8 Batteries	<u> </u>		<u> </u>					
P9 Energy consumption (See NOTE B8) P9.	If mercu				•	er lamp: r		
P9								
P9.1 For the product the following power levels or energy consumptions are reported: Energy mode * Power level at 100 V AC 115 V AC 230 V AC modes and test method * Power level at 230 V AC modes and test method * Power le			<u> </u>					
Energy mode * Power level at 100 V AC 115 V AC 230 V AC modes and test method * 100 V AC 115 V AC 230 V AC modes and test method * 115 V AC 230 V AC modes and test method * 115 V AC 230 V AC modes and test method * 115 V AC 230 V AC modes and test method * 115 V AC 230 V AC modes and test method * 115 V AC 230 V AC 230 V AC modes and test method * 115 V AC 230 V AC 230 V AC modes and test method * 115 V AC 230 V A		•						
Steep mode for ENERGY W W W W W W Standby W W W W Standby W W W W W W W W W	P9.1 For the	product the	following power levels	or energy consum	ptions are reported:			
STAR® Operational Mode (CMO) products Standby/off mode for ENERGY STAR Operational Mode (OM) products TEC value for ENERGY STAR kWh/week kWh/weak kWh/week kWh/week kWh/week kWh/weah kWh/weah led	Energy mode *						0,	
COM) products			W	W	W			
Standby/off mode for ENERGY STAR Operational Mode (OM) products W W W W W W W W W		Mode						
ENERGY STAR Operational Mode (OM) products TEC value for ENERGY STAR kWh/week kWh/week 5.7 kWh/week ENERGY STAR (US scheme), Eligibility Criteria Version 2.0 for Imaging Equipment N/A ENERGY STAR (US scheme), Eligibility Criteria Version 2.0 for Imaging Equipment N/A ENERGY STAR (US scheme), Eligibility Criteria Version 3.0 for Imaging Equipment N/A ENERGY STAR (US scheme), Eligibility Criteria Version 3.0 for Imaging Equipment N/A ENERGY STAR (US scheme), Eligibility Criteria Version 3.0 for Imaging Equipment N/A ENERGY STAR (US scheme), Eligibility Criteria Version 3.0 for Imaging Equipment N/A ENERGY STAR (US scheme), Eligibility Criteria Version 3.0 for Imaging Equipment N/A ENERGY STAR (US scheme), Eligibility Criteria Version 2.0 for Imaging Equipment N/A ENERGY STAR (US scheme), Eligibility Criteria Version 2.0 for Imaging Equipment N/A ENERGY STAR (US scheme), Eligibility Criteria Version 2.0 for Imaging Equipment N/A ENERGY STAR (US scheme), Eligibility Criteria Version 2.0 for Imaging Equipment N/A ENERGY STAR (US scheme), Eligibility Criteria Version 2.0 for Imaging Equipment N/A ENERGY STAR (US scheme), Eligibility Criteria Version 2.0 for Imaging Equipment N/A ENERGY STAR (US scheme), Eligibility Criteria Version 2.0 for Imaging Equipment N/A ENERGY STAR (US scheme), Eligibility Criteria Version 2.0 for Imaging Equipment N/A ENERGY STAR (US scheme), Eligibility Criteria Version 2.0 for Imaging Equipment N/A ENERGY STAR (US scheme), Eligibility Criteria Version 2.0 for Imaging Equipment N/A ENERGY STAR (US scheme), Eligibility Criteria Version 2.0 for Imaging Equipment N/A ENERGY STAR (US cheme), Eligibility Criteria Version 3.0 for Imaging Equipment N/A ENERGY STAR (US cheme), Eligibility Criteria Version 3.0 for Imaging Equipment N/A ENERGY STAR (US cheme), Eligibility Criteria Version 3.0 for Imaging Equipment N/A ENERGY STAR (US ches) Eligibility Criteria Version 3.0 for Imaging Equipment N/A ENERGY STAR (US ches) Eligibil		r	W	W	W			\neg
TEC value for ENERGY STAR KWh/week KWh/week S.7 kWh/week ENERGY STAR (US scheme), Eligibility Criteria Version 2.0 for Imaging Equipment ENERGY STAR (US scheme), Eligibility Criteria Version 3.0 for Imaging Equipment ENERGY STAR (US scheme), Eligibility Criteria Version 3.0 for Imaging Equipment ENERGY STAR (US scheme), Eligibility Criteria Version 3.0 for Imaging Equipment ENERGY STAR (US scheme), Eligibility Criteria Version 3.0 for Imaging Equipment ENERGY STAR (US scheme), Eligibility Criteria Version 3.0 for Imaging Equipment ENERGY STAR (US scheme), Eligibility Criteria Version 3.0 for Imaging Equipment ENERGY STAR (US scheme), Eligibility Criteria Version 3.0 for Imaging Equipment ENERGY STAR (US scheme), Eligibility Criteria Version 3.0 for Imaging Equipment ENERGY STAR (US scheme), Eligibility Criteria Version 3.0 for Imaging Equipment ENERGY STAR (US scheme), Eligibility Criteria Version 3.0 for Imaging Equipment ENERGY STAR (US scheme), Eligibility Criteria Version 3.0 for Imaging Equipment ENERGY STAR (US scheme), Eligibility Criteria Version 3.0 for Imaging Equipment ENERGY STAR (US scheme), Eligibility Criteria Version 3.0 for Imaging Equipment ENERGY STAR (US scheme), Eligibility Criteria Version 3.0 for Imaging Equipment ENERGY STAR (US scheme), Eligibility Criteria Version 3.0 for Imaging Equipment ENERGY STAR (US scheme), Eligibility Criteria Version 3.0 for Imaging Equipment ENERGY STAR (US scheme), Eligibility Criteria Version 3.0 for Imaging Equipment ENERGY STAR (US scheme), Eligibility Criteria Version 3.0 for Imaging Equipment ENERGY STAR (US scheme), Eligibility Criteria Version 3.0 for Imaging Equipment ENERGY STAR (US scheme), Eligibility Criteria Version 3.0 for Imaging Equipment ENERGY STAR (US scheme), Eligibility Criteria Version 3.0 for Imaging Equipment ENERGY STAR (US scheme), Eligibility Criteria Version 3.0 for Imaging Equipment ENERGY STAR (US scheme), Eligibility Criteria Version 3.0 for Imaging Equipment Energy Star (ш
TEC products (TEC= Typical Energy Consumption) N/A Eligibility Criteria Version 2.0 for Imaging Equipment ENERGY STAR (US scheme), Eligibility Criteria Version 3.0 for Imaging Equipment MAX W W 4400 W Canon's Own Standard Printing(Average) W W 1290 W Canon's Own Standard Standby W W 256 W Canon's Own Standard Low Power W W W Canon's Own Standard Sleep W W W Canon's Own Standard External Power Supply Efficiency Level (International Efficiency Marking Protocol)*: Print/Scan Speed 1 images per minute Default time to enter energy save mode: 65 minutes P9.2* Information about the energy save function is provided with the product. P10 Emissions Noise emission – Declared according to ISO 9296 (See NOTE B9) P10.1 Mode Mode description Statistical upper limit A-weighted sound power level, LWALC (B) Idle Standby Not Detect Operation Print * 7.50								
N/A ENERGY STAR (US scheme), Eligibility Criteria Version 3.0 for Imaging Equipment MAX W W 2400 W Canon's Own Standard Printing(Average) W W 1290 W Canon's Own Standard Standby W W W Canon's Own Standard Canon's Own		RGY STAR	kWh/week	kWh/week	Eligibility Criteria Version 2.0 fo		riteria Version 2.0 for	
MAX		gy			AI/A			
Printing(Average) W W 1290 W Canon's Own Standard Canon'	Consumption)				N/A	Eligibility Cr	riteria Version 3.0 for	
Standby W W W Canon's Own Standard Sleep W W W Canon's Own Standard Canon's Own Stand	MAX		W	W	2400 W	Canon's Ow	n Standard	
Low Power W W W Canon's Own Standard Sleep W W W W Canon's Own Standard	Printing(Average)		W	W	1290 W	Canon's Ow	n Standard	
W W W W W W W W W W	Standby		W	W	256 W	Canon's Ow	n Standard	
W W W W W W W W W W	Low Power		W	W	W	Canon's Ow	n Standard	$\overline{\boxtimes}$
External Power Supply Efficiency Level (International Efficiency Marking Protocol) * : Print/Scan Speed * : 1 images per minute Default time to enter energy save mode: 65 minutes P9.2* Information about the energy save function is provided with the product. P10 Emissions Noise emission – Declared according to ISO 9296 (See NOTE B9) P10.1 Mode Mode description Statistical upper limit A-weighted sound power level, LWA,C (B) Idle * Standby * Not Detect Operation * Print * 7.50	Sleep		W	W	0.9 W	Canon's Ow	n Standard	
Print/Scan Speed * : 1 images per minute Default time to enter energy save mode: 65 minutes P9.2* Information about the energy save function is provided with the product. P10 Emissions Noise emission – Declared according to ISO 9296 (See NOTE B9) P10.1 Mode Mode description Statistical upper limit A-weighted sound power level, \$L_{WA,c}\$ (B) Idle * Standby * Not Detect Operation * Print * 7.50			W	W	W			
Default time to enter energy save mode: 65 minutes P9.2* Information about the energy save function is provided with the product. P10 Emissions Noise emission – Declared according to ISO 9296 (See NOTE B9) P10.1 Mode Mode description Statistical upper limit A-weighted sound power level, \[\begin{align*}	External Power Sup	ply Efficiend	cy Level (International	Efficiency Marking	Protocol) *:			
P9.2* Information about the energy save function is provided with the product. P10 Emissions Noise emission – Declared according to ISO 9296 (See NOTE B9) P10.1 Mode Mode description Statistical upper limit A-weighted sound power level, \[L_{WA,c} \text{ (B)} \] Idle * Standby * Not Detect Operation * Print * 7.50	Print/Scan Speed *	:	1 images per minute					
P10 Emissions Noise emission – Declared according to ISO 9296 (See NOTE B9) P10.1 Mode Mode description Statistical upper limit A-weighted sound power level, LwA,c (B) Idle * Standby * Not Detect Operation * Print * 7.50	Default time to enter	Default time to enter energy save mode: 65 minutes						
Noise emission - Declared according to ISO 9296 (See NOTE B9) P10.1 Mode Mode description Statistical upper limit A-weighted sound power level, \(\L_{WA,c} \) (B) Idle	P9.2* Informat	tion about th	ne energy save function	n is provided with t	he product.			
P10.1 Mode Mode description Statistical upper limit A-weighted sound power level, $L_{WA,c}$ (B) Idle * Standby * Not Detect Operation * Print * 7.50	P10 Emission	ons					•	
Idle * Standby * Not Detect Operation * Print * 7.50		mission -	Declared according to	ISO 9296 (See NO	TE B9)			
Operation * Print * 7.50	P10.1 Mode	N	, , , , , , , , , , , , , , , , , , ,					
Operation * Print * 7.50	Idle	*	Standby		* Not Detect			
		·			\dashv			
1								
Measured according to: X ISO 7779 ECMA-74			a to: X ISO 7779	ECMA-74				

NOTE B7 The following is to be excluded from the calculation of percentage: printed circuit boards, labels, cables, connectors and electronic components and postconsumer recycled plastic.

(only if not covered by ECMA-74)

NOTE B8 A Guidance document on Energy Efficiency is available; see http://www.ecma-international.org/publications/standards/Ecma-370.htm

Other

NOTE B9 A Guidance document on Acoustic Noise is available; see http://www.ecma-international.org/publications/standards/Ecma-370.htm

Model number *	imageRUNNER ADVANCE DX 6765i	Logo	0
Issue date *	2019/12/20		Canon

Product	environmental attributes - Market requirements (continued)	Require	ment	met
Item		Yes	No	n.a.
	Chemical emissions from printing products (See NOTE B10)			
P10.2*	Test performed according to ECMA-328 Determination of Chemical Emission Rates from Electronic	\boxtimes	\Box	\Box
	Equipment (ISO/IEC 28360), other specify:			
P10.3	Typical emission rate (operation phase) is (mg/h):			\Box
	Electrophotographic devices: Ozone 0.79 Dust 3.22 Styrene 0.02 Benzene 0.01 TVOC 1.25			
	Ink devices: Dust Styrene Benzene TVOC			
	Note: compliance with maximum emission rates in eco labels to be declared in P14.			
P11	Consumable materials for printing products			
P11.1*	A Safety Data Sheet (SDS) is available for the ink/toner preparation, even if not legally required (see P4.3).	\boxtimes		
P11.2*	Paper containing post-consumer recycled fibers can be used, provided that it meets the requirements of EN 12281.			
P11.3*	2-sided (duplex) printing/copying is an integrated product function.	\square		
P11.4*	The product is delivered to end-user with default auto-duplex enabled.		一百	一
P13	Packaging and documentation			
P13.1*	Product packaging material type(s): <i>Plywood</i> weight (kg): 19.5			
	Product packaging material type(s): Corrugated Paper weight (kg): 13.6			
	Product packaging material type(s): EPS weight (kg): 1.88			
P13.2*	Product plastic primary packaging is free from PVC.	\boxtimes		
P13.3*	For product primary corrugated fiberboard packaging, specify the contained percentage of minimum post-consumer recovered fiber content: 25 %			
P13.4*	Specify media for user and product documentation (tick box):			
D40.5	Electronic , Paper , Other			
P13.5	(Please only complete this item if paper documentation used)			
	User and product documentation on paper media is chlorine-free: If Yes, please specify:		Ш	
	Totally chlorine-free			
	Elemental chlorine-free			
	Processed chlorine-free	\Box		
P14	Voluntary programs:			
P14.1	The product meets the requirements of the following voluntary program(s):			
	ENERGY STAR® Criteria version: Date: Product category:			
	Eco-label: Criteria version: Date: Product category:			
	Eco-label: Criteria version: Date: Product category:			
P15	Additional information (See NOTE B11)			
P1.1	Product on this declaration comply with EU RoHS Directive(2001/65/EU).			
	The current EU RoHS Directive restricts the use of following substances.			
	Lead			
	Mercury			
	Cadmium			
	Hexavalent chromium			
	Polybrominated biphenyls(PBB) Polybrominated diphenyl ethers(PBDE)			
	Note; This is based on knowledge as of the date of this document.			
P1.7	http://canon-europe.com/about_us/sustainebility/business/reach_customer_statement/			
P10.1	Sound Pressure (LpAm)			
7 70.7	Bystander's position			
	Active(BW) (1-sided/2-sided) : 57 / 58 dB			
	Standby : 37 dB			
	Operator position			
	Active(BW) (1-sided/2-sided) : 59 / 59 dB Standby : 41 dB			

NOTE B10 A Guidance document on Chemical Emissions is available; see http://www.ecma-international.org/publications/standards/Ecma-370.htm

NOTE B11 Additional lines may be inserted to declare further items, by positioning the cursor at the far right of the row and hitting the <Enter> key.

Legal references Europe Annex B1

Reference	Declaration item
Directive 2011/65/EU (RoHS Directive) * * Specific exemptions apply for certain products and applications.	P1.1, P4.1
(EC) 1907/2006(REACH, Annex XVII	P1.2, P1.4, P1.6, P1.7, P4.2
Regulation (EC) No. 2037/2000, 2038/2000, 2039/2000, (Marketing and use of Ozone layer depleting substances)	P1.3, 5.3
Norwegian regulation relating to restrictions on the use of certain dangerous chemicals 20.12.2002	P1.5
"REACH" Regulation (1907/2006), annex VII	P1.10
Directive 2013/56/EC (Battery and accumulators Directive) * * These provisions shall not apply where, for safety, performance, medical or data integrity reasons, continuity of power supply is necessary and requires a permanent connection between the appliance and the battery or accumulator.	P2.1, P2.2, P2,3, P8.1
Directive 2006/95/EC (Low Voltage Directive)	P3.1
Directive 2004/108/EC (EMC Directive)	P3.1
Directive 1999/5/EC (R&TTE Directive)	P3.1
Regulation (EC) 801/2013 amending Regulation (EC) No 1275/2008 with regard to ecodesign requirements for standby, off mode electric power consumption of electrical and electronic household and office equipment, and amending Regulation (EC) No 642/2009 with regard to ecodesign requirements for televisions	P3.1, P3.2
Regulation (EC) 1907/2006 (REACH Regulation), Article 31, annex II)	P4.3
Regulation (EC) 1272/2008 (CLP Regulation)	P4.3, P7.19
Directive 2004/12/EC (Packaging Directive)	P5.1
Decision 97/129/EC (Secondary packaging legislation)	P5.2
Directive 2012/19/EU (WEEE directive)	P6.1