

Ecma/TC38-TG3/2015/025 (Rev. 1 – 15 April 2015)

Annex B1 - Product environmental attributes Imaging equipment

The declaration may be published only when all rows and/or fields marked with * are filled-in (n.a. for not applicable). Additional information regarding each item may be found under P15.

Brand *	Canon	Logo
Company name *	Canon Europe Limited	
Contact information *	environment@canon-europe.com	Canon
e-mail address		Conton
Internet site *	www.canon-europe.com	
Additional information		

The company declares (based on product specification or test results based obtained from sample testing), that the product conforms to the statements given in this declaration.					
Type of product *	MFD				
Commercial name *	i-SENSYS MF267dw				
Model number *	i-SENSYS MF267dw				
Issue date *	2019/10/12				
Intended market *	🔄 Global 🔀 Europe 📃 Asia, Pacific & Japan 📃 Americas 📃 Other				
Additional information					

This is an uncontrolled copy when in printed form. Please refer to the contact information for the latest version.

About Annex B1

Annex B1 reflects Product environmental attributes relevant for Imaging products. The following items from the ECMA-370 Main body are not shown in the template:

P9.1 PTEC, ETEC and display resolution P12.1-P12.2 Ergonomic requirements.

Model number *		i-SENSYS MF267dw	Logo			
Issue date *		2019/10/12		Ca	10	
Product	t environ	mental attributes - Legal requirements		Requir	ement	met
Item				Yes	No	n.a.
P1		bus substances and preparations				
P1.1*		do comply with the current European RoHS Directive. (See legal reference and N	IOTE B1)	\square		
P1.2*	Commer	o do not contain Asbestos (see legal reference). nt: Legal reference has no maximum concentration value.		\boxtimes		
P1.3*	hydrobro trichloroe	e do not contain Ozone Depleting Substances: Chlorofluorocarbons (CFC), mofluorocarbons (HBFC), hydrochlorofluorcarbons (HCFC), Halons, carbontetrach ethane, methyl bromide (see legal reference). Comment: Legal reference has no n ation values.		1-		
P1.4*		do not contain more than; 0,005% polychlorinated biphenyl (PCB), 0,005% polych I (PCT) in preparations (see legal reference).	nlorinated	\square		
P1.5*	Products chain co	o do not contain more than 0,1% short chain chloroparaffins (SCCP) with 10-13 car ntaining at least 48% per mass of chlorine in the SCCP (see legal reference).				
P1.6*	(see lega	h direct and prolonged skin contact do not release nickel in concentrations above (al reference). nt: Max limit in legal reference when tested according to EN1811:2011-5.	0,5 μg/cm²/	week		
P1.7*		Article 33 information about substances in articles is available at (add URL or mail	contact):			
P2	Batterie	S				
P2.1*		duct contains a battery or an accumulator, the battery/accumulator is labeled with Information on proper disposal is provided in user manual. (See legal reference)	the disposa	al 🔀		
P2.2*	Batteries	or accumulators do not contain more than 0,0005% of mercury or 0,002% of cadr	nium. (See	legal 🔀		
P2.3*	Batteries	and accumulators are readily removable. (See legal reference)		\boxtimes		
P3	Conform	nity verification & Eco design (ErP)				
P3.1*	The Dec	duct is CE-marked to show conformance with applicable legal requirements (see le laration of Conformity can be requested at (add link or e-mail address): http://www. com/ce-documentation/		ce). 🔀		
P3.2*		luct complies with the Eco design requirements for energy-related products, al reference).		\boxtimes		
		l information is; given in item P15 or added to this document,		\boxtimes		
	•	available at (add URL): http://canon-europe.com/prin	ters/		_	_
P4	Consum	hable materials				
P4.1*	legal refe	o conductor (drum, belt etc.) is used in the product, it does not contain cadmium me erence and NOTE B1).				
P4.2*	If ink/ton	er is used in the product, it does not contain cadmium max 0,1% by weight (see leg	gal referend	ce). 🛛 🔀		
P4.3*	are Com applicab	/toner formulation/preparation is classified as hazardous or contains a substance fr munity workplace exposure limits, the product/packaging is adequately labeled act le regulations and a Safety Data Sheet (SDS) in accordance with these requirement al reference).	cording to			
P5	Product	packaging				
P5.1*	hexavale	ng and packaging components do not contain more than 0,01% lead, mercur ant chromium by weight of these together.				
P5.2*		caging materials are marked with abbreviations and numbers indicating the nature e legal reference).	of the mate	erial(s) 🔀		
P5.3*	The pro Protocol	duct packaging material is free from ozone depleting substances as specified (see legal reference). nt: Legal reference has no maximum concentration values.	in the Mo	ontreal 🔀		
P6		nt information				
P6.1*	Informati	on for recyclers/treatment facilities is available (see legal reference).				

NOTE B1 Restriction applies to the homogeneous material, unless other specified and expressed in weight %. Stating "Yes" means that the product is compliant with the mandatory requirements.

Model n	umber *	i-SENSYS MF267dw	Logo			
Issue date *		2019/10/12		Ca	10	n
	Environn	mental attributes - Market requirements (See General NOTE GN below) mental conscious design		Require		
Item		tory to fill in. Additional information regarding each item may be found under P14.		Yes	No r	i.a.
P7	Design	nbly, recycling				
P7.1*		t have to be treated separately are easily separable				
P7.2*		aterials in covers/housing have no surface coating.			<u>+</u>	+
P7.3*		arts > 100 g consist of one material or of easily separable materials.			<u> </u>	-
P7.4*		arts > 25 g have material codes according to ISO 11469 referring ISO 1043-4.			<u> </u>	+
P7.5		arts are free from metal inlays or have inlays that can be removed with commonly available from metal inlays or have inlays that can be removed with commonly available from the second	ailable too		<u> </u>	<u> </u>
P7.6*	-	e easily separable. (This requirement does not apply to safety/regulatory labels).			<u> </u>	<u> </u>
F7.0	Product					
P7.7*		g can be done e.g. with processor, memory, cards or drives				
P7.8*		g can be done using commonly available tools			+	⊢⊢
P7.9.		rts are available after end of production for: years				-
P7.10		s available after end of production for: years				╞
17.10		and substance requirements				
P7.11*		cover/housing material type (e.g. plastics, metal, aluminum):				
		ype: PC+ABS Material type: ABS Material	type:			
P7.12		materials of external electrical cables are PVC free.			\boxtimes	
P7.13	Insulatior	n materials of internal electrical cables are PVC free.			•	
P7.14	weight (1 polyvinyl	plastic casing/cover parts > 25 g contain no more than 0,1% weight (1000 ppm) bro 000 ppm) chlorine attributable to brominated flame retardants, chlorinated flame chloride or 0,3% weight (3000 ppm) bromine and 0,3% weight (3000 ppm) ch g more than 25% post-consumer recycled content.	retardants	, and 📃		
P7.15	Printed of	sircuit boards, PCBs (without components) are low halogen: all 🗌 PCBs > 25	g 🗌 are	e low		
P7.16	halogen as defined in IEC 61249-2-21. (See NOTE B2) Flame retarded plastic parts > 25 g in covers / housings are marked according ISO 1043-4: Marking:					
P7.17	<u>Alt. 1: Ch</u>	emical specifications of flame retardants in printed circuit boards > 25 g (without con additive) , TBBPA (reactive) (See NOTE B3), Other; chemical name:	nponents): CAS #:			
		emical specifications of flame retardants in printed circuit boards (without componen g ISO 1043-4:	ts) > 25 g			
P7.18	concentra 1. Chemi 2. Chemi	ame retarded plastic parts > 25 g contain the following flame retardant substances/ ations above 0,1%: cal name: , CAS #: (See NOTE B4) cal name: , CAS #: " cal name: , CAS #: "	preparatio	ns in		
	Alt. 2: Cł	nemical specifications of flame retardants in plastic parts > 25 g according ISO 1043-	4:			
P7.19	In plastic assigned	parts > 25 g, flame retardant substances/preparations above 0,1% are used which h the following Risk phrases; and Hazard statements:	ave been			
			OTE B5)			
P7.20*	Postcons	umer recycled plastic material content is used in the product (See NOTE B6):		\boxtimes		
	a) Of to perc	t least one of the two alternatives below shall be answered; otal plastic parts' weight > 25 g, the postconsumer recycled plastic material content (entage of total plastic by weight) is %.	calculated	as a		
	or b) The	weight of recycled material is 19.0 g.				

GENERAL NOTE Standard references should direct to the latest version of a standard. If an older version of a standard is used, section P15 shall be used for explanation.

NOTE B2 IEC 61249-2-21 defines maximum limits of 900 ppm for each of the substances chlorine and bromine and a maximum limit of 1500ppm of these substances combined. The standard does not address fluorine, iodine and astatine which are included in the group of halogens.

NOTE B3 and B4 A Guidance document on Chemical substances is available; see http://www.ecma-international.org/publications/standards/Ecma-370.htm

NOTE B5 If a certain substance has been assigned a certain risk phrases / hazard statement in the referenced source, this does not necessarily mean the substance has been tested for all of the hazards referred to by a certain customer.

NOTE B6 Applies to a product containing plastic parts whose combined weight exceeds 100 g with the exception of printed circuit boards, cables, connectors and electronic components and bio-based plastic material.

Model nu	mber *	i-SENSYS	MF267dw			Logo		
Issue date * 2019/10/1		2				Cano	n	
Product	environr	nental att	ributes - Market red	quirements (con	tinued)		Requiremer	nt met
ltem							Yes No	o n.a.
D7.04*			ance requirements (c					
P7.21* Biobased plastic material content is used in the product (See NOTE B7):								
	a) Of tota or	total plastic al plastic by	weight) is %.	the biobased plastic	wered; c material content (calcu	lated as a perce	entage of	
P7.22*	Light sou	urces are fre	he biobased plastic ma ee from mercury, i.e. le	ess than 0,1 mg/lam				
Do			pecify: Number of lamp	os. and maxi	mum mercury content pe	enamp. r	ng	
P8.1*	Batterie Battery o		mposition: <i>Lithium</i>					
P9	-		on (See NOTE B8)					
P9.1		-	following power levels	or energy consump	tions are reported:			
Energy m			Power level at 100 V AC	Power level at 115 V AC	Power level at 230 V AC	Reference/St modes and te		у 🗌
	de for ENE perational		W	W	W			
Standby/c ENERGY	off mode fo STAR Ope I) products	erational	W	W	W			
TEC value for ENERGY STAR TEC products		kWh/week	kWh/week	0.8 kWh/week		AR (US scheme), iteria Version 2.0 for ipment		
(TEC= Typical Energy Consumption)		ЭУ			0.31 kWh/week	ENERGY ST	AR (US scheme), iteria Version 3.0 for	
MAX			W	W	1180 W	Canon's Ow	n Standard	
Printing()	Average)		W	W	340 W	Canon's Ow	n Standard	<u> </u>
Standby			W	W	5.7 W	Canon's Ow	n Standard	<u> </u>
Low Pow	er		W	W	W			$\overline{\boxtimes}$
Sleep			W	W	0.8 W	Canon's Ow	n Standard	
•			W	W	W			
External P	ower Sup	olv Efficienc	y Level (International E					
Print/Scar			28 images per minute					<u> </u>
			e mode: 1 minutes				<u> </u>	<u> </u>
P9.2*			e energy save functior	n is provided with th	e product.			JЦ
P10	Emissio		Deployed assessible to the	50 0000 (Dec NOT				
P10.1	Mode		Declared according to ISO 9296 (See NOTE B9) ode description Statistical $L_{WA,c}$ (B) Statistical		Statistical upper limit A-v	veighted sound	oower level,	
	Idle	* Standby * Not Detect						
	Operatio						\dashv	
	Other m							
	Measure	ed according		ECMA-74 (only if not covered	by ECMA-74)			

NOTE B7 The following is to be excluded from the calculation of percentage: printed circuit boards, labels, cables, connectors and electronic components and postconsumer recycled plastic.

NOTE B8 A Guidance document on Energy Efficiency is available; see http://www.ecma-international.org/publications/standards/Ecma-370.htm

NOTE B9 A Guidance document on Acoustic Noise is available; see http://www.ecma-international.org/publications/standards/Ecma-370.htm

Model number *		i-SENSYS MF20	67dw			Logo			
Issue dat	9 *	2019/10/12					Cat	101	
Product	environ	mental attribut	es - Market requiremen	ts (continued)			Require	ement	met
Item							Yes	No	n.a.
			om printing products (See						
P10.2*			g to ECMA-328 Determinatic 60) 🔀, other specify:	n of Chemical Emiss	ion Rates from E	lectronic			
P10.3	Typical	emission rate (op	eration phase) is (mg/h):						
	Electro Ink dev		ces: Ozone <loq(=0.13)< b=""> [Dust</loq(=0.13)<>	Dust 0.66 Styrene Styrene	0.19 Benzene Benzene	0.00 TVOC TVOC	2.33		
	Note: c	ompliance with ma	aximum emission rates in ec	o labels to be declar	ed in P14				
P11			for printing products		50 111 14.				
P11.1*			S) is available for the ink/ton	er preparation, even	if not legally req	uired (see F	24.3).		
P11.2*			onsumer recycled fibers ca			-		H	⊢
	EN 122								
P11.3*	2-sided	(duplex) printing/	copying is an integrated proc	duct function.			\square		
P11.4*	The pro	duct is delivered t	to end-user with default auto	-duplex enabled.					
P13	Packag	ing and docume	entation						
P13.1*	Produc Produc Produc	t packaging mater t packaging mater t packaging mater	ial type(s): <i>Corrugated Pap</i> ial type(s): <i>EPS</i> we ial type(s): <i>PE</i> weight (kg):	eight (kg): 0.419	3.653				
P13.2*			ackaging is free from PVC.				\square		
P13.3*	For product primary corrugated fiberboard packaging, specify the contained percentage of minimum post- consumer recovered fiber content: 80 %								
P13.4*		media for user ar nic 🔀, Paper 🔀	nd product documentation (ti , Other	ck box):					
P13.5	Úser ar		is item if paper documentation entation on paper media is c						
		chlorine-free							
		Elemental chlorine-free							
		sed chlorine-free					님		
D1/									
P14 P14.1		ary programs:	equirements of the following	voluntary program(s)	•				
	ENERG Eco-lab	SY STAR®	Criteria version: Criteria version:	Date: Date:		category: category:			
	Eco-lab		Criteria version:	Date:		category:			
P15		nal information		Buto.	Tioddot	catogory.			
P1.1			n comply with EU RoHS Direc	tive(2001/65/EU).					
	The cur L		ective restricts the use of follo						
		admium							
		exavalent chromiu							
		olybrominated biph							
			enyl ethers(PBDE)						
	Note:Tl	his is based on know	wledge as of the date of this d	ocument.					
P1.7			m/about_us/sustainebility/						

NOTE B10 A Guidance document on Chemical Emissions is available; see http://www.ecma-international.org/publications/standards/Ecma-370.htm

NOTE B11 Additional lines may be inserted to declare further items, by positioning the cursor at the far right of the row and hitting the <Enter> key.

Legal references Europe Annex B1

Reference	Declaration item
Directive 2011/65/EU (RoHS Directive) * * Specific exemptions apply for certain products and applications.	P1.1, P4.1
(EC) 1907/2006(REACH, Annex XVII	P1.2, P1.4, P1.6, P1.7, P4.2
Regulation (EC) No. 2037/2000, 2038/2000, 2039/2000, (Marketing and use of Ozone layer depleting substances)	P1.3, 5.3
Norwegian regulation relating to restrictions on the use of certain dangerous chemicals 20.12.2002	P1.5
"REACH" Regulation (1907/2006), annex VII	P1.10
Directive 2013/56/EC (Battery and accumulators Directive) * * These provisions shall not apply where, for safety, performance, medical or data integrity reasons, continuity of power supply is necessary and requires a permanent connection between the appliance and the battery or accumulator.	P2.1, P2.2, P2,3, P8.1
Directive 2006/95/EC (Low Voltage Directive)	P3.1
Directive 2004/108/EC (EMC Directive)	P3.1
Directive 1999/5/EC (R&TTE Directive)	P3.1
Regulation (EC) 801/2013 amending Regulation (EC) No 1275/2008 with regard to ecodesign requirements for standby, off mode electric power consumption of electrical and electronic household and office equipment, and amending Regulation (EC) No 642/2009 with regard to ecodesign requirements for televisions	P3.1, P3.2
Regulation (EC) 1907/2006 (REACH Regulation), Article 31, annex II)	P4.3
Regulation (EC) 1272/2008 (CLP Regulation)	P4.3, P7.19
Directive 2004/12/EC (Packaging Directive)	P5.1
Decision 97/129/EC (Secondary packaging legislation)	P5.2
Directive 2012/19/EU (WEEE directive)	P6.1