

Ecma/TC38-TG3/2015/025 (Rev. 1 – 15 April 2015)

## Annex B1 - Product environmental attributes Imaging equipment

The declaration may be published only when all rows and/or fields marked with \* are filled-in (n.a. for not applicable). Additional information regarding each item may be found under P15.

| Brand *                | Canon                        | Logo  |
|------------------------|------------------------------|-------|
| Company name *         | Canon Europa N.V.            |       |
| Contact information *  | environment@canon-europe.com | Canon |
| e-mail address         |                              | Canon |
| Internet site *        | www.canon-europe.com         |       |
| Additional information |                              |       |

| The company declares (based on product specification or test results based obtained from sample testing), that the product conforms to the statements given in this declaration. |  |  |  |  |
|--|--|--|--|--|
| Type of product *  | MFD  |  |  |  |
| Commercial name *  | i-SENSYS MF543x  |  |  |  |
| Model number *   | i-SENSYS MF543x  |  |  |  |
| Issue date *   | 2019/10/12   |  |  |  |
| Intended market *  | 🔄 Global 🔀 Europe 📃 Asia, Pacific & Japan 📃 Americas 📃 Other |  |  |  |
| Additional information   |  |  |  |  |

This is an uncontrolled copy when in printed form. Please refer to the contact information for the latest version.

## About Annex B1

Annex B1 reflects Product environmental attributes relevant for Imaging products. The following items from the ECMA-370 Main body are not shown in the template:

P9.1 PTEC, ETEC and display resolution P12.1-P12.2 Ergonomic requirements.

| Model n      | umber *                | i-SENSYS MF543x  | Logo         |             |        | _           |
|--------------|------------------------|--|--------------|-------------|--------|-------------|
| Issue date * |                        | 2019/10/12   |              | Ca          | 10     |             |
| Product      | t environ              | mental attributes - Legal requirements   |              | Requi       | rement | met         |
| Item         |                        |  |              | Yes         | No     | n.a.        |
| P1           |                        | us substances and preparations   |              |             |        |             |
| P1.1*        | Products               | do comply with the current European RoHS Directive. (See legal reference and N   | IOTE B1)     | $\square$   |        |             |
| P1.2*        | Commer                 | e do not contain Asbestos (see legal reference).<br>nt: Legal reference has no maximum concentration value.  |              | $\boxtimes$ |        |             |
| P1.3*        | hydrobro<br>trichloroe | e do not contain Ozone Depleting Substances: Chlorofluorocarbons (CFC),<br>mofluorocarbons (HBFC), hydrochlorofluorcarbons (HCFC), Halons, carbontetracl<br>ethane, methyl bromide (see legal reference). Comment: Legal reference has no r<br>ation values.                   |              | 1-          |        |             |
| P1.4*        |                        | do not contain more than; 0,005% polychlorinated biphenyl (PCB), 0,005% polych<br>I (PCT) in preparations (see legal reference).   | nlorinated   | $\boxtimes$ |        |             |
| P1.5*        | Products               | do not contain more than 0,1% short chain chloroparaffins (SCCP) with 10-13 can nataining at least 48% per mass of chlorine in the SCCP (see legal reference).   | bon atoms    | in the      |        |             |
| P1.6*        | (see lega              | h direct and prolonged skin contact do not release nickel in concentrations above<br>al reference).<br>ht: Max limit in legal reference when tested according to EN1811:2011-5.  | 0,5 μg/cm²/  | week        |        | $\boxtimes$ |
| P1.7*        |                        | Article 33 information about substances in articles is available at (add URL or mail   | contact):    | $\boxtimes$ |        |             |
| P2           | Batterie               | S  |              |             |        |             |
| P2.1*        |                        | duct contains a battery or an accumulator, the battery/accumulator is labeled with<br>Information on proper disposal is provided in user manual. (See legal reference)   | the dispose  | al 🖂        |        |             |
| P2.2*        | Batteries              | or accumulators do not contain more than 0,0005% of mercury or 0,002% of cadr  | nium. (See   | legal 🛛 🖂   |        |             |
| P2.3*        | Batteries              | and accumulators are readily removable. (See legal reference)  |              | $\boxtimes$ |        |             |
| P3           | Conform                | nity verification & Eco design (ErP)   |              |             |        |             |
| P3.1*        | The proc<br>The Dec    | duct is CE-marked to show conformance with applicable legal requirements (see le<br>laration of Conformity can be requested at (add link or e-mail address): http://www.<br>com/ce-documentation/  |              | ce). 🔀      |        |             |
| P3.2*        |                        | luct complies with the Eco design requirements for energy-related products,<br>al reference).  |              | $\boxtimes$ |        |             |
|              | Required               | l information is; given in item P15 or added to this document,   |              | $\square$   |        |             |
|              | -                      | available at (add URL): http://canon-europe.com/prin   | ters/        |             |        |             |
| P4           | Consum                 | able materials   |              |             |        |             |
| P4.1*        |                        | o conductor (drum, belt etc.) is used in the product, it does not contain cadmium m<br>erence and NOTE B1).  | ax 0,01% (s  | see 🔀       |        |             |
| P4.2*        | If ink/ton             | er is used in the product, it does not contain cadmium max 0,1% by weight (see le  | gal referenc | :e). 🛛 🔀    |        |             |
| P4.3*        | are Com<br>applicab    | /toner formulation/preparation is classified as hazardous or contains a substance f<br>munity workplace exposure limits, the product/packaging is adequately labeled ac<br>le regulations and a Safety Data Sheet (SDS) in accordance with these requirement<br>al reference). | cording to   |             |        |             |
| P5           |                        | packaging  |              |             |        |             |
| P5.1*        | Packagii               | ng and packaging components do not contain more than 0,01% lead, mercur<br>ant chromium by weight of these together.   | y, cadmiun   | n and 🛛     |        |             |
| P5.2*        | The pac                | caging materials are marked with abbreviations and numbers indicating the nature e legal reference).   | of the mate  | erial(s) 🔀  |        |             |
| P5.3*        | The pro<br>Protocol    | duct packaging material is free from ozone depleting substances as specified (see legal reference).<br>(see legal reference).<br>it: Legal reference has no maximum concentration values.  | in the Mo    | ontreal 🔀   |        |             |
| P6           |                        | nt information   |              |             |        |             |
| P6.1*        |                        | on for recyclers/treatment facilities is available (see legal reference).  |              |             |        |             |
| 0.1          | monnau                 | on to recyclostication iacinices is available (see legal lefelence).   |              | $\square$   |        |             |

NOTE B1 Restriction applies to the homogeneous material, unless other specified and expressed in weight %. Stating "Yes" means that the product is compliant with the mandatory requirements.

| Model n  | umber *  | i-SENSYS MF543x  | Logo        |             |           | _             |
|----------|--|--|-------------|-------------|-----------|---------------|
| Issue da |  | Ca   | <b>no</b>   | n           |           |               |
|          | Environn   | mental attributes - Market requirements (See General NOTE GN below)<br>mental conscious design   |             | Require     | ment r    | net           |
| Item     |  | tory to fill in. Additional information regarding each item may be found under P14.  |             | Yes         | No n      | .a.           |
| P7       | Design   | nbly, recycling  |             |             |           |               |
| P7.1*    |  | t have to be treated separately are easily separable   |             |             |           |               |
| P7.2*    |  | aterials in covers/housing have no surface coating.  |             |             | +         | ╞             |
| P7.3*    |  | arts > 100 g consist of one material or of easily separable materials.   |             |             | +         | <u> </u>      |
| P7.4*    |  | arts > 25 g have material codes according to ISO 11469 referring ISO 1043-4.   |             |             | ╞         | ╞             |
| P7.5     |  | arts are free from metal inlays or have inlays that can be removed with commonly ava   | ailable too |             | +         | <u>+</u>      |
| P7.6*    |  | e easily separable. (This requirement does not apply to safety/regulatory labels).   |             |             | <u> </u>  | <u> </u>      |
| F7.0     | Product  |  |             |             |           |               |
| P7.7*    |  | g can be done e.g. with processor, memory, cards or drives   |             |             |           |               |
| P7.8*    |  | g can be done using commonly available tools   |             |             | +         | +             |
| P7.9.    | 10   | rts are available after end of production for: years   |             |             |           | <del>  </del> |
| P7.10    |  | s available after end of production for: years   |             |             |           | ╞             |
| 17.10    |  | and substance requirements   |             |             |           |               |
| P7.11*   |  | over/housing material type (e.g. plastics, metal, aluminum):   |             |             |           |               |
|          | Material t   | ype: ABS Material type: PC+ABS Material  | type:       |             |           |               |
| P7.12    | Insulation   | materials of external electrical cables are PVC free.  |             |             | $\square$ |               |
| P7.13    | Insulatior   | materials of internal electrical cables are PVC free.  |             |             |           |               |
| P7.14    | weight (1<br>polyvinyl   | plastic casing/cover parts > 25 g contain no more than 0,1% weight (1000 ppm) bro<br>000 ppm) chlorine attributable to brominated flame retardants, chlorinated flame r<br>chloride or 0,3% weight (3000 ppm) bromine and 0,3% weight (3000 ppm) ch<br>g more than 25% post-consumer recycled content. | retardants  | , and 📃     |           |               |
| P7.15    | Printed of   | sircuit boards, PCBs (without components) are low halogen: all PCBs > 25 as defined in IEC 61249-2-21. (See NOTE B2)   | g 🗌 are     | e low       |           |               |
| P7.16    | Flame retarded plastic parts > 25 g in covers / housings are marked according ISO 1043-4:  |  |             |             |           |               |
| P7.17    | Alt. 1: Chemical specifications of flame retardants in printed circuit boards > 25 g (without components):   TBBPA (additive) , TBBPA (reactive)   (See NOTE B3), Other; chemical name: , CAS #: |  |             |             |           |               |
|          |  | emical specifications of flame retardants in printed circuit boards (without componen<br>g ISO 1043-4:   | ts) > 25 g  |             |           |               |
| P7.18    | concentra<br>1. Chemi<br>2. Chemi  | ame retarded plastic parts > 25 g contain the following flame retardant substances/<br>ations above 0,1%:<br>cal name: , CAS #: (See NOTE B4)<br>cal name: , CAS #: "<br>cal name: , CAS #: "  | preparatio  | ns in       |           |               |
|          | <u>Alt. 2: </u> Cł   | emical specifications of flame retardants in plastic parts > 25 g according ISO 1043-  | 4:          |             |           |               |
| P7.19    | In plastic   | parts > 25 g, flame retardant substances/preparations above 0,1% are used which h the following Risk phrases; and Hazard statements:   |             |             |           |               |
|          |  |  | OTE B5)     |             |           |               |
| P7.20*   | Postcons   | umer recycled plastic material content is used in the product (See NOTE B6):   |             | $\boxtimes$ |           |               |
|          | a) Of to<br>perc   | t least one of the two alternatives below shall be answered;<br>otal plastic parts' weight > 25 g, the postconsumer recycled plastic material content (<br>entage of total plastic by weight) is %.  | calculated  | as a        |           |               |
|          | or<br>b) The   | weight of recycled material is 26.9 g.   |             |             |           |               |

GENERAL NOTE Standard references should direct to the latest version of a standard. If an older version of a standard is used, section P15 shall be used for explanation.

NOTE B2 IEC 61249-2-21 defines maximum limits of 900 ppm for each of the substances chlorine and bromine and a maximum limit of 1500ppm of these substances combined. The standard does not address fluorine, iodine and astatine which are included in the group of halogens.

NOTE B3 and B4 A Guidance document on Chemical substances is available; see <a href="http://www.ecma-international.org/publications/standards/Ecma-370.htm">http://www.ecma-international.org/publications/standards/Ecma-370.htm</a>

NOTE B5 If a certain substance has been assigned a certain risk phrases / hazard statement in the referenced source, this does not necessarily mean the substance has been tested for all of the hazards referred to by a certain customer.

NOTE B6 Applies to a product containing plastic parts whose combined weight exceeds 100 g with the exception of printed circuit boards, cables, connectors and electronic components and bio-based plastic material.

| Model nu   | mber *                            | i-SENSYS                     | MF543x   |                                |                                   | Logo                         |   |             | _                 |
|--|-----------------------------------|------------------------------|--|--------------------------------|-----------------------------------|------------------------------|---|-------------|-------------------|
| Issue date * 2019/10/1   |                                   |                              | 2  |                                |                                   |                              | Can   | 011         |                   |
| Product  | environn                          | nental atti                  | ibutes - Market red  | quirements (cont               | tinued)                           |                              | Require   | ment r      | met               |
| Item   |                                   |                              |  |                                |                                   |                              | Yes   | No          | n.a.              |
| <b>DT a</b> <i>i</i> <b>b</b>  |                                   |                              | ance requirements (c   |                                |                                   |                              |   |             |                   |
| P7.21* Biobased plastic material content is used in the product (See NOTE B7): |                                   |                              |  |                                |                                   |                              |   | $\boxtimes$ |                   |
|  | a) Of t<br>tota<br>or             | otal plastic<br>l plastic by |  | he biobased plastic            | vered;<br>material content (calcu | lated as a perce             | entage of                                       |             |                   |
| P7.22*   | Light sou                         | irces are fre                | e from mercury, i.e. le<br>becify: Number of lamp  | ss than 0,1 mg/lam             | p.<br>num mercury content pe      | er lamp: r                   | mg  |             |                   |
| P8   | Batteries                         |                              | ceny. Number of lamp   |                                |                                   | criamp. i                    | iig   |             |                   |
| P8.1*  |                                   |                              | mposition: <i>Lithium</i>  |                                |                                   |                              |   |             |                   |
| P9   |                                   |                              | on (See NOTE B8)   |                                |                                   |                              |   |             | <u> </u>          |
| P9.1   |                                   | -                            | following power levels   | or energy consump              | tions are reported:               |                              |   |             |                   |
| Energy mo  |                                   |                              | Power level at<br>100 V AC   | Power level at<br>115 V AC     | Power level at<br>230 V AC        | Reference/St<br>modes and te |   | nergy       |                   |
|  | de for ENE<br>perational<br>lucts |                              | W  | W                              | W                                 |                              |   |             |                   |
| Standby/off mode for<br>ENERGY STAR Operational<br>Mode (OM) products          |                                   | erational                    | W  | W                              | W                                 |                              |   |             |                   |
| TEC value for ENERGY STAR<br>TEC products                                      |                                   |                              | kWh/week   | kWh/week                       | 1.4 kWh/week                      |                              | AR (US scheme)<br>iteria Version 2.0<br>lipment |             |                   |
| (TEC= Typical Energy<br>Consumption)   |                                   | IJ                           |  |                                | <b>0.41</b> kWh/week              | ENERGY ST                    | AR (US scheme)<br>iteria Version 3.0            |             |                   |
| MAX  |                                   |                              | W  | W                              | <b>1420</b> W                     | Canon's Ow                   | n Standard                                      |             |                   |
| Printing(/   | Average)                          |                              | W  | W                              | <b>590</b> W                      | Canon's Ow                   | n Standard                                      |             | Ħ                 |
| Standby  |                                   |                              | W  | W                              | <b>13.6</b> W                     | Canon's Ow                   | n Standard                                      |             | Ē                 |
| Low Pow  | er                                |                              | W  | W                              | W                                 | Canon's Ow                   | n Standard                                      |             |                   |
| Sleep  |                                   |                              | W  | W                              | 0.9 W                             | Canon's Ow                   | n Standard                                      |             | Ē                 |
|  |                                   |                              | W  | W                              | W                                 |                              |   |             | 一                 |
| External P   | ower Supr                         | ly Efficienc                 | y Level (International E   | Efficiency Marking F           | rotocol) * :                      |                              |   |             | ⊢                 |
| Print/Scar   |                                   |                              | 43 images per minute   |                                | ,                                 |                              |   |             | $\overline{\neg}$ |
|  | •                                 |                              | e mode: 1 minutes  |                                |                                   |                              |   |             | 늼                 |
| P9.2*  |                                   |                              | e energy save functior   | is provided with the           | e product                         |                              |   |             | 늼                 |
|  | Emissio                           |                              |  |                                |                                   |                              |   |             |                   |
| P10  |                                   | -                            | Declared according to L  | SO 9296 (See NOT               | F B9)                             |                              |   |             |                   |
| P10.1  | Mode                              |                              | Declared according to ISO 9296 (See NOTE B9)     ode description   Statistical upper limit A-weig $L_{WA,c}$ (B) |                                | veighted sound                    | power level,                 |   |             |                   |
|  | Idle                              | *                            | Standby  | *                              | Not Detect                        |                              |   |             |                   |
|  | Operatio                          |                              | Print  |                                | 7.29                              |                              |   |             | Η                 |
|  | Other mo                          |                              |  |                                |                                   |                              |   |             | <u> </u>          |
|  | Measure                           | d according                  |  | ECMA-74<br>only if not covered | by ECMA-74)                       |                              |   |             |                   |

NOTE B7 The following is to be excluded from the calculation of percentage: printed circuit boards, labels, cables, connectors and electronic components and postconsumer recycled plastic.

NOTE B8 A Guidance document on Energy Efficiency is available; see <a href="http://www.ecma-international.org/publications/standards/Ecma-370.htm">http://www.ecma-international.org/publications/standards/Ecma-370.htm</a>

NOTE B9 A Guidance document on Acoustic Noise is available; see <a href="http://www.ecma-international.org/publications/standards/Ecma-370.htm">http://www.ecma-international.org/publications/standards/Ecma-370.htm</a>

| Model nu         | mber *                  | i-SENSYS MF543x   | Log                   |               |             |      |           |
|------------------|-------------------------|---|-----------------------|---------------|-------------|------|-----------|
| Issue dat        | e *                     | 2019/10/12  |                       | C             | an          | 01   | 1         |
|                  |                         |   |                       |               |             | · -  | -         |
| Product          | environ                 | mental attributes - Market requirements (continued)   |                       | R             | equire      | ment | met       |
| Item             |                         | · · · · ·   |                       |               | Yes         | No   | n.a.      |
|                  |                         | al emissions from printing products (See NOTE B10)  |                       |               |             |      |           |
| P10.2*           |                         | formed according to ECMA-328 Determination of Chemical Emissi   | on Rates from Electro | onic          | $\boxtimes$ |      |           |
| D40.0            |                         | ent (ISO/IEC 28360), other specify:   |                       |               |             |      |           |
| P10.3            |                         | emission rate (operation phase) is (mg/h):  |                       |               |             |      |           |
|                  |                         | bhotographic devices: Ozone <loq(=0.12) 0<="" 1.24="" dust="" styrene="" td=""><td></td><td></td><td></td><td></td><td></td></loq(=0.12)> |                       |               |             |      |           |
|                  | Ink dev                 | ces: Dust Styrene   | Benzene T             | VOC           |             |      | $\bowtie$ |
|                  | Note: c                 | ompliance with maximum emission rates in eco labels to be declare   | d in P14.             |               |             |      |           |
| P11              |                         | nable materials for printing products   |                       |               |             |      |           |
| P11.1*           |                         | / Data Sheet (SDS) is available for the ink/toner preparation, even i   |                       |               | $\boxtimes$ |      |           |
| P11.2*           |                         | containing post-consumer recycled fibers can be used, provided  | that it meets the re  | quirements of | $\boxtimes$ |      |           |
| P11.3*           | EN 122                  | 81.<br>(duplex) printing/copying is an integrated product function.   |                       |               |             |      |           |
| P11.3*<br>P11.4* |                         | duplex) printing/copying is an integrated product function.<br>duct is delivered to end-user with default auto-duplex enabled.            |                       |               |             | ⊢⊢   | <u> </u>  |
|                  |                         |   |                       |               |             |      |           |
| P13<br>P13.1*    |                         | ing and documentation<br>packaging material type(s): Corrugated Paper weight (kg): 4  | .49                   |               |             |      |           |
|                  | Product                 | packaging material type(s): EPS weight (kg): 0.68   |                       |               |             |      |           |
| D40 Ct           |                         | packaging material type(s): <i>PE</i> weight (kg): 0.13   |                       |               |             |      |           |
| P13.2*           |                         | plastic primary packaging is free from PVC.   |                       |               | $\square$   |      | <u> </u>  |
| P13.3*           |                         | duct primary corrugated fiberboard packaging, specify the contait<br>er recovered fiber content: 25%%                                     | ined percentage of r  | nınımum post- |             |      |           |
| P13.4*           |                         | media for user and product documentation (tick box):<br>nic $\bigotimes$ , Paper $\bigotimes$ , Other $\Box$                              |                       |               |             |      |           |
| P13.5            | (Please<br>User ar      | only complete this item if paper documentation used)<br>d product documentation on paper media is chlorine-free:<br>olease specify:       |                       |               |             |      |           |
|                  | Totally                 | Totally chlorine-free   |                       |               |             |      |           |
|                  | Elemen                  | tal chlorine-free   |                       |               | H           |      |           |
|                  | Process                 | ed chlorine-free  |                       |               | Ы           |      |           |
| P14              | Volunta                 | ry programs:  |                       |               |             |      |           |
| P14.1            | The pro                 | duct meets the requirements of the following voluntary program(s):  |                       |               |             |      |           |
|                  |                         | Y STAR® Criteria version: Date:   | Product categ         |               |             |      |           |
|                  | Eco-lab<br>Eco-lab      |   | Product categ         |               |             |      |           |
| P15              |                         | nal information (See NOTE B11)  | Product categ         | ory.          |             |      |           |
| P1.1             |                         | on this declaration comply with EU RoHS Directive(2001/65/EU).  |                       |               |             |      |           |
|                  | The cur<br>La<br>M<br>C | rent EU RoHS Directive restricts the use of following substances.<br>ead<br>ercury<br>admium  |                       |               |             |      |           |
|                  | P                       | exavalent chromium<br>hybrominated biphenyls(PBB)<br>hybrominated diphenyl ethers(PBDE)   |                       |               |             |      |           |
|                  |                         | is is based on knowledge as of the date of this document.   |                       |               |             |      |           |
| P1.7             |                         | anon-europe.com/about_us/sustainebility/business/reach_cus  | tomer_statement/      |               |             |      |           |
| 10.1             | Sound                   | Pressure (LpAm)<br>Bystander's position<br>Active(BW) (1-sided/2-sided) : 54 / 53 dL<br>Standby : 24 dB<br>Operator position              | 8                     |               |             |      |           |
|                  |                         | Active(BW) (1-sided/2-sided) : 59/59 dB   |                       |               |             |      |           |
|                  |                         | Standby : 26 dB   |                       |               |             |      |           |

NOTE B10 A Guidance document on Chemical Emissions is available; see <a href="http://www.ecma-international.org/publications/standards/Ecma-370.htm">http://www.ecma-international.org/publications/standards/Ecma-370.htm</a>

NOTE B11 Additional lines may be inserted to declare further items, by positioning the cursor at the far right of the row and hitting the <Enter> key.

## Legal references Europe Annex B1

| Reference  | Declaration item             |
|--|------------------------------|
| Directive 2011/65/EU (RoHS Directive) *<br>* Specific exemptions apply for certain products and<br>applications.   | P1.1, P4.1                   |
| (EC) 1907/2006(REACH, Annex XVII   | P1.2, P1.4, P1.6, P1.7, P4.2 |
| Regulation (EC) No. 2037/2000, 2038/2000, 2039/2000,<br>(Marketing and use of Ozone layer depleting<br>substances)   | P1.3, 5.3                    |
| Norwegian regulation relating to restrictions on the use of certain dangerous chemicals 20.12.2002   | P1.5                         |
| "REACH" Regulation (1907/2006), annex VII  | P1.10                        |
| Directive 2013/56/EC (Battery and accumulators<br>Directive) *<br>* These provisions shall not apply where, for safety,<br>performance, medical or data integrity reasons, continuity of<br>power supply is necessary and requires a permanent<br>connection between the appliance and the battery or<br>accumulator.            | P2.1, P2.2, P2,3, P8.1       |
| Directive 2006/95/EC (Low Voltage Directive)   | P3.1                         |
| Directive 2004/108/EC (EMC Directive)  | P3.1                         |
| Directive 1999/5/EC (R&TTE Directive)  | P3.1                         |
| Regulation (EC) 801/2013 amending Regulation (EC)<br>No 1275/2008 with regard to ecodesign requirements for<br>standby, off mode electric power consumption of<br>electrical and electronic household and office<br>equipment, and amending Regulation (EC) No 642/2009<br>with regard to ecodesign requirements for televisions | P3.1, P3.2                   |
| Regulation (EC) 1907/2006 (REACH Regulation),<br>Article 31, annex II)   | P4.3                         |
| Regulation (EC) 1272/2008 (CLP Regulation)   | P4.3, P7.19                  |
| Directive 2004/12/EC (Packaging Directive)   | P5.1                         |
| Decision 97/129/EC (Secondary packaging legislation)   | P5.2                         |
| Directive 2012/19/EU (WEEE directive)  | P6.1                         |