



i-SENSYS X C1530P Series

HIGH-CAPACITY, FAST COLOUR PRINTERS FOR BUSY WORKGROUPS AND MEDIUM TO LARGE BUSINESSES



PRODUCTIVITY



CONNECTIVITY



CONTROL AND
MAINTENANCE



SECURITY



COMPACT DESIGN

Canon

i-SENSYS X C1530P Series

PRODUCTIVITY

- Fast print speeds
- Automatic double-sided printing as standard
- Wide range of media support

CONNECTIVITY

- Print directly from USB, Wi-Fi
- Compatible with Canon PRINT Business app
- Support for Apple Air Print and Mopria
- Streamline print processes with uniFLOW Online software
- Universal Print by Microsoft enabled

CONTROL AND MAINTENANCE

- iW Enterprise Management Console allows centralised management of devices
- Remote eMaintenance services include meter capture, automatic consumables management and remote diagnostics
- Content Delivery System enables automatic firmware updates
- Toner status tool reduces downtime

SECURITY

- Secure print as standard prevents unauthorised viewing of printed material
- Embedded McAfee security safeguards device against external attacks
- Security enhancements include SIEM and TLS1.3

COMPACT DESIGN

- Small footprint and weight allow for any office configuration
- Add additional cassettes for enhanced input capacity without compromising on device size
- All-in-one, space-saving toner cartridge

QUICK FACTS

i-SENSYS X C1533P

- Print speed: 33ppm (A4)
- Print resolution: up to 1,200 x 1,200 dpi
- Automatic double-sided printing
- uniFLOW Online Express
- Network, USB and Wi-Fi connectivity
- Standard paper input: 550-sheet cassette

i-SENSYS X C1538P

- Print speed: 38ppm (A4)
- Print resolution: up to 1,200 x 1,200 dpi
- Automatic double-sided printing
- uniFLOW Online Express
- Network, USB and Wi-Fi connectivity
- Standard paper input: 550-sheet cassette

SERVICES

CORE

Perform routine office operations safely and with ease, utilising embedded software including uniFLOW Online Express and other available services offering complete device maintenance and support.



HARDWARE



SOFTWARE



SERVICES

BESPOKE

Choose a tailored service to suit your business needs by removing unnecessary print management burdens. Consult with Canon experts about your specific requirements to find a fitting Print Managed Services option.

ENHANCED

Expand cloud capabilities with uniFLOW Online, Canon's all-in-one print management system.

TECHNICAL SPECIFICATIONS

i-SENSYS X C1530P Series

PRINTER ENGINE

Print speed	i-SENSYS X C1533P: Single sided : Up to 33 ppm (A4) Up to 55 ppm(A5-Landscape) Double sided : Up to 33 ipm (A4) i-SENSYS X C1538P: Single sided : Up to 38 ppm (A4) Up to 59 ppm(A5-Landscape) Double sided : Up to 38 ipm (A4)
Printing method	Colour laser beam printing
Print resolution	Up to 1200 x 1200 dpi
Warm-up time	Print ready message shown: Approx. 2 seconds or less from power on
First Page Out Time	Colour: approx. 6.3 seconds Mono: approx. 5.3 seconds
Recommended Monthly Print Volume	i-SENSYS X C1533P: 1,000-5,000 pages i-SENSYS X C1538P: 1,500-5,000 pages
Duty cycle	i-SENSYS X C1533P: 40,000 pages i-SENSYS X C1538P: 50,000 pages
Print margins	4 mm-top, bottom, left and right
Advanced printing features	Secure Print Print from USB memory key (JPEG/TIFF/PDF/XPS) Barcode Print ¹ iOS: AirPrint, Canon PRINT Business app Android: Mopria certified, Canon Print Service Plug-in, Canon PRINT Business app Microsoft Universal Print

MEDIA HANDLING

Paper input (Standard)	550-sheet cassette 100-sheet multi-purpose tray
Paper input (Option)	550-sheet cassette x 3 (Paper Feeder PF-D1) 550-sheet cassette (Cassette Feeding Unit-AV1)
Paper output	200-sheet
Media types	Multi-Purpose Tray: Plain paper, Recycled paper, Heavy Paper, Thin paper, Colour paper, Coated paper, Pre-punched, Post card, Envelope Cassette: Plain paper, Recycled paper, Heavy Paper, Thin paper, Label, Colour paper, Coated paper, Pre-punched
Media sizes	Cassette (Standard): A4, A5, A5 (Landscape), A6, B5, Letter, Executive, Statement, GLTR, 16K, Custom sizes: Min. 101.6 x 148 mm Max. 216.0 x 297 mm. Multi-purpose tray: A4, A5, A5 (Landscape), A6, B5, Legal, Letter, Executive, Statement, OFFICIO, B-OFFICIO, M-OFFICIO, GLTR, ILGL, GLGL, Foolscap, 16K, Post card, Envelop (COM10, Monarch, C5, DL), Custom sizes: Min. 76.2 x 127 mm Max. 216.0 x 355.6 mm. Cassette (Optional): A4, A5, A5 (Landscape), A6, B5, Legal, Letter, Executive, Statement, GLTR, ILGL, GLGL, Foolscap, F4A, 16K, Custom sizes: Min. 101.6 x 148 mm Max. 216.0 x 355.6 mm
Media weights	Cassette (standard and optional): 60 to 163 g/m ² Multi-purpose tray: 60 to 216 g/m ²
Double sided printing	Automatic Cassette: A4, A5, B5, Legal, Letter, Executive, OFFICIO, B-OFFICIO, M-OFFICIO, GLTR, ILGL, GLGL, Foolscap, F4A, 16K Custom size - Min. 148 x 210 mm Max. 216 x 355.6 mm 60 to 163 g/m ²

GENERAL FEATURES

Power requirements	220-240V (±10%) 50/60Hz (±2Hz)
Power consumption	Maximum: Approx. 1500W or less Active: i-SENSYS X C1533P Approx. 623W or less i-SENSYS X C1538P Approx. 729W or less Standby: Approx. 34.4W or less Sleep: Approx. 1.1W or less Typical Electricity Consumption (TEC): ⁷ i-SENSYS X C1533P: 0.41kWh/week i-SENSYS X C1538P: 0.45kWh/week For detailed information relating to Lot26 regulation, please go to: http://www.canon-europe.com/For-Work/Lot26/index.aspx
Noise level	i-SENSYS X C1533P: Sound power ² Active: Simplex 65 dB or less (BW) / 65 dB or less (CL) Duplex 67 dB or less (BW) / 67 dB or less (CL) Standby: 48 dB or less Sound pressure ² Active: Simplex 50 dB or less (BW) / 51 dB or less (CL) Duplex 52 dB or less (BW) / 52 dB or less (CL) Standby: 33 dB or less i-SENSYS X C1538P: Sound power ² Active: Simplex 65 dB or less (BW) / 66 dB or less (CL) Duplex 67 dB or less (BW) / 68 dB or less (CL) Standby: 48 dB or less Sound pressure ² Active: Simplex 50 dB or less (BW) / 51 dB or less (CL) Duplex 52 dB or less (BW) / 52 dB or less (CL) Standby: 33 dB or less

Dimensions (W x D x H)

Weight	Approx. 25 kg
Operating environment	Temperature: 10 to 30°C (50 to 86°F) Humidity 20 to 80% RH (no condensation)
Control panel	5 Line LCD, 5 LED (Online, Ready, Message, Job and Energy saver), Buttons, 10-key numeric keypad
CONTROLLER	
Processor Speed	1GHz x 2
Memory	2GB
Storage	32GB eMMC (available space 15GB)
Printer Languages	UFRII (Ultra Fast Rendering), PCL5c ³ , PCL6, Adobe® PostScript3
Fonts	93 PCL fonts (93 Roman, 10 Bitmap fonts, 2 OCR fonts) Andalé Mono WT J/K/S/T (Japanese, Korean, Simplified and Traditional Chinese) ^{4*} Barcode Fonts ⁵ 136 PostScript fonts
Interface and connectivity	USB 2.0 Hi-Speed, 10BASE-T/100BASE-TX/1000Base-T, Wireless 802.11b/g/n, Wireless Direct Connection
Network Protocol	Print: TCP/IP (LPD/Port9100/IPP/IPPS/FTP/WSD) Management: SNMPv1, SNMPv3 (IPv4,IPv6) Security: TLS1.3, IPsec, IP/Mac address filtering, IEEE802.1X, SNMPv3, SSL (HTTPS, IPPS), Dual Network Support Security (wireless):Infrastructure Mode: WEP(64/128 bit), WPA-PSK(TKIP/AES), WPA2-PSK(TKIP/AES), WPA-EAP (AES), WPA2-EAP (AES) Access Point Mode:WPA2-PSK(AES) Wi-Fi Direct Mode:WPA2-PSK (AES)

Software and Printer Management

Operating Systems Compatibility	Remote User Interface (RUI), Department ID Management, Toner Status Tool, iW Enterprise Management Console: Server-based software for centralised management of a fleet of devices eMaintenance: embedded RDS allows remote eMaintenance services such as meter capture, automatic consumables management and remote diagnostics. Content Delivery System: Server platform enables automatic firmware update to the device. uniFLOW online / uniFLOW online Express / uniFLOW compatibility Windows [®] 10 / Windows [®] 8.1 / Server [®] 2019 / Server [®] 2016 / Server [®] 2012R2 / Server [®] 2012 / Mac OS X version 10.11 & up Linux ³ /Citrix
--	--

CONSUMABLES

All-in-One cartridges	TONER T10 Black (13,000 pages ⁶) TONER T10 Cyan (10,000 pages ⁶) TONER T10 Magenta (10,000 pages ⁶) TONER T10 Yellow (10,000 pages ⁶) TONER T10L Black (6,000 pages ⁶) TONER T10L Cyan (5,000 pages ⁶) TONER T10L Magenta (5,000 pages ⁶) TONER T10L Yellow (5,000 pages ⁶)
------------------------------	--

ACCESSORIES/ OPTIONS

Items	Paper Feeder PF-D1 (550-sheet cassette) x 3 CST-Feeding Unit-AV1 (550-sheet cassette pedestal) Barcode Printing Kit-D1 (Enables barcode printing capability) PCL Font Set-A1 (Enables Unicode printing capability on SAP and supports Andale font) Plain Pedestal-P2 Plain Pedestal-AA1 MiCard Multi (Card reader for identification with RFID or magnetic cards with uniFLOW) Micard Plus (Card reader for identification with RFID or magnetic cards with uniFLOW)
--------------	---

Notes:

- [1] Accessory - Barcode Printing Kit-E1E - is required
- [2] Declared noise emission in accordance with ISO 9296
- [3] A Canon PCL5c driver is not supplied, however PCL5c commands are supported on the device.
- [4] Accessory - PCL FONT SET-A1E - is required
- [5] Web distribution only. Driver will be available in 2H, 2021
- [6] Based on ISO/IEC 19798
- [7] As per US ENERGY STAR[®] version3.0.



Software & Solutions



Compatibility



Canon

Canon Inc.
canon.com

Canon Europe
canon-europe.com

English edition
© Canon Europa N.V., 2021