


QUICK, COMPACT AND ENERGY EFFICIENT MONO LASER PRINTER



i-SENSYS LBP6030B

Affordable, compact mono laser printers, ideal for desktop use at home or a small office delivering fast, high quality prints.



**RAPID PRINT
PERFORMANCE**



**SEAMLESS
CONNECTIVITY**



**EFFICIENT AND
SUSTAINABLE**

Rapid print performance

Thanks to Canon's Quick First-Print technologies with fast 18 pages per minute print speed, there's no waiting for documents.

Easy connectivity

Packed with high speed USB connectivity for direct connection to PC.

Efficient and Sustainable

Canon's Recyclable All-in-One print cartridge allows for a maintenance free operation. Packed with energy saving features, save time and money with market leading energy efficiency.

Canon

TECHNICAL SPECIFICATIONS

i-SENSYS LBP6030B

PRINTER ENGINE

Print speed	18ppm mono(A4) ¹
Printing method	Monochrome laser beam printing
Print quality	Up to 2400 x 600 dpi with Automatic Image Refinement
Print resolution	Up to 600 x 600 dpi
Warm-up time	Approx. 1 second from Sleep 10 seconds or less from power on
First Page Out Time	Approx. 7.8 seconds or less
Duty cycle	Max 5,000 pages per month
Print margins	5 mm-top, bottom, left and right

MEDIA HANDLING

Paper input (Standard)	150-sheet multi-purpose tray
Paper output	100-sheet face down
Media types	Plain paper, Heavy Paper, Transparency, Label, Envelope
Media sizes	A4/B5/A5/LGL/LTR/EXE/16K/Custom size Env. COM10/Env. Monarch/Env. C5/Env. DL width 76.2 to 216 mm x length 188 to 356 mm
Media weights	Multi-purpose tray: 60 to 163 g/m ²

GENERAL FEATURES

Power requirements	AC 220-240V (±10%), 50/60Hz (±2Hz)
Power consumption	Maximum: Approx. 870 W or less Active: Average approx. 330 W Standby: Average approx. 1.8 W or less Sleep: Average approx. 0.8 W or less Typical Electricity Consumption (TEC): 0.47 kWh/week
Noise level	Sound power ² : Active: 6.34 B or less Standby: Inaudible Sound pressure ² : Active: 49.2 dB(A) Standby: Inaudible
Dimensions (W x D x H)	364 mm x 249 mm x 199 mm
Weight	Approx. 5.0 Kg
Operating environment	Temperature : 10 to 30°C Humidity : 20 to 80%RH (no condensation)
Control panel	2 LED indicator, 2 operation key

CONTROLLER

Memory	32MB
Printer Languages	UFRII LT
Interface and connectivity	USB 2.0 Hi-Speed
Operating Systems	Windows* 11 / Windows* 10 / Windows* 8.1 / Server* 2022 / Server* 2019 / Server* 2016 / Server* 2012R2 / Server* 2012 / Server* 2008R2 / Server* 2008
Compatibility	Mac OS10.6 to 10.9/Linux3/Citrix(FR2)

CONSUMABLES

All-in-One cartridges	Standard: Cartridge 725 (1,600 pages ⁴) ⁵
-----------------------	------------------------------------------------------------------

Footnote

- ⁽¹⁾ The print speed may drop depending on the printer driver settings, paper size, paper type and number of pages printed
- ⁽²⁾ Declared noise emission in accordance with ISO 9296
- ⁽³⁾ Web distribution only
- ⁽⁴⁾ Based on ISO/IEC 19752
- ⁽⁵⁾ Printer ships with 700 pages starter cartridge

Standard disclaimers

All specifications subject to change without notice

Canon Inc.
canon.com

Canon Europe
canon-europe.com

English edition
© Canon Europa N.V., 2022