

# THE BEST SINGLE-FUNCTION COLOUR PRINTER DESIGNED FOR HYBRID WORKPLACES AND FOR PROFESSIONALS WORKING REMOTELY



## i-SENSYS LBP732Cdw

One of the most secure, sustainable and productive single-function printer, ideal as a main printer for small offices and sub-printer for medium offices.

### Enhanced connectivity

Embrace flexible working with a variety of connectivity features, including Wi-Fi support and Universal Print for easy remote management.

### Exceptional image quality

Achieve superior colour graphics, images and texts with laser-quality printing for professional-level documents.



AUTOMATIC DUPLEX PRINT  
TO SAVE PAPER AND  
ENERGY CONSUMPTION



AUTOMATIC RECOVERY



EASY SECURITY SETUP



STRONG PASSWORD SETTING



WPA3 PROTOCOL SUPPORT



WI-FI AS STANDARD



EMMC ENCRYPTION

### Boost productivity

Maximise your print output and improve running costs with rapid print speeds and an expandable paper capacity of up to 2,300 sheets.

### Improved serviceability

Simple installation, easy maintenance and excellent durability enable minimal downtime and reduced service costs.

**Canon**

---

# TECHNICAL SPECIFICATIONS

# i-SENSYS LBP732Cdw

## PRINTER ENGINE

<b>Print speed</b>	Single sided (A4): Up to 38 ppm colour and mono Double sided : Up to 38 ppm (Cassette), 21 ppm (Multi Purpose Tray) Single sided (A5-Landscape): Up to 59 ppm colour and mono
<b>Printing method</b>	Colour laser beam printing
<b>Print quality</b>	Up to 1200 x 1200 dpi
<b>Warm-up time</b>	Print ready message shown: Approx. 2 seconds or less from power on
<b>First Page Out Time</b>	Colour: approx. 6.3 seconds Mono; approx. 5.3 seconds
<b>Recommended Monthly Print Volume</b>	2,000 - 7,500 pages per month
<b>Duty cycle</b>	Max. 80,000 pages per month <sup>1</sup>
<b>Print margins</b>	4 mm-top, bottom, left and right
<b>Advanced printing features</b>	Encrypted Secure Print Secure Print Print from USB memory key (JPEG/TIFF/PDF/XPS) Barcode Print <sup>2</sup> iOS: AirPrint, Canon PRINT Business app Android; Mopria certified, Canon Print Service Plug-in, Canon PRINT Business app Microsoft Universal Print

## MEDIA HANDLING

<b>Paper input (Standard)</b>	550-sheet cassette 100-sheet multi-purpose tray
<b>Paper input (Option)</b>	550-sheet cassette x 3 (Paper Feeder PF-D1) 550-sheet cassette (Cassette Feeding Unit-AV1)
<b>Maximum paper input capacity</b>	Up to 2,300 sheets
<b>Paper output</b>	200-sheet face down
<b>Media types</b>	Multi-Purpose Tray: Plain paper, Recycled paper, Heavy Paper, Thin paper, Colour paper, Coated paper, Pre-punched, Post card, Envelope Cassette: Plain paper, Recycled paper, Heavy Paper, Thin paper, Label, Colour paper, Coated paper, Pre-punched
<b>Media sizes</b>	Cassette (Standard): A4, A5, A5 (Landscape), A6, B5, B6 Letter, Executive, Statement, GLTR, 16K, Custom sizes: Min. 101.6 x 148 mm Max. 216.0 x 297 mm.  Multi-purpose tray: A4, A5, A5 (Landscape), A6, B5, B6 Legal, Letter, Executive, Statement, OFFICIO, B-OFFICIO, M-OFFICIO, GLTR, ILGL, GLGL, Foolscap, 16K, Post card, Envelop (COM10, Monarch, C5, DL), Custom sizes: Min. 76.2 x 127 mm Max. 216.0 x 355.6 mm.  Cassette (Optional): A4, A5, A5 (Landscape), A6, B5, B6 Legal, Letter, Executive, Statement, GLTR, ILGL, GLGL, Foolscap, F4A, 16K, Custom sizes: Min. 101.6 x 148 mm Max. 216.0 x 355.6 mm
<b>Media weights</b>	Cassette (standard and optional): 60 to 163 g/m <sup>2</sup> Multi-purpose tray: 60 to 216 g/m <sup>2</sup>
<b>Double sided printing</b>	Automatic Cassette: A4, A5, B5, Legal, Letter, Executive, OFFICIO, B-OFFICIO, M-OFFICIO, GLTR, ILGL, GLGL, Foolscap, F4A, 16K Custom size - Min. 148 x 210 mm Max. 216 x 355.6 mm 60 to 163 g/m <sup>2</sup>

## GENERAL FEATURES

<b>Power requirements</b>	220-240V (±10%) 50/60Hz (±2Hz)
<b>Power consumption</b>	Maximum: Approx. 1500W or less Active: Approx. 640W or less Standby: Approx. 30.1W or less Sleep: Approx. 0.9W or less Typical Electricity Consumption (TEC): 0.0.39kWh/week <sup>3</sup> For detailed information relating to Lot26 regulation, please go to: <a href="http://www.canon-europe.com/For_Work/Lot26/index.aspx">http://www.canon-europe.com/For_Work/Lot26/index.aspx</a>
<b>Noise level</b>	Sound power <sup>3</sup> Active: Simplex 65 dB or less (BW) / 66 dB or less (CL) Duplex 67 dB or less (BW) / 68 dB or less (CL) Standby: 48 dB or less Sound pressure <sup>3</sup> Active: Simplex 50 dB or less (BW) / 51 dB or less (CL) Duplex 52 dB or less (BW) / 52 dB or less (CL) Standby: 33 dB or less
<b>Dimensions (W x D x H)</b>	458 mm x 464 mm x 388 mm
<b>Weight</b>	Approx. 29 kg
<b>Operating environment</b>	Temperature: 10 to 30°C (50 to 86°F) Humidity 20 to 80% RH (no condensation)
<b>Control panel</b>	5 Line LCD, 5 LED (Online, Ready, Message, Job and Energy saver), Buttons, 10-key numeric keypad

## CONTROLLER

<b>Processor Speed</b>	1.6GHz x 2
<b>Memory</b>	2GB
<b>Storage</b>	32GB eMMC (available space 15GB)
<b>Printer Languages</b>	UFRII (Ultra Fast Rendering), PCL5c <sup>4</sup> , PCL6, Adobe® PostScript <sup>3</sup>
<b>Fonts</b>	93 PCL fonts (93 Roman, 10 Bitmap fonts, 2 OCR fonts) Andale Mono WT J/K/S/T (Japanese, Korean, Simplified and Traditional Chinese) <sup>5</sup> Barcode Fonts <sup>2</sup> 136 PostScript fonts
<b>Interface and connectivity</b>	USB 2.0 High-Speed, 10BASE-T/100 BASE-TX/1000BASE-T Wireless 802.11b/g/n, Wireless Direct Connection
<b>Network Protocol</b>	Print: TCP/IP (LPD/Port9100/IPP/IPPS/FTP/WSD)

## Management

<b>Management:</b>	SNMPv1, SNMPv3 (IPv4,IPv6)
<b>Security:</b>	TLS1.3, IPSec, IP/Mac address filtering, IEEE802.1X, (LAN/WLAN), SNMPv3, SSL (HTTPS, IPPS), Dual Network Support
<b>Security (wireless):</b>	Infrastructure Mode: WEP(64/128 bit), WPA-PSK(TKIP/AES), WPA2-PSK(TKIP/AES), WPA3-SAE (AES), WPA-EAP (AES), WPA2-EAP (AES), WPA3-EAP (AES)
<b>Access Point Mode:</b>	WPA2-PSK(AES)
<b>Wi-Fi Direct Mode:</b>	WPA2-PSK (AES)
<b>Remote User Interface (RUI), Remote Operation Viewer, Department ID Management, Toner Status Tool,</b>	iW Enterprise Management Console: Server-based software for centralised management of a fleet of devices
<b>eMaintenance: embedded RDS allows remote eMaintenance services such as meter capture, automatic consumables management and remote diagnostics.</b>	Content Delivery System: Server platform enables automatic firmware update to the device.
<b>Operating Systems Compatibility</b>	Windows® 11/ Windows® 10 / Server® 2022 / Server® 2019 / Server® 2016 / Mac OS X version 10.13 & up Linux®/Citrix

## CONSUMABLES

<b>All-in-One cartridges</b>	Standard: Cartridge 064 Black (6,000 pages <sup>6</sup> ) <sup>8</sup> Cartridge 064 Cyan (5,000 pages <sup>6</sup> ) <sup>8</sup> Cartridge 064 Magenta (5,000 pages <sup>6</sup> ) <sup>8</sup> Cartridge 064 Yellow (5,000 pages <sup>6</sup> ) <sup>8</sup> High yield: Cartridge 064H Black (13,400 pages <sup>6</sup> ) <sup>8</sup> Cartridge 064H Cyan (10,400 pages <sup>6</sup> ) <sup>8</sup> Cartridge 064H Magenta (10,400 pages <sup>6</sup> ) <sup>8</sup> Cartridge 064H Yellow (10,400 pages <sup>6</sup> ) <sup>8</sup>
------------------------------	--

## ACCESSORIES/OPTIONS

<b>Items</b>	Paper Feeder PF-D1 (550-sheet cassette) x 3 CST.Feeding Unit-AV1 (550-sheet cassette pedestal) Barcode Printing Kit-D1 (Enables barcode printing capability) PCL Font Set-A1 (Enables Unicode printing capability on SAP and supports Andale font) Plain Pedestal-P2 Plain Pedestal-AA1 Waste Toner Box WT-B1
--------------	---

## Notes

- <sup>[1]</sup> Duty cycle is defined as the maximum number of printed pages for a single peak month. Any usage above the recommended duty cycle may decrease the life of the product
- <sup>[2]</sup> Accessory - Barcode Printing Kit-D1 - is required
- <sup>[3]</sup> Declared noise emission in accordance with ISO 9296
- <sup>[4]</sup> Commands supported only. Third party driver or direct printing from application required.
- <sup>[5]</sup> Accessory - PCL FONT SET-A1E - is required
- <sup>[6]</sup> Web distribution only. Driver will be available in 1H 2024
- <sup>[7]</sup> Based on ISO/IEC 19798
- <sup>[8]</sup> Printer ships with Black: 6,000 pages, C/M/Y: 3,200 pages starter cartridges
- <sup>[9]</sup> As per US ENERGY STAR® version3.2



# THE BEST SINGLE-FUNCTION COLOUR PRINTER DESIGNED FOR HYBRID WORKPLACES AND FOR PROFESSIONALS WORKING REMOTELY

One of the most secure, sustainable and productive single-function printer, ideal as a main printer for small offices and sub-printer for medium offices.



## PRODUCT DETAILS:

PRODUCT NAME	Mercury Code	EAN Code
i-SENSYS LBP732Cdw GB SFP	6173C011AA	8714574685434

## ACCESSORIES:

PRODUCT NAME	Mercury Code	EAN Code
Paper Feeder PF-D1	0942C001AA	4549292050714
Cassette Feeding Unit-AV1 (NEW)	4997C001AA	4549292182989
PCL FONT SET-A1E	4821B003AA	-
Barcode Printing Kit-D1E	3999B005AA	-
Plain Pedestal Type-P2	1632C002AA	8714574668635
Plain Pedestal Type-AA1	5512C002AA	8714574668666
Waste Toner Box WT-B1	0942C002AA	4549292052688

## CONSUMABLES

PRODUCT NAME	Mercury Code	EAN Code
Cartridge 064 Yellow	4931C001AA	4549292182491
Cartridge 064 Magenta	4933C001AA	4549292182514
Cartridge 064 Cyan	4935C001AA	4549292182538
Cartridge 064 Black	4937C001AA	4549292182552
Cartridge 064H Yellow	4932C001AA	4549292182507
Cartridge 064H Magenta	4934C001AA	4549292182521
Cartridge 064H Cyan	4936C001AA	4549292182545
Cartridge 064H Black	4938C001AA	4549292182569



**Canon Ireland**  
3006 Lake Drive  
Citywest, Saggart  
Co. Dublin, Ireland  
Telephone No: 01 2052400  
Facsimile No: 01 2052525  
canon.ie

**Canon (UK) Ltd**  
5 The Square  
Stockley Park  
Uxbridge  
UB11 1ET  
Tel: 01895 648 000  
www.canon.co.uk

**Canon Inc.**  
canon.com  
**Canon Europe**  
canon-europe.com  
English edition  
© Canon Europa N.V., 2024