

FAST, SECURE AND HIGHLY PRODUCTIVE A4 BW DEVICE WITH FAST DOCUMENT PROCESSING CAPABILITIES.

Ideal for a busy small to medium size business looking for a compact and reliable device, capable to cater for all their print and scan needs.

i-SENSYS MF563dw



HIGH PRODUCTIVITY

Fast print and scan speeds, support for wide range of media and flexible configuration with up to 2,300 sheets of paper input ensuring high productivity.

SMOOTH USER EXPERIENCE

Large 7" display offering a variety of convenient functions to suit your individual print and scan needs. Benefit from increased flexibility and cost efficiency thanks to mobile and cloud connectivity.

ROBUST SECURITY

Incorporating advance security features and machine learning-AI technology helping you select appropriate security settings to prevent data breaches and ensure secure printing and scanning.

PROMOTING SUSTAINABILITY

Reduce your carbon footprint and save your energy costs thanks to low energy consumption. Boost your sustainability efforts further thanks to the device built with 25% recyclable materials.

TECHNICAL SPECIFICATIONS

i-SENSYS MF563dw

i-SENSYS MF563dw	
Machine Type	Mono Laser All-In-One
Available functions	Print, Copy, Scan and Fax
PRINTER	
Print speed	Single sided : Up to 43 ppm (A4) Up to 65.2 ppm (A5-Landscape) Double sided : Up to 36 ipm (A4)
Printing method	Monochrome laser beam printing
Print resolution	Up to 1200 x 1200 dpi
Warm-up time	4 Seconds or Less* * Time from device power-on to when key operations can be performed on the touch panel display. From Sleep Mode: 20 Seconds or less
First Print Out Time	Approx: 6.2 seconds or less
Printer languages	UFRII, PCL 5e ¹ , PCL6, Adobe® PostScript ³
Fonts	93 PCL fonts (93 Roman, 10 Bitmap fonts, 2 OCR fonts) ² Andalé Mono WT J/K/S/T (Japanese, Korean, Simplified and Traditional Chinese) ² Barcode Fonts ³ 136 PostScript fonts
Print margins	5 mm-top, bottom, left and right 10 mm-top, bottom, left and right (Envelope)
Toner saver mode	Yes
Advanced printing features	Encrypted Secure Print Secure Print Forced Hold Print Print from USB memory key (JPEG/TIFF/PDF/XPS) Barcode Print ³ Microsoft Universal Print iOS: AirPrint, Canon PRINT app Android; Mopria certified, Canon PRINT app, Canon Print Service Plug-in, IPP everywhere
COPIER	
Copy speed	Single sided (A4): Up to 43 ppm Double sided (A4): Up to 36 ipm
First Copy Output Time (FCOT)	Platen: Approx. 6.3 seconds or less ADF: Approx. 6.4 seconds or less
Copy resolution	Up to 600 x 600 dpi
Copy modes	Text, Text/Photo (Default), Text/Photo (High Quality), Photo
Double sided copying	2-sided to 2-sided (Automatic)
Multiple copy	Up to 9999 copies
Reduction / Enlargement	25-400% in 1% increments
Other features	Preset R/E Ratios by Area, Two-Sided, Density Adjustment, Original Type Selection, Interrupt Mode, Two-sided Original, Sort, Job Build, N on 1, Sharpness, Erase Frame, Copy ID Card, Reserved copy, Copy Sample

SCANNER	
Type	Colour
Scan resolution	Optical: Up to 600 x 600 dpi
Scan speed	Single sided: 50ipm (300x300dpi) Double sided: 100ipm (300x300dpi) Single sided: 50ipm (300x600dpi) Double sided: 100ipm (300x600dpi)
Colour scanning depth	24 bit/24 bit (input/output)
Greyscales	256 levels
Compatibility	TWAIN, WIA, ICA
Max. scan width	216 mm
Scan to E-mail	Standard TIFF (MMR), JPEG(single page only), PDF (Compact, Searchable, PDF/A-1b, Encrypted), XPS (Compact, Searchable), PDF/XPS (Device Signature, Office Open XML (PowerPoint, Word)
Scan to PC	
Scan to USB memory key	
Scan to FTP	
Scan to Cloud¹	JPEG/PDF ⁴
iFAX	ITU-T.37
FAX	
Modem speed	33.6 Kbps (Up to 3 seconds/page ⁵)
Receive mode	Fax only, Fax/Tel Auto Switch, Answer Mode, Manual
Fax resolution	Standard: 200 x 100 dpi Fine: 200 x 200 dpi Super fine: 200 x 400 dpi Ultra fine: 400 x 400 dpi
FAX memory	Up to 30000 pages ⁵
Speed dials	Up to 200 dials
Group dials/ destinations	Max. 199 dials / Max. 199 destinations
Sequential broadcast	Max. 256 destinations
Memory backup	Permanent fax memory backup (Backup with flash memory)
Double sided faxing	Yes (Transmit and Receive)
Other features	Sender's Name (TTI), Direct Send, Delayed Send, Preview, Finished Stamp, Job Done Notice, TX Report, Interrupt Transmission, Sequential Broadcasting, Password/ Subaddress Sending, Confidential Mailbox
MEDIA HANDLING	
Scanner type	Platen, 2-sided ADF (single pass)
Paper input (Standard)	550-sheet cassette 100-sheet multi-purpose tray 50-sheet ADF
Paper input (Option)	550-sheet cassette x 3
Maximum paper input capacity	2,300 sheets
Paper output	150 sheet

TECHNICAL SPECIFICATIONS

i-SENSYS MF563dw

Media types	Plain paper, Recycled paper, Heavy Paper, Thin paper, Color paper, Label, Letterhead, Post card, Envelope
Media sizes	Cassette (Standard and optional): A4, A5, A5 (Landscape), A6, B5, Legal, Letter, Executive, Statement, OFFICIO, B-OFFICIO, M-OFFICIO, GLTR, GLGL, Foolscap, 16K, Custom sizes: Min. 105 x 148 mm Max. 216.0 x 355.6 mm. Multi-purpose tray: A4, A5, A5 (Landscape), A6, B5, Legal, Letter, Executive, Statement, OFFICIO, B-OFFICIO, M-OFFICIO, GLTR, GLGL, Foolscap, 16K, Indexcard, Envelope (COM10, Monarch, C5, DL), Custom sizes: Min 76.2 x 127 mm Max. 216.0 x 355.6 mm. ADF: A4, A5, A6, B5, Legal, Letter, Statement, Custom sizes: Min. 48 x 85.0 mm Max 216 x 355.6 mm
Media weights	Cassette (standard and optional): 60 to 120 g/m ² Multi-purpose tray: 60 to 200 g/m ² ADF: 60 to 105 g/m ²
Double sided printing	A4, Legal, Letter, OFFICIO, B-OFFICIO, M-OFFICIO, GLGL, Foolscap Custom size - Min. 210 x 279.4 mm Max. 216.0 x 355.6 mm 60 to 120 g/m ²
INTERFACE & SOFTWARE	
Interface type	USB 2.0 Hi-Speed, 10BASE-T/100BASE-TX/1000Base-T, Wireless 802.11b/g/n, Wireless Direct Connection
Operating System compatibility	Windows® 11 / Windows® 10 / Server® 2025 / Server® 2022 / Server® 2019 / Server® 2016 Mac OS X version 10.15 & up Linux ⁶

Network Protocol	Print: TCP/IP (LPD/Port9100/IPP/IPPS/FTP/WSD) Scan: Push Scan: File: FTP (TCP/IP), SMB3.1.1 (TCP/IP), Web DAV, E-mail/I-Fax: SMTP (send), POP3 (receive) Pull Scan: TCP/IP Management: SNMPv1, SNMPv3 (IPv4,IPv6) Security: TLS1.3, IPsec, IP/Mac address filtering, IEEE802.1X(LAN/WLAN), SNMPv3, SSL (HTTPS, IPPS), Dual Network Support Security (wireless): Infrastructure Mode: WPA-PSK(AES), WPA2-PSK(AES), WPA3-SAE (AES), WPA-EAP(AES), WPA2-EAP(AES), WPA3-EAP(AES) Access Point Mode: WPA2-PSK(AES), WPA3-SAE (AES)
Software and printer management	Network Scan Gear2, Remote Operation Viewer, Remote User Interface (RUI), Department ID Management, Access Management System, Toner Status Tool, iW Enterprise Management Console: Server-based software for centralised management of a fleet of devices eMaintenance: embedded RDS allows remote eMaintenance services such as meter capture, automatic consumables management and remote diagnostics. Content Delivery System: Server platform enables automatic firmware update to the device.

GENERAL FEATURES	
Recommended Monthly Print Volume	2,000 - 7,500 pages per month
Duty cycle	Max. 150,000 pages per month ⁷
Processor Speed	1.6GHz Dual Core Processor and 800MHz Single Core Processor
Memory	2GB
Storage	64GB eMMC
Control panel	17.8 cm / 7" LCD Colour Touch Screen
Dimensions with trays (W x D x H)	480 mm x 518 mm x 458 mm
Installation space (W x D x H)	680 mm x 980 mm x 1120 mm

TECHNICAL SPECIFICATIONS

i-SENSYS MF563dw

Weight	Approx. 20 Kg
Operating environment	Temperature: 10 to 30°C (50 to 86°F) Humidity: 20 to 80% RH (no condensation)
Power Source	220-240V(±10%) 50/60Hz (±2Hz)
Power Consumption	Maximum: Approx. 1,400 W Active printing: Approx. 522 W Standby: Approx. 12.2 W Sleep mode: Approx. 0.8 W Typical Electricity Consumption (TEC): 0.38 kWh/week (230V) ^[1] For detailed information relating to Lot26 regulation, please go to: http://www.canon-europe.com/For_Work/Lot26/index.aspx
Noise Levels	Sound Pressure ^[8] : Active: 53 dB Standby: 25 dB Sound Power ^[8] : Active: Duplex 67dB / Simplex 68dB Standby: 40 dB
CONSUMABLES	
Cartridges	Cartridge 056L (5,100 pages ^[9]) ^[10] Cartridge 056H (21,000 pages ^[9]) ^[10]
ACCESSORIES/ OPTIONS	
Items	Paper Feeder PF-C1 (550-sheet cassette) Plain Pedestal V2 Plain Pedestal AB1 PCL FONT SET-A1E Barcode Printing Kit-D1E

Notes:

[1] A Canon PCL5e driver is not supplied, however PCL5e commands are supported on the device.

[2] Accessory - PCL FONT SET-A1E - is required

[3] Accessory - Barcode Printing Kit-D1E - is required

[4] Scan by Canon PRINT

[5] Based on ITU-T Standard Chart No. 1

[6] Linux support both printing and scanning

[7] Duty cycle is defined as the maximum number of printed pages for a single peak month.

Any usage above the recommended duty cycle may decrease the life of the product

[8] Declared noise emission in accordance with ISO 9296

[9] Based on ISO/IEC 19752

[10] Printer ships with Cartridge 056L (5,100 pages)

[11] As per US ENERGY STAR[®] version 3.2