

imageRUNNER ADVANCE DX C7700 Series

SECURE A3 COLOUR MULTIFUNCTION DEVICES TO SUPPORT YOUR BUSINESS' DIGITAL TRANSFORMATION WITH ADVANCED CLOUD SOLUTIONS

MAIN CONFIGURATION OPTIONS




Canon uniFLOW Online
Outstanding Cloud Output Management Solution



Canon uniFLOW Online
Outstanding Cloud Output Management Solution




New to the Line




STAPLE FINISHER-AC1

- 3 tray, 3,500 sheet capacity
- Corner and double stapling up to 65 sheets (90 gsm)
- Supports Eco stapling 4 sheets (80 gsm) and Staple on Demand 65 sheets (90 gsm)
- Supports optional internal 2/4 and 4 hole inner punchers (2/4 Hole Puncher Unit-A1 and 4 Hole puncher unit-A1)




BOOKLET FINISHER-AC1

- 3 tray, 3,500 sheet capacity
- Corner and double stapling up to 65
- Supports optional internal 2/4 and 4 hole inner punchers (2/4 Hole Puncher Unit-A1 and 4 Hole puncher unit-A1)



DOCUMENT INSERTION UNIT-Q1

- Insert pre-printed sheets
- Up to A3
- 1-tray, 100 sheet capacity



DOCUMENT INSERTION/FOLDING UNIT-K1

- Insert pre-printed sheets
- Up to A3
- 1-tray, 100-sheet capacity
- Z-fold and C-fold



IR ADV DX C7765i / C7770i / C7780i




PAPER DECK UNIT-E1

- Supports A4
- Media weight 52 - 256 gsm
- 3,500 sheets (80gsm)




POD DECK LITE-C1

- Supports up to A3
- Media weight 52 - 300 gsm
- 3,500 sheets (80 gsm)



UNIFLOW ONLINE

- Device-based Cloud Subscription for Document Output and Capture Management



IMAGEPASS-N2

PDL • PCL/PS

MEMORY • 4GB/500GB

SYSTEM • Fiery FS350

- Delivers fast processing speed, outstanding image quality, and time-saving workflow
- Personalised printing with the built-in, entry-level Fiery FreeForm (TM) or with the supported industry-leading variable data printing (VDP) formats
- Integrates print production workflows with EFI (TM) management information systems, Web-to-Print systems, and popular prepress workflows for end-to-end automation
- Communicates with the full suite of optional uniFLOW modules

This flat configuration is for illustration purpose only. For a complete list of options and the exact compatibility relationships, please refer to the online [product configurator](#).

The Unified Firmware Platform (UFP) ensures that the latest feature upgrades and protection are available, for an enhanced user experience across the entire iR ADVANCE DX portfolio.

TECHNICAL SPECIFICATIONS

imageRUNNER ADVANCE DX C7700 Series

MAIN UNIT

Machine type
A3 Color Laser Multifunctional

Core functions
Print, Copy, Scan, Send, Store and Optional Fax

Processor
1.7GHz Dual Core Processor

Control Panel
Standard: 10.1" TFT LCD WSVGA Color Touch panel
Optional: 10.4" TFT LCD SVGA Color Upright Touch Panel

Memory
Standard: 4.0GB RAM

Hard Disk drive
Standard*: 320 GB(available disk space: 250 GB),
Optional: 250GB, 1TB
* A different initial HDD may be used.

Mirroring Hard Disk Drive
Optional

Interface Connection

NETWORK
Standard: 1000Base-T/100Base-TX/10Base-T, Wireless LAN(IEEE 802.11 b/g/n)
Optional: NFC, Bluetooth Low Energy

OTHERS
Standard: USB 2.0(Host) x1, USB 3.0(Host) x1, USB 2.0(Device) x1
Optional: Serial Interface, Copy Control Interface

Paper Supply Capacity (A4, 80gsm)
Standard: 3,550 sheets
250-sheet Multi-purpose tray,
1,100-sheet Paper Deck x 2,
550-sheet Paper Cassette x 2
Maximum: 7,050 sheets
(with Paper Deck Unit-E1 or POD Deck Lite-C1)

Paper output capacity (A4, 80gsm)
250 sheets (with Copy Tray-R2)
Maximum: 3,500 Sheets
(with Staple Finisher-AC1 or Booklet Finisher-AC1)

Finishing capabilities
With options: Collate, Group, Offset, Staple, Saddle Stitch, Hole Punch, Eco Staple, Staple On Demand, Document Insertion, Z-fold, Half-fold, C-fold

Supported media types

Multi-purpose tray: Thin, Plain, Recycled, Color, Heavy, Coated, Textured, Tracing, Bond, Transparency, Label, Pre-punched, Letterhead, Tab, Envelope

Paper Decks(Right/Left): Thin, Plain, Recycled, Color, Heavy, Tracing, Bond, Transparency, Bond, Pre-punched, Letterhead

Paper Cassettes (Upper/Lower): Thin, Plain, Recycled, Color, Heavy, Bond, Transparency, Pre-punched, Letterhead, Tab*, Envelope**

* Tab Feeding Attachment-F1 is required
** Envelope Feeder Attachment-F1 is required.

Supported media sizes

Multi-purpose tray:
Standard size: SRA3, A3, A4, A4R, A5, A5R, A6R, B4, B5, B5R
Custom size: 100.0 x 148.0 mm to 330.2 x 487.7 mm
Free size: 100.0 x 148.0 mm to 330.2 x 487.7 mm
Envelope: COM10 No.10, Monarch, DL, ISO-C5
Free size: 100.0 x 148.0 mm to 330.2 x 487.7 mm
Envelope custom size: 90.0 x 148 mm to 330.2 x 487.7 mm

Paper Decks (Right/Left):
Standard size: A4, B5

Paper Cassettes(Upper/ Lower):
Standard size: SRA3, A3, A4, A4R, A5, A5R, A6R, B4, B5, B5R
Custom size: 139.7 x 182.0 mm to 330.2 x 487.7 mm
Envelope: COM10 No.10, Monarch, DL, ISO-C5
Envelope custom size: 98.0 x 148.0 mm to 330.2 x 487.7 mm

Supported media weights

Multi-purpose tray: 52 to 300 gsm
Paper Deck (Right/Left): 52 to 220 gsm
Paper Cassette (Upper/Lower): 52 to 256 gsm
Duplex: 52 to 220 gsm

Warm-up Time

Quick startup mode: 4 seconds or less*
*Time from device power on to when the copy icon appears and is enabled to operate on the touch panel display

From Sleep Mode: 30 Seconds or Less
From Power On: 30 seconds or less*
*Time from device power-on, until copy ready(not print reservation)

Dimensions (W x D x H)
689 x 937 x 1,185 mm

Installation Space(W x D)
Basic: 2,026 x 1,524 mm (with Front door open + Multi-purpose tray/upper-right cover open + Buffer Pass-M1 + Booklet Finisher-AC1/extension tray & rotary tray extended)
Fully Configured: 2,621 x 1,524 mm (with POD Deck Lite-C1 + Buffer Pass-M1 + Document Insertion Unit-Q1 + Booklet Finisher-AC1/extension tray extended)

Weight
Approx. 255 kg (including toner)

PRINT SPECIFICATIONS

Print Speed (BW/CL)

iR-ADV DX C7780i:
Up to 80/70 ppm (A4, A5*, A5R, A6R*),
Up to 40/35 ppm (A3), Up to 56/49 ppm (A4R)

iR-ADV DX C7770i:
Up to 70/65 ppm (A4, A5*, A5R, A6R*),
Up to 35/32 ppm (A3), Up to 49/46 ppm (A4R)

iR-ADV DX C7765i:
Up to 65/60 ppm (A4, A5*, A5R, A6R*),
Up to 32/30 ppm (A3), Up to 46/42 ppm (A4R)

*A5/A6R (1-sided)
2,400 x 2,400

Print Resolution (dpi)
Standard: UFR II, PCL6, Adobe® PostScript®3™

Page description languages
Supported file types: PDF, EPS, TIFF, JPEG, and XPS

Direct Print
AirPrint, Mopria, Universal Print by Microsoft, Canon PRINT Business, and uniFLOW Online

Printing from mobile and cloud

A range of software and MEAP-based solutions are available to provide printing from mobile devices or internet-connecte d devices and cloud-based services depending on your requirements.
Please contact your sales representative for further information.

Fonts

PS fonts: 136 Roman
PCL fonts: 93 Roman, 10 Bitmap fonts, 2 OCR fonts, Andale Mono WT J/K/S/T*1 (Japanese, Korean, Simplified and Traditional Chinese), Barcode fonts*2
*1 Optional PCL International Font Set-A1 is required.
*2 Optional Barcode Printing Kit-D1 is required.

Print Features
Secured Print, Secure Watermark, Header/Footer, Page Layout, Two-sided Printing, Mixed Paper Sizes/Orientations, Front/Back Covers, Toner Reduction, Poster Printing, Forced hold printing, Print Date, Scheduled Printing, Printing Using a Virtual Printer

Operating System

UFR II: Windows®7/8.1/10/Server2008/Server2008 R2/Server2012/Server2012 R2/Server2016/Server2019, Mac OS X(10.10 or later)
PCL: Windows®7/8.1/10/Server2008/Server2008 R2/Server2012/Server2012 R2/Server2016/Server2019
PS: Windows®7/8.1/10/Server2008/Server2008 R2/Server2012/Server2012 R2/Server2016/Server2019, Mac OS X(10.10 or later)
PPD: Windows®7/8.1/10, Mac OS X(10.9 or later)
McAfee Embedded Control
As of July,2019.

COPY SPECIFICATIONS

Copy Speed (BW/CL)

iR-ADV DX C7780i:
Up to 80/70 ppm (A4, A5*, A5R, A6R*),
Up to 40/35 ppm (A3), Up to 56/49 ppm (A4R)

iR-ADV DX C7770i:
Up to 70/65 ppm (A4, A5*, A5R, A6R*),
Up to 35/32 ppm (A3), Up to 49/46 ppm (A4R)

iR-ADV DX C7765i:
Up to 65/60 ppm (A4, A5*, A5R, A6R*),
Up to 32/30 ppm (A3), Up to 46/42 ppm (A4R)

*A5/A6R (1-sided)

iR-ADV DX C7780i: Approx. 4.4/5.4 seconds or less

iR-ADV DX C7770i: Approx. 4.8/5.9 seconds or less

iR-ADV DX C7765i: Approx. 4.8/5.9 seconds or less

600 x 600

Up to 9,999 copies

Automatic or Manual (9 Levels)

Variable zoom: 25% to 400% (1% Increments)
Preset reduction/enlargement: 25%, 50%, 70%, 100%(1:1), 141%, 200%, 400%

Copy Features
Preset R/E Ratios by Area, Two-Sided, Density Adjustment, Original Type Selection, Interrupt Mode, Book to Two Pages, Two-sided Original, Job Build, N on 1, Add Cover, Insert Sheets, Different Size Originals, Page Numbering, Copy Set Numbering, Sharpness, Erase Frame, Secure Watermark, Print Date, Gutter, Print & Check, Negative/Positive, Repeat Images, Merge Job Blocks, Mirror Image, Store in Mail Box, Superimpose Image, Copy ID Card, Skip Blank Pages, Free Size Original, Color Mode, Reserved copy, Copy Sample

SCAN SPECIFICATIONS

Type
Single-pass Duplexing Automatic Document Feeder*
[2-sided to 2-sided (Automatic)]
*Detect Feeder Multi Sheet Feed is supported.

Document Feeder Paper Capacity (80 gsm)
Up to 200 Sheets

Acceptable originals and weights
Platen: Sheet, Book, and 3-Dimensional objects
Document Feeder media weight:
1-sided scanning: 38 to 220 gsm (BW, CL)
2-sided scanning: 38 to 220 gsm (BW, CL)
*An acceptable weights of A6R or smaller is 50 to 220gsm.

Supported media sizes
Platen: max. scanning size up to 297.0 x 431.8 mm
Document Feeder media size:
A3, A4, A4R, A5, A5R, A6R, B4, B5, B5R, B6R,
Custom size: 70.0 x 139.7 mm to 304.8 x 431.8 mm

Scan Speed (ipm: BW/CL; A4)
1-sided Scanning:
135/135 (300 x 300 dpi, send), 80/80 (600 x 600 dpi, copy),
2-sided Scanning:
270/270 (300 x 300 dpi, send), 160/90 (600 x 600 dpi, copy)

Scan Resolution (dpi)
Scan for Copy: 600 x 600
Scan for Send: (Push) 600 x 600 (SMB/FTP/WebDAV/IFAX), (Pull) 600 x 600
Scan for Fax: 600 x 600

Pull Scan Specifications
Color Network ScanGear2. For both TWAIN and WIA
Supported OS: Windows®7/8.1/10/Server2008/Server2008 R2/Server2012/Server2012 R2/Server 2016

Scan Method
Push Scan, Pull Scan, Scan to Box, Scan to Advanced Space, Scan to Network, Scan to USB Memory Key, Scan to Mobile device, Scan to cloud (uniFLOW Online)

SEND SPECIFICATIONS

Destination
Standard: E-mail/Internet Fax (SMTP), SMB3.0, FTP, WebDAV, Mail Box
Optional: Super G3 FAX, IP FAX

Address Book
LDAP (2,000)/Local(1,600)/Speed dial(200)

Send resolution (dpi)
Push: up to 600 x 600
Pull: up to 600 x 600

Communication protocol
File: FTP(TCP/IP), SMB3.0 (TCP/IP), WebDAV
E-mail/I-Fax: SMTP, POP3

File Format
Standard: TIFF, JPEG, PDF(Limited Color, Compact, Searchable, Apply policy, Optimize for Web, PDF/A-1b, Trace & Smooth, Encrypted, Device Signature, User Signature), XPS(Compact, Searchable, Device Signature, User Signature), Office Open XML (PowerPoint, Word)



TECHNICAL SPECIFICATIONS

imageRUNNER ADVANCE DX C7700 Series

Universal Send Features	Original Type Selection, Two-sided Original, Book to Two Pages, Different-size Originals, Density Adjustment, Sharpness, Copy Ratio, Erase Frame, Job Build, Delayed Send, Preview, Job Done Notice, File Name, Subject/Message, Reply-to, E-mail Priority, TX Report, Original Content Orientation, Skip Blank Pages	Power consumption	Maximum: Approx. iR-ADV DX C7780i: 2,500 W, iR-ADV DX C7770i/C7765i: 2,000 W Copying (with DADF continuous scan): Approx. 1,319 W ^{*1} Standby: Approx. 119.6 W ^{*1} Sleep mode: Approx. 0.9 W ^{*2} ^{*1} Reference value: measured one unit ^{*2} 0.9W sleep mode is not available in all circumstances due to certain settings.
FAX SPECIFICATIONS		Noise levels (BW/CL)	Typical Electricity Consumption (TEC) : iR-ADV DX C7780i: (BW): 1.35 kWh iR-ADV DX C7770i: (BW): 1.19 kWh iR-ADV DX C7765i: (BW): 1.14 kWh Note: Regarding ENERGY STAR program, the EU-US agreement expired on 20 February 2018. Although TEC values are provided, ENERGY STAR certification is not valid in Europe.
Maximum Number of Connection Lines	2		ENERGY STAR Product Specification for Imaging Equipment Version 3.0 Sound Power Level (LWA_m) Active(BW) (1-sided) iR-ADV DX C7780i/C7770i/C7765i: 5.1 B*, Kv 0.3 B* ^{*Reference value: measured only one unit with ISO7779, described with ISO9296 (2017)} Sound Pressure (LpA_m) Bystander's position: Active (BW/CL) (1-sided) iR-ADV DX C7780i: 57 dB*/56 dB* iR-ADV DX C7770i: 56 dB*/56 dB* iR-ADV DX C7765i: 56 dB*/55 dB* Stand-by iR-ADV DX C7780i/C7770i/C7765i: 36 dB* ^{*Reference value: measured only one unit with ISO7779, described with ISO9296 (2017)}
Modem Speed	Super G3: 33.6 kbps G3: 14.4 kbps	Standards	Blue Angel
Compression Method	MH, MR, MMR, JBIG	CONSUMABLES	
Resolution (dpi)	400 x 400 (Ultra Fine), 200 x 400 (Super Fine), 200 x 200 (Fine), 200 x 100 (Normal)	Toner Cartridges	C-EXV 52 Toner BK/C/M/Y
Sending/Receiving Size	Sending: A3, A4, A4R, A5 ^{*1} , A5R ^{*1} , B4, B5 ^{*2} , B5R ^{*1} Receiving: A3, A4, A4R, A5R, B4, B5, B5R ^{*1} Sent as A4 ^{*2} Sent as B4 short	Toner Yield (Estimated @ 5% Coverage)	C-EXV 52 Toner BK: 82,000 pages C-EXV 52 Toner C/M/Y: 66,500 pages
FAX memory	Up to 30,000 pages (2,000 jobs)	SOFTWARE AND PRINTER MANAGEMENT	
Speed dials	Max. 200	Tracking and reporting	Universal Login Manager (ULM) uniFLOW Online Express
Group dials/destinations	Max. 199 dials	Remote management tools	iW Management Console eMaintenance Content Delivery System
Sequential broadcast	Max. 256 addresses	Scanning software	Network ScanGear
Memory backup	Yes	Optimisation tools	Canon Driver Configuration Tool NetSpot Device Installer
Fax Features	Sender's Name (TTI), Selecting the Telephone Line (when sending fax), Direct Send, Delayed Send, Preview, Job Done Notice, TX Report, Interrupt Transmission, Sequential Broadcasting, Password/Subaddress Sending, Confidential Mailbox, 2 on 1 Log	Platform	MEAP (Multifunctional Embedded Application Platform)
		Document Administration	Kofax Power PDF (Optional)
STORE SPECIFICATIONS		FIERY PRINT CONTROLLER SPECIFICATIONS (EMBEDDED)	
Mail Box (Number supported)	100 User Inboxes, 1 Memory RX Inbox, 50 Confidential Fax Inboxes Maximum 10,000 Pages (2,000 jobs) Stored	Optional/Standard	Optional
Advanced Space	Communication Protocol: SMB or WebDAV Supported Client PC: Windows [*] 8.1/10 Concurrent Connections (Max.): SMB:64, WebDAV:3	Name	imagePASS-N2 V1.1 (Embedded)
Advanced Space available disc space	Standard:16 GB (With option: max. 480GB.)	Print Resolution (dpi)	1200 x 1200, 600 x 600
Advanced Space Features	Authentication for Advanced Space Log-in, Sort Function, Printing a PDF File with a Password, imageWARE Secure Audit Manager Support, Search, File Preview, Authentication Management, Open to public, URI TX, Backup/Restore	Page Description Language(s)	Adobe PS3, PCL6
		Memory	4GB (1 x 4GB)
SECURITY SPECIFICATIONS		Hard Disk Drive	500 GB SATA
Authentication and Access Control	User Authentication (Picture Login, Picture and PIN Login, Card Login, Username and Password Login, Function Level Login, Mobile Login), Department ID Authentication (Department ID and PIN Login, Function Level Login), uniFLOW Online Express (PIN Login, Picture Login, Picture and PIN Login, Card Login, Card and PIN Login, Username and Password Login, Department ID and PIN Login, Function Level Login), Access Management System (Access Control)	Processor Speed	Intel Pentium G4400 (3.3 GHz)
Document Security	Print Security (Secure Print, Encrypted Secure Print, Forced Hold Printing, uniFLOW Secure Print [™]), Receive Data Security (Confidential Fax Inbox Forwarding Received Documents Automatically), Scan Security (Encrypted PDF, Device Signature PDF/XPS, User Signature PDF/XPS, Adobe LiveCycle [®] Rights Management ES2.5 Integration), BOX Security (Mail Box Password Protected, Advanced Space Access Control), Send Data Security (Setting for requesting password input per transmission, Restricted E-mail/File send functions, Confirming FAX number, Allow/Restrict Fax Driver Transmissions, Allow/Restrict Sending from History, S/MIME Support), Document Tracking (Secure Watermark) ^{**Requires uniFLOW Online / uniFLOW}	System	FS350
Network Security	TLS 1.3, IPsec, IEEE802.1X authentication, SNMP V3.0, Firewall Functionality (IP/MAC Address Filtering), Dual Network Support (Wired LAN/Wireless LAN, Wired LAN/Wired LAN), Disabling Unused Functions (Enabling/Disabling Protocols/Applications, Enabling/Disabling Remote UI, Enabling/Disabling USB Interface), Communication Line Separation (G3 FAX, USB Port, Advanced Space, Scan and Send -Virus Concerns for E-mail Reception)	Fonts	PS: 138 Fonts PCL: 113 Fonts
Device Security	Protecting HDD Data (HDD Data Encryption (FIPS140-2 Validated), HDD Data Overwrite Erase, HDD Lock), Standard HDD Initialize, Trusted Platform Module (TPM), Job Log Conceal Function, Protecting MFD Software Integrity, Checking MFD Software Integrity (Verify System at Startup, Runtime Intrusion Detection), Comply IEEE2600.2 (Common Criteria Certification) (TBD) Administrator Password, Digital Certificate And Key Management, Audit Log, Cooperating with External Security Audit System (Security Information and Event Management), Image Data Logging, Security Policy Setting	Supported Operating Systems	Windows [*] 7 64 bit/Windows 8.1 64 bit/Windows10 64 bit/Windows Server 2008 R2 64 bit only/Windows Server 2012 64 bit only (Only Printer driver support)/ Windows Server 2012 R2 64 bit only/Windows Server 2016 R2 64 bit only/ MAC OS (10.11, 10.12, 10.13, 10.14)
Device Management and Auditing		Interface	2 x Ethernet (1000Base-T/100Base-TX/10Base-T), USB3.0 x 2 (Rear), USB2.0 x 4 (Rear)
ENVIRONMENTAL SPECIFICATIONS		Network protocols	TCP/IP (FTP, SMTP, POP, HTTP, SNMP, LDAP, SLP, SMB, LPD, IPP, WS-Discovery, Bonjour, Direct Mobile Printing, Port9100, SNT, 802.1X, DHCP, DNS, NTP)
Operating Environment	Temperature: 10 to 30 °C Humidity: 20 to 80 % RH (Relative Humidity)	Direct Print	PDF1.7, EPS, TIFF6, JDF1.4/JMF(Optional)
Power source	iR-ADV DX C7780i: 220-240V 50/60Hz 11A iR-ADV DX C7770i/C7765i: 220-240V 50/60Hz 10A	VDP	FreeForm v1, v2.1
		Fiery Print Controller Standard Features	Fiery Command WorkStation 6/Paper Catalog/Fiery Spot-On/Fiery Remote Scan/Fiery Hot Folders & Virtual Printers
		Fiery Print Controller Options	Fiery Impose/Fiery Compose/Fiery Impose and Compose/Productivity Package Web Activate (Include Fiery JDF)
		HW Platform	E400
		Base OS	Debian of Linux
		Power source	AC100-240V, 50Hz/60Hz, 3.0A (100V) - 1.3A (240V)
		Maximum Power consumption	47 W
		Dimensions (W x D x H)	285 x 93 x 295 mm
		Weight	Fiery unit only (with plate): 5 kg



TECHNICAL SPECIFICATIONS

imageRUNNER ADVANCE DX C7700 Series

PAPER SUPPLY OPTIONS

Paper Deck Unit-E1

Paper Capacity: 3,500 sheets (80 gsm)
 Paper Type: Thin, Plain, Recycled, Color, Heavy, Bond, Pre-punched, Letterhead
 Paper Size: A4, B5
 Paper Weight: 52 to 256 gsm
 Power Source: from the Main Unit
 Dimensions (W x D x H): 340 x 630 x 572 mm (attached to the main unit)
 Weight: Approx. 34 kg

POD Deck Lite-C1

Paper Capacity: 3,500 sheets (80 gsm)
 Paper Type: Thin, Plain, Recycled, Color, Heavy, Coated, Textured, Tracing, Bond, Transparency, Label, Pre-punched, Letterhead, Tab, Envelope*
 Paper Size: SRA3, A3, B4, A4, A4R, A5R, B5, B5R, Envelope (COM10 No10, Monarch, DL, ISO-C5), Custom size: 139.7 x 148.0 mm to 330.2 to 487.7 mm
 Paper Weight: 52 to 300 gsm
 Power Source: 220-240V/1.2A 50/60Hz
 Dimensions (W x D x H): 633 x 686 x 574 mm (attached to the main unit)
 Weight: Approx. 68 kg
 *Envelope Feeder Attachment-G1 is required.

OUTPUT OPTIONS*

Copy Tray-R2

Provides a simple tray for basic output needs.
 Capacity: 250/100 sheets (1-sided/2-sided, 80 gsm)
 Dimensions (W x D x H): 420 x 382 x 175 mm

Staple Finisher-AC1(External)

Tray Capacity (with 80gsm paper):
 Upper Tray: A4, A5, A5R, A6R, B5: 250 sheets
 SRA3, A3, A4R, B4, B5R: 125 sheets
 Envelope: 30 sheets
 Mid Tray: Same as upper tray
 Lower Tray: A4, A5, A5R, B5: 3,000 sheets
 SRA3, A3, A4R, B4, B5R: 1,500 sheets
 A6R: 250 sheets
 Envelope: Monarch: 30 sheets, COM10 No.10, DL, ISO-C5: 100 sheets
 Paper Weight:
 Upper Tray: 52 to 256 gsm
 Mid Tray: same as Upper tray
 Lower Tray: 52 to 300 gsm
 Staple Position: Corner, Double
 Staple Capacity:
 A4/B5: 65 sheets (52 to 90 gsm)
 A3/A4R/B4: 40 sheets (52 to 90 gsm)
 Eco Staple:
 A3/A4: 5 sheets (52 to 64 gsm)
 4 sheets (65 to 81.4 gsm)
 3 sheets (82 to 105 gsm)
 Staple On Demand: 65 sheets (52 to 90 gsm)
 Power supply: From the main unit
 Dimensions (W x D x H): 656 x 623 x 1,195 mm (when the extension tray and rotary tray are extended)
 Weight: Approx. 36 kg

Booklet Finisher-AC1 (External)

(Includes the above Staple Finisher-AC1 basic staple specifications.)
 Saddle Stitch paper size: A3, A4R, B4, Custom Size (195.0 x 270.0 mm to 304.8 x 457.2 mm)
 Saddle Stitch Staple Capacity: up to 20 sheets x 10 sets (52 to 81.4 gsm) (including 1 cover sheet up to 256 gsm)
 Non Staple Folded Bunch Capacity: up to 3 sheets (52 to 105 gsm)
 Power supply: From the main unit
 Dimensions (W x D x H): 656 x 623 x 1,195 mm (when the extension tray and rotary tray are extended)
 Weight: Approx. 60 kg

2/4 Hole Puncher Unit-A1

(Requires either the Staple Finisher-AC1 or Booklet Finisher-AC1)
 Two or Four Holes
 Acceptable Punch Paper Weight: 52 to 300 gsm
 Acceptable Punch Paper Size:
 Two holes A3, A4, A4R, A5, B4, B5, B5R
 Four holes A3, A4
 Power Source: From the finisher

4 Hole Puncher Unit-A1

(Requires either the Staple Finisher-AC1 or Booklet Finisher-AC1)
 Four Holes
 Acceptable Punch Paper Weight: 52 to 300 gsm
 Acceptable Punch Paper Size:
 Four holes A3, A4, A4R, A5, B4, B5, B5R
 Power Source: From the finisher

Document Insertion Unit-Q1

(Requires either the Staple Finisher-AC1 or Booklet Finisher-AC1)
 Number of trays: 1
 Tray Capacity: Up to 100 Sheets (80 gsm)
 Acceptable Paper Type: Thin, Plain, Recycled, Color, Heavy, Coated, Textured, Bond, Letterhead, Tab
 Acceptable Paper Sizes: SRA3, A3, A4, A4R, B4, B5, B5R
 Acceptable Paper Weight: 60 to 256 gsm
 Power Source: 100-240V/50/60Hz 1.0A
 Dimensions (W x D x H): 247x 679 x 1,242 mm (attached to the device: width excluding document tray)
 Weight: Approx. 40 kg

Document Insertion/Folding Unit-K1

(Requires either the Staple Finisher-AC1 or Booklet Finisher-AC1)
 Number of trays: 1
 Supported Folding Type: Z-Fold, C-Fold
 Acceptable Paper Type:
 Insertion Unit: Thin, Plain, Recycled, Color, Heavy, Coated, Textured, Bond, Letterhead, Tab
 Z-Fold/C-Fold: Thin, Plain, Recycled, Color
 Acceptable Paper Sizes:
 Insertion Unit: SRA3, A3, A4, A4R, B4, B5, B5R
 Z-Fold: A3, A4R, B4
 C-Fold: A4R
 Acceptable Paper Weight:
 Insertion Unit: 60 to 256 gsm
 Z-Fold/C-Fold: 60 to 105 gsm
 Tray Capacity (with 80 gsm paper):
 Insertion: Up to 100 Sheets
 Z-Fold*: A3, B4: 30 sheets
 A4R: 10 sheets
 C-fold: A4R: 40 sheets
 *Z-Fold output to the Staple Finisher-AC1 or Booklet Finisher-AC1
 Power Source: 100-240V/50/60Hz 1.0A
 Dimensions (W x D x H): 247 x 679 x 1,242 mm (attached to the device: width excluding document tray)
 Weight: Approx. 76 kg

HARDWARE ACCESSORIES

Card Readers

MiCARDPLUS FOR ULM
 Copy Card Reader-F1
 Copy Card Reader Attachment-A4

Others

Utility Tray-B1
 Printer Cover-H2
 Tab Feeding Attachment-F1
 Upright Control Panel-J1
 Numeric Keypad-A1
 Finisher Jogger Kit-A1
 Envelope Feeder Attachment-F1
 Envelope Feeder Attachment-G1

SECURITY OPTIONS

Data Security

HDD Mirroring Kit-J1
 2.5inch/250GB HDD-N1
 2.5inch/1TB HDD-P1

SYSTEM AND CONTROLLER OPTIONS

Print Accessories

PCL International Font Set-A1

Barcode Printing

Barcode Printing Kit-D1

Efi-Fiery Based Controller

imagePASS-N2 V1.1

Efi-fiery Based Controller Options

Fiery Impose
 Fiery Compose
 Fiery Impose and Compose

System Accessories

Copy Control Interface Kit-A1
 Connection Kit-A2 for Bluetooth LE
 Serial Interface Kit-K3
 NFC Kit-E1

Fax Accessories

Super G3 FAX Board-AS1
 Super G3 2nd Line Fax Board-AS1
 Remote Fax Kit-A1
 IP FAX Expansion Kit-B1

OTHER OPTIONS

Accessibility Accessories

ADF Access Handle-A1
 Voice Guidance Kit-G1
 Voice Operation Kit-D1

Staple Cartridge

Staple-N1
 Staple-P
 Staple Cartridge-X1
 Staple Cartridge-Y1

Software & Solutions



Certifications and compatibility



Canon Ireland
 3006 Lake Drive
 Citywest, Saggart
 Co. Dublin, Ireland
 Telephone No: 01 2052400
 Facsimile No: 01 2052525
 canon.ie

Canon (UK) Ltd
 5 The Square
 Stockley Park
 Uxbridge
 UB11 1ET
 Tel: 01895 648 000
 www.canon.co.uk

Canon Inc.
 canon.com
 Canon Europe
 canon-europe.com
 English edition
 © Canon Europa N.V., 2020

