



i-SENSYS X C1127i Series

ENHANCE YOUR FLEET OF DOCUMENT WORKFLOW SOLUTIONS

High quality, compact A4 colour multifunction printers with cloud connectivity



PRODUCTIVITY



**CONTROL AND
MAINTENANCE**



CONNECTIVITY



COMPACT DESIGN



SECURITY

Canon

i-SENSYS X C1127i Series

PRODUCTIVITY

- Large, responsive touchscreen display
- Easy customisation of device functions
- Double-sided printing as standard
- One Pass Scan for fast digitisation of paper documents

SECURITY

- Verify System at Start-up protects device functionality
- User Authentication secures device access
- Secure Print function prevents unauthorised viewing of printed material
- Scan and send documents securely with optional Encrypted PDF mode

CONNECTIVITY

- Remote device set-up and control with the Canon Print Business App
- Compatible with Mopria, Apple Air Print and Google Cloud Print
- Near field communication (NFC) support (C1127iF only)

COMPACT DESIGN

- Solve cost and space limitations
- Compact devices feature an all-in-one toner cartridge
- Flexible configuration integrates into any office environment
- Easy access to replace consumables

CONTROL AND MAINTENANCE

- Remote diagnostics and assistance help minimise downtime
- Cloud and server-based software options centralise fleet control
- Access printer control functions via PC or mobile devices
- Easy toner replacement

QUICK FACTS

i-SENSYS X C1127i

- Print, Copy, Scan and Send
- 5-inch/12.7cm TFT LCD touchscreen
- Print Speed: 27ppm (A4)
- Print resolution: up to 1,200 x 1,200 dpi
- Automatic double-sided printing
- Scan speed: up to 47ipm
- Network, Wi-Fi, USB and QR code connectivity
- Max paper input capacity: 850 sheets

i-SENSYS X C1127iF

- Print, Copy, Scan, Send and Fax
- 5-inch/12.7cm TFT LCD touchscreen
- Print Speed: 27ppm (A4)
- Print resolution: up to 1,200 x 1,200 dpi
- Automatic double-sided printing
- Scan speed: up to 47ipm
- Network, Wi-Fi, USB, QR code and NFC connectivity
- Max paper input capacity: 850 sheets

SERVICES

CORE

Perform routine office operations safely and with ease, utilising embedded software including uniFLOW Online Express and other available services offering complete device maintenance and support



HARDWARE



SOFTWARE



SERVICES

BESPOKE

Choose a tailored service to suit your business needs by removing unnecessary print management burdens. Consult with Canon experts about your specific requirements to find a fitting Print Managed Services option

ENHANCED

Expand cloud capabilities with uniFLOW Online, Canon's all-in-one print management system

TECHNICAL SPECIFICATIONS

i-SENSYS X C1127i Series

Machine type	Colour Laser All-In-One	FAX memory	Up to 512 pages ⁵
Available functions	i-SENSYS X C1127iF: Print, Copy, Scan and Fax i-SENSYS X C1127i: Print, Copy, Scan	Speed dials	Up to 281 dials
PRINTER		Group dials/destinations	Max. 299 dials / Max. 299 destinations
Print speed	Single sided : Up to 27 ppm (A4) Up to 49 ppm(A5-Landscape) Double sided : Up to 24.5 ipm (A4)	Sequential broadcast	Max. 310 destinations
Printing method	Colour laser beam printing	Memory backup	Permanent fax memory backup (Backup with flash memory)
Print resolution	1200 x 1200 dpi	Double sided faxing	Yes (Transmit and Receive)
Warm-up time	Approx. 13 seconds or less from power on	Other features	Fax Forwarding, Dual Access, Remote Reception, PC Fax (TX only) DRPD, ECM, Auto Redial, Fax Activity Reports, Fax Activity Result Reports, Fax Activity Management Reports
First Print Out Time	Colour approx.: 8.6 seconds or less Mono approx.: 7.7 seconds or less	MEDIA HANDLING	
Printer languages	UFRII, PCL 5c, PCL6, Adobe® PostScript3	Scanner type	Platen, 2-sided ADF (single pass)
Fonts	93 PCL fonts 136 PostScript fonts	Scanner type	250-sheet cassette 50-sheet multi-purpose tray 50-sheet ADF
Print margins	5 mm-top, bottom, left and right 10 mm-top, bottom, left and right (Envelope)	Paper input (Standard)	550-sheet cassette
Toner saver mode	Yes	Paper input (Option)	150-sheet
Advanced printing features	i-SENSYS X C1127iF: Secure Print Print from USB memory key (JPEG/TIFF/PDF) Barcode Print ² Touch & Print (NFC) Google Cloud Print Ready iOS: AirPrint, Canon PRINT Business app Android; Mopria certified, Canon Print Service Plug-in, Canon PRINT Business app i-SENSYS X C1127i: Secure Print Print from USB memory key (JPEG/TIFF/PDF) Barcode Print ² Google Cloud Print Ready iOS: AirPrint, Canon PRINT Business app Android; Mopria certified, Canon Print Service Plug-in, Canon PRINT Business app	Paper output	Plain paper, Recycled paper, Heavy Paper, Thin paper, Colour paper, Coated paper, Label, Post card, Envelope
COPIER		Media types	Platen paper, Recycled paper, Heavy Paper, Thin paper, Colour paper, Coated paper, Label, Post card, Envelope
Copy speed	Single sided (A4): Up to 27 ppm Double sided (A4): Up to 21.9 ipm	Media sizes	Cassette (Standard): A4, A5, A5 (Landscape), B5, Legal, Letter, Executive, Statement, OFFICIO, B-OFFICIO, M-OFFICIO, GLTR, GLGL, Foolscap, 16K, Post card, Envelop (COM10, DL, C5), Custom sizes: Min. 100 x 148 mm Max. 216.0 x 355.6 mm.
First Copy Output Time (FCOT)	ADF (A4): Colour Approx. 12.0 seconds or less Mono Approx. 10.2 seconds or less Platen (A4): Colour Approx. 11.3 seconds or less Mono Approx. 9.8 seconds or less	Media weights	Multi-purpose tray: A4, A5, A5 (Landscape), B5, Legal, Letter, Executive, Statement, OFFICIO, B-OFFICIO, M-OFFICIO, GLTR, GLGL, Foolscap, 16K, Post card, Indexcard, Envelope (COM10, DL, C5, Monarch), Custom sizes: Min 76.2 x 127 mm Max. 216.0 x 355.6 mm.
Copy resolution	Up to 600 x 600 dpi	Double sided printing	Cassette (Optional): A4, A5, B5, Legal, Letter, Executive, Statement, OFFICIO, B-OFFICIO, M-OFFICIO, GLTR, GLGL, Foolscap, 16K, Post card, Envelop (COM10, DL, C5), Custom sizes: Min. 100 x 148 mm Max. 216.0 x 355.6 mm.
Copy modes	Text/Photo/Map (Default),Text/Photo/Map (quality), Printed Image, Text	Interface & SOFTWARE	
Double sided copying	2-sided to 2-sided (Automatic)	Interface type	USB 2.0 Hi-Speed, 10BASE-T/100BASE-TX/1000Base-T, Wireless 802.11b/g/n, Wireless Direct Connection
Multiple copy	Up to 999 copies	Operating System compatibility	Windows® 10 / Windows® 8.1 / Windows® 7 / Server® 2016 / Server® 2012R2 / Server® 2012 / Server® 2008R2 / Server® 2008 / Mac OS X version 10.9.5 & up / Mac OS 10.15 & up Linux®
Reduction / Enlargement	25-400% in 1% increments	Network Protocol	Print: LPD, RAW, WSD-Print (IPv4,IPv6) Scan: Email, SMB, WSD-Scan(IPv4, IPv6), FTP-Scan, iFAX TCP/IP Application Services: Bonjour(mDNS), HTTP, HTTPS, POP before SMTP (IPv4,IPv6) DHCP, ARP+PING, Auto IP, WINS (IPv4) DHCPv6 (IPv6) Management: SNMPv1, SNMPv3 (IPv4,IPv6) Security (wired): IP/Mac address filtering, IEEE802.1X, SNMPv3, SSL (HTTPS, IPPS) Security (wireless): Infrastructure Mode: WEP(64/128 bit), WPA-PSK(TKIP/AES), WPA2-PSK(TKIP/AES) Access Point Mode: WPA2-PSK(AES)
Other features	Frame Erase, Collate, 2 on 1, 4 on 1, ID card copy		
SCANNER			
Type	Colour		
Scan resolution	Optical: Up to 600 x 600 dpi Enhanced: Up to 9600 x 9600 dpi		
Scan speed	Single sided mono: 27ipm (300x600dpi) Single sided colour: 14ipm (300x600dpi) Double sided mono: 47ipm (300x600dpi) Double sided colour: 27ipm (300x600dpi)		
Colour scanning depth	24 bit/24 bit (input/output)		
Greyscales	256 levels		
Compatibility	TWAIN , WIA, ICA		
Max. scan width	216mm		
Scan to E-mail	TIFF/JPEG/PDF/Compact PDF/Searchable PDF/ Encrypted PDF ³ /PDF (Digital signature) ³		
Scan to PC	TIFF/JPEG/PDF/Compact PDF/Searchable PDF/ Encrypted PDF ³ /PDF (Digital signature) ³		
Scan to USB memory key	TIFF/JPEG/PDF/Compact PDF/Searchable PDF/ Encrypted PDF ³ /PDF (Digital signature) ³		
Scan to FTP	TIFF/JPEG/PDF/Compact PDF/Searchable PDF/ Encrypted PDF ³ /PDF (Digital signature) ³		
Scan to Cloud	TIFF/JPEG/PDF/PNG ⁴		
iFAX	ITU-T.37		
FAX	i-SENSYS X C1127iF only		
Modem speed	33.6 Kbps (Up to 3 seconds/page ⁵)		
Receive mode	Fax only, Fax/Tel Auto Switch, Answer Mode, Manual		
Fax resolution	Standard: 200 x 100 dpi Fine: 200 x 200 dpi Super fine: 200 x 400 dpi Ultra fine: 400 x 400 dpi		

TECHNICAL SPECIFICATIONS

i-SENSYS X C1127i Series

Software and printer management

MF Scan Utility, Remote User Interface (RUI), Department ID Management, Toner Status Tool, iW Enterprise Management Console Server-based software for centralised management of a fleet of devices
eMaintenance: embedded RDS allows remote eMaintenance services such as meter capture, automatic consumables management and remote diagnostics.
Universal Log-in Manager / uniFLOW online / uniFLOW online Express / uniFLOW Compatibility Application Library

GENERAL FEATURES

Recommended Monthly Print Volume

750 - 4,000 pages per month

Duty cycle

Max. 50,000 pages per month⁷

Processor Speed

800MHz x 2

Memory

1GB

Control panel

12.7 cm LCD Colour Touch Screen

Dimensions with trays (W x D x H)

471 mm x 469 mm x 460 mm

Installation space (W x D x H)

671 mm x 1,312 mm x 966 mm

Weight

Approx. 24.5 Kg

Operating environment

Temperature: 10 to 30°C (50 to 86°F)
Humidity: 20 to 80% RH (no condensation)

Power Source

220-240V(±10%) 50/60Hz (±2Hz)

Power Consumption

Maximum: Approx. 1,390 W
Active printing: Approx. 530W
Standby: Approx. 18.0 W
Sleep mode: Approx. 0.7 W
Typical Electricity Consumption (TEC): 0.31 kWh/week¹⁰

For detailed information relating to Lot26 regulation, please go to: http://www.canon-europe.com/For_Work/Lot26/index.aspx

Noise Levels

Sound Pressure⁸ :
i-SENSYS X C1127iF
Active: Simplex 48 dB / Duplex 49 dB
Standby: 26 dB
i-SENSYS X C1127i
Active: Simplex 48 dB / Duplex 50 dB
Standby: 28 dB

Sound Power⁹:
i-SENSYS X C1127iF
Active: Simplex 62 dB or less / Duplex 63 dB or less
Standby: 42dB or less
i-SENSYS X C1127i
Active: Simplex 63dB or less / Duplex 64 dB or less
Standby: 42dB or less

CONSUMABLES

Cartridges

TONER T09 Black (7,600 pages⁹)
TONER T09 Cyan (5,900 pages⁹)
TONER T09 Magenta (5,900 pages⁹)
TONER T09 Yellow (5,900 pages⁹)

ACCESSORIES/ OPTIONS

Items

i-SENSYS X C1127iF:
CST.Feeding Module-AF1 (550-sheet cassette)
TEL 6 Kit Long Cord (Telephone handset)
Barcode Printing Kit-E1E
MiCard Multi (Card reader for identification with RFID or magnetic cards with uniFLOW)
Micard Plus (Card reader for identification with RFID or magnetic cards with uniFLOW)
MiCard Attachment Kit-B1
Send PDF Security Feature Set-E1

i-SENSYS X C1127i:
CST.Feeding Module-AF1 (550-sheet cassette)
Barcode Printing Kit-E1E
MiCard Multi (Card reader for identification with RFID or magnetic cards with uniFLOW)
Micard Plus (Card reader for identification with RFID or magnetic cards with uniFLOW)
MiCard Attachment Kit-B1
Send PDF Security Feature Set-E1

Notes:

- ^[1] Commands supported only. Third party driver or direct printing from application required.
- ^[2] Accessory Barcode Printing Kit-E1E - is required
- ^[3] Accessory - Send PDF Security Feature Set-E1 is required
- ^[4] Scan by MF Scan Utility or Canon PRINT Business app
- ^[5] Based on ITU-T Standard Chart No. 1
- ^[6] Web distribution only. Linux support printing only.
- ^[7] Duty cycle is defined as the maximum number of printed pages for a single peak month. Any usage above the recommended duty cycle may decrease the life of the product
- ^[8] Declared noise emission in accordance with ISO 9296
- ^[9] Based on ISO/IEC 19798
- ^[10] As per US ENERGY STAR® version3.0.

Software & Solutions



Compatibility



Canon Ireland
3006 Lake Drive
Citywest, Saggart
Co. Dublin, Ireland
Telephone No: 01 2052400
Facsimile No: 01 2052525
canon.ie

Canon (UK) Ltd
5 The Square
Stockley Park
Uxbridge
UB11 1ET
Tel: 01895 648 000
www.canon.co.uk

Canon Inc.
canon.com
Canon Europe
canon-europe.com
English edition
© Canon Europa N.V., 2020