ENJOY QUICK AND EASY PRINTING FROM A COMPACT A4 SINGLE FUNCTION

Compact yet powerful A4 colour single-function devices, delivering all the essential features you need for reliable printing.

COLOUR DEVICE.

imageFORCE C1333P



MAXIMISED PRODUCTIVITY

Work efficiently and save time with fast print speed. Quick machine warm up and first printout time means you'll get the output you need in seconds.

360-DEGREE SECURITY

Keep documents, devices, and network safe with advanced security designed to simplify protection. Built-in tools make it easy to manage settings and reduce reliance on IT support.

IMPROVE SUSTAINABILITY
EFFORTS

Make a conscious effort to help the environment with devices that are made up of recycled plastic. Low energy use and light device weight helps to reduce carbon footprint.

SMOOTH USER EXPERIENCE

An intuitive user interface and QR code guiding users to an online manual helps with seamlessly carrying out print jobs. Self-maintenance is simplified via an all-in-one toner cartridge while the compact size of devices means you can place devices anywhere within small working environments.

Canon

TECHNICAL SPECIFICATIONS

imageFORCE C1333P

MAIN UNIT		
Machine Type	A4 Color Laser Beam Printing	
Core Functions	Print	
Processor	1.2GHz Single Core Processor	
Control Panel	5" LCD Colour Touch Screen	
Memory	RAM: 1.0GB	
Storage	eMMC 4GB	
Interface Connection	NETWORK Standard: 1000Base-T/100Base-TX/10Base-T Wireless LAN (IEEE 802.11b/g/n) OTHERS Standard: USB 2.0 (Host) x 2, USB 2.0 (Device) x 1	
Paper Supply Capacity (A4, 80gsm)	Standard: 250 sheets 50-sheet Multi-purpose tray x 1 550-sheet Paper cassette x 1 Maximum: 850 sheets (with 1 x Paper Feeder PF-K1)	
Paper Output Capacity (A4, 80gsm)	150 sheets	
Supported Media Types	Thin, Plain, Recycled, Color, Heavy, Bond, Label, Pre-Punched, Letterhead, Envelope	
Supported Media Sizes	Multi-purpose tray: Standard size: A4, A5, A5R, A6, B5 Custom size: 76.0 x 127.0 mm to 216.0 x 356.0 mm Envelopes: COM10 No.10, Monarch, DL, ISO-C5 Envelope custom size: 76.0 x 127.0 mm to 216.0 x 356.0 mm Paper Cassette: Standard size: A4, A5, A5R, A6, B5 Custom size: 98.0 x 148.0 mm to 216.0 x 356.0 mm	
Supported media weights	Multi-purpose tray: 60 to 176 gsm (Up to 200gsm with Coated Paper) Paper Cassette: 60 to 163 gsm (Up to 200gsm with Coated Paper) Duplex: 60 to 200 gsm	
Warm-up Time	Approx. 19.4 seconds or less from power on From Sleep Mode: 1.7 Seconds or less	
Dimensions (W x D x H)	425 x 427 x 380 mm	
Installation Space (W x D)	625 x 1117 mm	

PRINT SPECIFICATIONS		
Print Speed (BW and CL)	1-sided: Up to 33 ppm (A4), Up to 44.9 ppm (A5R), Up to 60 ppm (A5) 2-sided: Up to 29.5 ipm (A4)	
Print Resolution (dpi)	Up to 1,200×1,200	
Page description languages	Standard: UFR II, PCL6, PCL5*, Adobe® PostScript®3TM	
	*Commands supported only. Third party driver or direct printing from application required.	

Weight* *including regular toner	Approx. 17.7 Kg
Direct Print	Supported file types: PDF, TIFF/JPEG (From USB Memory)
Printing from mobile and cloud	AirPrint, Mopria, IPP Everywhere, Canon PRINT, uniFLOW Online, Universal Print
OS Standard Printing	Android/Windows® 10/Windows® 11/Chrome OS/macOS (11.2.2 or later) /iOS /iPadOS
Fonts	PS fonts: 136 Roman PCL fonts: 93 Roman, Barcode fonts ¹
	*1 Optional Barcode Printing Kit-D1 is required.
Print Features	Secured Print, Encrypted Secured Print, Header/Footer, Page Layout, Two-sided Printing, Mixed Paper Sizes/Orientations, Toner Reduction, Poster Printing, Print Date
Operating System	UFRII: Windows® 10/11/Server2016/Server2019/ Server2022/Server2025, macOS (10.15 or later) PCL: Windows® 10/11/Server2016/Server2019/ Server2022/Server2025 PS: Windows® 10/11/Server2016/Server2019/ Server2022/Server2025, macOS (10.15 or later) PPD: Windows® 10/11, macOS (10.15 or later)
-	As of Jun. 2025
SECURITY SPECIFICATIONS	
Authentication and Access Control	Department ID Authentication (Department ID and PIN Login, Function Level Login), uniFLOW Online/uniFLOW*1(PIN Login, Card Login, Card and PIN Login)
	*1 Optional
Document Security	Print Security (Secure Print, Encrypted Secure Print, uniFLOW Secure Print*1), *1 Optional
Network Security	TLS 1.3, IPSec (FIPS140-3), IEEE802.1X authentication, SNMPv3, Firewall Functionality (IP/MAC Address Filtering), WPA3 support (Wi-Fi), Enabling/Disabling (Network Applications, Remote UI, USB Interface), USB Port separation from LAN
Device Security	Job Log Conceal Function, Protecting MFP Software Integrity: Verify System at Startup (NIST SP800-193: Protection), Checking MFP Software Integrity & Platform Firmware Resiliency: Automatic System Recovery (NIST SP800-193: Recovery)
Device Management and Auditing	Administrator Password, Digital Certificate And Key Management, Cooperating with External Security Audit System (Security Information and Event Management), Security Policy Setting
ENVIRONMENTAL SPECIFICATIONS	
Operating Environment	Temperature: 10 to 30 °C Humidity: 20 to 80 % RH (Relative Humidity/ No condensation)
Power source	220-240V(±10%) 50/60Hz (±2Hz)
Power consumption	Maximum: Approx. 1,380 W Active printing: Approx. 700W Sleep mode: Approx. 1.0 W Typical Electricity Consumption (TEC): 0.31 kWh/week (230V) For detailed information relating to Lot26 regulation, please go to: https://www.canoneurope.com/business/lot26/



TECHNICAL SPECIFICATIONS

imageFORCE C1333P

Noise Levels	Sound Pressure: Active: 50dB (BW), 51dB (CL) Standby: 25 dB Sound Power: Active: 65dB or less Standby: 36dB or less	
Standards	Blue Angel	
CONSUMABLES		
Toner Cartridges	TONER T12 Black (7,400 pages*) TONER T12 Cyan (5,300 pages*) TONER T12 Magenta (5,300 pages*) TONER T12 Yellow (5,300 pages*)	
	*Based on ISO/IEC 19798	
SOFTWARE AND PRINTER MANAGEMENT		
Tracking and reporting	uniFLOW Online	
Remote management tools)	iW Enterprise Management Console Monitoring Service	
Optimisation tools	Canon Driver Configuration Tool Application Library	
	PAPER SUPPLY OPTIONS	
PAPER FEEDER PF-KI	Paper Capacity: 550 sheets (80 gsm) Paper Type: Thin, Plain, Recycled, Color, Heavy, Bond, Label, Pre-Punched, Letterhead Paper Size: A4, A5, A5R, A6, B5 Custom size: 100.0 x 148.0 mm to 216.0 x 356.0 mm Paper Weight: 60 to 163 gsm (Up to 200gsm with Coated Paper)	
HARDWARE ACCESSORIES		
Others	MiCard Attachment Kit-B1	
SYSTEM & CONTROLLER OPTIONS		
Print Accessories	Barcode Printing Kit-E1E	



TECHNICAL SPECIFICATIONS

imageFORCE C1333P





Certifications and compatibility





Canon Inc. Canon.com

Canon Europe canon-europe.com

English Edition© Canon Europa N.V. 2025

