

RELIABLE A4 COLOUR PRINT AND SCAN PERFORMANCE FOR BUSY, MODERN WORKPLACES.

imageFORCE C1700 Series

Power everyday productivity with intuitive workflows, vibrant colour output and advanced security in a compact A4 device.



ENHANCED PRODUCTIVITY

Scan, print, and process documents faster, making information searchable, shareable, and more valuable to your business. Take on more diverse print requirements with expanded media and output capacity, helping teams work more efficiently.

SMOOTH USER EXPERIENCE

An intuitive and easy-to-use 7-inch user interface with clear icons helps simplify operations across print and scan workflows. Easily access an online manual via QR code for assistance.

ROBUST SECURITY


Keep your documents, devices and network safe with advanced security, including validated encryption, secure access controls and encrypted data transfer. AI machine learning-supported security settings help simplify protection and reduce configuration effort.

IMPROVED SUSTAINABILITY

Support sustainability goals with increased use of recycled materials, including plastics and steel. Built on a unique welded frame, ensuring strength and long-term durability and reliability.

imageFORCE C1700 Series

MAIN CONFIGURATION OPTIONS



This flat configuration is for illustration purpose only. For a complete list of options and the exact compatibility relationships, please refer to the [online product configurator](#).

TECHNICAL SPECIFICATIONS

imageFORCE C1700 Series

MAIN UNIT	
Machine type	A4 Colour Laser Multifunctional
Core functions	Print, Copy, Scan, Send and optional Fax
Processor	1.6GHz Dual Core Processor and 800MHz Single Core Processor
Control Panel	7" LCD Colour Touch Screen
Memory	RAM: 2.5GB
Storage	eMMC 64GB
Interface Connection	NETWORK Standard: 1000Base-T/100Base-TX/10Base-T Optional: Wireless LAN (IEEE 802.11a/b/g/n) OTHERS Standard: USB 2.0 (Host) x 2, USB 2.0 (Device) x 1
Paper Supply Capacity (A4, 80gsm)	Standard: 650 sheets 100-sheet Multi-purpose tray x 1 550-sheet Paper cassette x 1 Maximum: 2,300 sheets (with 2 x Cassette Module-AL1 + 1 x Cassette Feeding Unit-BA1)
Paper output capacity (A4, 80gsm)	400 sheets
Supported Media Types	Multi-purpose tray: Thin, Plain, Recycled, Color, Heavy, Bond, Label, Letterhead, Coated, Envelope Paper Cassette: Thin, Plain, Recycled, Color, Heavy, Bond, Label, Letterhead, Coated, Pre-punched
Supported Media Sizes	Multi-purpose tray: Standard size: A4, A5, A5R, A6, B5, B6 Custom size: 76.0 x 127.0 mm to 216.0 x 355.6 mm Envelopes: COM10, NO10, Monarch, DL, ISO-C5 Envelope custom size: 76.0 x 127.0 mm to 216.0 x 355.6 mm Paper Cassette: Standard size: A4, A5, A5R, A6, B5, B6 Custom size: 101.6 x 148.0 mm to 216.0 x 355.6 mm
Supported media weights	Multi-purpose tray: 60 to 216 gsm Paper Cassette: 60 to 200 gsm Duplex: 60 to 200 gsm
Warm-up Time	Quick Start-up 4 Seconds or Less* From Sleep Mode: 10 seconds or less From Power On: 10 seconds or less** *Time from device power-on to when key operations can be performed on the touch panel display. **Time from device power-on, until copy ready (not print reservation)
Dimensions (W x D x H)	500 mm x 603 mm x 645 mm

Installation Space(W x D)	770 mm x 847 mm
Weight	Approx. 44kg including toner
PRINT SPECIFICATIONS	
Print Speed	imageFORCE C1743 1-sided: Up to 43 ppm (A4), Up to 60 ppm (A5-Landscape), Up to 69 ppm (A5, A6) 2-sided: Up to 43 ipm (A4), Up to 52ipm (A5-Landscape) imageFORCE C1752 1-sided: Up to 52 ppm (A4), Up to 72 ppm (A5-Landscape), Up to 84 ppm (A5), Up to 69ppm (A6) 2-sided: Up to 52 ipm (A4), Up to 69 ipm (A5-Landscape)
Print Resolution (dpi)	Up to 1,200 x1,200
Page description languages	Standard: UFR II, PCL6, PCL5*, Adobe® PostScript®3TM *Commands supported only. Third party driver or direct printing from application required.
Direct Print	Supported file types: PDF, TIFF/JPEG, XPS (From USB Memory, Network Place)
Mobile / Cloud Printing	AirPrint, Mopria, IPP Everywhere, Canon PRINT, Canon Print Assistant, uniFLOW Online, Universal Print by Microsoft
OS Standard Printing	Android, Windows® 10/11, Chrome OS, macOS (11.2.2 or later), iOS (15.2 or later) /iPadOS
Fonts	PS fonts: 136 Roman PCL fonts: 93 Roman, 10 Bitmap fonts, 2 OCR fonts, Andalé Mono WT J/K/S/T ¹ (Japanese, Korean, Simplified and Traditional Chinese) , Barcode fonts ² *1 Requires optional PCL INTERNATIONAL FONT SET-A1 *2 Require optional BARCODE PRT KIT-D1
Print Features	Secure Print, Secure Watermark, Header/Footer, Page Layout, Two-sided Printing, Mixed Paper Sizes/ Orientations, Toner Reduction, Poster Printing, Forced hold printing, Print Date, Scheduled Printing, Printing Using a Virtual Printer
Operating System	UFR II: Windows® 10/11/Server2016/Server2019/Server2022/Server2025, macOS (11.7 or later) PCL: Windows® 10/11/Server2016/Server2019/Server2022/Server2025 PS: Windows® 10/11/Server2016/Server2019/Server2022/Server2025, macOS (11.7 or later) PPD: Windows® 10/11, macOS (11.7 or later) As of Oct. 2025

TECHNICAL SPECIFICATIONS

imageFORCE C1700 Series

COPY SPECIFICATIONS	
Copy Speed	imageFORCE C1743 1-sided: Up to 43 ppm (A4), Up to 60 ppm (A5-Landscape), Up to 69 ppm (A5, A6) 2-sided: Up to 43 ipm (A4), Up to 52ipm (A5-Landscape) imageFORCE C1752 1-sided: Up to 52 ppm (A4), Up to 72 ppm (A5-Landscape), Up to 84 ppm (A5), Up to 69ppm (A6) 2-sided: Up to 52 ipm (A4), Up to 69 ipm (A5-Landscape)
First-Copy-Out Time	imageFORCE C1743 Platen: Approx. 6.2 seconds or less (BW), Approx. 6.8 seconds or less (CL) imageFORCE C1752 Platen: Approx. 5.5 seconds or less (BW), Approx. 5.9 seconds or less (CL)
Copy resolution (dpi)	600 x 600
Multiple Copies	Up to 9,999 copies
Copy Density	Automatic or Manual (9 Levels)
Magnification	Variable zoom: 25% to 400% (1% Increments)
Copy Features	Preset R/E Ratios by Area, Two-Sided, Density Adjustment, Original Type Selection, Interrupt Mode, Two-sided Original, Sort, Job Build, N on 1, Sharpness, Erase Frame, Copy ID Card, Skip Blank Page, Reserved copy, Copy Sample
SCAN SPECIFICATIONS	
Type	Single-pass Duplexing Automatic Document Feeder [2-sided to 2-sided (Automatic)]
Document Feeder Paper Capacity (80 gsm)	up to 100 Sheets
Document Feeder acceptable paper weight	Platen: Sheet, Book Document Feeder media weight : 1-sided scanning: 42 to 128 gsm (BW), 64 to 128 gsm (CL) 2-sided scanning: 50 to 128 gsm (BW), 64 to 128gsm (CL)
Supported media sizes	Platen scanning size: up to 216 x 355.6 mm Document Feeder media size: A4, A5R, A6, B5 Custom size: 48.0 x 128.0 mm to 216.0 x 355.6 mm
Scan Speed (ipm: A4)	DADF: 1-sided Scanning: 95/95 (300 dpi, send), 50/95 (600 dpi, copy) 2-sided Scanning: 190/190 (300 dpi, send), 140/100 (600 dpi, copy)

Scan Resolution (dpi)	600 x 600
Pull Scan Specifications	Color Network ScanGear2. For both TWAIN and WIA
Scan Method	Push Scan, Pull Scan, Scan to Network, Scan to USB Memory Key, Scan to Mobile, Scan to cloud (uniFLOW Online)
SEND SPECIFICATIONS	
Destination	Standard: E-mail/Internet FAX (SMTP*), SMB3.0, FTP, SFTP, FTPS, WebDAV, Mail Box Optional: Super G3 FAX * Available OAuth 2.0 authentication method on Microsoft 365 and Google Workspace
Address Book	LDAP (2000)/Local (1600)/Speed dial (200)
Communication protocol	File: FTP (TCP/IP), SFTP (TCP/IP), FTPS (TCP/IP), SMB3.1.1 (TCP/IP), WebDAV E-mail/I-Fax: SMTP, POP3
File Format	Standard: TIFF, JPEG*, PDF (Compact, Searchable, PDF/A-1a, PDF/A-1b, PDF/A-2a, PDF/A-2b, PDF/A-2u, PDF/A-3a, PDF/A-3b, PDF/A-3u, PDF Encrypted) XPS (Compact, Searchable), PDF/XPS (Device Signature), Office Open XML (PowerPoint, Word) Optional: PDF (Trace&Smooth), PDF/XPS (User Signature) *Single page only
Universal Send Features	Original Type Selection, Two-sided Original, Density Adjustment, Sharpness, Erase Frame, Job Build, Delayed Send, Preview, Job Done Notice, File Name, Subject/Message, Reply-to, E-mail Priority, TX Report, Original Content Orientation, Skip Blank Originals
FAX SPECIFICATIONS	
Optional / Standard	Optional
Maximum Number of Connection Lines	1
Modem Speed	Super G3: 33.6 kbps G3: 14.4 kbps
Compression Method	MH, MR, MMR, JBIG
Resolution (dpi)	400x400 (Ultra Fine), 200x400 (Super Fine), 200x200 (Fine), 200x100 (Normal)
Sending/Receiving Size	Sending: A4, A5R*, A6*, B5* Receiving: A4, A5, A5R, B5 * Sent as A4
FAX memory	Up to 30,000 pages
Group dials/destinations	Max. 199 dials
Sequential broadcast	Max. 256 addresses

TECHNICAL SPECIFICATIONS

imageFORCE C1700 Series

Memory backup	Yes
Fax Features	Sender's Name (TTI), Direct Send, Delayed Send, Preview, Finished Stamp, Job Done Notice, TX Report, Interrupt Transmission, Sequential Broadcasting, Password/Subaddress Sending, Confidential Mailbox
SECURITY SPECIFICATIONS	
Authentication and Access Control	User Authentication (Picture Login, Picture and PIN Login, Card Login, Username and Password Login, Function Level Login, Mobile Login), Department ID Authentication (Department ID and PIN Login, Function Level Login), uniFLOW Online (PIN Login, Picture Login, Picture and PIN Login, Card Login, Card and PIN Login, Username and Password Login, Department ID and PIN Login, Function Level Login), Access Management System (Access Control), Microsoft Entra ID (PIN Login, Card Login), Two-Factor Authentication at LUI/RUI, Access Management System (Access Control)
Network Security	TLS1.3, IPSec, IEEE802.1X authentication (LAN/WLAN), SNMPv3, Firewall Functionality(IP/MAC Address Filtering), WPA3 support, Dual Network Support (Wired LAN/Wireless LAN, Wired LAN/Wired LAN), Disabling Unused Functions (Enabling/Disabling Protocols/Applications, Enabling/Disabling Remote UI, Enabling/Disabling USB Interface), G3 FAX separation from LAN, USB Port separation from LAN, Scan and Send -Virus Concerns for E-mail Reception
Document Security	Print Security(Secure Print, Encrypted SecurePrint, Forced Hold Printing, uniFLOW Secure Print*), Recieve Data Security (Confidential Fax Inbox Forwarding Received Documents Automatically), Scan Security (Encrypted PDF, Device Signature PDF/XPS, User Signature PDF/XPS), Scan Security (Encrypted PDF, Device Signature PDF/XPS, User Signature PDF/XPS*), Send Data Security (Setting for requesting password input per transmission, Restricted E-mail/File send functions, Confirming FAX number, Allow/Restrict Fax Driver Transmissions, Allow/Restrict Sending from History, S/MIME Support, Document Tracking (Secure Watermark)) *1 Requires optional uniFLOW Online / uniFLOW *2 Requires optional Universal Send Digital User Signature Kit-C1

Device Security	Protecting eMMC Data (FIPS140-2), Standard Storage Initialize, Trusted Platform Module (TPM2.0) *, Job Log Conceal Function, Protecting MFP Software Integrity, Checking MFD Software Integrity & Platform Firmware Resiliency (NIST SP800-193) with Automatic System Recovery (Verify System at Start-up, Runtime Intrusion Detection enabled with Trelix Embedded Control) *1 Requires optional TPM2.0 optional
Device Management and Auditing	Administrator Password, Digital Certificate and Key Management, Audit Log, Cooperating with External Security Audit System (Security Information and Event Management), Security Policy Setting
ENVIRONMENTAL SPECIFICATIONS	
Operating Environment	Temperature: 10 to 30 °C Humidity: 20 to 80 % RH (Relative Humidity/No condensation)
Power source	220-240V(±10%) 50/60Hz (±2Hz)
Power consumption	Maximum: Approx. 1760 W Active printing: Approx. 716.4W Standby: Approx. 34.9 W Sleep mode: Approx. 0.79 W Typical Electricity Consumption (TEC): C1743 0.42 kWh/week (230V) C1752 0.51 kWh/week (230V) As per Energy Star 3.2 For detailed information relating to Lot26 regulation, please go to: http://www.canon-europe.com/For_Work/Lot26/index.aspx
Noise Levels	Sound Pressure: Active: C1752 Duplex 55dB / Simplex 54dB C1743 Duplex 54dB / Simplex 53dB Standby: 22 dB Sound Power: Active: C1752 69dB (BW), 70dB (CL) C1743 Duplex 68dB / Simplex 67dB Standby: C1752 35dB C1743 36dB
Standards	Blue Angel (Validation Pending)
CONSUMABLES	
Toner Cartridges	TONER T1009 BK (18,700 pages) TONER T1009 C/M/Y (12,000 pages) TONER T1009L BK (3,800 pages) TONER T1009L C/M/Y (3,100 pages) *Based on ISO/IEC 19798

SOFTWARE AND PRINTER MANAGEMENT

Tracking and reporting	uniFLOW Online
Remote management tools	iW Enterprise Management Console Monitoring Service
Scanning software	Color Network ScanGear2. For both TWAIN and WIA
Optimisation tools	Canon Driver Configuration Tool
Printing Utilities	Canon Print Assistant (Windows)
Platform	MEAP (Multifunctional Embedded Application Platform)

PAPER SUPPLY OPTIONS

Cassette Module-AL1	Paper Capacity: 550 sheets (80 gsm) Paper Type: Thin, Plain, Recycled, Color, Heavy, Bond, Label, Pre-Punched, Letterhead Paper Size: A4, A5, A5R, A6, B5 Custom size: 101.6 x 148.0 mm to 216.0 x 355.6 mm Paper Weight: 60 to 200 gsm
Cassette Feeding Unit-BA1	Paper Capacity: 550 sheets (80 gsm) Paper Type: Thin, Plain, Recycled, Color, Label, Heavy, Bond, Pre-punched, Letterhead Paper Size: A4, A5, A5R, A6, B5 Custom size: 101.6 x 148.0 mm to 216.0 x 355.6 mm Paper Weight: 60 to 200 gsm

HARDWARE ACCESSORIES

Others	IC Card Reader Box-D2 Plain Pedestal Type-AC1 TBC Plain Pedestal Type-AD1 TBC
---------------	---

SYSTEM & CONTROLLER OPTIONS

Print Accessories	Barcode Printing Kit-D1 PCL International Font Set-A1
System Accessories	Wireless LAN Board-J1 Wireless LAN 5GHz License-C1 Universal Send Trace & Smooth PDF Kit-A1 Universal Send Digital User Signature Kit-C1 TPM BOARD-A1
FAX Accessories	Super G3 FAX Board-BW1 Remote Fax Kit-A1
Accessibility Accessories	ADF Access Handle-A1



Certifications and compatibility



Canon Inc.
Canon.com

Canon Europe
canon-europe.com

English Edition
© Canon Europa N.V. 2026