

## imagePRESS V900 series

# COMPACT AND RELIABLE DIGITAL COLOUR PRESS WITH INNOVATIVE TECHNOLOGIES

Robustly built and with sustainability a key consideration, the series has been engineered for continuous, reliable productivity, consistent, stable colour and class-leading front and back registration accuracy



### Maximise efficiency

Featuring progressive technology that takes its performance to a new level, the V Series helps you overcome your everyday production challenges

### Print in high quality

Ensure consistent print quality across all documents by automatically adjusting colour with the in-line spectrophotometric sensor.

### Expand your application range

Extensive media-handling capabilities mean you can print a wide range of media including envelopes, business cards, thin coated paper, and luxury textured paper.

### Optimal space utilisation

Compact design to fit into your environment with A magnetic plate on the edge of the printer also provides space to attach notes.

### More automation

Designed to reduce turnaround time and the skills required to produce high-quality output.

**Canon**

---

# TECHNICAL SPECIFICATIONS

# imagePRESS V900 series

## MAIN UNIT

### PRINT SPECIFICATIONS

	imagePRESS V900	imagePRESS V800	imagePRESS V700
Print speed (BW/CL)	90 ppm	80 ppm	70 ppm
Recommended monthly volume	40,000 - 250,000 pages	30,000 - 220,000 pages	15,000 - 190,000 pages
Maximum monthly peak volume	Up to 500,000 pages	Up to 400,000 pages	Up to 350,000 pages
Registration tolerance	Front to Back: 0.8 mm		
Printing method	Colour Laser Beam Printing		
Print Resolution (dpi)	2,400 x 2,400		

### PAPER SUPPLY OPTIONS

Paper supply capacity (A4, 80gsm)	Standard: 1,650 sheets 550-sheet Paper Cassette x 3 Maximum: 10,400 sheets (Engine (550x3), Multi Drawer Deck(1,500+1,500+2000), POD Deck Lite XL(3,500), Bypass(250))
-----------------------------------	---

### Supported media types

Engine Drawer :  
Thin(52-63gsm), Plain(64-105gsm), Thick(106-300gsm), Recycled, Color, Tab, Tranceparency, Bond, Pre-punched, Letterhead, Postcard, Envelope

Multi Drawer Deck-E1

Upper/Middle :  
Thin(52-63gsm), Plain(64-105gsm), Recycled, Color, Thick(106-350gsm), Coated(70-350gsm), Embossed, Bond, Transparency, Label, Pre Punched, Letterhead, Index, Bellum, Transparent film, Translucent film, Envelope\*

Lower :  
Thin(52-63gsm), Plain(64-105gsm), Recycled, Color, Thick(106-350gsm), Coated(70-350gsm), Embossed, Bond, Transparency, Label, Pre Punched, Letterhead, Index, Transparent film, Translucent film, Envelope\*, Synthetic, Magnetic(TBD)

POD Deck Lite :  
Thin(52-63gsm), Plain(64-105gsm), Recycled, Color, Thick(106-350gsm), Coated(85-350gsm), Embossed, Bellum, Bond, Transparency, Transparent film, Translucent film, Label, Pre Punched, Letterhead, Index, Postcard, Envelope, Synthetic

POD Deck Lite XL :  
19.2" or shorter  
Thin(52-63gsm), Plain(64-105gsm), Recycled, Color, Thick(106-350gsm\*), Coated(85-350gsm\*), Embossed, Bellum, Bond, Transparency, Transparent film, Translucent film, Label, Pre Punched, Letterhead, Index, Postcard, Envelope, Synthetic

Longer than 19.2"  
Uncoated(64-300gsm), Coated(100-300gsm)

Multi-purpose tray:  
Thin(64-105gsm), Recycled, Thick(106-350gsm), Color, Transparency, Label, Postcard, Envelope, Coated(70-350gsm), Embossed, Bond, Pre-punched, Letterhead, Vellum, Tab

### Supported media sizes

Engine Drawer :  
A3S,B4S,A4L,A4S,B5S,B5L,A5S,A5L,A6S,SRA3S, 11"x17"S, LGLS, LTRL, LTRS, EXE\_L, STMTS, 12"x18"S, 13"x19"S, 8KS, 16KL, 16KS, Envelope, Custom size  
(Cross track:100-330.2mm, In track:148-487.7mm)

Envelope specification  
Size:ISO-C5, DL  
Custom size :  
Cross track: 98-330.2mm,  
In track: 148mm-487.7mm

POD Deck Lite :  
SRA3S, A3S, A4L, A4S, A5S, B4S, B5L, B5S, 13"x19"S, 12"x18"S, 11"x17"S, LGLS, LTRL, LTRS, EXECL, STMS, 8KS, 16KL, 16KS, DL, ISO-C5 \*

Custom(139.7x182.0mm-330.2x487.7mm)  
Envelope custom size(6"x9", 9"x12", 10"x13")<sup>(\*)</sup>

<sup>(\*)</sup> Optional Envelope kit is needed (except10"x13")

POD Deck Lite XL :  
SRA3S, A3S, A4L, A4S, A5S, B4S, B5L, B5S, 13"x19"S, 12"x18"S, 11"x17"S, LGLS, LTRL, LTRS, EXECL, STMS, 8KS, 16KL, 16KS, DL, ISO-C5\*  
Custom(139.7x182.0mm-330.2x487.7mm)

\* Optional envelop kit is needed

Long Sheet(297.0x487.8-330.2x762.0mm)

Multi Drawer Deck-E1

Universal Cassette:  
SRA3S, A3S, A4L, A4S, A5S, B4S, B5L, B5S, 13"x19"S, 12"x18"S, 11"x17"S, LGLS, LTRL, LTRS, EXECL, STMTS, 8KS, 16KL, 16KSDL  
DL, ISO-C5\*

Custom(139.7x182.0mm-330.2x487.7mm)  
Custom Envelope(6"x9", 9"x12", 10"x13")\*

<sup>(\*)</sup>Optional envelop kit is needed

### Supported media weights

### Machine type

### Core functions

### Processor

### Control Panel

### Memory

### Hard Disk drive

### Mirroring Hard Disk Drive

### Interface Connection

### Power <supply

### Dimensions main engine (W x D x H)

### Installation Space(W x D) Weight

### COPY SPECIFICATIONS

### First-Copy-Out Time (A4) (BW/CL)

### Copy resolution (dpi)

### Multiple Copies

### Copy Density

### Magnification

### Preset Reductions

### Preset Enlargements

### Basic Copy Features

### Special Copy Features

### SCAN SPECIFICATIONS

### Name

### Type

### Document Feeder Paper Capacity (80 gsm)

### Acceptable originals and weights

### Supported media sizes

### Scan Speed (ipm: BW/CL; A4)

Multi-purpose tray:  
A3S, B4S, A4L, A4S, B5S, B5L, A5S, A5L, A6S, SRA3S, 11"x17"S, LGLS, LTRL, LTRS, EXECL, STMTS, 12"x18"S, 13"x19"S, 8KS, 16KL, 16KS, Envelope Monarch, DL, ISO-C5

Custom size(Cross track:100-330.2mm, In track:148-487.7mm)  
Long Sheet(210.0x487.8-330.2x1,300.0mm)  
Envelope Custom size:  
(98.0x148.0mm-330.2mmx487.7mm)

Engine Drawer: 52 to 300 gsm  
Multi Drawer Deck: 52 to 350 gsm  
POD Deck Lite: 52 to 350 gsm  
POD Deck Lite XL: 52-350 gsm  
Multi-purpose tray: 52 to 350 gsm

A3 Colour Laser Multifunctional

Print, Copy, Scan, Send, Store

1.8GHz Dual Core

10.1 inch WSVGA

6GB

SSD 512GB

SSD 512GB

NETWORK  
Standard: 1000Base-T/100Base-TX/10Base-T

220-240V 50/60Hz 13A+13A

1,327mm\* x 872mm x 1,185 mm\*\* (W x D x H)

<sup>(\*)</sup>Includes optional Control panel and Copy Tray-R2

<sup>(\*\*)</sup> Includes Operation Panel-A1 Reader-P1 (If Operating Panel-A5 and Operator Attention Light-A1 are attached, total height is 1,632 mm)

Approx 284kg

<sup>(\*)</sup>includes ADF

BW 6.9 seconds or less  
CL 7.7 seconds or less

600dpix600dpi  
600dpix300dpi  
300dpix300dpi

Up to 9,999 copies

Automatic or Manual (9 Levels)

25% - 400% (1% Increments)

25%, 50%, 70%

141%, 200%, 400%

Preset R/E Ratios by Area, Paper Setting, Previous Setting, Favourite Setting, Finishing, Two-Sided, Density Adjustment, Original Type Selection, Interrupt Mode, Setting Confirmation/Cancel

Book to Two Pages, Two-sided Original, Finishing, Booklet, Job Build, N on 1, Add Cover, Insert Sheets, Different Size Originals, Density Adjustment, Original Type Selection, Transparency Cover Sheets, Page Numbering, Copy Set Numbering, Sharpness, Erase Frame, Secure Watermark, Print Date, Shift, Gutter, Print & Check, Negative/Positive, Repeat Images, Merge Job Blocks, Job Done Notice, Mirror Image, Print on Tab, Store in Mail Box, Superimpose Image,Copy ID Card, Skip Blank Pages, Detect Feeder Multi Sheet Feed, Free Size Original

Duplex Color Image Reader Unit

Colour Platen and Single-pass Duplexing Automatic Document Feeder\* [2-sided to 2-sided (Automatic)]

\* Detect Feeder Multi Sheet Feed is supported.

200 sheets (75/80gsm)

Sheet, Book, 3-Dimensional objects

Document Feeder media weight:

<Single sided>  
38-220gsm (A/B)(<sup>(\*)</sup>)(<sup>(\*)</sup>)(<sup>(\*)</sup>),  
50-220gsm (inch)(<sup>(\*)</sup>)(<sup>(\*)</sup>)

<Double sided>  
38-220gsm (A/B)(<sup>(\*)</sup>)(<sup>(\*)</sup>)(<sup>(\*)</sup>),  
50-220gsm (inch)(<sup>(\*)</sup>)(<sup>(\*)</sup>)

(<sup>(\*)</sup>) 38-50gsm: Thin mode,160-220gsm: heavy mode

(<sup>(\*)</sup>)A6R or less: 50-220gsm

(<sup>(\*)</sup>)BW/CL mixed original same as Non mixed

Platen: max. scanning size: 297.0 x 431.8 mm

Document Feeder media size: A3S, A4L, A4S, A5L, A5S, A6S, B4S, B5L, B5S, B6S, 11"x17"S, LGLS, LTRL, LTRS, STMTL, STMTS, 8KS,16KL

BW:270ipm(A4/LTR)(<sup>(\*)</sup>)

CL:270ipm(A4/LTR)(<sup>(\*)</sup>)

(<sup>(\*)</sup>)Plain mode



# TECHNICAL SPECIFICATIONS

# imagePRESS V900 series

Scan Resolution (dpi)	600dpix600dpi 600dpix300dpi 300dpix300dpi	OUTPUT OPTIONS	
CONSUMABLES		Staple finisher-AG1	Upper Tray (A) Capacity: A4/A4R/A5R/A3/SRA3/13"x19" 1,000 sheets (52-300 gsm) / 200 sheets (301-350 gsm) Long sheet (Over 487.7 mm up to 762 mm length) 100 sheets (52-79 gsm) / 50 sheets (80-150 gsm) / 25 sheets (151-300 gsm) / 20 sheets (301-350 gsm)
Toner Cartridges	TONER T01 BK/C/M/Y		Lower Tray (B) Capacity: A4 4,000 sheets (52-80 gsm) / 3,000 sheets (801-300 gsm), A4R 2,000 sheets (52-300 gsm), A3 1,500 sheets (52-300 gsm), SRA3 1,000 sheets (52-300 gsm), Any size 200 sheets (301-350 gsm) Paper Weight: 52 to 350 gsm Staple Position: Corner, Double Staple Capacity: A4: 100 sheets, A3/A4R: 50 sheets Dimensions (W x D x H): 800 mm x 792 mm x 1,239 mm (with Long Sheet Tray : 1,136 mm x 792 mm x 1,239 mm) Weight: Approx. 130 kg Power: 220-240V, 50-60Hz, 8A
FIERY PRINT CONTROLLER SPECIFICATIONS		Booklet finisher-AG1	Tray Capacity / Paper Weight / Staple Position / Staple Capacity: same as Staple Finisher-AG1 Booklet stitch paper size: A3, A4R, SRA3, 13"x19", Free size (210 x 279.4 mm to 330.2 x 487.7 mm) Booklet stitch paper weight: Body sheet 52-220 gsm, Cover sheet 64-300 gsm Booklet stitch staple capacity: 25 sheets (52-80 gsm, include cover) Non Staple Folded Bunch Capacity: up to 5 sheets (60 to 105 gsm) Power Source: 100-240V, 50/60Hz, 2.8A Dimensions (W x D x H): 896 x 765 x 1,040 mm (when the extension tray is extended) Weight: Approx. 110 kg
Optional/Standard	Optional		(Requires either the STAPLE FINISHER-AG1 or BOOKLET FINISHER-AG1) Two or Four Holes Punch Hole type: BT1: 2 holes and 4 holes (FRN) selectable, BU1: 4 holes (SWE) Punch Paper Weight: 52-300 gsm Punch Paper Size: 2 holes: A3, A4, A4R, Free size (182 x 182 mm to 297 x 432.0 mm excluding 203 x257 mm to 297 x 270 mm) 4 holes: A3, A4, Free size (257 x 182 mm to 297 x 432 mm)
Name	imagePRESS Server N500/P400	Puncher unit-BT1/BU1	Paper Size: All available size on marking engine Paper Weight: 52 to 350 gsm Output Capacity: 250 sheets at simplex/duplex printing,100 sheets at length over 487.7 mm (Long Sheet Tray is required) Dimensions (W x D x H): 422 mm x 382 mm x175 mm Weight: Approx. 1.2 kg
Print Resolution (dpi)	1200 x 1200, 600 x 600		(Requires either the STAPLE FINISHER-AG1 or BOOKLET FINISHER-AG1) Paper Weight: <Punch> 75-300 gsm (Plain paper), 118-300 gsm (Coated paper) <Crease> 157-300 gsm (Plain paper / Coated paper) <Through> All substrates supported by engine
Page Description Language(s)	PS3/PCL6		Paper Size: <Through> All substrates supported by engine <Punch> SRA3, A3, SRA4, SRA4R, A4, A4R <Crease> SRA3, A3, A4R, 13"x19", 13"x19.2"
Memory	8GB	Copy tray-R2	Punch Tools: Plastic Comb 21-Hole, Twin Loop 23-Hole (Round/Square), Twin Loop 34-Hole (Round/Square), Color Coil 47-Hole, Velo Bind 12-Hole, Loose Leaf 4-Hole Punch, Loose Leaf 2-Hole Punch, Loose Leaf 4-Hole (Swedish), Crease Dimensions (W x D x H): 445 mm x 795 mm x 1,040 mm Weight: Approx. 102kg Power: 230V, 50Hz, 1.9A
Hard Disk Drive	N500: HDD 1TB SSD 240GB P400: HDD 500GB		Requires Booklet Finisher-AG1 Trim Width: 2-28mm Trim Thickness: Up to 50 sheets (include cover) Paper Weight: 52 to 300 gsm Chip tray capacity: Approx. 5,000 sheets (Trim width 20mm, A4, 80 gsm) Dimensions (W x D x H): 2,095 mm (including joint, conveyor and output tray) x 790 mm x 1,040 mm Weight: Approx. 178 kg (including conveyor and output tray)
Processor Speed	N500: Intel Core i5 8500 P400: Intel Pentium Gold G5400	Multi function professional puncher-C1	Requires Booklet Trimmer-G1 Trim Width: 2-15 mm Trim Thickness: Up to 50 sheets (include cover) Paper Weight: 52 to 300 gsm (Trim 60 to 300 gsm) Chip tray capacity: Approx. 1,500 sheets (Trim width 15mm, A4, 80 gsm) Dimensions (W x D x H): 2,312 mm (including Booklet Trimmer-G1) x 790 mm x 1,040 mm Weight: Approx. 145 kg Power: 220-240V, 60Hz, 2.3A
System	N500: FS500 Pro P400: FS500		
Fonts	PS:138, PCL:80		
Supported Operating Systems	Windows 8.1 32/64, Windows 10 32/64, Windows 11 64, Windows Server 2012 64, Windows Server 2012 R2 64, Windows Server 2016 64, Windows Server 2019 64, Windows Server 2022 64, macOS Mojave (10.14.x), macOS Catalina (10.15.x), macOS Big Sur(version 11.0), macOS Monterey(version 12)		
Interface	N500: 2 x Ethernet(1000Base-T/100Base-TX/10 Base-T), USB3.2 x 5, USB2.0 x 2 P400: 2 x Ethernet(1000Base-T/100Base-TX/10 Base-T), USB3.0 x 2		
Network protocols	TCP/IP (FTP, SMTP, POP, HTTP, SNMP, LDAP, SMB, LPD, IPP, WS-Discovery, Bonjour, Direct Mobile Printing, Port 9100, 802.1X, DHCP, DNS, NTP)		
Direct Print	PDF2, EPS, TIFF, JDF1.8/JMF		
VDP	N500: PPML 3.0, PDF/VT-1, PDF/VT2, VPS, FreeForm, FreeForm Plus P400: PDF/VT-1(Requires Fiery JobExpert and PDF Processing Kit), FreeForm, FreeForm Plus		
Fiery Print Controller Standard Features	Fiery Command WorkStation 6 / Paper Catalog / Fiery Remote Scan / Fiery Hot Folders & Virtual Printers		
Fiery Print Controller Options	Fiery Impose / Fiery Compose / Fiery Impose and Compose / Removable HDD Kit(N500 only)		
HW Platform	N500: NX Pro P400: E500		
Dimensions (W x D x H)	tbd		
Weight	tbd		
PRISMA SYNCCONTROLLER SPECIFICATIONS			
Optional/Standard	Optional		
Name	PRISMAsync for iPR V900 series		
Print Resolution (dpi)	1200x1200dpi, 600x600dpi		
Page Description Language(s)	Postscript L3, PDF 2.0, APPE V5.7, PPML, IPDS (IS/3 standard compliant), PCL/PJL (transaction printing)		
Memory	1x DDR4-2400 8GB, 8GB total		
Hard Disk Drive	1x 500GB 2,5 inch, 1 x TB 3,5 inch		
Processor Speed	Intel Core i5-8500 (8th Gen Coffee Lake CPU)		
System	PRISMAsync Mark 9		
Fonts	139 Type 1 fonts for Roman languages; User import of PS fonts via Settings Editor; Optional Adobe Asian fonts: Japanese: 5 fonts Chinese: 2 fonts for simplified Chinese, 1 font for traditional Chinese; Korean: 1 font for Korean		
Supported Operating Systems	Windows Server 2012 R2, 8.1 (32/64bit) and 10, Server 2016 & 2019 MacOS 10.15 (64 bit), MacOS 11 (64 bit, Big Sur, Intel)	Booklet trimmer-G1	
Interface	1000Base-T/100Base-TX/10Base-T x " USB3.0x8		
Network protocols	TCP/IP, IPv6 Support, IPSec, NetBEUI/SMB (hotfolders, scan-to-file), secure IPP, SNMP V3, Job MIB, HTTP, HTTPS, Socket printing (port9100), LPR/LPD, JDF/JMF, LDAP, WebDav.		
Direct Print	PDF, JDF	Two-Knife Booklet Trimmer-B1 and Two-Knife Booklet Trimmer Conveyor-B1	
VDP	PDF/VT-1, PPML		
PRISMAsync Controller Standard Features	PS/PDF, Scheduler, Multiple Queues/hotfolders, Streaming, Accounting, Scanning, PPML, Remote Manager, Remote Service, Integrity checker		
PRISMAsync Controller Options	E-shredding, Advanced Color Management, Advanced Impose, DocBox, Page Programming, DP Link, PCL6 TP, IPDS, PDF for IPDS		
Dimensions (W x D x H)	200mm x 430mm x 420mm		
Weight	18 kg		



# TECHNICAL SPECIFICATIONS

# imagePRESS V900 series

<b>Document insertion unit-r1</b>	(Requires either the STAPLE FINISHER-AG1 or BOOKLET FINISHER-AG1) Number of trays: 2 Tray Capacity: Upper Tray: 200 Sheets (80 gsm), Lower Tray: 200 Sheets (80 gsm) Acceptable Paper Type: Thin, Plain, Recycled, Colour, Thick, Pre-punched, Letterhead, Bond, Coated, Tab, Tracing, Textured Acceptable Paper Sizes: SRA3, A3, A4, A4R, B4, B5, B5R, Custom size (182.0 × 182.0 mm to 330.2 × 487.7 mm) Acceptable Paper Weight: 52 to 300 gsm Power Source: 100-240V/50/60Hz 1.0A Dimensions (W x D x H): 336 × 793 × 1,407 mm (width excluding document tray) Weight: Approx. 61 kg	<b>Booklet Finisher-AC2</b> (only compatible with V800 and V700)	Tray Capacity / Paper Weight / Staple Position / Staple Capacity: same as Staple Finisher-AC2 but if there are any sheets on the saddle tray, the capacity of Tray A becomes limited to 1,500 sheets Booklet stitch paper size: A3, A4R, Free size (195 x 270 mm to 304.8 × 457.2 mm) Booklet stitch paper weight: Body sheet 52-220 gsm, Cover sheet 52-256 gsm Booklet stitch staple capacity (including 1 cover sheet): Non coated media; 20 sheets (52-81.4 gsm), 10 sheets (82-105 gsm), 5 sheets (106-150 gsm), 4 sheets (151-209 gsm), 3 sheets (210-220 gsm) Coated media; 5 sheets (85-150 gsm), 4 sheets (151-209 gsm), 3 sheets (210-220 gsm) Dimensions (W x D x H): 527 mm (Max 656 mm*) x 623 mm x 1,099 mm (Max 1,195 mm*)
<b>Paper folding unit-k1</b>	(Requires either the STAPLE FINISHER-AG1 or BOOKLET FINISHER-AG1) Supported Folding Type: Z-Fold, Accordion Z-Fold, C-Fold, Half-Fold, Double Parallel Fold Acceptable Paper Type: Thin, Plain, Recycled, Colour, Bond Acceptable Paper Sizes: Z-Fold : A3, A4R , B4 Accordion Z-Fold, C-Fold, Half-Fold, Double Parallel Fold: A4R Acceptable Paper Weight: Z-Fold, Accordion Z-Fold, C-Fold, Half-Fold :52 to 105 gsm Double Parallel Fold : 52 to 90 gsm Power Source: From the Finisher Dimensions (W x D x H): 336 × 793 × 1,190 mm Weight: Approx. 71 kg	<b>Finisher Jogger Kit-A1</b>	*when the auxiliary tray is extended.  Weight: Approx. 60 kg Requires either Staple or Booklet Finisher-AC1. Paper Weight: Non Sort 52-300 gsm, Bunch Shift 52-256 gsm Paper Size: Non Sort A3/A4/A4R, Bunch Shift A3/A4/A4R
<b>Perfect Binder-F1</b>	(Requires either the STAPLE FINISHER-AG1 or BOOKLET FINISHER-AG1) Booklet size: 203 x 138 mm to 297 x 216 mm Booklet thickness: Up to 25mm Cutting Range: Top/bottom: 6.5 to 39.5mm at each edge, fore edge: 6.5 to 49.5mm Body pages: Sizes: A4, SRA4, Free size (257 x 182 mm to 320 x 228.6 mm) Paper weight and number of sheets: Thin Paper (52-63 gsm): 30-200 sheets Plain Paper (64-80 gsm): 10-200 sheets Plain Paper (81-90 gsm): 10-150 sheets Thick Paper (91-105 gsm): 10-150 sheets Thick Paper (106-163 gsm): up to 10 sheets as insertion sheet or up to 25mm as thickness of bunch Cover: Number of Sheets: 1 sheet Sizes: A3, SRA3, Free size (257 x 364 mm to 330.2 x 487.7mm) Paper weight: 90 to 300 gsm Tray capacity: Approx.127mm or approx.1,000 sheets of paper as a total Dimensions : 922 mm x 791 mm x 1,300 mm Weight Approx. 308kg Power: 220-240V, 50/60Hz, 3.0A	<b>2/4 Hole Puncher Unit-A1</b>	Requires either Staple or Booklet Finisher-AC1. Punch Hole type: 2 holes and 4 holes (FRN) selectable Paper Weight: 52-300 gsm Paper Size: 2 holes: A3, A4, A4R 4 holes: A3, A4
<b>High Capacity Stacker-J1</b>	Paper Size: A3, A4, A4R, A5R, SRA3, 13"x19", Free size (140 x 182 mm to 330.2 x 1,300 mm) Paper Weight: 52 to 350 gsm Output Capacity Stack tray: 6,000 sheets (80 gsm) in two stacks of 3,000 sheets each Top tray: 200 sheets up to 487.7mm; 100 sheets up to 762mm; 10 sheets up to 1300mm Dimensions (W x D x H): 899 mm × 745 mm × 1,040 mm Weight: Approx. 120 kg Power: 90-264V, 47-63Hz, 10A	<b>4 Hole Puncher Unit-A1</b>	Requires either Staple or Booklet Finisher-AC1. Punch Hole type: 4 holes (SWE) Paper Weight: 52-300 gsm Paper Size: A3, A4, A4R
<b>Staple Finisher-AC2</b> (only compatible with V800 and V700)	Lower Tray (A) Capacity: A4/A5R 3000 sheets (81 gsm), A4R/A3/SRA3/13"x19" 1500 sheets (81 gsm), Long sheet* (Over 487.7 mm up to 762 mm length) 100 sheets (79 gsm) Long sheet* (Over 762mm length) 1 sheet All size of thin paper (52-59 gsm) 1,500 sheets Capacity for coated paper is half of that for plain paper  *Long Sheet Tray is required  Upper Tray (B) Capacity: A4/A5R 250 sheets (80 gsm), A4R/A3/SRA3/13"x19" 125 sheets (80 gsm) Mid Tray (C) Capacity: A4/A5R 250 sheets (80 gsm), A4R/A3/SRA3/13"x19" 125 sheets (80 gsm) Paper Weight for Tray A: Non Sort 52-350 gsm, Bunch Shift / Staple 52-256 gsm excluding duplex printed thin paper (52-59 gsm) and any special media, Eco Staple 52-105 gsm Paper Weight for Tray B/C: Non Sort / Bunch Shift 52-256 gsm excluding duplex printed thin paper (52-59 gsm), coated paper (85-105.9 gsm) and any special media Staple Position: Corner, Double Staple Capacity: <Non coated media, 52-90 gsm> A4: 65 sheets, A3/A4R: 40 sheets <Coated media> 2 sheets Dimensions (W x D x H): 527 mm (Max 656 mm*) x 623 mm x 1,099 mm (Max 1,195 mm*)  *when the auxiliary tray is extended.  Weight: Approx. 36 kg	<b>DFD Adapter-B1</b>	Basic information: Enables DFD connectivity directly beside the engine Paper Weight: Plain Paper 52-350 gsm, Coated Paper 128-350gsm Paper Size: 182 x 182 mm - 330.2 x 762 mm Optionals: Finisher Bridge Height Kit 1002-A1 (Standard DFD height is 860 mm) Dimensions (W x D x H): 300 mm x 745 mm x 1040 mm Weight: Approx. 60 kg Power: 90-264V, 47-63Hz, more than 10A
		<b>Finisher Bridge-A1</b>	Basic information: Offers connectivity of Staple Finisher-AG1 and Booklet Finisher-AG1 with 3rd party DFD finishing equipments. Always in combination with DFD Adapter-B1. Paper Weight: Plain Paper 52-350gsm, Coated Paper 128-350 gsm Paper Size: 182 x 182 mm - 330.2 x 762 mm Dimensions (W x D x H): 600 mm x 745 mm x 150 mm Weight: Approx. 30 kg Power: Power and control from DFD Adapter-B1
		<b>3rd Party Finishers</b>	Basic information: The imagePRESS V900 series can be configured also with 3rd party finishers. Please find here a list of listed and approved finishers. Plockmatic BLM35 Booklet Maker and Plockmatic BLM50 Upgrade Kit Plockmatic MPS (Multi-Purpose Stacker) GBC MF ProPuncher
		<b>STAPLE CARTRIDGE</b>	STAPLE-N1 - for Stapling (3 x 5,000 pcs) (for Staple Finisher-AG1 and Booklet Finisher-AG1) STAPLE-P1 - for Saddle Stitching (2 x 5,000 pcs) (for Booklet Finisher-AG1) STAPLE CARTRIDGE-X1 - For Stapling (3 x 5,000 pcs) (Staple Finisher-AC1 and Booklet Finisher-AC1) STAPLE CARTRIDGE-Y1 - For saddle stitching (2 x 2,000 pcs) (for Booklet Finisher-AC1)

## Software & Solutions



Canon Inc.  
canon.com

Canon Europe  
canon-europe.com

English edition  
© Canon Europa N.V.,2022

