

imagePROGRAF  
GP-2000

# PRODUCE OUTSTANDING CG DESIGNS WITH VIVID COLOUR QUALITY

A large format CG design  
printer for outstanding  
applications with vibrancy.



- **Superior colour gamut**

Elevate CG designs with vivid, superior quality printing, using a wide colour gamut that features five new colours – red, orange, green and violet – plus the fluorescent pink, capable of producing neon and pastel shades

- **Professional quality prints**

The imagePROGRAF GP-2000 is the world's first PANTONE™<sup>(1)</sup> calibrated printer<sup>(2)</sup> for PANTONE PASTEL & NEON GUIDE Coated<sup>(3)</sup>, in addition to 99% coverage from the PANTONE FORMULA GUIDE Solid Coated<sup>(4)</sup>

- **High productivity**

Multifunction roll system and Smart Roll Paper support the delivery of professional quality output, while hot swap ink tanks allow inks to be replaced without disrupting the print process

- **Security assured**

Security Print feature with PIN access helps provide the protection against loss or leakage, allowing you to print with peace of mind that all your data is being managed securely

## PRODUCT RANGE



imagePROGRAF GP-4000



imagePROGRAF GP-200



imagePROGRAF GP-300

**Canon**

---

# TECHNICAL SPECIFICATIONS

# imagePROGRAF GP-2000

## TECHNOLOGY

<b>Printer Type</b>	11 Colour 24"
<b>Print Technology</b>	Canon Bubblejet on Demand 11 colours integrated type (12 chips per print head x 1 print head)
<b>Print Resolution</b>	2,400 x 1,200 dpi
<b>Number of Nozzles</b>	Total : 18,432 nozzles MBK, PBK, C, M, Y, GY, R, O, G, V, FP : 1,536 nozzles each
<b>Line Accuracy</b>	±0.1% or less User adjustments necessary. Printing environment and media must match those used for the adjustments. CAD paper required : Plain paper, CAD tracing paper, coated paper, CAD translucent matte film only
<b>Nozzle Pitch</b>	600 dpi x 2 includes Non-firing nozzle detection and compensation system
<b>Ink Droplet Size</b>	minimum 4 pl per colour
<b>Ink Capacity</b>	Bundled Starter Ink : 330 ml (MBK), 160 ml (Others) Sales Ink : 160 ml, 330 ml, 700 ml
<b>Ink Type</b>	Pigment inks : 11 colour MBK, PBK, C, M, Y, GY, R, O, G, V, FP
<b>OS Compatibility</b>	Microsoft Windows 32 Bit : 7, 8.1, 10 Microsoft Windows 64 Bit : 7, 8.1, 10, Windows Server 2008R2, 2012, 2012R2, 2016, 2019 Apple Macintosh : macOS 10.13.6 - macOS 11
<b>Printer Languages</b>	PDF (Ver.1.7), JPEG (Ver. JFIF 1.02)
<b>Standard Interfaces</b>	USB A Port : USB Memory Direct Print for JPEG/PDF files USB B Port : Built-in Hi-Speed USB Ethernet : IEEE 802.3 10base-T, IEEE 802.3u 100base-TX / Auto-Negotiation, IEEE 802.3ab 1000base-T / Auto-Negotiation, IEEE 802.3x Full Duplex Wireless LAN : IEEE802.11n/IEEE802.11g/IEEE802.11b *Please refer to user manual how to activate/deactivate the wireless LAN

## MEMORY

<b>Standard memory</b>	3GB Expansion slot : No
<b>Hard Drive</b>	500GB (Encrypted)

## PRINTING SPEED

<b>Poster:</b>	0:59 (Fast) 1:37 (Standard)
<b>Plain Paper (A1)</b>	0:59 (Fast) 1:37 (Standard)
<b>Heavy coated Paper (A1)</b>	1:37 (Standard) 3:09 (High Quality)
<b>Glossy photo Paper (A1)</b>	3:08 (Standard) 4:40 (High Quality)

## MEDIA HANDLING

<b>Media Feed and Output</b>	Upper Roll Paper : One Roll, Front-loading, Front Output Lower Roll Paper (option) : One Roll, Front-loading, Front Output Cut Sheet : Front-loading, Front Output (Manual feed using media locking lever)
<b>Media Width</b>	Roll paper : 152.4 mm - 610 mm Cut sheet : 152.4 mm - 610 mm
<b>Media Thickness</b>	Roll/Cut : 0.07 mm - 0.8 mm
<b>Minimum Printable Length</b>	Roll paper : 101.6 mm Cut sheet : 203.2 mm
<b>Maximum Printable Length</b>	Roll paper : 18 m (Varies according to the OS and application) Cut sheet : 2133.6 mm (With Stand)
<b>Maximum Media Roll Diameter</b>	170 mm
<b>Media Core Size</b>	Internal diameter of roll core : 2"/3"
<b>Margins Recommended area</b>	Roll paper : Top: 20 mm, Bottom: 3 mm, Side: 3 mm Cut sheet : Top: 20 mm, Bottom: 20 mm, Side: 3 mm
<b>Margins Printable area</b>	Roll paper : Top: 3 mm, Bottom: 3 mm, Side: 3 mm Roll paper (borderless print) : Top: 0 mm, Bottom: 0 mm, Side : 0 mm Cut sheet : Top: 3 mm, Bottom: 20 mm, Side: 3 mm
<b>Media Feed Capacity</b>	Roll Paper : 1 roll Cut Sheet : 1 sheet
<b>Media Take-up roll unit</b>	Dual direction roll take up unit allowing print surface to be wound inside or outside of the roll.
<b>Borderless Printing Width (Roll Only)</b>	[Recommended] 515 mm (JIS B2), 594 mm (ISO A1), 10", 14", 17", 24" [Printable] 257 mm (JIS B4), 297 mm (ISO A3), 329 mm (ISO A3+), 420 mm (ISO A2), 6", 8", 12", 15", 16", 20", 22", 300 mm, 500 mm, 600 mm, and custom roll width (152.4 - 610 mm)

## Maximum number of delivered prints

Standard position : 1 sheet  
Flat position : A2 landscape, glossy paper up to 10 sheets, coated paper up to 20 sheets (excludes strong curled condition)

## DIMENSIONS AND WEIGHT

<b>Physical Dimensions WxDxH (mm) and Weight (Kg)</b>	1100 x 984 x 1168 mm (Basket Open) 1100 x 766 x 1168 mm (Basket Closed) 102 kg (Main Unit + Stand + Basket, including Roll Holder Set, excluding ink and print head)
<b>Packaged Dimensions WxDxH (mm) and Weight (Kg)</b>	Printer (Main unit with pallet) : 1324 x 902 x 1042 mm 125 kg Stand + Basket : 1111 x 797 x 223 mm 23 kg Roll Unit : 1244 x 562 x 461 mm 26 kg

## POWER AND OPERATING REQUIREMENTS

<b>Power Supply</b>	AC 100-240V (50-60Hz)
<b>Power Consumption</b>	Operation : Approx. 99 W Sleep mode : Approx. 2.3 W Default setting for the time to enter the Sleep mode : Approx. 5 Minutes Power off : Approx. 0.2 W
<b>Operating Environment</b>	Temperature : 15-30°C, Humidity : 10-80% RH (no dew condensation)
<b>Acoustic Noise (Power/Pressure)</b>	Pressure Operation : 48 dB (A) (Plain paper, Standard mode, Poster) (Measured on ISO7779 standard) Standby : 35 dB (A) or less Power Operation : 6.5 Bels (Plain paper, Standard mode, Poster) (Measured on ISO7779 standard)
<b>Regulations</b>	Europe : CE mark Other Countries : CB certification
<b>Environment Certificates</b>	TUV, CB

## WHAT'S INCLUDED

<b>What's in the Box?</b>	Printer, 1 print head, 1 roll holder (spool), 3 inch paper core attachment, Power Cable, 1 set of starter ink tanks, Set up guide, Printer Stand Setup Guide, Quick Guide, Safety/Standard Environment leaflet, User software CD-ROM (Win), PosterArtist Lite CD-ROM, EU Biocide Sheet, Important Information Sheet
<b>Software Included</b>	imagePROGRAF GP Printer Driver and PosterArtist Lite Other software available as Download from Web.

## OPTIONS

<b>Optional Items</b>	Printer Stand : SD-21 2/3" Roll Holder : RH2-29 Roll Unit : RU-23
-----------------------	---

## CONSUMABLES

<b>User Replaceable Items</b>	Ink Tank : PFI-2100 (160ml), PFI-2300 (330ml), PFI-2700 (700ml) Print Head : PF-10 Cutter Blade : CT-07 Maintenance Cartridge : MC-30
-------------------------------	--

<sup>(1)</sup> PANTONE™ is a trademark or registered trademark of Pantone LLC.

<sup>(2)</sup> As of 31st August, 2021 according to professional services performed by Pantone.

<sup>(3)</sup> PANTONE PASTELS & NEONS GUIDE Coated colour gamut coverage rate is 97% for GP-4000 / GP-2000 when using Photo Paper Pro Platinum with imagePROGRAF printer driver at [Poster/Photo (Fluorescent)] [Highest] (600 dpi)

<sup>(4)</sup> When using Photo Paper Pro Platinum with imagePROGRAF printer driver at [Poster/Photo (Fluorescent)] [Highest] (600 dpi)

## Disclaimer

Some images are simulated for clarity of reproduction. All data is based on Canon's standard testing methods. This leaflet and the specifications of the product have been developed prior to the date of product launch. Final specifications are subject to change without notice.™ and ®. All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.

Canon recommends you use Canon Media for the best results. Please check media (paper) compatibility list to see which variety of paper/media is recommended.



Canon Inc.  
canon.com  
Canon Europe  
canon-europe.com  
English edition  
© Canon Europa N.V., 2024