imagePROGRAF

MAXIMISE YOUR PRINT MARKETING POTENTIAL WITH VIBRANT, EYE-CATCHING POSTER PRODUCTION





Vivid colours

Print eye-catching posters every time with advanced spot colour accuracy and fluorescent colour expression using newly developed fluorescent pink ink

· Easy poster creation

Create attractive and impactful marketing materials with PosterArtist, featuring new templates and built-in stock photo service, helping you produce stylish posters for any purpose

Professional finish

High-precision paper edge detection supports free-size borderless printing for all paper roll sizes, making it easy to create borderless posters without cutting a printout

Direct to print

Built in HDD allows for convenient and efficient printing of the saved data, also PDF and JPEG file can be printed from a USB memory without connecting to a PC

· Compact design

Maximise available office space with a small footprint printer that fits flat against the wall to offer full front usability, perfect for smaller offices

Security assured

Have complete confidence in the security of your printouts with PIN-accessed Security Print feature

A compact, large format printer with newly developed fluorescent pigment ink for easy, high impact poster design, ideal for maximising sales and profits from retail and hospitality marketing.



PRODUCT RANGE



imagePROGRAF GP-300



imagePROGRAF GP-4000



imagePROGRAF GP-2000



TECHNICAL SPECIFICATIONS

imagePROGRAF **GP-200**

TECHNOLOGY

Printer Type

Canon Bubblejet on Demand 6 colours integrated type (6 chips per print head \times 1 print head)

Print Resolution 2.400 x 1.200 dpi

Number of Nozzles

Line Accuracy

Nozzle Pitch

Ink Droplet Size

Ink Capacity

Pigment inks : 6 colour MBK, BK, C, M, Y, FP Ink Type

OS Compatability

Microsoft Windows 32 Bit : 7, 8.1, 10 Microsoft Windows 64 Bit : 7, 8.1, 10, Windows Server 2008R2, 2012, 2012R2, 2016, 2019 Apple Macintosh : macOS 10.13.6 - macOS 11

PDF (Ver.1.7), JPEG (Ver. JFIF 1.02) **Printer Languages**

Standard Interfaces

MEMORY

500GB

PRINTING SPEED

Poster:

Media Feed and Output

Media Thickness

Minimum Printable Length

Maximum Printable Length

Maximum Media Roll Diameter

Media Core Size

Margins Printable area

Media Feed Capacity

Total: 15,360 nozzles MBK, BK, C, M, Y, FP: 2,560 nozzles

±0.1% or less
User adjustments necessary. Printing environment and
media must match those used for the adjustments.
CAD paper required: Plain paper, CAD tracing paper,
coated paper, CAD translucent matte film only

1.200 dpi x 2 includes Non-firing nozzle detection and compensation system

minimum 5 pl per colour

Bundled Starter Ink : 90 ml (MBK, BK, C, M, Y, FP) Sales Ink : 130 ml, 300 ml $\,$

USB A Port : USB Memory Direct Print for JPEG/PDF files USB B Port : Built-in Hi-Speed USB Ethernet : IEEE 802.3 l 100bser-T, IEEE 802.3u 100bsse-TX / Auto-Negotiation, IEEE 802.3sh 1000base-T/ Auto-Negotiation, IEEE 802.3sh 100uplex Wireless LAN : IEEE802.1mi/IEEE802.1

Standard memory

2GB Expansion slot : No

Plain Paper (A1)

0:25 (Fast) 0:44 (Standard) Heavy coated Paper (A1) 0:55 (Fast) 1:22 (Standard)

3:28 (Standard) 5:18 (High Quality) Glossy photo Paper (A1)

MEDIA HANDLING

Media Width

Roll Paper: One Roll, Upper-loading, Front Output Cut Sheet: Upper-loading, Front Output (Manual feed using media locking lever) Roll paper : 203.2 mm - 610 mm Cut sheet : 203.2 mm - 610 mm

Roll/Cut: 0.07 mm - 0.8 mm Roll paper : 203.2 mm Cut sheet : 279.4 mm

Roll paper : 18 m (Varies according to the OS and application) Cut sheet : 1.6 m

Internal diameter of roll core: 2"/3"

Roll paper : Top: 3 mm, Bottom: 3 mm, Side: 3 mm Roll paper (borderless print) : Top: 0 mm, Bottom: 0 mm, Side: 0 mm Cut sheet : Top: 3 mm, Bottom: 20 mm, Side: 3 mm

Borderless Printing Width (Roll Only)

[Recommended] 515 mm (JIS B2), 594 mm (ISO A1), 10", 14", 17", 24" [Printable] 257 mm (JIS B4), 297 mm (ISO A3), 329 mm (ISO A3+), 420 mm (ISO A2), 8", 12", 15", 16", 18", 20", 22", 300 mm, 500 mm, 600 mm, and custom roll width (203.2 - 610 mm)

Maximum number of delivered prints

DIMENSIONS AND WEIGHT

Physical Dimensions WxDxH (mm) and Weight (Kg)

Packaged Dimensions WxDxH (mm) and Weight (Kg)

POWER AND OPERATING REQUIREMENTS

Power Supply

Power Consumption

Operating Environment

Regulations

Enviroment Certificates

WHAT'S INCLUDED

What's in the Box?

Software Included

CONSUMABLES

User Replaceable Items

OPTIONS

Roll paper: Top: 20 mm, Bottom: 3 mm, Side: 3 mm Cut sheet: Top: 20 mm, Bottom: 20 mm, Side: 3 mm

Roll Paper: 1 roll Cut Sheet: 1 sheet

Standard position of the basket: 1 sheet

982 x 870 x 1060 mm (Basket Open) 982 x 757 x 1060 mm (Basket Closed) 50 kg (Main Unit + Stand + Basket, including Roll Holder Set, excluding ink and print head)

Printer (Main unit with pallet): 1152 x 913 x 705 mm

69 kg Stand + Basket : 1055 x 824 x 268 mm 16 kg

AC 100-240V (50-60Hz)

Operation : Approx. 72 W Sleep mode : Approx. 2.0 W Default setting for the time to enter the Sleep mode : Approx. 5 Minutes Power off : Approx. 0.2 W

Temperature : 15~30°C, Humidity : 10~80% RH (no dew condensation)

Pressure
Operation : 49 dB (A)
(Plain paper, Standard mode, Poster)
(Measured on ISO7779 standard)
Standby : 35 dB (A) or less
Power

Power
Operation: 6.7 Bels
(Plain paper, Standard mode, Poster)
(Measured on ISO7779 standard)

Europe : CE mark, Other Countries : CB certfication TUV, CB

Printer, 1 print head, 1 roll holder (spool), 3 inch paper core attachment, Power Cable, 1 set of starter ink tanks, Set up guide, Printer Stand Setup Guide, Quick Guide, Safety/Standard Environment leaflet, User software.

CD-ROM, (Win), PosterArtist Lite CD-ROM, EU Biocide Sheet, Important Information Sheet

imagePROGRAF GP Printer Driver and PosterArtist Lite Other software available as Download from Web.

2/3" Roll Holder : RH2-28 Printer Stand : SD-24 Optional Items

Ink Tank: PFI-120 (130ml), PFI-320 (300ml) Print Head: PF-07 Cutter Blade: CT-08 Maintenance Cartridge: MC-31

Disclaimer Some images are simulated for clarity of reproduction. All data is based on Canon's standard testing methods. This leaflet and the specifications of the product have been developed prior to the date of product launch. Final specifications are subject to change without notice. ** and **. All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.

Canon recommends you use Canon Media for the best results. Please check media (paper) compatibility list to see which variety of paper/media is recommended.









3006 Lake Drive Citywest, Saggart

Telephone No: 01 2052400 Facsimile No: 01 2052525

The Bower 4 Roundwood Avenue Canon Inc. canon.com

canon-europe.com

© Canon Europa N.V., 2024

Canon

Canon Ireland

Co. Dublin, Ireland

canon.ie

Canon (UK) Ltd

Stocklev Park Uxbridge **UB11 1AF**

Canon Europe English edition