



imagePROGRAF GP-2600S

PRECISION PALETTE, CRAFTING BRILLIANCE

A revolution in printing premium posters and entry photos for chain retail & franchised stores, as well as local photo shops, with a sustainable 24" large format printer - where accuracy meets vibrancy. Unlock an eye-catching spectrum of colours with PANTONE™¹ precision, thanks to the innovative new LUCIA PRO II ink³, especially orange ink. Get sustained productivity without compromising on image quality and longevity.

- **Professional image quality**
Dive into a world of vivid and faithful colours that captivate, paired with enhanced black density that brings more depth to your photographs and premium posters. The imagePROGRAF GP-2600S goes beyond ink – it provides total colour accuracy, perfect colour gradation and highlights a wide PANTONE™ coverage²
- **Enhanced productivity**
Transform printing workflows with easier media handling and simplified settings. Enhance efficiency with dual rolls, auto media loading, mirrored ink arrangement with high speed printing. With new print head monitoring function and auto alignment adjustment, masterpieces are created with confidence without image deterioration.
- **Increased durability**
Preserve your premium posters for 200 years⁴ with better light fastness using high light-resistance ink. Improve image robustness with high scratch resistant ink helps ensure your prints last a lifetime
- **Improved sustainability**
Protect the environment by using less power during both operation and power-off. It is EPEAT Gold rated⁵ and its packaging is free from expanded polystyrene

¹PANTONE™ is a trademark or registered trademark of Pantone LLC.

²PANTONE FORMULA GUIDE Solid Coated colour gamut coverage rate is 96% for GP-6600S/4600S/2600S, when using Premium Semi-Glossy Paper 2 with imagePROGRAF printer driver at [High] [Color Correction Off]; coverage rate is 82% when using Heavyweight Coated Paper HG with imagePROGRAF printer driver at [High] [Color Correction Off]

³Five of the seven inks are newly developed. The matte black and orange inks are the same as those used by the imagePROGRAF GP-2000/4000.

⁴When using Canon Heavyweight Coated Paper HG 145gsm. Predicted value calculated in accordance with the indoor light resistance test method and life evaluation criteria of the digital colour photographic print image preservation evaluation method (JEITA CP-3901B) published by JEITA (Japan Electronics and Information Technology Industries Association).

⁵EPEAT Gold registered in the U.S.

Canon

TECHNICAL SPECIFICATIONS

imagePROGRAF GP-2600S

PRINTER TECHNOLOGY		Margins Printable Area	
Printer Type	7 Colours 24"	Roll paper: Top: 3mm, Bottom: 3mm, Side: 3mm Roll paper (borderless): Top: 0mm, Bottom: 0mm, Side: 0mm Cut sheet: Top: 3mm, Bottom: 12.7mm, Side: 3mm	
Print Technology	Canon Bubblejet on Demand 12 colours integrated type (12 chips per print head x 1 print head)	Media Feed Capacity	
Print Resolution	2,400 x 1,200 dpi	Roll Paper: Two rolls. Automatic switching is possible Roll Paper, Cut Sheet: Manual switching is possible Cut Sheet: 1 sheet	
Number of Nozzles	18,432 nozzles (MBK/C/M/Y/O:1536nozzles x2, PBK/GY:1536nozzles x1)	Media Take-Up Roll Unit	
Line Accuracy	±0.1% or less User adjustments necessary. Printing environment and media must match those used for the adjustments.	Dual direction roll take up unit allowing print surface to be wound inside or outside of the roll	
Nozzle Pitch	600 dpi x 2 includes Non-firing nozzle detection and compensation system	Borderless Printing Width (Roll Only)	
Ink Droplet Size	minimum 4pl per colour	[Recommended] 515mm(JIS B2), 594mm(ISO A1), 10", 14", 17", 24" [Printable] 257mm(JIS B4), 297mm(ISO A3), 329mm(ISO A3+), 364mm(JIS B3/B4), 420mm(ISO A2), 6", 8", 12", 15", 16", 18", 20", 22", 300mm, 500mm, 600mm Other than above, free size borderless printing is supported on only roll paper by user definition	
Ink Capacity	Bundled Starter Ink: 1970ml (160ml for PBK & Grey, 330ml for others) Sales Ink: 160ml / 330ml / 700ml	Maximum Number of Delivered Prints	
Ink Type	Pigment inks : 7 colours (Matte Black, Photo Black, Cyan, Magenta, Yellow, Grey, Orange)	Standard position: 1 sheet Flat position: A2 landscape, glossy paper less than 10 sheets, coated paper less than 20 sheets (excludes strong curled condition)	
OS Compatibility	32 Bit: Windows7, Windows 8.1, Windows 10 64 Bit: Windows 7, Windows 8.1, Windows 10, Windows 11, Windows Server 2008R2, 2012, 2012R2, 2016, 2019, 2022 Apple Macintosh: macOS 10.15.7-macOS 13	POWER AND OPERATING REQUIREMENTS	
Others supported job submission protocol	Apple AirPrint	Power Supply	
Printer Languages	PDF (Ver.1.7), JPEG (Ver. JFIF 1.02)	Power Consumption	
Standard Interfaces	USB A Port: USB Memory (Direct Print) for PDF/JPEG files USB B Port: Hi-Speed USB Ethernet: IEEE802.3ab(1000base-T), IEEE802.3u(100BASE-TX)/IEEE802.3 (10BASE-T) Wireless LAN ¹⁾ : IEEE802.11n/IEEE802.11g/IEEE802.11b	AC 100-240V (50-60Hz) Operation: 91W or less Sleep mode: 2.2W or less Default setting for the time to enter the Sleep mode: Approx. 5 minutes Power off: 0.1W or less	
MEMORY		Operating Environment	
Standard Memory	3GB Expansion slot: No	Temperature: 15-30°, Humidity: 10-80% RH (no dew condensation) Operation: Approx. 48dB(A) (Measured based on ISO7779 Photo Glossy Paper HG/Standard/24") Standby: 35 dB(A) or less Operation: 6.5 Bels or less (Measured based on ISO7779 Photo Glossy Paper HG/Standard/24")	
Hard Drive	500 GB (Encrypted HDD)	Regulations	
PRINTING SPEED		Environment	
Plain paper (A1) 0:29 (Level 5)		CB certification, EPEAT GOLD ²⁾	
Coated paper (A1) 0:47 (Fast) 1:23 (Standard)		DIMENSIONS AND WEIGHT	
Glossy Photo Paper (A1) 1:42 (Fast) 2:43 (Standard)		Physical Dimensions and Weight	
MEDIA HANDLING		W x D x H Main unit + Stand 1110×984×1168 mm (Basket Opened) 1110×766×1168 mm (Basket Closed) 100kg (including Roll Holder Set, excluding ink and print head)	
Media Feed and Output	Upper Roll Paper : One Roll, Upper-loading, Front Output Lower Roll Paper: One Roll, Front-loading, Front Output Cut Sheet : Upper-loading, Front Output (Manual feed using media locking lever)	Packaged Dimensions and Weight	
Media Width	Roll paper: 152.4 - 610mm Cut sheet: 152.4 - 610mm	WHAT'S INCLUDED	
Media Thickness	Roll/Cut : 0.07 - 0.8mm	What's in the Box?	
Minimum Printable Length	Roll paper: 101.6mm (Cross and canvas paper: 200mm) Cut sheet: 203.2mm	Printer, Printer Stand, 1 Print head, Power Cable, 1 Set of starter ink tanks, 1 Roll holder (spool), 3" Paper Core Attachment, Installation Guide, Safety/Standard Environment leaflet, LFP Eur Address Sheet, Important Information Sheet, Stack Printer Stand Setup Guide, Notice for PosterArtist WEB	
Maximum Printable Length	Roll paper : 18m (varies according to the OS and application) Cut sheet : 1.6m	Software Included	
Maximum Media Roll Diameter	170mm	OPTIONS	
Media Core Size	Internal diameter of roll core: 2"/3"	Optional Items	
Margins Recommended Area	Roll paper: Top: 20mm, Bottom: 3mm, Side: 3mm Cut sheet: Top: 20mm, Bottom:20mm, Side:3mm	CONSUMABLES	
		User Replaceable Items	
		Ink Tank: MBK/Orange: PFI-2100(160ml)/PFI-2300(330ml)/PFI-2700(700ml) Others:PFI-3100(160ml)/PFI-3300(330ml)/PFI-3700(700ml) Print Head: PF-10 Cutter Blade: CT-07 Maintenance Cartridge: MC-30	



^[1] Please refer to user manual how to activate/deactivate the wireless LAN

^[2] EPEAT Gold registered in the U.S.

Disclaimer

Some images are simulated for clarity of reproduction. All data is based on Canon's standard testing methods. This leaflet and the specifications of the product have been developed prior to the date of product launch. Final specifications are subject to change without notice.TM and ®: All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.

Canon recommends you use Canon Media for the best results. Please check media (paper) compatibility list to see which variety of paper/media is recommended.

Canon Inc.
canon.com

Canon Europe
canon-europe.com

English edition
© Canon Europa N.V., 2025

