## imagePROGRAF GP-300

# STAND OUT FROM THE CROWD WITH VIBRANT, PREMIUM QUALITY POSTERS

A compact, large format printer expertly designed for high impact poster design, POS and signage with vibrant colours, ideal for stand-out retail and hospitality marketing.





• Vibrant neon colours

Stand out from other stores with the vibrant fluorescent pink ink, adding neon expression to your poster design for an eye-catching finish

• Simple design software

Embrace the power of customisation with easy-to-use design software, including new PosterArtist with new templates and stock photo resource

Free-size borderless printing

Free-size borderless printing makes poster production easier than ever, with high-precision paper edge detection supporting prints of all sizes

Direct to print

Built-in HDD allows to reprint saved data easily, plus JPG/PDF images can be printed directly from a USB memory

Compact design

Maximise available office space with a small footprint printer that fits flat against the wall to offer full front usability, perfect for smaller offices

Security assured

Have confidence in your data security with pin-accessed Security Print feature, plus built-in secure file erasure function, preventing information leakage or loss



### PRODUCT RANGE



imagePROGRAF GP-200



imagePROGRAF GP-4000



imagePROGRAF GP-2000



## **TECHNICAL SPECIFICATIONS**

## imagePROGRAF GP-300

TECHNOLOGY		Media Feed Capacity	Roll Paper : 1 roll Cut Sheet : 1 sheet
Printer Type	6 Colour 36"	Borderless Printing Width	[Recommended] 515 mm (JIS B2), 728 mm (JIS B1), 594
Print Technology	Canon Bubblejet on Demand 6 colours integrated type (6 chips per print head x 1 print head)	(Roll Only)	mm (ISO A1), 841 mm (ISO A0), 10", 14", 17", 24", 36" [Printable] 257 mm (JIS B4), 297 mm (ISO A3), 329 mm
Print Resolution	2,400 x 1,200 dpi		(ISO A3+), 420 mm (ISO A2), 8", 12", 15", 16", 18", 20", 22", 30", 34", 300 mm, 500 mm, 600 mm, 800 mm, and
Number of Nozzles	Total : 15,360 nozzles MBK, BK, C, M, Y, FP : 2,560 nozzles each		custom roll width (203.2 - 917 mm)
Line Accuracy	±0.1% or less User adjustments necessary. Printing environment and media must match those used for the adjustments. CAD paper required: Plain paper, CAD tracing paper, coated paper, CAD translucent matte film only	Maximum number of delivered prints DIMENSIONS AND WEIGHT	Standard position of the basket : 1 sheet
Nozzle Pitch	1,200 dpi x 2 includes Non-firing nozzle detection and compensation system	Physical Dimensions WxDxH (mm) and Weight (Kg)	1289 x 870 x 1060 mm (Basket Open) 1289 x 757 x 1060 mm (Basket Closed) 59 kg (Main Unit + Stand + Basket, including Roll Holder
Ink Droplet Size	minimum 5 pl per colour		Set, excluding ink and print head)
Ink Capacity	Bundled Starter Ink: 90 ml (MBK, BK, C, M, Y, FP) Sales Ink: 130 ml/300 ml	Packaged Dimensions WxDxH (mm) and Weight (Kg)	Printer (Main unit with pallet) : 1462 x 913 x 709 mm 79 kg
Ink Type	Pigment inks : 6 colour MBK/BK/C/M/Y/FP		Stand + Basket : 1362 x 824 x 268 mm 17 kg
OS Compatability	Microsoft Windows 32 Bit : 7, 8.1, 10 Microsoft Windows 64 Bit : 7, 8.1, 10, Windows Server 2008R2, 2012, 2012R2, 2016, 2019 Apple Macintosh : macOS 10.13.6 - macOS 11	POWER AND OPERATING REQUIREMENTS	
Printer Languages	PDF (Ver.1.7), JPEG (Ver. JFIF 1.02)	Power Supply	AC 100-240V (50-60Hz)
Standard Interfaces	USB A Port : USB Memory Direct Print for JPEG/PDF files USB B Port : Built-in HI-Speed USB Ethermet : IEEE 802.3 10base-T, IEEE 802.3u 100base-TX / Auto-Negotiation, IEEE 802.3ab 1000base-T /	Power Consumption	Operation : Approx. 75 W Sleep mode : Approx. 2.0W Default setting for the time to enter the Sleep mode : Approx. 5 Minutes Power off : Approx. 0.2 W
	Auto-Negotiation, IEEE 802.3x Full Duplex Wireless LAN : IEEE802.11n/IEEE802.11g/IEEE802.11b *Please refer to user manual how to activate/deactivate the	Operating Environment	Temperature : 15-30°c, Humidity : 10-80% RH (no dew condensation)
MEMORY	wireless LAN	Accoustic Noise (Power/Pressure)	Pressure Operation : 49 dB (A) (Plain paper, Standard mode, Poster) (Measured on ISO7779 standard)
Standard memory	2GB Expansion slot : No		Standby : 35 dB (A) or less Power Operation : 6.7 Bels (Plain paper, Standard mode, Poster)
Hard Drive	500GB	Regulations	(Measured on ISO7779 standard) Europe : CE mark
PRINTING SPEED			Other Countries : CB certfication
Poster:		Enviroment Certificates	TUV, CB
Plain Paper (A0)	0:44 (Fast) 1:18 (Standard)	WHAT'S INCLUDED	
Heavy coated Paper (A0)	1:41 (Fast) 2:36 (Standard)	What's in the Box?	Printer, 1 print head, 1 roll holder (spool), 3 inch paper core attachment, Power Cable, 1 set of starter ink tanks, Set up
Glossy photo Paper (A0)	6:19 (Standard) 9:41 (High Quality)		guide, Printer Stand Setup Guide, Quick Guide, Safety/ Standard Environment leaflet, User software CD-ROM (Win), PosterArtist Lite CD-ROM, EU Biocide Sheet, Important Information Sheet
MEDIA HANDLING		Software Included	imagePROGRAF GP Printer Driver and PosterArtist Lite
Media Feed and Output	Roll Paper : One Roll, Upper-loading, Front Output Cut Sheet : Upper-loading, Front Output (Manual feed using media locking lever)		Other software available as Download from Web.
Media Width	Roll paper : 203.2 mm - 917 mm Cut sheet : 203.2 mm - 917 mm	OPTIONS Optional Items	2/3" Roll Holder : RH2-35
Media Thickness	Roll/Cut : 0.07 mm - 0.8 mm		
Minimum Printable Length	Roll paper : 203.2 mm Cut sheet : 279.4 mm	CONSUMABLES User Replaceable Items	Ink Tank : PFI-120 (130ml), PFI-320 (300ml)
Maximum Printable Length	Roll paper : 18 m (Varies according to the OS and application) Cut sheet : 1.6 m		Print Head : PF-07 Cutter Blade : CT-08 Maintenance Cartridge : MC-31
Maximum Media Roll Diameter	150 mm		
	150 11111	Disclaimer	

Some images are simulated for clarity of reproduction. All data is based on Canon's standard testing methods. This leaflet and the specifications of the product have been developed prior to the date of product launch. Final specifications are subject to change without notice.<sup>14</sup> and \* All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.

Canon recommends you use Canon Media for the best results. Please check media (paper) compatibility list to see which variety of paper/media is recommended.









Canon Ireland 3006 Lake Drive Citywest, Saggart Co. Dublin, Ireland Telephone No: 01 2052400 Facsimile No: 01 2052525 canon.ie

### Canon (UK) Ltd The Bower 4 Roundwood Avenue Stockley Park Uxbridge UB11 1AF

Canon Inc. canon.com Canon Europe canon-europe.com English edition © Canon Europa N.V.,2024



#### MEDIA HANDLI Media Feed and

Maximum Media Media Core Size Margins Recommended area

Margins Printable area

ernal diameter of roll core : 2"/3" Roll paper: Top: 20 mm, Bottom: 3 mm, Side: 3 mm Cut sheet: Top: 20 mm, Bottom: 20 mm, Side: 3 mm Roll paper : Top: 3 mm, Bottom: 3 mm, Side: 3 mm Roll paper (borderless print) : Top: 0 mm, Bottom: 0 mm, Side: 0 mm Cut sheet : Top: 3 mm, Bottom: 20 mm, Side: 3 mm