

imagePROGRAF TM-250 MFP Lm24 imagePROGRAF TM-255 MFP Lm24

# PERFORMANCE REIMAGINED

Elevate experiences with a sustainable 24" multifunction printer, with less noise operation, enhanced productivity and intuitive functionality to create professional quality prints with sharp, crisp lines and vivid red colour -perfect for eye-catching CAD drawings and marketing materials. Integrated scanning functionality with dedicated software boosts productivity, print and scan at speed for a more seamless workflow

#### Integrated functionality

Print and scan seamlessly with an easy-to-use multi-tasking device, featuring a 3" touchscreen panel on the scanner and dedicated software, for parallel processing with printing and scanning simultaneously

### Professional printing quality

Use stable image enhancements to create sharp, crisp lines and new magenta ink for vivid red colour. As a result, you'll produce vivid and accurate CAD drawings, posters and educational materials

#### Enhanced productivity

Produce A1 CAD prints in just 20 seconds, or A1 posters in 22 seconds. Save time trimming excess margins with borderless prints of any size and easily meet high print demand with larger ink tanks, quick processing time and a fast return from sleep mode

#### Intuitive functionality

Follow easy instructions and take in important information like media type, remaining media and ink amount on a 4.3" touchscreen panel. Save time by setting roll paper with quick access through a flat-top cover



## **TECHNICAL SPECIFICATIONS**

## imagePROGRAF TM-250 MFP Lm24 imagePROGRAF TM-255 MFP Lm24

SCANNER TECHNOLOGY

Scan Technology Maximum Resolution (dpi)

Scan Speed

Scan Modes

24" / 609.6mm Maximum Scan Width

Minimum Scan Width Maximum Document Width Maximum Scan Length

Document Thickness

Scan Accuracy Interface USB Scan to Network

Languages

Control Panel Weight of Scanner Dimensions (W x D x L)

Compliances

PRINTER TECHNOLOGY

Print Technology Print Resolution

Printer Type

Number of Nozzles

Line Accuracy Nozzle Pitch

Ink Droplet Size Ink Capacity

Ink Type OS Compatibility

Others supported job submission protocol

Printer Languages

SingleSensor with multiple LED Illumination

600dpi

COPY
300/300dpi Draft = 1ips colour, 4.5ips mono
300/600dpi Standard = 1ips colour, 3ips mono
600/600dpi Standard = 1ips colour, 1.5ips mono
600/600dpi Best = 0.5ips colour, 1.5ips mono
SCAN
200dpi Draft = 1ips colour, 4.5ips mono
300/600dpi Standard = 1ips colour, 3ips mono
600/600dpi Best = 0.5ips colour, 1.5ips mono

Scan to USB - RGB/Greyscale/BW, TIFF (No ScanAppL) Scan to USB - RGB/Greyscale/BW, JPG, PDF, PDF/A, M-PDF (ScanAppL available) Scan to PC - RGB/Greyscale/BW, Tiff, JPEG, PDF, PDF/A, TiffG4, M-PDF

M-PDF Copy - RGB/Greyscale/BW Copy & Archive - (Combination of Copy and Scan to PC above). Cloud connectivity is a chieved by a link to Canon's Direct Print & Share. PRINT is achieved by using Canon's Direct Print & Share.

Face up, rear exit. Forward document transport only Document return guide(s) included

6.2" / 157.4mm 26" / 660.4mm 109" / 2768mm

Designed to scan Canon iPF printer CAD paper. Min = 0.07mm Max = 0.8mm

Accuracy 0.2% +/-1 pixel USB2, 128GB FAT32.

ScanAppl - Sets scan directory.
Minimum PC specification: • Windows 10/11 - 32bit.
• 100Mbs Ethernet - Intel Celeron, Core-Duo, Core-2-Duo or
2.8GHz Hyper-Threading (HT) or AMD Dual-Core processors
• 20B RAM - High speed 7,200pm Serial ATA (SATA) HDD with
minimum 20B for applications and 206 free for images.

ScanAppL English/French/German/Italian/Spanish/Simplified Chinese/Traditional Chinese/Korean/Russian/Portuguese Japanese/Czech/Polish

3" touch screen display

5.28kg (11.6lbs) without Doc return guide

Midth: 935mm, Height 131mm Depth: Without Doc Return Guide - Paper tray folded: 146mm Without Doc Return Guide - Paper Tray flat: 193mm With Doc Return Guide - Paper Tay flat: 263mm With Doc Return Guide - Paper Tray flat: 253mm

Europe : CE mark, Other countries : CB certification

Lm24 scanner
Printer mounting brackets, fixings & 3mm tool
2 feet for desktop use
2 paper edge guides
1 Document return guides
Calibration target
CD for ScanAppL software and PDF documentation:
Lm24 Scanner User Manual per language and Quick Start Guide.
Ethernet cable (2 meter)
Power Supply
Regional - Mains power cord(s) (2 meter)

Canon Bubblejet on Demand 6 colours integrated type (6 chips per print head x 1 print head)

2.400 x 1.200 dpi

Total: 15360 nozzles MBK: 5120 nozzles BK, C, M, Y: 2560 nozzles each

 $\pm 0.1\%$  or less User adjustments necessary. Printing environment and media must match those used for the adjustments.

1,200 dpi x 2 lines minimum 5pl per colour

Bundled Starter Ink: 490ml (130ml for MBK, 90mlx4 for BK, C, M, Y) Sales Ink: 300 / 130ml (MBK, BK, C, M, Y) Pigment inks : 5 colours MBK/BK/C/M/Y

32 Bit: Windows7, Windows 8.1, Windows 10 64 Bit: Windows 7, Windows 8.1, Windows 10, Windows 11, Windows Server 2008R2, 2012, 2012R2, 2016, 2019, 2022 Apple Macintosh: macOS 10.15.7 macOS 13

Apple AirPrint

TM 250

HP-GL/2, HP RTL, JPEG (Ver. JFIF 1.02), CALS G4 (submission via FTP only)

TM 255

HP-GL/2, HP RTL, PDF (Ver. 1.7), JPEG (Ver. JFIF 1.02), CALS G4 (Submission via FTP)

Standard Interfaces

USB B PORT: HI-Speed USB Ethernet: IEEE802.3ab(1000base-T), IEEE802.3u(100BASE-TX)/ IEEE802.3 (10BASE-TX) Wireless LAN: IEEE802.1lb LEEE802.1lb LEEE80 \*Please refer to user manual how to activate/deactivate the wireless LAN

2GB Expansion slot: No

N/A

PRINTING SPEED CAD Drawing

Standard Memory

MEMORY

Hard Drive

Poster

MEDIA HANDI ING

Media Feed and Output

Minimum Printable Length

Maximum Printable Length

Maximum Media Roll Diameter Media Core Size

Margins Recommended Area

Margins Printable Area

Media Feed Capacity Media Take-Up Roll Unit

Borderless Printing Width (Roll Only)

Maximum Number of Delivered Prints

WHAT'S INCLUDED What's in the Box?

Software Included

Optional Items

CONSUMABLES User Replaceable Items SB A Port: N/A SB B Port: Hi-Speed USB

USB A Port: USB Memory (Direct Print) USB B Port: Hi-Speed USB

USB B POT: HI-Speed USB Ethernet: IEEE802.3ab(100Dbase-T), IEEE802.3u(100BASE-TX)/ IEEE802.3 (10BASE-T) Wireless LAN: IEEE802.11n/ IEEE802.1g/IEEE802.11b "Please refer to user manual how to activate/deactivate the wireless LAN

128GB (Physcial memory 2GB) Expansion slot : No

500GB (Encrypted)

Plain paper (A1): 0:20 (Fast Economy Mode) 0:23 (Fast) 0:40 (Standard)

Plain paper (A1): 0:22 (Fast Economy Mode) 0:25 (Fast) 0:44 (Standard)

Heavy coated paper (A1): 0:55 (Fast) 1:23 (Standard)

Roll Paper : One Roll, Upper-loading, Front Output Cut Sheet : Upper-loading, Front Output (Manual feed using media locking lever)

Roll paper: 203.2 - 610mm Cut sheet: 203.2 - 610mm Roll/Cut : 0.07mm - 0.8mm

Roll paper: 203.2mm Cut sheet: 279.4mm Roll paper : 18m (varies according to the OS and application) Cut sheet : 1.6m

150mm

Internal diameter of roll core: 2"/3"

Roll paper: Top: 20mm, Bottom: 3mm, Side: 3mm Cut sheet (AppleAirPrint): Top: 20mm, Bottom: 31mm, Side: 3mm Cut sheet (Others): Top: 20mm, Bottom:20mm, Side:3mm

Roll paper: Top: 3mm, Bottom: 3mm, Side: 3mm Roll paper (borderless): Top: 0mm, Bottom: 0mm, Side: 0mm Cut sheet (AppleAiPPrint): Top: 3mm, Bottom: 12.7mm, Side: 3mm Cut sheet (Others): Top: 3mm, Bottom: 20mm, Side: 3mm

Roll Paper: One roll Cut Sheet: 1 sheet

[Recommended] 515mm(JIS B2), 594mm (ISO A1), 10", 14", 17", 24"

[Printable] 257mm(JIS B4), 297mm(ISO A3), 329mm(ISO A3+), 420mm(ISO A2), 515mm(JIS B3), 8", 12", 15", 16", 18", 20", 22", 300mm, 500mm, 600mm Other than above, free size borderless printing is supported on only roll paper by user definition

Standard position: 1 sheet Folding position: Plain paper 20 sheets on A1 portrait Flat position: Plain paper 20 sheets on A2 landscape (exclude strong curled position)

Printer, Printer Stand, 1 Print head, Power Cable, 1 Set of starter ink tanks, Installation Guide, Safety/Standard Environment leaflet, LFP Eur Address Sheet, Important Information Sheet, Stack Printer Stand Setup Guide, Notice for PosterArtist WEB

Software available as Download from Web

2"/3" Roll Holder: RH2-28 IC Card Reader Holder: RA-02

Ink Tank: M:PFI-321(300ml) / PFI-121(130ml), MBK/RX/C/Y:PFI-320(300ml)/ PFI-120(130ml) Print Head: PF-06 Cutter Blade: CT-08 Maintenance Cartridge: MC-31

#### Disclaimer

Some images are simulated for clarity of reproduction. All data is based on Canon's standard testing methods. This leaflet and the specifications of the product have been developed prior to the date of product launch. Final specifications are subject to change without notice.\*\* and \*\*, All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.

Canon recommends you use Canon Media for the best results. Please check media (paper) compatibility list to see which variety of paper/media is recommended.









Canon Inc. canon.com

Canon Europe canon-europe.com

English edition © Canon Europa N.V.,2025

