



imagePROGRAF TM-340

PERFORMANCE REIMAGINED

Reimagine printing performance with the sustainable 36" imagePROGRAF TM-340, offering less noise printing, more intuitive functionality and brilliant image quality. Seamlessly produce sharp, crisp lines and vivid red colour for eye-catching marketing materials and accurate CAD prints for AEC offices, retail and education.

- **Enhanced professional quality**
The new magenta ink produces a more brilliant red and stable image enhancements mean crisper lines. Print vivid and accurate CAD drawings, posters, educational materials and more
- **Reliable productivity**
Productivity that you can count on, with reliable performance, faster processing time and a quick return from sleep mode. Save time trimming excess margins with borderless print, giving full bleed images of any size, straight from the device
- **Intuitive functionality**
Functional design with a 4.3" touch screen panel displaying intuitive instructions and important information, like media type, remaining media and ink amount. Roll paper can be replaced with ease on the flat-top cover
- **Improved sustainability**
Environmentally conscious EPEAT Gold* rated device for low energy consumption, with power reduction during standby and packaging free from polystyrene foam. Less noise printing makes it ideal for quiet offices

*EPEAT Gold registered in the U.S.

Canon

TECHNICAL SPECIFICATIONS

imagePROGRAF TM-340

PRINTER TECHNOLOGY

Printer Type	5 Colours 36"
Print Technology	Canon Bubblejet on Demand 6 colours integrated type (6 chips per print head x 1 print head)
Print Resolution	2,400 x 1,200 dpi
Number of Nozzles	Total: 15360 nozzles MBK: 5120 nozzles BK, C, M, Y: 2560 nozzles each
Line Accuracy	±0.1% or less User adjustments necessary. Printing environment and media must match those used for the adjustments.
Nozzle Pitch	1,200 dpi x 2 lines
Ink Droplet Size	minimum 5pl per colour
Ink Capacity	Bundled Starter Ink: 300ml (80ml for MBK, 55ml x 4 for BK, C, M, Y) Sales Ink: 55ml (MBK, BK, C, M, Y)
Ink Type	Pigment inks : 5 colours MBK/BK/C/M/Y
OS Compatability	32 Bit: Windows 7, Windows 8.1, Windows 10 64 Bit: Windows 7, Windows 8.1, Windows 10, Windows 11, Windows Server 2008R2, 2012, 2012R2, 2016, 2019, 2022 Apple Macintosh: macOS 10.15.7-macOS 13
Others supported job submission protocol	Apple AirPrint
Printer Languages	HP-GL/2, HP RTL, JPEG (Ver. JFIF 1.02), CALS G4 (submission via FTP only)
Standard Interfaces	USB A Port: N/A USB B Port: Hi-Speed USB Ethernet: IEEE802.3ab (1000base-T), IEEE802.3u (100BASE-TX)/IEEE802.3 (10BASE-T) Wireless LAN: IEEE802.11n/IEEE802.11g/IEEE802.11b *Please refer to user manual how to activate/deactivate the wireless LAN
MEMORY	
Standard memory	2GB Expansion slot : No
PRINTING SPEED	
CAD Drawing	
Plain Paper (A1)	0:21 (Fast Economy Mode), 2.7ppm
Plain Paper (A0)	0:41 (Fast Economy Mode) 0:42 (Fast) 1:25 (Standard)
Poster	
Plain Paper (A0)	0:43 (Fast Economy Mode) 0:43 (Fast) 1:25 (Standard)
Heavy coated paper (A0)	1:42 (Fast) 3:10 (Standard)
MEDIA HANDLING	
Media Feed and Output	Roll Paper : One Roll, Upper-loading, Front Output Cut Sheet : Upper-loading, Front Output (Manual feed using media locking lever)
Media Width	Roll paper: 203.2 - 917mm Cut sheet: 210 - 917mm
Media Thickness	Roll/Cut : 0.07mm - 0.8mm
Minimum Printable Length	Roll paper: 203.2mm Cut sheet: 279.4mm
Maximum Printable Length	Roll paper : 18m (varies according to the OS and application) Cut sheet : 1.6m
Maximum Media Roll Diameter	150 mm
Media Core Size	Internal diameter of roll core: 2 1/3" (Optional)
Margins Recommended area	Roll paper: Top: 20mm, Bottom: 3mm, Side: 3mm Cut sheet(AppleAirPrint): Top: 20mm, Bottom: 31mm, Side: 3mm Cut sheet (Others): Top: 20mm, Bottom:20mm, Side:3mm
Margins Printable area	Roll paper: Top: 3mm, Bottom: 3mm, Side: 3mm Roll paper (borderless): Top: 0mm, Bottom: 0mm, Side: 0mm Cut sheet (AppleAirPrint): Top: 3mm, Bottom: 12.7mm, Side: 3mm Cut sheet (Others): Top: 3mm, Bottom: 20mm, Side: 3mm
Media Feed Capacity	Roll Paper: One roll Cut Sheet: 1 sheet

Borderless Printing Width (Roll Only)

	[Recommended] 515mm(JIS B2), 728mm(JIS B1), 594mm(ISO A1), 841mm(ISO A0), 10", 14", 17", 24", 36" [Printable] 257mm(JIS B4), 297mm(ISO A3), 329mm(ISO A3+), 420mm(ISO A2), 515mm(JIS B3), 8", 12", 15", 16", 18", 20", 22", 30", 34", 300mm, 500mm, 600mm, 800mm Other than above, free size borderless printing is supported on only roll paper by user definition Standard position - 1 sheet
Maximum number of delivered prints	
POWER AND OPERATING REQUIREMENTS	
Power Supply	AC 100-240V (50-60Hz)
Power Consumption	Operation: 65W or less Sleep mode: 2.2W or less Default setting for the time to enter the Sleep mode: Approx. 5 minutes Power off: 0.1W or less
Operating Environment	Temperature: 15-30°C, Humidity: 10-80% RH (no dew condensation) Operation: Approx. 39dB(A) (Standard Plain Paper, Standard mode, Line Drawing/Text mode) (Measured based on ISO7779 standard) Standby: 35 dB(A) or less Operation: 6.0 Bels or less (Standard Plain Paper, Standard mode, Line Drawing/Text mode) (Measured based on ISO7779 standard)
Acoustic Noise (Power/Pressure)	
Regulations	CE mark, UKCA mark
Enviroment Certificates	CB certification, EPEAT GOLD ¹⁾
DIMENSIONS AND WEIGHT	
Physical Dimensions and Weight	W x D x H Main unit with stand 1285 x 868 x 1060 mm (Operation panel is not tilted up/Basket Opened) 1285 x 756 x 1060 mm (Operation panel is not tilted up/Basket Closed) 59.2 kg (including Roll Holder Set, excluding ink and print head)
Packaged Dimensions and Weight	Printer (Main unit with stand and pallet): 1462 x 912 x 801 mm, 100kg
WHAT'S INCLUDED	
What's in the Box?	Printer, Printer Stand, 1 Print head, Power Cable, 1 Set of starter ink tanks, 1 Roll holder (spool), Installation Guide, Safety/Standard Environment leaflet, LFP Eur Address Sheet, Important Information Sheet, Basic Printer Stand Setup Guide, Notice for PosterArtist WEB
Software Included	Software available as Download from Web
OPTIONS	
Optional Items	2 1/3" Roll Holder: RH2-35 IC Card Reader Holder: RA-02
CONSUMABLES	
User Replaceable Items	Ink Tank: M: PFI-031(55ml), MBK/BK/C/Y:PFI-030(55ml) Print Head: PF-06 Cutter Blade: CT-08 Maintenance Cartridge: MC-31

¹⁾ EPEAT Gold registered in the U.S.

Disclaimer

Some images are simulated for clarity of reproduction. All data is based on Canon's standard testing methods. This leaflet and the specifications of the product have been developed prior to the date of product launch. Final specifications are subject to change without notice.™ and ®: All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.

Canon recommends you use Canon Media for the best results. Please check media (paper) compatibility list to see which variety of paper/media is recommended.



Canon Inc.
canon.com

Canon Europe
canon-europe.com

English edition
© Canon Europa N.V., 2025