

imagePROGRAF TM-350 MFP Lm36 imagePROGRAF TM-355 MFP Lm36

PERFORMANCE REIMAGINED

Elevate experiences with a sustainable 36" multifunction printer, with less noise operation, enhanced productivity and intuitive functionality to create professional quality prints with sharp, crisp lines and vivid red colour -perfect for eye-catching CAD drawings and marketing materials. Integrated scanning functionality with dedicated software boosts productivity, print and scan at speed for a more seamless workflow.

Integrated functionality

Print and scan seamlessly with an easy-to-use multi-tasking device, featuring a 3" touchscreen panel on the scanner and dedicated software, for parallel processing with printing and scanning simultaneously

Professional printing quality

Use stable image enhancements to create sharp, crisp lines and new magenta ink for vivid red colour. As a result, you'll produce vivid and accurate CAD drawings, posters and educational materials Enhanced productivity

Produce A1 CAD prints in just 17 seconds, or A1 posters in 22 seconds. Save time trimming excess margins with borderless prints of any sizes and easily meet higher print demand with larger ink tanks, quick processing time and a fast return from sleep mode

Intuitive functionality

Follow easy instructions and take in important information like media type, remaining media and ink amount on a 4.3" touch screen panel. Save time by setting roll paper with quick access through a flat-top cover



TECHNICAL SPECIFICATIONS

imagePROGRAF TM-350 MFP Lm36 imagePROGRAF TM-355 MEP | m36

SPECIFICAT	ions ir	nagePROGRA	F IM-355 P	1FP LM36
SCANNER TECHNOLOGY			TM350	TM355
Scan technology	SingleSensor with multiple LED Illumination	Printer Languages	HP-GL/2, HP RTL, JPEG (Ver. JFIF 1.02), CALS G4	HP-GL/2, HP RTL, PDF (Ver. 1.7), JPEG
Maximum Resolution (dpi)	600dpi		(Submission via FTP only)	(Ver. JFIF 1.02), CALS G4
Scan Speed	COPY 300/300dpi Draft = 1ips colour, 3ips mono	Standard Interfaces	USB A Port: N/A	(Submission via FTP only) USB A Port: USB Memory
	300/600dpi Standard = 1ips colour, 3ips mono 600/600dpi Best = 0.5ips colour, 1.5ips mono	Standard Interfaces	USB B Port: Hi-Speed USB	(Direct Print)
			Ethernet: IEEE802.3ab(1000base-T),	USB B Port: Hi-Speed USB Ethernet:
	SCAN 200dpi Draft = 1ips colour, 3ips mono		IEEE802.3u(100BASE-TX)/ IEEE802.3 (10BASE-T)	IEEE802.3ab(1000base-T), IEEE802.3u(100BASE-TX)/
	300dpi Standard = 0.5ips colour, 1.5ips mono 600dpi Best = 0.33ips colour, 1ips mono		Wireless LAN: IEEE802.11n/	IEEE802.3 (10BASE-T)
Scan Modes	Scan to USB - RGB/Greyscale/BW, TIFF (No ScanApp)		IEEE802.11g/IEEE802.11b *Please refer to user manual how	Wireless LAN: IEEE802.11n/ IEEE802.11g/IEEE802.11b
	Scan to USB - RGB/Greyscale/BW, JPG, PDF, PDF/A, M-PDF (ScanApp available)		to activate/deactivate the wireless LAN	*Please refer to user manual how to activate/deactivate the
	Scan to PC - RGB/Greyscale/BW, Tiff, JPEG, PDF, PDF/A,		WITEIESS LAIN	wireless LAN
	TiffG4, M-PDF Copy - RGB/Greyscale/BW	MEMORY		
	Copy & Archive - (Combination of Copy and Scan to PC above).	Standard memory	2GB	128GB (Physcial memory
	Cloud connectivity is achieved by a link to Canon's Direct		Expansion slot: No	2GB) Expansion slot : No
	Print & Share. PRINT is achieved by using Canon's Direct Print & Share.	Hard Drive	N/A	500GB (Encrypted)
Paper Path	Face up, rear exit. Forward document transport only			
Mauinaum Casa Width	Document return guide(s) included	PRINTING SPEED		
Maximum Scan Width Minimum Scan Width	36" / 914.4mm 6" / 152.4mm	CAD Drawing Plain paper (A1)	0:17 (Fast Economy Mode) 3	2000
Maximum Document Width	38" / 965.2mm	Plain paper (A0)	0:32 (Fast Economy Mode)	.20011
Maximum Scan Length	109" / 2768mm		0:42 (Fast) 1:08 (Standard)	
Document Thickness	Designed to scan Canon iPF printer CAD paper.	Poster	1.06 (Stanuard)	
	Min = 0.07mm Max = 0.8mm	Plain paper (A0)	0:37 (Fast Economy Mode)	
Scan Accuracy	Accuracy 0.2% +/-1 pixel		0:43 (Fast) 1:08 (Standard)	
Interface USB	USB2, 128GB FAT32.	Heavy coated paper (A0)	1:40 (Fast)	
Scan to Network	ScanApp - Sets scan directory. Minimum PC specification: • Windows 7/8/10 - 32bit.		2:33 (Standard)	
	 100Mbs Ethernet. Intel Celeron, Core-Duo, Core-2-Duo 	MEDIA HANDLING		
	or 2.8GHz Hyper-Threading (HT) or AMD Dual-Core processors	MEDIA HANDLING Media Feed and Output	Roll Paper : One Roll, Upper-	loading Front Output
	 2GB RAM • High speed 7,200rpm Serial ATA (SATA) HDD with minimum 2GB for applications and 20GB free for 	Media Feed and Output	Cut Sheet : Upper-loading, F	ront Output
	images.	A	(Manual feed using media lo	cking lever)
	Suggested PC specification: • Windows 7/8/10 - 64bit. • GB Ethernet. • Intel i3,i5 or i7 processors • 4GB RAM	Media Width	Roll paper: 203.2 - 917mm Cut sheet: 203.2 - 917mm	
	High speed 7,200rpm Serial ATA (SATA) HDD with minimum 2GB for applications and 20GB free for images.	Media Thickness	Roll/Cut : 0.07mm - 0.8mm	
Languages	ScanApp	Minimum Printable Length	Roll paper: 203.2mm Cut sheet: 279.4mm	
	English/French/German/Italian/Spanish/Simplified Chinese/Traditional Chinese/Korean/Russian/Portuguese/	Maximum Printable Length	Roll paper : 18m	
	Japanese/Czech/Polish		(varies according to the OS a Cut sheet : 1.6m	and application)
Control Panel	3" touch screen display	Maximum Media Roll Diameter	150mm	
Weight of Scanner	6.56kg (14.5lbs) without Doc return guide	Media Core Size	Internal diameter of roll core: 2"/3"	
Dimensions (W x D x L)	Width: 1238mm, Height 131mm Depth:	Margins Printable area	Roll paper: Top: 3mm, Bottom: 3mm, Side: 3mm Roll paper (borderless): Top: 0mm, Bottom: 0mm, Side: 0mm	
	Without Doc Return Guide - Paper tray folded: 146mm Without Doc Return Guide - Paper Tray flat: 193mm		Roll paper (borderless): Top: 0 Cut sheet (AppleAirPrint): Top	
	With Doc Return Guide - Paper tray folded: 206mm With Doc Return Guide - Paper Tray flat: 253mm		Side: 3mm Cut sheet (Others): Top: 3mm,	Bottom: 20mm. Side: 3mm
Compliances	Europe : CE mark, Other countries : CB certification	Media Feed Capacity	Roll Paper: One roll	
What's in the Box?	Lm36 scanner		Cut Sheet: 1 sheet	
	Printer mounting brackets, fixings & 3mm tool 2 feet for desktop use	Borderless Printing Width (Roll Only)	[Recommended] 515mm(JIS B2), 728mm (JIS B1), 594mm (ISO A1), 841mm (ISO A0), 10", 14", 17", 24", 36"	
	2 paper edge guides 3 Document return guides		[Printable] 257mm(JIS B4), 2 (ISO A3+), 420mm(ISO A2),	297mm(ISO A3), 329mm
	Calibration target CD for ScanApp software and PDF documentation:		16", 18", 20", 22", 30", 34", 30 800mm	00mm, 500mm, 600mm,
	Lm36 Scanner User Manual per language and Quick Start		Other than above, free size	borderless printing is
	Guide. Lm36 Scanner Quick Start Guide.	Maximum Number of Delivered	supported on only roll paper Standard position: 1 sheet	by user definition
	Ethernet cable (2 meter) Power Supply	Prints	Folding position: Plain paper	20 sheets on A1 portrait /
	Regional - Mains power cord(s) (2 meter)		A0 portrait Flat position: Plain paper 20	sheets on A2 landscape /
			A1 landscape (exclude strong	g curled position)
PRINTER TECHNOLOGY	E Colours 70"	WHAT'S INCLUDED		
Printer Type Print Technology	5 Colours 36" Canon Bubblejet on Demand 6 colours integrated type (6	What's in the Box?	Printer, Printer Stand, 1 Print	head, Power Cable 1 Set of
Finit reciniology	Canon Bubblejet on Demand 6 colours integrated type (6 chips per print head x 1 print head)		starter ink tanks, Installation	Guide, Safety/Standard
Print Resolution	2,400 x 1,200 dpi		Environment leaflet, LFP Eur Information Sheet, Stack Prin	nter Stand Setup Guide,
Number of Nozzles	Total : 15360 nozzles MBK : 5120 nozzles BK, C, M, Y: 2560 nozzles each	Coffman Included	Notice for PosterArtist WEB	and from W/
Line Accuracy	±0.1% or less	Software Included	Software available as Downlo	bad from Web
	User adjustments necessary. Printing environment and media must match those used for the adjustments.	OPTIONS		
Nozzle Pitch	1,200 dpi x 2 lines	Optional Items	2"/3" Roll Holder: RH2-35	
Ink Droplet Size	minimum 5 pl per colour		IC Card Reader Holder: RA-02	
Ink Capacity	Bundled Starter Ink: 490ml	CONSUMABLES		
	(130ml for MBK, 90mlx4 for BK, C, M, Y) Sales Ink: 300 / 130ml (MBK, BK, C, M, Y)	User Replaceable Items	Ink Tank: M:PFI-321(300ml) / PFI-121(130ml),	
Ink Type	Pigment inks : 5 colours MBK/BK/C/M/Y		MBK/BK/C/Y:PFI-320(300ml) / PFI-120(130ml) Print Head: PF-06	
OS Compatability	32 Bit: Windows7, Windows 8.1, Windows 10	Dissiples of	Cutter Blade: CT-08 Maintenance Cartridge: MC-31	
	64 Bit: Windows 7, Windows 8.1, Windows 10, Windows 11, Windows Server 2008R2, 2012, 2012R2, 2016, 2019,		Disclaimer	
	2022 Apple Macintosh: macOS 10.15.7-macOS 13	leaflet and the specifications of the produ	uct have been developed prior to the da	te of product launch. Final
Others supported job	Apple AirPrint	specifications are subject to change with registered trademarks of their respective		
submission protocol	1	Canon recommends you use Canon Media for the best results. Please check media (paper) compatibility list to see		
		which variety of paper/media is recomme		
••••		Canon Ireland	Canon (UK) Ltd	Canon Inc.
				canon com

Canon Ireland 3006 Lake Drive Co. Dublin, Ireland Telephone No: 01 2052400 Facsimile No: 01 2052525 canon.ie

Canon (UK) Ltd The Bower Citywest, Saggart 4 Roundwood Avenue Stockley Park

canon.com Canon Europe canon-europe.com

English edition Uxbridge © Canon Europa N.V.,2023 UB11 1AF

L-COA PROI FINE



LUCIA TD