

imagePROGRAF TM-350 MFP Z36 imagePROGRAF TM-355 MFP Z36

PERFORMANCE REIMAGINED

Streamline print and scan workflows with a sustainable 36" multifunctional printer. Benefit from less noise operation, enhanced productivity and intuitive functionality to create professional quality prints with sharp, crisp lines and vivid red colour - perfect for eyecatching CAD drawings and marketing materials. Boost productivity with integrated scanning functionality with print and scan at speed for an efficient workflow.

Integrated functionality

Streamline print and scan process with a premium multi-tasking device. Embrace the 15.6" touchscreen panel on the scanner and latest software for seamless processing with printing and scanning simultaneously

Professional printing quality

Use stable image enhancements to create sharp, crisp lines and new magenta ink for vivid red colour. As a result, you'll produce vivid and accurate CAD drawings, posters and educational materials

Enhanced productivity

Produce A1 CAD prints in just 17 seconds, or A1 posters in 22 seconds. Save time trimming excess margins with borderless prints of any sizes and easily meet higher print demand with larger ink tanks, quick processing time and a fast return from sleep mode

Intuitive functionality

Follow easy instructions and take in important information like media type, remaining media and ink amount on a 4.3" touch screen panel. Save time by setting roll paper with quick access through a flat-top cover



TECHNICAL SPECIFICATIONS

imagePROGRAF TM-350 MFP Z36 imagePROGRAF TM-355 MFP Z36

SCANNER TECHNOLOGY

Scan Technology

Maximun Resolution (dpi)

Scan Width

Min. Scan Width

Document Width

Max. Scan Length

Weight of Scanner Dimension (W x D x L)

Document Handling - Face up/down

Document Thickness

Scan Speed 8-bit Grayscale & Mono @200dpi

Scan to PC: Scan Speed 24-bit Color @200dpi

Copy: Scan Speed 24-bit Color @200dpi

Interface USB

Branding/Colour

Software Included

PRINTER TECHNOLOGY

Printer Type

Print Resolution

Line Accuracy

Nozzle Pitch Ink Droplet Size Ink Capacity

Ink Type

OS Compatability

Others Supported Job Submission Protocol

Printer Languages

Standard Interfaces

Hard Drive

Single Sensor

1200dpi

36" (914mm) 6" (150mm)

38" (965mm) 8m (JPEG/PDF), 15.2m (TIFF)

7.8Kg

1056 x 199 x 118mm 1056 x 251 x 156mm with Doc return guide

Europe : CE mark, Other countries : CB Certification

Rear (front eject via Document Return Guide)

0.07 - 1.0mm

13ips

6ips

3.0 (backward compatible to USB2)

Stop, Advance, Rewind, LED status

None / Canon black SmartWorks MFP V6

SmartWorks MEP V6
Z36 scanner
Suspension mount for printer and system controller mount
2 paper edge guides
3 Document return guides
Calibration target
Assembly & Start Up Guide
USB3 cable (2 meter)
Fower Supply
15 Fower Supploiler
3:1 Trident power cord - requires 1 local mains cable

SSD: 256GB, RAM: 8GB DDR4.
Display: Multi touch 15.6", 1366 x 768. 3 x USB3 & 1 x USB2,
1 x GbF (rear). Power button and 1 x USB3 (Front)

5 Colours 36"

Canon Bubblejet on Demand 6 colours integrated type (6 chips per print head x 1 print head)

2,400 x 1,200 dpi

±0.1% or less User adjustments necessary. Printing environment and media must match those used for the adjustments.

1,200 dpi (2 lines)

minimum 5pl per colou

Bundled Starter Ink: 490ml (130ml for MBK, 90mlx4 for BK, C, M, Y) Sales Ink: 300 / 130ml (MBK, BK, C, M, Y)

Pigment inks: 5 colours MBK/BK/C/M/Y

HP-GL/2, HP RTL, JPEG (Ver. JFIF 1.02), CALS G4

USB A Port: N/A

HP-GL/2, HP RTL, PDF (Ver. 1.7), JPEG (Ver. JFIF 1.02), CALS G4 USB A Port: USB Memory (Direct

USB B Port: Hi-Speed USB Ethernet: IEEE802 3abt(1000base-T), IEEE802.3u (100BASE-TX)/IEEE802.3 (10BASE-T) Wireless LAN: IEEE802.1ln/IEEE802.1lg/IEEE802.1lb

*Please refer to user manual how to activate/deactivate the wireless LAN

2GB Expansion slot: No

N/A

128GB (Physcial memory 2GB) Expansion slot : No 500GB (Encrypted)

PRINTING SPEED

CAD Drawing:

Plain paper (A1): Plain Paper (A0):

Plain Paper (A0)

MEDIA HANDI ING

Media Feed and Output

Minimum Printable Length

Maximum Printable Length

Maximum Media Roll Diameter

Media Core Size Margins Recommended Area

Margins Printable area

Media Feed Capacity

Borderless Printing Width (Roll Only)

Maximum number of delivered prints

POWER AND OPERATING REQUIREMENTS

Power Supply

Power Consumption

Operating Environment

Accoustic Noise (Power/Pressure)

Physical Dimensions and Weight

WHAT'S INCLUDED

What's in the Box?

Software Included

OPTIONS Ontional Items

CONSUMABLES User Replaceable Items

0:17 (Fast Economy Mode) 3.2ppm

0:32 (Fast Economy Model) 0:41 (Fast) 1:08 (Standard)

0:37 (Fast Economy Model) 0:43 (Fast) 1:18 (Standard)

1:40 (Fast) 2:33 (Standard)

Roll Paper : One Roll, Upper-loading, Front Output Cut Sheet : Upper-loading, Front Output (Manual feed using media locking lever)

Roll paper: 203.2 - 917 mm Cut sheet: 203.2 - 917 mm

Roll/Cut: 0.07 - 0.8 mm

Roll paper: 203.2 mm Cut sheet: 279.4 mm

Roll paper: 18 m (Varies according to the OS and application) Cut sheet: 1.6 m

Internal diameter of roll core: 2"/3"

Roll paper: Top: 20mm, Bottom: 3mm, Side: 3mm Cut sheet (AppleAirPrint): Top: 20mm, Bottom: 31mm, Side: 3mm Cut sheet (Others): Top: 20mm, Bottom:20mm, Side:3mm

Roll paper: Top: Smm, Bottom: Smm, Side: 3mm Roll paper (borderless): Top: Omm, Bottom: Omm, Side: Omm Cut sheet (AppleAirPrint): Top: Smm, Bottom: 12/7mm, Side: 3mm Cut sheet (Others): Top: 3mm, Bottom: 20mm, Side: 3mm

[Recommended] 515mm(JIS B2), 728mm(JIS B1), 594mm (ISO A1), 841mm(ISO A0), 10", 14", 17", 24", 36"

[Printable] 257mm (JIS B4), 297mm (ISO A3), 329mm (ISO A3+), 420mm (JIS DA), 515mm (JIS B3), 512-115-116-118-, 20°, 22°, 30°, 34°, 300mm, 500mm, 600mm, 800mm Other than above, free size borderless printing is supported on only roll paper by user definition

Standard position: 1 sheet
Folding position: Plain paper 20 sheets on A1 portrait
/ AQ portrait
Flat position: Plain paper 20 sheets on A2 landscape / A1 landscape
(exclude strong curled position)

AC 100-240V (50-60Hz)

Operation: 65W or less Sleep mode: 2.2W Default setting for the time to enter the Sleep mode: Approx. 5 minutes Power off: 0.1W or less

Operation: 69W or less Sleep mode: 2.2W Default setting for the time to enter the Sleep mode: Approx. 5 minutes Power off: 0.1W or less

Humidity: 10-80% RH Temperature: 15-30°(no dew c

(no dew condensation)

Operation: Approx. 416B(A) (Standard Plain Paper,
Standard mode, Line Drawing/Text mode)
(Measured based on ISO7779 standard)
Standby: 35 dB(A) or less
Operation: 6.2 Bels or less (Standard Plain Paper, Standard
mode, Line Drawing/Text mode)
(Measured based on ISO7779 standard)

 $W \times D \times H$ Main unit with stand 1285 x 885 x 1060mm (Basket Opened) 1285 x 756 x 1060mm (Basket Closed) 63kg (incl. Roll Holder set, excl. ink and print head)

Printer, Printer Stand, 1 Print head, Power Cable, 1 Set of starter ink tanks, 1 Roll holder (spool), 3" Paper Core Attachment, Installation Guide, Safety/Standard Environment leaflet, LFP Eur Address Sheet, Important Information Sheet, Stack Printer Stand Setup Guide, Notice for Poster Artist WEB

Software available as Download from Web

2"/3" Roll Holder: RH2-35 IC Card Reader Holder: RA-02

Ink Tank: M:PFI-321(300ml) / PFI-121(130ml), MBK/BK/C/Y:PFI-320(300ml) / PFI-120(130ml) Print Head: PF-06 Cutter Blade: CT-08 Maintenance Cartridge: MC-31

Disclaimer

Some images are simulated for clarity of reproduction. All data is based on Canon's standard testing methods. This leaflet and the specifications of the product have been developed prior to the date of product launch. Final specifications are subject to change without notice." and "All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.

Canon recommends you use Canon Media for the best results. Please check media (paper) compatibility list to see which variety of paper/media is recommended.

FINE







Canon Inc. canon.com

> Canon Europe canon-europe.com

English edition © Canon Europa N.V.,2025

Canon

