



imagePROGRAF TM-610 / TM-615

QUALITY AND VERSATILITY FOR EVERY WORKSPACE

Elevate every print with vivid colour and thin-line precision in accurate CAD and eye-catching marketing material production. The 36" printer combines enhanced productivity, intuitive usability and sustainability – wrapped up in a low-noise printing with a wide range of applications in mid productivity segment, designed for large corporate and sizable AEC offices, the retail and education sectors.

BENEFITS

- **Quality across every application**
New high-density MBK ink and enhanced image processing deliver sharper thin lines and cleaner technical detail, while improved plain paper colour mapping produces darker, more vivid output across various applications like posters and retail materials.
- **Enhanced productivity**
Keep workflows moving with 3.2ppm (A1) print speed and print with larger ink tanks, less time waiting with fast processing and quick-return sleep mode. With first-print confidence using Free Layout Plus to minimise misprints, and no more excess margin trimming with borderless printing.
- **Ease of use**
Control all key settings from a 4.3" tiltable touch screen panel, with essential displays like media type, remaining media and ink amount. Simplified media setting with auto detection of media type streamlines the workflow. Supports Apple AirPrint, IPP Everywhere, and Mopria for effortless driver free printing with different devices.
- **Built for sustainability**
No more disruptions with a low-noise operation, perfect for quieter office environments. Engineered with more recycled materials, EPS-free packaging, and EPEAT certification*, the TM series helps organisations hit sustainability procurement targets without compromising on quality.

*EPEAT 1.0 Gold certified, EPEAT 2.0 Bronze certified, registered in the U.S.

TECHNICAL SPECIFICATIONS

imagePROGRAF TM-610/TM-615

PRINTER TECHNOLOGY	TM-610	TM-615	TM-610	TM-615
Printer Type	5 Colours 36"		Margins Printable area	
Print Technology	Canon Bubblejet on Demand 6 colours integrated type (6 chips per print head x 1 print head)		Roll paper: Top: 3mm, Bottom: 3mm, Side: 3mm Roll paper (borderless): Top: 0mm, Bottom: 0mm, Side: 0mm Cut sheet (AppleAirPrint): Top: 3mm, Bottom: 127mm, Side: 3mm Cut sheet (Others): Top: 3mm, Bottom: 20mm, Side: 3mm	
Print Resolution	2,400 x 1,200 dpi		Media Feed Capacity	
Number of Nozzles	Total: 15360 nozzles MBK: 5120 nozzles BK, C, M, Y: 2560 nozzles each		Roll Paper: 1 roll Cut Sheet: 1 sheet	
Line Accuracy	±0.1% or less User adjustments necessary. Printing environment and media must match those used for the adjustments.		Borderless Printing Width (Roll Only)	
Nozzle Pitch	1,200 dpi x 2 lines		[Recommended] 515mm (JIS B2), 728mm (JIS B1), 594mm (ISO A1), 841mm (ISO A0), 10", 14", 17", 24", 36" [Printable] 257mm (JIS B4), 297mm (ISO A3), 329mm (ISO A3+), 420mm (ISO A2), 515mm (JIS B3), 8", 12", 15", 16", 18", 20", 22", 30", 34", 300mm, 500mm, 600mm, 800mm	
Ink Droplet Size	minimum 5pl per colour		Other than above, free size borderless printing is supported on only roll paper by user definition	
Ink Capacity	Bundled Starter Ink: 490ml (130ml for MBK, 90ml x 4 for BK, C, M, Y) Sales Ink: 300/130ml (MBK, BK, C, M, Y)		Maximum number of delivered prints	
Ink Type	Pigment inks : 5 colours MBK/BK/C/M/Y		Standard position: 1 sheet Folding position: Plain paper 20 sheets on A1 portrait / A0 portrait Flat position: Plain paper 20 sheets on A2 landscape / A1 landscape (exclude strong curled position)	
OS Compatibility	32 Bit: Windows 7, Windows 8.1, Windows 10 64 Bit: Windows 7, Windows 8.1, Windows 10, Windows 11, Windows Server 2008R2, 2012, 2012R2, 2016, 2019, 2022, 2025 Apple Macintosh: macOS 12-macOS 26		POWER AND OPERATING REQUIREMENTS	
Others supported job submission protocol	Apple AirPrint (for macOS/iOS/iPadOS), Mopria (for Android, Windows), IPP Everywhere (for ChromeOS)		Power Supply	
Printer Languages	HP-GL/2, HP RTL, JPEG (Ver. JFIF 1.02), CALS G4 (submission via FTP only)	HP-GL/2, HP RTL, PDF (Ver. 1.7), JPEG (Ver. JFIF 1.02), CALS G4 (submission via FTP only)	Power Consumption	
Standard Interfaces	USB A Port: N/A	USB A Port: USB Memory (Direct Print)	AC 100-240V (50-60Hz)	
	USB B Port: Hi-Speed USB Ethernet: IEEE802.3ab(1000base-T), IEEE802.3u (100BASE-TX)/IEEE802.3 (10BASE-T) Wireless LAN: IEEE802.11n/IEEE802.11g/IEEE802.11b		Operation: Approx. 65W Sleep mode: Approx. 2.2W Default setting for the time to enter the Sleep mode: Approx. 5 minutes Power off: Approx. 0.06W	
	*Please refer to user manual how to activate/deactivate the wireless LAN		Operating Environment	
MEMORY			Temperature: 15-30°C, Humidity: 10-80% RH (no dew condensation)	
Standard memory	2GB Expansion slot: No	128GB (Physical memory 2GB) Expansion slot : No	Acoustic Noise (Power/Pressure)	
SSD Storage	N/A	256 GB (Encrypted)	Operation: Approx. 41dB(A) (Standard Plain Paper, Standard mode, Line Drawing/Text mode) (Measured based on ISO7779 standard) Standby: 35 dB(A) or less Operation: 6.2 Bels or less (Standard Plain Paper, Standard mode, Line Drawing/Text mode) (Measured based on ISO7779 standard)	
PRINTING SPEED			CE mark, UKCA mark	
CAD Drawing			CB certification, EPEAT certification ¹	
Plain Paper (A1)	0:17 (Fast Economy Mode) 3.2ppm		DIMENSIONS AND WEIGHT	
Plain Paper (A0)	0:32 (Fast Economy Mode) 0:40 (Fast) 1:08 (Standard)		Physical Dimensions and Weight	
Poster:			W x D x H	
Plain Paper (A0)	0:36 (Fast Economy Mode) 0:42 (Fast) 1:04 (Fast new) 1:16 (Standard)		Main unit with stand 1285 x 885 x 1041mm (Basket Opened) 1285 x 756 x 1041mm (Basket Closed) 65 kg (including Roll Holder Set, excluding ink and print head)	
Heavy coated paper (A0)	1:38 (Fast) 2:30 (Standard)		Packaged Dimensions and Weight	
			Printer (Main unit with stand and pallet): 1462 x 1122 x 769mm, 112kg	
MEDIA HANDLING			WHAT'S INCLUDED	
Media Feed and Output	Roll Paper : One Roll, Upper-loading, Front Output Cut Sheet : Upper-loading, Front Output (Manual feed using media locking lever)		What's in the Box?	
Media Width	Roll paper: 203.2 - 917mm Cut sheet: 203.2 - 917mm		Printer, Printer Stand, 1 Print head, Power Cable, 1 Set of starter ink tanks, 1 Roll holder (spool), 3" Paper Core Attachment, Installation Guide, Safety/Standard Environment leaflet, LFP Eur Address Sheet, Important Information Sheet, Printer Stand Setup Guide, Notice for PosterArtist WEB	
Media Thickness	Roll/Cut : 0.07mm - 0.8mm		Software Included	
Minimum Printable Length	Roll paper: 203.2mm Cut sheet: 279.4mm		Software available as Download from Web	
Maximum Printable Length	Roll paper: 18 m (Varies according to the OS and application) Cut sheet: 1.6 m		OPTIONS	
Maximum Media Roll Diameter	150 mm		Optional Items	
Media Core Size	Internal diameter of roll core: 2 7/3"		2 7/3" Roll Holder: RH2-35 IC Card Reader Holder: RA-02	
Margins Recommended area	Roll paper: Top: 20mm, Bottom: 3mm, Side: 3mm Cut sheet (AppleAirPrint): Top: 20mm, Bottom: 31mm, Side: 3mm Cut sheet (Others): Top: 20mm, Bottom: 20mm, Side: 3mm		CONSUMABLES	
			User Replaceable Items	
			Ink Tank MBK: PFI-323 (300ml) / PFI-123 (130ml) M: PFI-321 (300ml) / PFI-121 (130ml) BK/C/Y: PFI-320 (300ml) / PFI-120 (130ml) Print Head: PF-06 Cutter Blade: CT-08 Maintenance Cartridge: MC-31	
			Footnotes	
			¹ EPEAT 1.0 Gold certified, EPEAT 2.0 Bronze certified, registered in the U.S.	
			Disclaimer	
			Some images are simulated for clarity of reproduction. All data is based on Canon's standard testing methods. This leaflet and the specifications of the product have been developed prior to the date of product launch. Final specifications are subject to change without notice. TM and [®] : All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.	
			Canon recommends you use Canon Media for the best results. Please check media (paper) compatibility list to see which variety of paper/media is recommended.	



Canon Inc.
Canon.com

Canon Europe
canon-europe.com

English Edition
© Canon Europa N.V. 2026