

# imageRUNNER ADVANCE C3530i ES

**COMPACT A3 COLOUR  
MULTIFUNCTIONAL  
FOR ALL YOUR  
DOCUMENT  
WORKFLOW NEEDS**



## Main configuration options



### INNER FINISHER - K1 ES

- 2-tray, 600-sheet capacity
- Corner and double stapling up to 50 sheets (80 gsm)
- Supports Eco stapling 4 sheets (80 gsm) and Staple On Demand 40 sheets (80 gsm)

This flat configuration is for illustration purpose only. For a complete list of options and the exact compatibility relationships, please refer to the online product configurator.

**Canon**

---

# TECHNICAL SPECIFICATIONS

# imageRUNNER ADVANCE C3530i ES

<b>MAIN UNIT</b>		<b>Print Features</b>	Suspend Job Timeout, Subset Finishing (PS only), Profile Settings, Secured Print, Watermark, Page Border, Header/Footer, Page Layout, Two-sided Printing, Collating, Booklet Printing, Grouping, Mixed Paper Sizes/Orientations, Offsetting, Printing on Transparencies, Front/Back Covers, Toner Reduction, Poster Printing, Job hold printing
<b>Machine Type</b>	Colour Laser Multifunctional	<b>Operating System</b>	UFRIL: Windows® 8.1/10/11/Server2012/Server2012 R2/Server2016/Server2019/Server2022, Mac OS X (10.11 or later) PCL: Windows® 8.1/10/11/Server2012/Server2012 R2/Server2016/Server2019/Server2022 PS: Windows® 8.1/10/11/Server2012/Server2012 R2/Server2016/Server2019/Server2022, Mac OS X (10.11 or later) PPD: Windows® 8.1/10/11, Mac OS X (10.11 or later)
<b>Core Functions</b>	Print, Copy, Scan, Send, Store and Optional Fax	<b>COPY SPECIFICATIONS</b>	
<b>Processor Speed</b>	Canon Dual Custom Processor (Shared) 1.75 Ghz	<b>Copy Speed</b>	30 ppm (A4), 15 ppm (A3), 20 ppm (A4R), 30 ppm (A5R)
<b>Control Panel</b>	25.6 cm (10.1 inch) TFT LCD WSVGA Colour Touch panel	<b>First-Copy-Out Time (BW/CL)</b>	Approx. 5.9/8.2 seconds or less
<b>Memory</b>	Standard: 3.0 GB RAM	<b>Copy Resolution</b>	Reading: 600 dpi x 600 dpi Printing: Up to 2,400dpi equivalent x 600dpi
<b>Storage</b>	Standard: 320GB	<b>Multiple Copies</b>	Up to 999 copies
<b>Interface Connection</b>	<b>NETWORK</b> Standard: 1000Base-T/100Base-TX/10Base-T, Wireless LAN (IEEE 802.11 b/g/n) <b>OTHERS</b> Standard: USB 2.0 (Host) x1, USB 3.0 (Host) x1, USB 2.0 (Device) x1	<b>Copy Exposure</b>	Automatic or Manual (9 Levels)
		<b>Magnification</b>	Variable zoom: 25% to 400% (1% Increments) Preset reduction/enlargement: 25%, 50%, 70%, 100%(1:1), 141%, 200%, 400%
<b>Paper Supply Capacity (A4, 80 gsm)</b>	4 x 550-sheet cassettes 100-sheet multi-purpose tray	<b>Basic Copy Features</b>	Preset R/E Ratios by Area, Paper Setting, Previous Setting, Favourite Setting, Finishing, Two-Sided, Density Adjustment, Exposure Adjustment, Original Type Selection, Interrupt Mode, Setting Confirmation/Cancel
<b>Paper output capacity (A4, 80gsm)</b>	Standard: 250 sheets With Inner Finisher: 600 sheets	<b>Special Copy Features</b>	Book to Two Pages, Two-sided Original, Finishing, Booklet, Job Build, N on 1, Add Cover, Insert Sheets, Different Size Originals, Density Adjustment, Original Type Selection, Transparency Cover Sheets, Page Numbering, Copy Set Numbering, Sharpness, Erase Frame, Secure Watermark, Print Date, Shift, Gutter, Print & Check, Negative/Positive, Repeat Images, Merge Job Blocks, Job Done Notice, Mirror Image, Print on Tab, Store in Mail Box, Superimpose Image, Cascade Copy, Copy ID Card, Multi Sheet Feed Detection, Free Size Original
<b>Finishing Capabilities</b>	Standard: Collate, Group With Inner Finisher: Collate, Group, Offset, Staple, Staple-Free Staple, Staple on Demand	<b>SCAN SPECIFICATIONS</b>	
<b>Supported Media Types</b>	Upper Cassettes 1/2: Thin paper, Plain paper, Recycled paper, Colour paper, Pre-punched paper, Thick paper, Bond paper, Transparency, Envelope Lower Cassettes 3/4: Thin paper, Plain paper, Recycled paper, Colour paper, Pre-punched paper, Thick paper, Bond paper, Transparency Multi-purpose tray: Thin paper, Plain paper, Recycled paper, Colour paper, Pre-punched paper, Thick paper, Bond paper, Transparency, Labels, Envelopes, Tracing paper, Coated paper,	<b>Standard type</b>	Duplexing Automatic Document Feeder (DADF)
		<b>Pull Scan Specifications</b>	Colour Network ScanGear2. For both TWAIN and WIA Supported OS: Windows® 8.1/10/11/Server2012/Server2012 R2/Server 2016/Server 2019/Server 2022
<b>Supported Media Sizes</b>	Cassette 1: Standard size: A4, B5, A5R Envelopes: No.10 (COM10), ISO-C5, DL Custom Size: 139.7 mm x 182 mm to 297 mm x 215.9 mm  Cassette 2: Standard size: A4, A4R, A3, B4, B5, A5R Envelopes: No.10 (COM10), Monarch, DL Custom Size: 139.7 mm x 182 mm to 304.8 x 457.2 mm  Cassette 3/4: A4, A4R, A3, B4, B5, B5R, A5R, Custom Size: 139.7 mm x 182 mm to 304.8 mm x 457.2 mm	<b>Scan Resolution</b>	100 x 100 dpi, 150 x 150 dpi, 200 x 100 dpi, 200 x 200 dpi, 200 x 400 dpi, 300 x 300 dpi, 400 x 400 dpi, 600 x 600 dpi
<b>Supported Media Weights</b>	Cassettes: 52 to 220 gsm  Multi-purpose tray: 52 to 300 gsm  Duplex: 52 to 220 gsm	<b>Supported Media Sizes</b>	A4, A4R, A3, B4, B5, B5R, A5, A5R, B6
		<b>Supported Media Weightss</b>	1-sided scanning: 38 to 128 gsm/64 to 128 gsm (BW/CL) 2-sided scanning: 50 to 128 gsm/64 to 128 gsm (BW/CL)
<b>Warm-up Time</b>	From Power On: 34 Seconds or Less <sup>1</sup> From Sleep Mode: 10 Seconds or Less Quick Start-up Mode: 10 seconds or less	<b>Scan Method</b>	Send functionality: Available Scan to USB Memory Key: Available Scan to Mobiles or internet-connected devices: A range of solutions is available to provide scanning to mobile devices or internet-connected devices depending on your requirements. Please contact your sales representative for further information Scan to cloud-based services: A range of solutions is available to provide scanning to cloud-based services depending on your requirements. Please contact your sales representative for further information. TWAIN/WIA Pull scanning available on all models
<b>Dimensions (W x D x H)</b>	565 mm x 736 mm x 1,128 mm	<b>Scan Speed (BW/CL; A4)</b>	Single-sided Scanning: 70 ipm (300pi) / 51 ipm (600 dpi)  Double-sided Scanning: 35 ipm (300pi) / 25.5 ipm (600 dpi)
<b>Installation Space (W x D)</b>	978 mm x 1,117 mm (with Multi-purpose tray extension extended)	<b>Document Feeder Paper Capacity (80 gsm)</b>	100 Sheets
<b>Weight</b>	Approx. 92.2 kg including toner	<b>Double Sided Scanning</b>	2-sided to 2-sided (Automatic)
<b>PRINT SPECIFICATIONS</b>		<b>SEND SPECIFICATIONS</b>	
<b>Printing Method</b>	Colour Laser Beam Printing	<b>Optional / Standard</b>	Standard
<b>Print Speed (BW/CL)</b>	30 ppm (A4), 15 ppm (A3), 20 ppm (A4R), 30 ppm (A5R)	<b>Destination</b>	E-mail/Internet FAX (SMTP), SMB, FTP, WebDAV, Mail Box, Super G3 FAX(Optional)
<b>Print Resolution</b>	600dpi×600dpi, 1200dpi×1200dpi	<b>Colour Mode</b>	Auto Colour Select (Full Colour, Grayscale), Auto Colour Select (Full Colour/ Black-and-White) Full Colour, Grayscale, and Black-and-White
<b>Page Description Languages</b>	UFR II, PCL 6, Genuine Adobe PostScript Level 3 (Standard)	<b>Address Book/Speed dials</b>	LDAP (2,000)/Local (1,600)/Speed dial (200)
<b>Double Sided Printing</b>	Automatic (Standard)	<b>Send Resolution</b>	100 x 100 dpi, 150 x 150 dpi, 200 x 100 dpi, 200 x 200 dpi, 200 x 400 dpi, 300 x 300 dpi, 400 x 400 dpi, 600 x 600 dpi
<b>Direct Print</b>	Supported file types <sup>2</sup> : TIFF, JPEG, PDF, EPS, and XPS.		
<b>Mobile / Cloud Printing</b>	A range of software and MEAP-based solutions is available to provide printing from mobile devices or internet-connected devices and cloud-based services depending on your requirements. Please contact your sales representative for further information		
<b>Fonts</b>	PCL fonts: 93 Roman, 10 Bitmap fonts, 2 OCR fonts, Andalé Mono WT J/K/S/T* (Japanese, Korean, Simplified and Traditional Chinese), Barcode fonts** PS fonts: 136 Roman		
	<sup>1</sup> Requires optional PCL INTERNATIONAL FONT SET-A1 <sup>2</sup> Require optional BARCODE PRINTING KIT-D1		

# TECHNICAL SPECIFICATIONS

# imageRUNNER ADVANCE C3530i ES

<b>Communication Protocol</b>	File: FTP, SMB v3.0, WebDAV E-mail/i-Fax: SMTP, POP3, i-Fax (Simple, Full)	<b>ENVIRONMENTAL SPECIFICATIONS</b>	
<b>File Format</b>	Standard: TIFF, JPEG, PDF(Compact, Searchable, Apply policy, Optimize for Web, PDF A/1-b, Encrypted), XPS(Compact, Searchable), Office Open XML (PowerPoint, Word), PDF/XPS(Digital Signature) Optional: PDF(Trace&Smooth)	<b>Operating Environment</b>	Temperature: 10 to 30 °C (50 to 86 °F) Humidity: 20 to 80 % RH (no condensation) 220-240 V (±10 %), 50/60 Hz (±2 Hz), 4 Amp
<b>Universal Send Features</b>	Original Type Selection, Two-sided Original, Book to Two Pages, Different-size Originals, Density Adjustment, Sharpness, Copy Ratio, Erase Frame, Job Build, Sender's Name (TTI), Select Line, Direct Send, Delayed Send, Preview, Finished Stamp, Job Done Notice, File Name, Subject/Message, Reply-to, E-mail Priority, TX Report, Original Content Orientation, Skip Blank Originals, Multi Sheet Feed Detection.	<b>Power Source</b>	Maximum: Approx. 1.5 kW Printing: Approx. 435.7 Wh or less <sup>3</sup> Standby: Approx. 41.2 Wh Sleep mode: Approx. 0.8 W <sup>4</sup> Plugin Off: Approx. 0.2W <sup>5</sup> Typical Electricity Consumption (TEC) rating <sup>6</sup> : 0.35 kWh
<b>FAX SPECIFICATIONS</b>		<b>Power Consumption</b>	
<b>Optional / Standard</b>	Optional	<b>Noise Levels (BW/CL)</b>	For detailed information relating to Erp:Lot6/26 regulation, please go to: <a href="https://www.canon-europe.com/for_work/lot26/">https://www.canon-europe.com/for_work/lot26/</a>
<b>Maximum Number of Connection Lines</b>	2		Sound Power Level (LwAd) <sup>6</sup> Active (BW): 64.2 dB or Less <sup>3</sup> , Active (CL): 64.3 dB or Less <sup>3</sup> , Standby: 27 dB or Less <sup>7</sup>
<b>Modem Speed</b>	Super G3: 33.6 kbps G3: 14.4 kbps		Sound Pressure (LpAm) <sup>5</sup> Bystander's position: Active (BW): 49.5 dB or Less <sup>3</sup> , Active (CL): 49.6 dB or less <sup>3</sup> , Standby: 9.6 dB or Less <sup>7</sup>
<b>Compression Method</b>	MH, MR, MMR, JBIG	<b>SOFTWARE AND PRINTER MANAGEMENT</b>	
<b>Resolution</b>	400 x 400 dpi, 200 x 400 dpi, 200 x 200 dpi, 200 x 100 dpi	<b>Tracking &amp; Reporting</b>	<b>Universal Login Manager (ULM)</b> : Manage your costs easily by using the embedded reporting capability to identify and control costs on a user-based level by device.
<b>Sending/Recording Size</b>	A5* and A5R* to A3 *Sent as A4	<b>Remote Management Tools</b>	<b>iW Management Console</b> : Server-based software for centralised management of a fleet of devices (Includes monitoring or consumables, status monitoring and alerts, distribution of address books, configuration settings, firmware and MEAP applications, meter capture and reporting, driver and resource management)
<b>FAX Memory</b>	Up to 30,000 pages		<b>eMaintenance</b> : Compatible with eMaintenance services via embedded RDS (Enables meter capture, automatic consumables management, remote diagnostics and reporting for service providers to offer efficient, fast and proactive maintenance)
<b>Speed Dials</b>	Max. 200		<b>Content Delivery System</b> : Allows the Remote distribution of firmware, iR options and MEAP applications, Remote User Interface (RUI)
<b>Group Dials/Destinations</b>	Max. 199 dials		Web based interface to each device that helps to provide remote device management and control
<b>Sequential Broadcast</b>	Max. 256 addresses		<b>Network ScanGear</b> : TWAIN-compliant scanner driver that enables computers on a network to use the pull scan functionality of the device
<b>Memory Backup</b>	Yes		Canon Driver Configuration Tool
<b>Fax Features</b>	Original Type Selection, Two-sided Original, Book to Two Pages, Different-size Originals, Density for Scanning, Sharpness, Copy Ratio, Erase Frame, Job Build, Specifying the Sender's Name (when sending fax), Sender's Name (TTI), Selecting the Telephone Line (when sending fax), Direct Send, Delayed Send, Preview, Finished Stamp, Job Done Notice, TX Report, Multi Sheet Feed Detection.		MEAP (Multifunction Embedded Application Platform)
<b>STORE SPECIFICATIONS</b>			Optional: Therefore™, Kofax Power PDF Advanced
<b>Mail Box</b>	100 User Inboxes, 1 Memory RX Inbox, 50 Confidential Fax Inboxes 30,000 Maximum Pages Stored	<b>Scanning Software</b>	
<b>Advanced Space</b>	Communication Protocol: SMB or WebDAV Supported Client PC: Windows (Windows Vista/7/8/8.1/10) Concurrent Connections (Max.): SMB: 64, WebDAV: 3 (Active Sessions)		
<b>Advanced Space Available</b>	Approx. 16GB (Standard HDD)	<b>Optimisation Tools</b>	
<b>Advanced Space Features</b>	Disabling Advanced space, Storage Filtering, Authentication for Advanced Space Log-in, Search Function, Sort Function, Printing a PDF File with a Password, imageWARE Secure Audit Manager Support	<b>Platform</b>	
<b>Memory Media</b>	Standard: USB Memory	<b>Document Publishing</b>	
<b>SECURITY SPECIFICATIONS</b>		<b>CONSUMABLES</b>	
<b>Authentication &amp; Access Control</b>	<b>Standard</b> : Universal Login Manager (Device and Function Level Log-in), User Authentication, Department ID, Authentication, Access Management System <b>Optional</b> : My Print Anywhere secure print* *Requires uniFLOW Online/uniFLOW	<b>Toner Cartridge/s</b>	C-EXV 49 TONER BK/C/M/Y
<b>Data</b>	<b>Standard</b> : Trusted Platform Module (TPM), Hard Disk Password Lock, Hard Disk Drive Erase, Mail Box Password Protection, Hard Disk Drive Encryption(FIPS140-2 Validated), Common Criteria Certification (DIN ISO 15408) <b>Optional</b> : Hard Disk Drive removal, Data Loss Prevention* *Requires uniFLOW Online/uniFLOW	<b>Toner (Estimated Yield @ 6% Coverage)</b>	C-EXV 49 TONER BK: 36,000 pages C-EXV 49 TONER C/M/Y: 19,000 pages
<b>Document Security</b>	<b>Standard</b> : Secure Print, Adobe LiveCycle® Rights Management ES2.5 Integration, Encrypted PDF, Encrypted Secure Print, Device signature, Secure Watermarks <b>Optional</b> : User signature	<b>OUTPUT OPTIONS</b>	
<b>Network Security</b>	<b>Standard</b> : IP/Mac Address Filtering, IPSEC, TLS Encrypted Communication, SNMP V3.0, IEEE 802.1X, IPv6, SMTP Authentication, POP Authentication before SMTP	<b>INNER FINISHER</b>	Name: INNER FINISHER-K1 ES Number of Trays: 2 Tray A (Upper) Capacity: A4, B5, A5, A5R 100 sheets, A3, B4, A4R, B5R, SRA3 50 sheets Tray B (Lower) Capacity: A4, B5, A5, A5R 500 sheets, A3, B4, A4R, B5R, SRA3 250 sheets Paper Weight: 52 to 300 gsm Staple Position: Corner, Double Staple Capacity: Corner and Double stapling: A4/B5: 50 sheets (52 to 90 gsm) A3/B4/A4R: 30 sheets (52 to 90 gsm) Eco Staple: A3/B4/B5/A4: 5 sheets (52 to 64 gsm) 4 sheets (65 to 81.4 gsm) 3 sheets (81.5 to 105 gsm) Staple On Demand: 40 sheets (80 gsm) Dimensions (W x D x H): 604 mm x 525 mm x 188 mm *With the tray extension extended. Weight: Approx. 8 kg
<b>Device Management &amp; Auditing</b>	Administrator Password, Digital Certificate And Key Management, Audit Log, Image Data Logging, Security Policy Setting	<b>HARDWARE ACCESSORIES</b>	
		<b>Card Readers</b>	MiCARDPLUS FOR ULM - A proximity card reader for card based user authentication, supporting multiple card technologies (HID, HiTag, Casi Rusco, Indala and MiFare etc.). Integrates with Universal Login Manager and uniFLOW
		<b>Others</b>	COPY CARD READER-F1 - Magnetic physical card access system. (Integrates with Department ID, not for use with uniFLOW) COPY CARD READER ATTACHMENT-B5 - Attachment kit for Copy Card Reader-F1 only.

# TECHNICAL SPECIFICATIONS

# imageRUNNER ADVANCE C3530i ES

## SYSTEM AND CONTROLLER OPTIONS

Print Accessories	PCL INTERNATIONAL FONT SET-A1 - Adds PCL support for Andalé Mono WT J/K/S/T (Japanese/Korean/Simplified Chinese/Traditional Chinese).
Send Options	UNIVERSAL SEND DIGITAL USER SIGNATURE KIT-C1 - Ensures the authenticity of a PDF/XPS by identifying the user that sent the document through a visible and/or invisible digital signature.
Barcode Printing	UNIVERSAL SEND TRACE & SMOOTH PDF KIT-A1 - Enables the device to create and send Trace and Smooth PDF.
Direct Printing	BARCODE PRINTING KIT-D1 - Provides the ability to print 1D and 2D barcodes on output using jet caps technology.
Fax Accessories	SUPER G3 FAX BOARD-AU1 ES - Adds fax functionality. REMOTE FAX KIT-A1 - Enables the device to send and receive fax from another device connected with a fax board.
<b>OTHER OPTIONS</b>	
Staple Cartridge	STAPLE-P1 - For stapling (2 x 5,000 pcs)

## Notes:

- <sup>[1]</sup> Time between device power-on and when the start key is enabled. Quick startup Mode ON
- <sup>[2]</sup> Only PDF print from websites is supported
- <sup>[3]</sup> Data taken from Blue Angel Certification User Notes
- <sup>[4]</sup> 0.8W sleep mode is not available in all circumstances due to certain settings.
- <sup>[5]</sup> As per Energy Star v 3.0
- <sup>[6]</sup> Declared noise emission in accordance with ISO 7779
- <sup>[7]</sup> Data taken from ECO declaration

## Software & Solutions



## Certifications and compatibility



# Canon

Canon Inc.  
canon.com

Canon Europe  
canon-europe.com

English edition  
© Canon Europa N.V., 2024