

imageRUNNER ADVANCE C5500 ES series

PROMOTE YOUR BUSINESS SUSTAINABILITY GOALS WITH EFFICIENT AND RELIABLE A3 COLOUR MULTIFUNCTION DEVICES

MAIN CONFIGURATION OPTIONS



BOOKLET FINISHER-Y1 ES

- 2-tray, 3,250 -sheet capacity
- Corner and double stapling up to 50 sheets (80 gsm)
- Booklet-making up to 20 sheets and non-staple saddle folded capacity up to 3 sheets (A3/ A4R)
- Supports Eco stapling 4 sheets (80 gsm) and Staple On Demand 50 sheets (80 gsm)
- Includes Buffer Pass Unit-L1



STAPLE FINISHER-Y1 ES

- 2-tray, 3,250 -sheet capacity
- Corner and double stapling up to 50 sheets (80 gsm)
- Supports Eco stapling 4 sheets (80 gsm) and Staple On Demand 50 sheets (80 gsm)
- Includes Buffer Pass Unit-L1



iR ADV C5560i ES+



iR ADV C5560i ES



INNER FINISHER - H1 ES

- 2-tray, 545 -sheet capacity
- Corner and double stapling up to 50 sheets (80 gsm)
- Supports Eco stapling 4 sheets (80 gsm) and Staple On Demand 40 sheets (80 gsm)

This flat configuration is for illustration purpose only. For a complete list of options and the exact compatibility relationships, please refer to the online product configurator.

TECHNICAL SPECIFICATIONS

imageRUNNER ADVANCE C5500 ES series

MAIN UNIT

Machine type
Core functions
Processor Speed
Control Panel
Memory
Storage
Interface Connection

Colour Laser Multifunctional
Print, Copy, Scan, Send, Store and Optional Fax
Canon Dual Custom Processor (Shared) 1.75 Ghz
25.6 cm (10.1 inch) TFT LCD WSVGA Colour Touch panel
Standard: 4.0GB RAM
Standard: 320GB HDD
NETWORK Standard: 1000Base-T/100Base-TX/10Base-T,
Wireless LAN (IEEE 802.11 b/g/n)
OTHERS Standard: USB 2.0 (Host) x2, USB 3.0 (Host) x1,
USB 2.0 (Device) x1

Paper Supply Capacity
(A4, 80 gsm)

Standard: 2,300 Sheets
4 x 550 sheet Cassettes
100 sheet Multi-purpose tray

Paper output capacity
(A4, 80 gsm)

Standard: 250 sheets
Maximum: 3,250 sheets (with Booklet Finisher-Y1 ES or
Staple Finisher-Y1 ES)

Finishing capabilities

Standard: Collate, Group
Optional:
With Inner Finisher : Collate, Group, Offset, Staple,
Staple-Free Staple, Staple On Demand
With External Finisher, Staple Finisher and Booklet
Finisher : Collate, Group, Offset, Staple, Booklet*,
Staple-Free Staple, Staple On Demand

Supported media types

Upper Cassette 1:
Thin paper, Plain paper, Thick paper, Color paper,
Recycled paper, Pre-punched paper, Transparency,
Bond paper, Envelope, Letterhead

Lower Cassettes 2/3/4:
Thin paper, Plain paper, Thick paper, Color paper,
Recycled paper, Pre-punched paper, Transparency,
Bond paper, Envelope, Letterhead

Supported media sizes

Multi-purpose tray:
Thin paper, Plain paper, Thick paper, Color paper,
Recycled paper, Pre-punched paper, Transparency,
Tracing paper[†], Label, Tab paper, Bond paper, Coated
paper, Envelope, Letterhead

Upper Cassette 1:
Standard size: A4, B5, A5, A5R
Custom size: Min. 98.0 mm x 148 mm up to
297 mm x 215.9 mm

Lower Cassettes 2/3/4:
Standard size: A3, B4, A4, A4R, B5, B5R, A5, A5R
Custom size: Min. 98.0 mm x 182 mm up to
304.8 mm x 457.2 mm

Multi-purpose tray:
Standard size: A3, B4, A4, A4R, B5, B5R, A5, A5R, SRA3,
Envelopes (No. 10 (COM 10)), Monarch, ISO-C5, DL),
Envelope Custom Size (Min. 98.0 mm x 98.4 mm up to
320.0 mm x 457.2 mm)
Free Size: Min. 98.0 mm x 139.7 mm up to 320.0 mm x
457.2 mm

Supported media weights

Cassettes: 52 to 256 gsm
Multi-purpose tray: 52 to 300 gsm
Duplex: 52 to 220 gsm

Warm-up Time

From Power On: 30 Seconds or Less[‡]
From Sleep Mode: 10 Seconds or Less
(with Quick Start ON)

Dimensions (W x D x H)

620 mm x 742 mm x 950 mm

Installation Space (W x D)

Basic: 980 mm x 1,176 mm
(Multi-purpose tray extended + cassette drawers open)
Approx. 142 kg including toner

Weight

PRINT SPECIFICATIONS

Print Speed (BW/CL)

Up to 60 ppm (A4), 32 ppm (A3), 36 ppm (A4R),
60.5 ppm (A5R)

Print Resolution(dpi)

600 dpi x 600, 1,200 dpi x 1,200 (half-speed)

Page description languages

Standard: UFR II, PCL6, Adobe® PostScript® 3™

Double Sided Printing

Standard: Automatic

Direct Print

Supported file types*: TIFF, JPEG, PDF, EPS, and XPS

*Only PDF print from websiteseis supported

Printing from mobile and cloud

AirPrint, Mopria, Canon PRINT Business app and
uniFLOW Online (optional)

A range of software and MEAP-based solutions are
available to provide printing from mobile devices or
internet-connected devices and cloud-based services
depending on your requirements.
Please contact your sales representative for further
information

OS Standard Printing

Android, Windows® 10/11, Chrome OS,
macOS (11.2.2 or later), iOS (15.2 or later), iPadOS

Fonts

PS fonts: 136 Roman
PCL fonts: 93 Roman, 10 Bitmap fonts, 2 OCR fonts,
Andalé Mono WT J/K/S/T[†] (Japanese, Korean,
Simplified and Traditional Chinese), Barcode fonts[‡]

[†] Optional PCL International Font Set-A1 is required.

[‡] Optional Barcode Printing Kit-D1 is required.

Print Features

Suspend Job Timeout, Subset Finishing (PS only),
Profile Settings, Secured Print, Watermark, Page Border,
Header/Footer, Page Layout, Two-sided Printing,
Collating, Booklet Printing, Grouping,
Mixed Paper Sizes/ Orientations, Offsetting,
Printing on Transparencies, Front/Back Covers,
Toner Reduction, Poster Printing, Job hold printing

Operating System

UFR II: Windows® 8.1/10/11/Server2012/Server2012 R2/
Server2016/Server2019/Server2022,
Mac OS X (10.11 or later)

PCL: Windows® 8.1/10/11/Server2012/Server2012 R2/
Server2016/Server2019/Server2022

PS: Windows® 8.1/10/11/Server2012/Server2012 R2/
Server2016/Server2019/Server2022,
Mac OS X (10.11 or later)

PPD: Windows® 8.1/10/11, Mac OS X (10.11 or later)

As of Sep. 2022

COPY SPECIFICATIONS

Copy Speed

Up to 60 ppm (A4), 32 ppm (A3), 36 ppm (A4R),
60 ppm (A5R)

First-Copy-Out Time (BW/CL)

Approx. 2.9/4.5 seconds or less

Copy resolution (dpi)

Reading: 600 dpi x 600
Printing: Up to 1,200 x 1,200

Multiple Copies

Up to 999 copies

Copy Density

Automatic or Manual (6 Levels)

Magnification

Variable zoom: 25% to 400% (1% Increments)
Preset reduction/enlargement: 25%, 50%, 70%, 100% (1:1),
141%, 200%, 400%

Basic Copy Features

Preset R/E Ratios by Area, Two-Sided,
Density Adjustment, Original Type Selection,
Interrupt Mode, Book to Two Pages, Two-sided Original,
Job Build, N on 1, Add Cover, Insert Sheets,
Different Size Originals, Page Numbering,
Copy Set Numbering, Sharpness, Erase Frame,
Secure Watermark, Print Date, Gutter, Print & Check,
Negative/Positive, Repeat Images, Merge Job Blocks,
Mirror Image, Store in Mail Box, Copy ID Card,
Free Size Original, Color Mode, Reserved copy,
Copy Sample

SCAN SPECIFICATION

Type

Single-pass Duplexing Automatic Document Feeder*
(2-sided to 2-sided (Automatic))

Pull Scan Specifications

*Multi-sheet feed detection

Colour Network ScanGear2. For both TWAIN and WIA
Supported OS: Windows® 8.1/10/11/Server2012/
Server2012 R2/Server 2016/Server 2019/Server 2022

As of Sep. 2022

Scan Resolution (dpi)

Scan for Copy: 600 x 600
Scan for Send: (Push) 600 x 600 (SMB/FTP/WebDAV/
IFAX), (Pull) 600 x 600
Scan for Fax: 600 x 600

Document Feeder Paper Capacity (80 gsm)

Up to 150 sheets

Supported media size/s

A3, B4, A4, A4R, B5, B5R, A5, A5R, B6R

Supported media weight/s

One-sided scanning: 38 to 157 gsm/64 to 157 gsm
(BW/CL)
Double-sided scanning: 50 to 157 gsm/64 to 157 gsm
(BW/CL)

Scan Method

Push Scan, Pull Scan, Scan to Box, Scan to Advanced
Space, Scan to Network, Scan to USB Memory Key,
Scan to Mobile device, Scan to cloud
(uniFLOW Online - optional)

Scan Speed (ipm, BW/CL, A4)

Scan to cloud-based services: A range of solutions is
available to provide scanning to cloud-based services
depending on your requirements. Please contact your
sales representative for further information.

Single-sided Scanning : 80/80 (300pi), 80/60 (600 dpi)
Double-sided Scanning : 160/150 (300pi), 150/80
(600 dpi)

SEND SPECIFICATIONS

Optional/ standard

Standard on all models

Destination

Standard: E-mail/Internet FAX (SMTP), SMB, FTP,
WebDAV, Mail Box

Optional: Super G3 FAX

LDAP (2,000)/Local (1,600)/Speed dial (200)

Address Book/Speed dials

Push: up to 600 x 600

Pull: up to 600 x 600

Communication protocol

File: FTP, SMB v3.0, WebDAV

E-mail/I-Fax: SMTP, POP3

File Format

Standard: TIFF, JPEG, PDF (Compact, Searchable,
Apply policy, Optimize for Web, PDF A/1-b, Encrypted),
XPS (Compact, Searchable), Office Open XML
(PowerPoint, Word), PDF/XPS (Digital Signature)
Optional: PDF (Trace & Smooth)

Universal Send Features

Original Type Selection, Two-sided Original, Book to
Two Pages, Different-size Originals, Density Adjustment,
Sharpness, Copy Ratio, Erase Frame, Job Build, Delayed
Send, Preview, Job Done Notice, File Name, Subject/
Message, Reply-to, E-mail Priority, TX Report, Original
Content Orientation, Skip Blank Originals

TECHNICAL SPECIFICATIONS

imageRUNNER ADVANCE C5500 ES series

FAX SPECIFICATIONS

Optional/ standard	Optional on all models
Maximum Number of Connection Lines	2
Modem Speed	Super G3: 33.6 kbps G3: 14.4 kbps
Compression Method	MH, MR, MMR, JBIG
Resolution (dpi)	400 x 400 (Ultra Fine), 200 x 400 (Super Fine), 200 x 200 (Fine), 200 x 100 (Normal)
Sending/Receiving Size	Sending: A3, A4, A4R, A5 ¹ , A5R ¹ , B4, B5 ² , B5R ¹ Receiving: A3, B4, A4, A4R, A5R, B5, B5R ¹ Sent as A4 ² Sent as B4 short
FAX memory	Up to 30,000 pages
Speed dials	Max. 200
Group dials/destinations	Max. 199 dials
Sequential broadcast	Max. 256 addresses
Memory backup	Yes
Fax Features	Sender's Name (TTI), Selecting the Telephone Line (when sending fax), Direct Send, Delayed Send, Preview, Job Done Notice, TX Report, Interrupt Transmission, Sequential Broadcasting, Password/Subaddress Sending, Confidential Mailbox, 2 on 1 Log

STORE SPECIFICATIONS

Mail Box (Number supported)	100 User Inboxes, 1 Memory RX Inbox, 50 Confidential Fax Inboxes, 30,000 Maximum Pages Stored
Advanced space	Communication Protocol: SMB or WebDAV Supported Client PC: Windows* 8.1/10/11 Concurrent Connections (Max.): SMB:64, WebDAV:3 Standard: 16GB
Advanced Space available disc space	
Advanced Space Features:	Authentication for Advanced Space Log-in, Sort Function, Printing a PDF File with a Password, imageWARE Secure Audit Manager Support, Search, File Preview, Authentication Management, Open to public, URI TX, Backup/Restore
Memory Media	Standard: USB Memory

SECURITY SPECIFICATIONS

Authentication & Access Control	Standard: User Authentication (Picture Login, Picture and PIN Login, Card Login*), Username and Password Login, Function Level Login, Mobile Login), Department ID Authentication (Department ID and PIN Login, Function Level Login), uniFLOW Online Express (PIN Login, Picture Login, Picture and PIN Login, Card Login, Card and PIN Login, Username and Password Login, Department ID and PIN Login, Function Level Login), Access Management System (Access Control)
---------------------------------	--

*Card readers are optional, please refer to Hardware Accessories. Activation is required

Optional: My Print Anywhere secure print*
*Requires uniFLOW Online/uniFLOW

Network

Standard: IP/Mac Address Filtering, IPSEC, TLS 1.3
Encrypted Communication, SNMP V3.0, IEEE 802.1X, IPv6, SMTP Authentication, POP Authentication before SMTP, S/MIME

Document

Standard: Secure Print, Adobe LiveCycle® Rights Management ES2.5 Integration, Encrypted PDF, Encrypted Secure Print, Device signature, Secure Watermarks, uniFLOW Secure Print®
Optional: User signature, Document Scan locking

Device

*Requires uniFLOW Online/uniFLOW
Standard: Trusted Platform Module (TPM), Hard Disk Password Lock, Hard Disk Drive Erase, Mail Box Password Protection, Hard Disk Drive Encryption (AES-256bit/CBC, FIPS140-2 Validated), Common Criteria Certification (DIN ISO 15408)

Optional: Data Loss Prevention*
*Requires uniFLOW Online/uniFLOW

Device Management & Auditing

Administrator Password, Digital Certificate And Key Management, Audit Log, Image Data Logging, Security Policy Setting

ENVIRONMENTAL SPECIFICATIONS

Operating Environment	Temperature: 10 to 30 °C (50 to 86 °F) Humidity: 20 to 80 % RH (Relative Humidity)
Power source	220-240V 50/60Hz 5A
Power consumption	Maximum: Approx. 1.8 kW Printing: Approx. 849 W or less Standby: Approx. 67.9 W Sleep mode: Approx. 0.8 W ⁴ Plugin Off: Approx. 0.23W Typical Electricity Consumption (TEC)*: 0.86kWh

*As per US ENERGY STAR version 3.2

For detailed information relating to Erp:Lot6/26 regulation, please go to:
https://www.canon-europe.com/for_work/lot26/

Noise levels (BW/CL)

Sound Power Level (LwAd)⁵
Active(BW): 67.5 dB or Less, Active(CL): 68.1 dB or Less, Standby: 40 dB or Less⁶

Sound Pressure (LpAm)⁵
Bystander's position:
Active(BW): 49.6 dB or Less, Active(CL): 50.2 dB or Less, Standby: 24 dB or Less⁶

SOFTWARE AND PRINTER MANAGEMENT

Tracking and reporting

Standard: Universal Login Manager (ULM)
uniFLOW Online Express*
Optional: uniFLOW Online*

*For more information, please refer to: uniFLOW Online Express, uniFLOW Online

Remote management tools

iWEMC
eMaintenance
Content Delivery System

Scanning software

Network ScanGear

Optimisation tools

Canon Driver Configuration Tool

Platform

MEAP (Multifunction Embedded Application Platform)

Document Publishing

Optional: Therefore™, Kofax Power PDF Advanced

CONSUMABLES

Toner Cartridge/s

C-EXV 51 TONER BK/C/M/Y
C-EXV 51L TONER C/M/Y

Toner Estimated Yield

C-EXV 51 TONER BK: 69,000 pages
C-EXV 51 TONER C/M/Y: 60,000 pages
C-EXV 51L TONER C/M/Y: 26,000 pages
(Estimated @ 5% Coverage)

OUTPUT OPTIONS

Inner Finisher

INNER FINISHER-HI ES
Number of Trays: 2
Tray A (Upper) Capacity: A4, B5, A5, A5R 45 sheets, A3, B4, A4R, B5R, SRA3 45 sheets
Tray B (Lower) Capacity: A4, B5, A5, A5R 500 sheets, A3, B4, A4R, B5R, SRA3 250 sheets
Paper Weight: 52 to 300 gsm
Staple Position: Corner, Double
Staple Capacity: Corner and Double Stapling:
A4/B5: 50 sheets (52 to 90 gsm)
A3/B4/A4R: 30 sheets (52 to 90 gsm)
Eco Staple:
A3/A4/B4/B5: 5 sheets (52 to 64 gsm)
4 sheets (65 to 81.4 gsm)
3 sheets (81.5 to 105 gsm)

Staple On Demand: 40 sheets (80 gsm)
Dimensions (W x D x H): 466 mm x 525 mm x 225 mm
Weight: Approx. 8.6 kg

Staple Finisher

STAPLE FINISHER-Y1 ES
(Includes BUFFER PASS UNIT- L1)
Number of Trays: 2
Tray A (Upper) Capacity: A4, B5, A5, A5R 250 sheets, A3, B4, A4R, B5R, SRA3 125 sheets
Tray B (Lower) Capacity: A4, B5, A5, A5R 3,000 sheets, A3, B4, A4R, B5R, SRA3 1,500 sheets
Paper Weight: Upper Tray 52 to 256 gsm
Lower Tray 52 to 300 gsm

Staple Position: Corner, Double
Staple Capacity: Corner and Double Stapling:
A4/B5: 50 sheets (52 to 90 gsm)

A3, B4, A4R: 30 sheets (52 to 90 gsm)
Eco Staple:
A3/A4: 5 sheets (52 to 64 gsm)
4 sheets (65 to 81.4 gsm)
3 sheets (81.5 to 105 gsm)

Booklet Finisher

Staple On Demand: 50 sheets (90 gsm)
Dimensions (W x D x H): 637 mm x 623 mm x 1,142 mm (when the extension tray is extended)
Weight: Approx. 31 kg
Name: BOOKLET FINISHER-Y1 ES
(Includes BUFFER PASS UNIT- L1)
Number of Trays: 2
Tray A (Upper) Capacity: A4, B5, A5, A5R 250 sheets, A3, B4, A4R, B5R, SRA3 125 sheets
Tray B (Lower) Capacity: A4, B5, A5, A5R 3,000 sheets, A3, B4, A4R, B5R, SRA3 1,500 sheets
Paper Weight: Upper Tray 52 to 256 gsm
Lower Tray 52 to 300 gsm

Staple Position: Corner, Double
Staple Capacity: Corner and Double Stapling:
A4/B5: 50 sheets (52 to 90 gsm)

A3, B4R, A4R: 30 sheets (52 to 90 gsm)
Eco Staple:
A3/A4: 5 sheets (52 to 64 gsm)
4 sheets (65 to 81.4 gsm)
3 sheets (81.5 to 105 gsm)

Staple On Demand: 50 sheets (90 gsm)
Booklet Stitch paper size:
A3, B4, A4R, Custom Size (195.0 mm x 270 mm to 304.8 mm x 457.2 mm)
Booklet Stitch Staple Capacity: 20 sheets x 10 sets (81 gsm) (including 1 cover sheet up to 256 gsm)
Dimensions (W x D x H): 637 mm x 623 mm x 1,142 mm (when the extension tray is extended)
Weight: Approx. 57 kg

HARDWARE ACCESSORIES

Card Readers

Various card readers are available, e.g. MiCard Plus. Please contact your local Canon Office for more details.



TECHNICAL SPECIFICATIONS

imageRUNNER ADVANCE C5500 ES series

SYSTEM AND CONTROLLER OPTIONS

Print Accessories

PCL INTERNATIONAL FONT SET-A1 (Adds PCL support for Andalé Mono WT J/K/S/T (Japanese/Korean/Simplified Chinese/Traditional Chinese).

Send Options

UNIVERSAL SEND DIGITAL USER SIGNATURE KIT-C1 - Ensures the authenticity of a PDF/XPS by identifying the user that sent the document through a visible and/or invisible digital signature.

UNIVERSAL SEND TRACE & SMOOTH PDF KIT-A1 - Enables the device to create and send Trace and Smooth PDF

Barcode Printing

BARCODE PRINTING KIT-D1 - Provides the ability to print 1D and 2D barcodes on output using jet caps technology.

Fax Accessories

SUPER G3 FAX BOARD-AS1 ER - Adds fax functionality.
REMOTE FAX KIT-A1 - Enables the device to send and receive fax from another device connected with a fax board.

OTHER OPTIONS

Stapler Accessories

STAPLE-P1 - For stapling (2 x 5,000 pcs)
STAPLE CARTRIDGE-Y1 - For saddle stitching (2 x 2,000 pcs)
INSTANT STAPLER-B1

Other

Antimicrobial Film - Various Sheets designed to fit the devices most common touch points*.

*Application by a Service engineer is recommended

Footnotes

^[1] Booklet Finisher-Y1 only

^[2] Some types of tracing paper cannot be used.

^[3] Time between device power-on and when the start key is enabled

^[4] 0.8W sleep mode is not available in all circumstances due to certain settings.

^[5] Declared noise emission in accordance with ISO 7779

^[6] Data taken from ECO declaration

Software & Solutions



Certifications and compatibility



Canon Ireland
3006 Lake Drive
Citywest, Saggart
Co. Dublin, Ireland
Telephone No: 01 2052400
Facsimile No: 01 2052525
canon.ie

Canon (UK) Ltd
The Bower
4 Roundwood Avenue
Stockley Park
Uxbridge
UB11 1AF

Canon Inc.
canon.com
Canon Europe
canon-europe.com
English edition
© Canon Europa N.V., 2023