

EVOLVE YOUR BUSINESS' PRINT ENVIRONMENT WITH SMART, HIGH-SPEED, MONO A4 MULTIFUNCTION DEVICES



MAIN CONFIGURATION OPTIONS

Choice of paper supply options*



iR-ADV 719i/619i/529i

DESKTOP USE WITHOUT FINISHER



iR-ADV 719iZ/619iZ/529iZ

DESKTOP USE WITH BUILT-IN FINISHER

STANDARD CASSETTE MODULE-AG1

- Media weight 60 to 135 gsm
- 550 sheets (80 gsm)

ENVELOPE CASSETTE MODULE-A1

- Envelope Size COM10 No.10, Monarch, DL, ISO-C5
- Media weight 80 to 100 gsm
- 75 sheets (envelope)

DESKTOP WITH EXTRA CASSETTE (OPTIONAL)

HIGH CAPACITY CASSETTE FEEDING UNIT-D1

- Media weight 60 to 135 gsm
- 2,000 sheets (80 gsm)

CASSETTE FEEDING UNIT-AR1

- Media weight 60 to 135 gsm
- 550 sheets (80 gsm)

CASSETTE FEEDING UNIT-AX1

- Media weight 60 to 135 gsm
- 1,650 sheets (80 gsm)

PLAIN PEDESTAL TYPE-W2

FLOOR STANDING (OPTIONAL - WITHOUT EXTRA CASSETTE)

PLAIN PEDESTAL TYPE-X2

- For use with 1 (i models) Envelope Cassette Module-A1 or additional Standard Cassette Module AG1

*Paper supply options include up to three additional cassettes for non finisher models (i series) and up to two additional cassettes for finisher models (iZ series)

This flat configuration is for illustration purpose only. For a complete list of options and the exact compatibility relationships, please refer to the [online product configurator](#).

The Unified Firmware Platform (UFP) ensures that the latest feature upgrades and protection are available, for an enhanced user experience across the entire iR ADVANCE DX portfolio.



TECHNICAL SPECIFICATIONS

imageRUNNER ADVANCE DX 719/619/529 Series

MAIN UNIT		Fonts	PS fonts: 136 Roman PCL fonts: 93 Roman, 10 Bitmap fonts, 2 OCR fonts, Andale Mono WT J/K/S/T*1 (Japanese, Korean, Simplified and Traditional Chinese), Barcode fonts*2 *1 Optional PCL International Font Set-A1 is required. *2 Optional Barcode Printing Kit-D1 is required.
Machine type	A4 Monochrome Laser Multifunctional	Print Features	Secured Print, Secure Watermark, Header/Footer, Page Layout, Two-sided Printing, Toner Reduction, Poster Printing, Forced Hold printing, Print Date, Scheduled Printing, Printing Using a Virtual Printer
Core functions	Print, Copy, Scan, Send and optional Fax	Operating System	UFRIL: Windows® 8.1/10/11/Server2012/Server2012 R2/ Server2016/Server2019/Server2022, Mac OS X (10.11 or later) PCL: Windows® 8.1/10/11/Server2012/Server2012 R2/ Server2016/Server2019/Server2022 PS: Windows® 8.1/10/11/Server2012/Server2012 R2/ Server2016/Server2019/Server2022, Mac OS X (10.11 or later) PPD: Windows® 8.1/10/11, Mac OS X (10.11 or later)
Processor	1.8GHz Dual Core Processor	COPY SPECIFICATIONS	
Control Panel	10.1" TFT LCD WSVGA Color Touch panel	Copy Speed*	iR-ADV DX 719i/719iZ 71 ppm (A4), 113 ppm (A5), 40 ppm (A5R, A6) iR-ADV DX 619i/619iZ 61 ppm (A4), 99 ppm (A5), 35 ppm (A5R, A6) iR-ADV DX 529i/529iZ 52 ppm (A4), 80 ppm (A5), 35 ppm (A5R, A6) *1-sided
Memory	Standard: 3.5GB RAM	First-Copy-Out Time (A4)	Approx. 5 seconds or less
Hard Disk drive	Standard: (SSD) 256 GB	Copy resolution (dpi)	600 x 600
Interface Connection	Network Standard: 1000Base-T/100Base-TX/10Base-T, Optional: Wireless LAN (IEEE 802.11b/g/n) Others Standard: USB 2.0 x 2 (Host), USB 3.0 x 1 (Host), USB 2.0 x 1 (Device) Optional: Copy Control Interface	Multiple Copies	Up to 9,999 copies
Paper Supply Capacity (A4, 80 gsm)	Standard: 650 sheets 100-sheets Multi-purpose tray 550-sheets Paper cassette x 1 Maximum: 3,200 sheets (with High Capacity Cassette Feeding Unit-D1)	Copy Density	Automatic or Manual (9 Levels)
Paper Output Capacity (A4, 80 gsm)	Standard model (iR-ADV DX 719i/619i/529i): 500 sheets Finisher model (iR-ADV DX 719iZ/619iZ/529iZ): 1,000 sheets	Magnification	Variable zoom: 25% to 400% (1% Increments) Preset reduction/enlargement: 25%, 50%, 70%, 100%(1:1), 141%, 200%, 400%
Finishing Capabilities	Standard model (iR-ADV DX 719i/619i/529i): Collate, Group Finisher Model (iR-ADV DX 719iZ/619iZ/529iZ): Collate, Group, Offset*, Staple *available with upper tray	Copy Features	Preset R/E Ratios by Area, Two-Sided, Density Adjustment, Original Type Selection, Interrupt Mode, Two-sided Original, Job Build, N on 1, Page Numbering, Copy Set Numbering, Sharpness, Erase Frame, Secure Watermark, Print Date, Copy ID Card, Skip Blank Pages, Reserved copy, Copy Sample
Supported Media Types	Multi-purpose tray: Thin, Plain, Recycled, Heavy, Color, Transparency, Bond, Envelope Paper Cassette: Thin, Plain, Recycled, Heavy, Color, Labels, Bond, Pre-punched	SCAN SPECIFICATIONS	
Supported Media Sizes	Multi-purpose tray: Standard size: A4, A5, A5R, A6, B5 Custom size: 76.2 x 127.0 mm to 216.0 x 355.6 mm Envelope: COM10 No.10, Monarch, DL, ISO-C5 Paper Cassette: Standard size: A4, A5, A5R, A6, B5 Custom size: 99.0 x 148.0 mm to 216.0 x 297.0 mm	Standard type	Single-pass Duplexing Automatic Document Feeder* [2-sided to 2-sided (Automatic)] * Detect Feeder Multi Sheet Feed is supported.
Supported Media Weights	Multi-purpose tray: 60 to 200 gsm Paper Cassette: 60 to 135 gsm Duplex: 60 to 120 gsm	Document Feeder Paper Capacity (80 gsm)	100 Sheets
Warm-up Time	Quick Startup Mode: 4 Seconds or less* *Time from device power-on to when the copy icon appears and is enabled to operate on the touch panel display. From Sleep Mode: 10 Seconds or less From Power On: 10 Seconds or Less* **Time from device power on, until copy ready (not print reservation)	Acceptable Originals and Weights	Platen: Sheet, Book, and 3-Dimensional Objects Document Feeder media weight: 1-sided scanning: 42 to 128 gsm (BW), 64 to 128 gsm (CL) 2-sided scanning: 50 to 128 gsm (BW), 64 to 128 gsm (CL) Note: Business card: 80 to 220 gsm Original width narrower than A6: 50 to 128 gsm
Dimensions (W x D x H)	Standard model (iR-ADV DX 719i/619i/529i): 500 x 598 x 617 mm Finisher model (iR-ADV DX 719iZ/619iZ/529iZ): 502 x 598 x 814 mm	Supported Media Sizes	Platen scanning size: up to 216.0 x 355.6 mm Document Feeder media size: A4, A5R, A6, B5, Custom size: 48.0 x 128.0 mm to 216.0 x 355.6 mm Business card: 48.0 x 85.0 mm to 55.0 x 91.0 mm
Installation Space(W x D)	Standard model/ Finisher model: 1,052 x 823 mm (with left CRG door open + right door open + the cassette drawer open)	Scan Speed (ipm; BW/CL, A4)	Send (300 x 300 dpi): up to 95/190 when Automatic Colour Select "OFF": 1-sided Scanning: 95 2-sided Scanning: 190 Automatic Color Select "ON": 1-sided Scanning: 50 2-sided Scanning: 100 Copy (600 x 600 dpi, BW only): 1-sided Scanning: 95 2-sided Scanning: 140
Weight	Standard model (iR-ADV DX 719i/619i/529i): Approx. 37 kg including toner Finisher model (iR-ADV DX 719iZ/619iZ/529iZ): Approx. 46 kg including toner	Scan Resolution (dpi)	Scan for Copy: up to 600 x 600 Scan for Send: (Push) up to 600 x 600 (SMB/FTP/ WebDAV/IFAX), (Pull) up to 600 x 600 Scan for Fax: up to 600 x 600
PRINT SPECIFICATIONS		Pull Scan Specifications	Colour Network ScanGear2. For both TWAIN and WIA Supported OS: Windows®7/ 8.1/ 10/ Server2008/ Server2008 R2/ Server2012/ Server2012 R2/ Server 2016 As of Feb. 2020
Print Speed*	iR-ADV DX 719i/719iZ 71 ppm (A4), 113 ppm (A5), 40 ppm (A5R, A6) iR-ADV DX 619i/619iZ 61 ppm (A4), 99 ppm (A5), 35 ppm (A5R, A6) iR-ADV DX 529i/529iZ 52 ppm (A4), 80 ppm (A5), 35 ppm (A5R, A6) *1-sided	Scan Method	Push Scan, Pull Scan, Scan to Box, Scan to Advanced Space, Scan to Network, Scan to USB Memory Key, Scan to Mobile devices, Scan to cloud (uniFLOW Online - Optional)
Print Resolution (dpi)	600 x 600 to 1,200 x 1,200 (equivalent)		
Duplex Print Speed (A4/LTR)	719i/719iZ: 58ipm/62ipm 619i/619iZ: 50ipm/53ipm 529i/529iZ: 50ipm/53ipm		
Page description languages	Standard: UFR II, PCL6, Adobe® PostScript®3™		
Direct Print	Supported file types: TIFF, JPEG, PDF, EPS, and XPS		
Printing from mobile and cloud	AirPrint, Mopria, Universal Print by Microsoft, Canon PRINT Business, and uniFLOW Online (optional) A range of software and MEAP-based solutions are available to provide printing from mobile devices or internet-connected devices and cloud-based services depending on your requirements. Please contact your sales representative for further information.		

TECHNICAL SPECIFICATIONS

imageRUNNER ADVANCE DX 719/619/529 Series

SEND SPECIFICATIONS

Destination	Standard: E-mail/Internet FAX (SMTP), SMB3.1.1, FTP, WebDAV, Mail Box Optional: G3 FAX, IP Fax
Address Book	LDAP (2,000)/Local (1,600)/Speed dial (200)
Send resolution (dpi)	Push: up to 600 x 600 Pull: up to 600 x 600
Communication protocol	File: FTP(TCP/IP), SMB3.1.1 (TCP/IP), WebDAV E-mail/I-Fax: SMTP, POP3
File Format	Standard: TIFF, JPEG, PDF (Compact, Searchable, Apply policy, Optimize for Web, PDF A/1-b, Trace & Smooth, Encrypted, Device Signature, User Signature), XPS (Compact, Searchable, Device Signature, User Signature), Office Open XML (PowerPoint, Word)
Universal Send Features	Original Type Selection, Two-sided Original, Density Adjustment, Sharpness, Erase Frame, Job Build, Delayed Send, Preview, Job Done Notice, File Name, Subject/Message, Reply-to, E-mail Priority, TX Report, Original Content Orientation, Skip Blank Pages

FAX SPECIFICATIONS

Maximum Number of Connection Lines	(Optional) 1
Modem Speed	Super G3: 33.6 kbps G3: 14.4 kbps
Compression Method	MH, MR, MMR, JBIG
Resolution (dpi)	400x400 (Ultra Fine), 200x400 (Super Fine), 200x200 (Fine), 200x100 (Normal)
Sending/Receiving Size	A4, A5*, A6* and B5* / A4, A5, B5 *Sent as A4
FAX memory	Up to 30,000 pages (2,000 jobs)
Speed dials	Max. 200
Group dials/destinations	Max. 199 dials
Sequential broadcast	Max. 256 addresses
Memory backup	Yes
Fax Features	Sender's Name (TTI), Selecting the Telephone Line (when sending fax), Direct Send, Delayed Send, Preview, Job Done Notice, TX Report, Interrupt Transmission, Sequential Broadcasting, Password/Subaddress Sending, Confidential Mailbox, 2 on 1 Log

STORE SPECIFICATIONS

Mail Box (Number supported)	100 User Inboxes, 1 Memory RX Inbox, 50 Confidential Fax Inboxes Maximum 30,000 Pages (2,000 jobs) Stored
Advanced Space	Communication Protocol: SMB or WebDAV Supported Client PC: Windows® 8.1/10 Concurrent Connections (Max.): SMB: 64, WebDAV: 3
Advanced Space available disc space	Standard: 16 GB
Advanced Space Features	Authentication for Advanced Space Log-in, Sort Function, Printing a PDF File with a Password, imageWARE Secure Audit Manager Support, Search, File Preview, Authentication Management, Open to public, URI TX, Backup/Restore

SECURITY SPECIFICATIONS

Authentication and Access Control	User Authentication (Picture Login, Picture and PIN Login, Card Login, Username and Password Login, Function Level Login, Mobile Login), Department ID Authentication (Department ID and PIN Login, Function Level Login), uniFLOW Online Express (PIN Login, Picture Login, Picture and PIN Login, Card Login, Card and PIN Login, Username and Password Login, Department ID and PIN Login, Function Level Login), Access Management System (Access Control)
Document Security	Print Security (Secure Print, Encrypted Secure Print, Forced Hold Printing, uniFLOW Secure Print*), Receive Data Security (Confidential Fax Inbox Forwarding Received Documents Automatically), Scan Security (Encrypted PDF, Device Signature PDF/XPS, User Signature PDF/XPS, Adobe LiveCycle® Rights Management ES2.5 Integration), BOX Security (Mail Box Password Protected, Advanced Space Access Control), Send Data Security (Setting for requesting password input per transmission, Restricted E-mail/File send functions, Confirming FAX number, Allow/Restrict Fax Driver Transmissions, Allow/Restrict Sending from History, S/MIME Support), Document Tracking (Secure Watermark) *1 Requires uniFLOW Online / uniFLOW

Network Security

Network Security	TLS 1.3, FTPS, IPsec, IEEE802.1X authentication, SNMP V3.0, Firewall Functionality (IP/MAC Address Filtering), Dual Network Support (Wired LAN/Wireless LAN, Wired LAN/Wired LAN), WPA3 support, Disabling Unused Functions (Enabling/Disabling Protocols/Applications, Enabling/Disabling Remote UI, Enabling/Disabling USB Interface), G3 FAX separation from LAN, USB Port separation from LAN, Prohibit the execution of files stored in Advanced Space in the MFP, Scan and Send -Virus Concerns for E-mail Reception
Device Security	Protecting SSD Data [SSD Data Encryption (FIPS 140-2/140-3)], SSD Lock, Standard SSD Initialize, Trusted Platform Module (TPM 2.0), Job Log Conceal Function, Protecting MFP Software Integrity, Checking MFD Software Integrity & Platform Firmware Resiliency (NIST SP800-193) with Automatic System Recovery (Verify System at Start-up, Runtime Intrusion Detection enabled with McAfee Embedded Control), HCD-PP Common Criteria Certification *validation pending
Device Management and Auditing	Administrator Password, Remote Management Two-factor Authentication, Digital Certificate And Key Management, Audit Log, Cooperating with External Security Audit System (Security Information and Event Management), Image Data Logging, Security Policy Setting Device administration and Security administration Passwords

ENVIRONMENTAL SPECIFICATIONS

Operating Environment	Temperature: 10 to 30 °C Humidity: 20 to 80 % RH (Relative Humidity) 220-240 V, 50/60 Hz, 4.8 A
Power source	Maximum: Approx. 1,500 W Copying (with DADF continuous scan): iR-ADV DX 719i/719iZ: 827.5 W*1 iR-ADV DX 619i/619iZ: 784.6 W*1 iR-ADV DX 529i/529iZ: 783.1 W*1
Power consumption	Network Printing: iR-ADV DX 719i/719iZ: 828.3 W*1 iR-ADV DX 619i/619iZ: 793.4 W*1 iR-ADV DX 529i/529iZ: 728.5 W*1 Standby: Approx. 28.92 W*1 Sleep mode: Approx. 1.0 W*2 *1 Reference value: measured one unit *2 1.0 W is not available in all circumstances due to certain settings.

Typical Electricity Consumption (TEC)* rating	iR-ADV DX 719i/719iZ: 0.73 kWh iR-ADV DX 619i/619iZ: 0.59 kWh iR-ADV DX 529i/529iZ: 0.49 kWh *As per USA Energy Star 3.0
--	---

For detailed information relating to Erp:Lot6/26 regulation, please go to:
https://www.canon-europe.com/for_work/lot26/

Noise levels

Sound Power Level (LWA, m)*	Active (1-sided) iR-ADV DX 719iZ/719i: 7.0 B, Kv 0.3 B /6.9 B, Kv 0.3 B iR-ADV DX 619iZ/619i: 6.8 B, Kv 0.3 B /6.8 B, Kv 0.3 B iR-ADV DX 529iZ/529i: 6.8 B, Kv 0.3 B /6.7 B, Kv 0.3 B *Reference value: measured only one unit with ISO7779, described with ISO9296 (2017)
Sound Pressure (LpAm)*	Bystander's position: Active(BW) (1-sided): iR-ADV DX 719i/719iZ: 56 dB iR-ADV DX 619i/619iZ: 55 dB iR-ADV DX 529i/529iZ: 54 dB Stand-by iR-ADV DX 719iZ/619iZ/529iZ: 25 dB iR-ADV DX 719i/619i/529i: 21 dB *Reference value: Measured only one unit with ISO7779, described with ISO9296 (2017)
Standards	Blue Angel

CONSUMABLES

Toner Cartridges	T03 Black
Toner Yield	Black: 51,500 pages Toner Cartridge yield in accordance with ISO/IEC 19752.

SOFTWARE AND PRINTER MANAGEMENT

Tracking and reporting	For detailed information please visit our website https://www.canon-europe.com/business/ Universal Login Manager (ULM) uniFLOW Online Express* * For more information, please refer to uniFLOW Online Express uniFLOW Online
Remote management tools	iW Management Console eMaintenance Content Delivery System
Scanning software	Network ScanGear
Platform	MEAP (Multifunctional Embedded Application Platform)
Document Publishing	Kofax PowerPDF (optional)



TECHNICAL SPECIFICATIONS

imageRUNNER ADVANCE DX 719/619/529 Series

PAPER SUPPLY OPTIONS

Cassette Module-AG1

Paper Capacity: 550 sheets (80 gsm)
 Paper Type: Thin, Plain, Recycled, Heavy, Color, Labels, Bond, Pre-punched
 Paper Size: A4, A5, A5R, A6, B5,
 Custom size: 99.0 x 148.0 mm to 216.0 x 355.6 mm
 Paper Weight: 60 to 135 gsm
 Power Source: From the Main Unit
 Dimensions (W x D x H): 484 x 450 x 127 mm
 (attached to the main unit)
 Weight: Approx. 7 kg

Envelope Cassette Module-A1

Paper Capacity: 75 Envelopes
 Envelope Size: COM10 No.10, Monarch, DL, ISO-C5
 Paper Weight: 80 to 100 gsm
 Power Source: From the Main Unit
 Dimensions (W x D x H): 484 x 450 x 127 mm
 (attached to the main unit)
 Weight: Approx. 7 kg

Cassette Feeding Unit-AX1

Paper Capacity: 1,650 sheets (80 gsm)
 Paper Type: Thin, Plain, Recycled, Heavy, Color, Labels, Bond, Pre-punched
 Paper Size: A4, A5, A5R, A6, B5, Custom size: 99.0 x 148.0 mm to 216.0 x 355.6 mm
 Paper Weight: 60 to 135 gsm
 Power Source: From the Main Unit
 Dimensions (W x D x H): 642 x 657 x 456 mm
 (attached to the main unit)
 Weight: Approx. 45 kg

Cassette Feeding Unit-AR1

Paper Capacity: 550 sheets (80 gsm)
 Paper Type: Thin, Plain, Recycled, Heavy, Color, Labels, Bond, Pre-punched
 Paper Size: A4, A5, A5R, A6, B5, Custom size: 99.0 x 148.0 mm to 216.0 x 355.6 mm
 Paper Weight: 60 to 135 gsm
 Power Source: From the Main Unit
 Dimensions (W x D x H): 642 x 657 x 456 mm
 (attached to the main unit)
 Weight: Approx. 19 kg

High Capacity Cassette Feeding Unit-D1

Upper cassette:
 Paper Capacity: 550 sheets (80 gsm)
 Paper Type: Thin, Plain, Recycled, Heavy, Color, Labels, Bond, Pre-punched
 Paper Size: A4, A5, A5R, A6, B5, Custom size: 99.0 x 148.0 mm to 216.0 x 355.6 mm
 Paper Weight: 60 to 135 gsm

Lower cassette:
 Paper Capacity: 2,000 sheets (80 gsm)
 Paper Type: Thin, Plain, Recycled, Heavy, Color, Bond, Pre-punched
 Paper Size: A4
 Paper Weight: 60 to 135 gsm
 Power Source: From the Main Unit
 Dimensions (W x D x H): 642 x 657 x 456 mm
 (attached to the main unit)
 Weight: Approx. 27 kg

OUTPUT FEATURES*

Finisher Model (IR-ADV DX 719IZ/ 619IZ/ 529IZ)

*Paper capacity may vary with different paper type/size.

Tray Capacity (80 gsm):
 Upper Tray: A4, A5R, B5: 400 sheets
 Lower Tray: A4, A5R, B5: 100 sheets
 Main unit output tray: A4, A5, A5R, A6, B5: 500 sheets
 Paper Type: Thin, Plain, Recycled, Heavy, Color, Bond, Transparency*, Envelope*
*only for Main Unit Output tray
 Staple Paper Weight: 60 to 120 gsm
 Staple Position: Corner
 Staple Paper Size: A4, Custom size (210.0 x 279.4 mm to 216.0 x 355.6 mm)
 Staple Capacity: 30 sheets (60 to 90 gsm), 20 sheets (91 to 120 gsm)

HARDWARE ACCESSORIES

Card Readers

Various card readers available e.g. MiCard Plus. Please contact local Canon Office for more details.
 Copy Card Reader-F1
 Copy Card Reader Attachment-B5

SYSTEM AND CONTROLLER OPTIONS

Print Accessories

PCL International Font Set-A1

Barcode Printing

Barcode Printing Kit-D1

System Accessories

Copy Control Interface Kit-A1
 Wireless LAN Board-D1

FAX Accessories

Super G3 FAX Board-BM1
 Remote Fax Kit-A1
 IP FAX Expansion Kit-B1

OTHER OPTIONS

Accessibility Accessories

ADF Access Handle-A1

Consumables

Staple-P1

Software & Solutions



Certifications and compatibility



Canon Inc.
 canon.com
 Canon Europe
 canon-europe.com
 English edition
 © Canon Europa N.V., 2023