



## Product environmental attributes – THE ECO DECLARATION

The declaration may be published only when all rows and/or fields marked with an \* are filled-in (n.a. for not applicable).

Additional information regarding each item may be found under P14.

Brand *	Canon	Logo
Company name *	Canon Europa N.V.	
Contact information *	environment@canon-europe.com	Canon
Internet site *	www.canon-europe.com	
Additional information		

	The company declares (based on product specification or test results based obtained from sample testing), that the product conforms to the statements given in this declaration.				
Type of product *	MFP				
Commercial name *	imageRUNNER ADVANCE 4225i EQ80				
Model number *	imageRUNNER ADVANCE 4225i EQ80				
Issue date *	2020/11/10				
Intended market *	Global 🔀 Europe 🗌 Asia, Pacific & Japan 🔲 Americas 🔲 Other				
Additional information					

This is an uncontrolled copy when in printed form. Please refer to the contact information for the latest version.

Quality Control			ent met
Item		Yes	No
QC1 *	The company enforces an internal quality control scheme to ensure the correctness of this eco declaration		
QC2 *	The company is a member of an eco declaration system that enforces regular independent quality control such as organized by IT-Företagen (see www.itecodeclaration.org).		

Model number *	imageRUNNER ADVANCE 4225i EQ80		
Issue date *	2020/11/10	Logo	

Product	environmental attributes - Legal requirements	Require	emer	nt met
Item		Yes	No	n.a.
P1	Hazardous substances and preparations	_	-	•
P1.1*	Products do not contain lead max 0.1%, cadmium max 0.01%, mercury max 0.1%, hexavalent chromium	$\boxtimes$		
	max 0.1%, polybrominated biphenyls (PBB) max 0.1% and polybrominated diphenyl ethers (PBDE) max			
	0,1% (see legal reference and Note 1).			
P1.2*	Products do not contain Asbestos (see legal reference).	$\boxtimes$		
	Comment: Legal reference has no maximum concentration value.			
P1.3*	Products do not contain Ozone Depleting Substances: Chlorofluorocarbons (CFC),	$\boxtimes$		
	hydrobromofluorocarbons (HBFC), hydrochlorofluorcarbons (HCFC), Halons, carbontetrachloride, 1,1,1-			
	trichloroethane, methyl bromide (see legal reference). Comment: Legal reference has no maximum			
P1.4*	concentration values.  Products do not contain polychlorinated biphenyl (PCB) max 0.005% by weight, polychlorinated terphenyl		$\overline{}$	
F 1.4	(PCT) max 0.005% by weight (see legal reference).	$\boxtimes$	Ш	
P1.5*	Products do not contain short chain chloroparaffins (SCCP) with 10-13 carbon atoms in the chain containing		$\overline{}$	
F 1.5	at least 48% per mass of chlorine in the SCCP max 0.1% (see legal reference).		Ш	
P1.6*	Textile and leather parts with direct skin contact do not contain Tri-(2,3,-dibromopropyl)-phosphate (TRIS),	$\neg$		$\square$
1 1.0	Tris-(aziridinyl)-phosphineoxide (TEPA), polybrominated biphenyl (PBB) (see legal reference).		Ш	$\boxtimes$
	Comment: Legal reference has no maximum concentration values.			
P1.7*	Textile and leather parts with direct skin contact do not contain Azo colorants that split aromatic amines			$\boxtimes$
	max 0.003% by weight (see legal reference and Note 1).	ш	ш	
P1.8*	Wooden parts do not contain arsenic and chromium as a wood preservation treatment as well as			$\boxtimes$
	pentachlorophenol and derivatives (see legal reference).	ш	ш	
	Comment: Legal reference has no maximum concentration values.			
P1.9*	Parts with direct and prolonged skin contact do not release nickel in concentrations above 0.5			$\boxtimes$
	microgram/cm2/week (see legal reference).			_
	Comment: Max limit in legal reference when tested according to EN1811:1998.			
P2	Batteries			
P2.1*	If the product contains a battery or an accumulator, it is labeled with the disposal symbol and if it contains	$\boxtimes$		
	more than 0.0005% of mercury (for button cells only) by weight, or more than 0.004% of lead, it shall be			
	marked with the chemical symbol for the metal concerned, Hg or Pb. Information on proper disposal is			
D0.0*	provided in user manual. (See legal reference)			_
P2.2*	Button cells used in the product do not contain more than 2% by weight of mercury. Other batteries or	$\boxtimes$		Ш
P2.3*	accumulators do not contain more than 0.0005% of mercury or 0.002% of cadmium. (See legal reference)  Batteries and accumulators are easily removable by either users or service providers (as dependent on the	$\boxtimes$	$\overline{}$	$\overline{}$
1 2.5	design of the product). Exception: Batteries that are permanently installed for safety, performance, medical		Ш	Ш
	or data integrity reasons do not have to be "easily removable". (See legal reference)			
P3	Safety, EMC connection to the telephone network and labeling		•	
P3.1*	The product complies with legally required safety standards as specified (see legal reference).			$\overline{}$
P3.2*	The product complies with legally required standards for electromagnetic compatibility (see legal reference).		+	-
			ᆜ	
P3.3*	If product is intended for connection to a public telecom network or contains a radio transmitter, it complies	$\boxtimes$	Ш	
P3.4*	with legally required standards for radio and telecommunication devices (see legal reference).		_	_
	The product is labeled to show conformance with applicable legal requirements (see legal reference).	<u> </u>	<u>Ш</u>	
P4	Consumable materials			
P4.1*	If a photo conductor (drum, belt etc.) is used in the product, it does not contain cadmium max 0.01% (see	$\boxtimes$		
	legal reference and Note 1).			
P4.2*	If ink/toner is used in the product, it does not contain cadmium max 0.1% by weight (see legal reference).	$\boxtimes$		
P4.3*	If the ink/toner formulation/preparation is classified as hazardous according to applicable regulations, the	$\boxtimes$		
	product/packaging is adequately labeled and a Safety Data Sheet (SDS/MSDS) in accordance with these			_
	requirements (see legal reference).			
P5	Product packaging			
P5.1*	Packaging and packaging components do not contain lead, mercury, cadmium and hexavalent chromium	$\boxtimes$		
DE C*	max 0.01% by weight of these together.		_	
P5.2*	Plastic packaging material is marked according to ISO 11469 referring ISO 1043 (see legal reference).			
P5.3*	The product packaging material is free from ozone depleting substances as specified in the Montreal	$\boxtimes$		
	Protocol (see legal reference).	_	_	_
1	Comment: Legal reference has no maximum concentration values.			

Note 1 Restriction applies to the homogeneous material, unless other specified and expressed in weight %.

Model number *	imageRUNNER ADVANCE 4225i EQ80		
Issue date *	2020/11/10	Logo	

Teatment information	Produc	roduct environmental attributes - Market requirements - Environmental conscious design Requirement met					
Posting   Disassembly, recycling   Disassemb	-	*=mandatory to fill in. Additional information regarding each item may be found under P14.	Yes	No	n.a.		
Disassembly, recycling   P7.1*   Parts that have to be treated separately are easily separable   P7.2*   Plastic materials in covers/housing have no surface coating.							
Disassembly, recycling  P7.1* Parts that have to be treated separately are easily separable  P7.2* Plastic materials in covers/housing have no surface coating.  P7.3* Plastic parts >250 gar be treated separately are easily separable materials.  P7.4* Plastic parts >250 gar be material codes according to 150 11489 referring ISO 1043.  P7.5* Plastic parts are free from metal inlays or have inlays that can be removed with commonly available tools.  P7.6* Labels are easily separable. (This requirement does not apply to safety/regulatory labels).  P7.6* Upgrading can be done e.g., with processor, memory, cards or drives  P7.8* Upgrading can be done e.g. with processor, memory, cards or drives  P7.9* Spare parts are available after end of production for: years  P7.9* Spare parts are available after end of production for: years  P7.11* Product cover/housing material type:  Material and substance requirements  P7.12* Electrical cable insulation material of power cables are halogen free (including PVC). (See Note 1)  P7.13* Electrical cable insulation material of signal cables are halogen free (including PVC). (See Note 1)  P7.14* All cover/housing plastic parts >25g are halogen free. (See Note 2)  P7.15* All printed circuit boards (without components) >25g are halogen free. (See Note 2)  P7.16* Flame retarded plastic parts >25g in covers / housings are marked according ISO 1043-4:  All: Chemical specifications of flame retardants in printed circuit boards (without components):  T8BPA (additive) . T8BPA (reactive) . Other; chemical name: , CAS #:  Alt: 2  Chemical specifications of flame retardants in printed circuit boards (without components):  T8BPA (additive) . T8BPA (reactive) . Other; chemical name: , CAS #:  Alt: 2  Chemical specifications of flame retardants in printed circuit boards (without components):  Comment. No legal limits exist, this is a market requirement.  1. Chemical name: , CAS #:  Alt: 2  Chemical specifications of flame retardants in plastic parts >25g according ISO 1043-4:  P7.19* Of total plast				Ш			
P7.1º Parts that have to be treated separately are easily separable P7.2º Plastic materials in covers/housing have no surface coating. P7.3º Plastic parts >25g have material or of easily separable materials. P7.4º Plastic parts >25g have material codes according to ISO 11469 referring ISO 1043.  P7.6º Labels are free from metal inlays or have inlays that can be removed with commonly available tools. P7.6º Labels are easily separable. (This requirement does not apply to safety/regulatory labels). Product lifetime P7.7º Upgrading can be done e.g. with processor, memory, cards or drives P7.8º Upgrading can be done e.g. with processor, memory, cards or drives P7.9. Spare parts are available after end of production for: years P7.10 Service is available after end of production for: years P7.11 Service is available after end of production for: years P7.12 Electrical cable insulation material of signal cables are halogen free (including PVC). (See Note 1) P7.13 Electrical cable insulation material of signal cables are halogen free (including PVC). (See Note 1) P7.14 All cover/housing plastic parts >25g are halogen free. (See Note 1) P7.15 All printed circuit boards (without components) >25g are halogen free. (See Note 2) P7.16 Flame retarded plastic parts >25g in covers / housings are marked according ISO 1043-4: Marking: FR(40) P7.17 Alt. 1 Chemical specifications of flame retardants in printed circuit boards (without components): TBBPA (additive) TBBPA (reactive) Other; chemical name: CAS #: Alt. 2 Chemical specifications of flame retardants in printed circuit boards (without components) >25g according ISO 1043-4:  P7.18 Alt. 1 Flame retarded plastic parts >25g ontain the following flame retardant substances/preparations in concentrations above 0.1%: Comment: No legal limits exist, this is a market requirement.  P7.19 Of total plastic parts >25g, hobased material content is %.  Of total plastic parts weight >25g, hobased material content is %.  P7.20 Of total plastic parts >25g, hobased material content is %.  P7.19	P7						
P7.2* Plastic materials in covers/housing have no surface coating.  P7.3* Plastic parts >25 glastic parts >25 glast parts >100 g consist of one material or of easily separable materials.  P7.4* Plastic parts >25 glast parts part	P7 1*						
P7.3° Plastic parts >100g consist of one material or of easily separable materials.  P7.4° Plastic parts >25g have material codes according to ISO 11469 referring ISO 1043.  P7.5° Plastic parts as refer from metal inlays or have inlays that can be removed with commonly available tools.  P7.6° Labels are easily separable. (This requirement does not apply to safety/regulatory labels).  P7.6° Labels are easily separable. (This requirement does not apply to safety/regulatory labels).  P7.7° Upgrading can be done e.g. with processor, memory, cards or drives  P7.7° Upgrading can be done e.g. with processor, memory, cards or drives  P7.8° Upgrading can be done using commonly available tools  P7.9° Spare parts are available after end of production for: years  Material and substance requirements  P7.10° Service is available after end of production for: years  Material and substance requirements  P7.11° Material and substance requirements  P7.11° Material and substance requirements  P7.12° Electrical cable insulation material of power cables are halogen free (including PVC). (See Note 1)  P7.13° Electrical cable insulation material of signal cables are halogen free (including PVC). (See Note 1)  P7.14° All cover/housing plastic parts >25g are halogen free. (See Note 2)  P7.15° All printed circuit boards (without components) >25g are halogen free. (See Note 2)  P7.16° Flame retarded plastic parts >25g in covers / housings are marked according ISO 1043-4:  Marking: FR40)  P7.17° All .1°  Chemical specifications of flame retardants in printed circuit boards >25g (without components):  TBBPA (additive)				+	╫		
P7.4* Plastic parts >25g have material codes according to ISO 11469 referring ISO 1043.  P7.5 Plastic parts are free from metal inlays or have inlays that can be removed with commonly available tools.  P7.6* Labels are easily separable. (This requirement does not apply to safety/regulatory labels).  P7.6* Product lifetime  P7.7* Upgrading can be done e.g. with processor, memory, cards or drives  P7.8* Upgrading can be done using commonly available tools  P7.9* Upgrading can be done using commonly available tools  P7.9* Spare parts are available after end of production for: years  P7.10 Service is available after end of production for: years  Material and substance requirements  P7.11* Product cover/housing material type: Material type: PC+ABS  Material vigotic cover/housing material of power cables are halogen free (including PVC). (See Note 1)  P7.14 All cover/housing plastic parts >25g are halogen free. (See Note 2)  P7.15 All printed circuit boards (without components) >25g are halogen free. (See Note 2)  P7.16 Flame retarded plastic parts >25g in covers / housings are marked according ISO 1043-4:  Marking: FR(40)  P7.17 Alt. 1  Chemical specifications of flame retardants in printed circuit boards (without components):  TBBPA (reactive) TBBPA (reactive) Other; chemical name: CAS #:  Alt. 2  Chemical specifications of flame retardants in printed circuit boards (without components):  Comment: No legal limits exist, this is a market requirement.  1. Chemical pastic parts >25g contain the following flame retardant substances/preparations in concentrations above 0.1%:  Comment: No legal limits exist, this is a market requirement.  1. Chemical specifications of flame retardants in plastic parts >25g according ISO 1043-4:  P7.19 Of total plastic parts 'weight >25g, total material content is %.  P7.20 Of total plastic parts' weight >25g, biobased material content is %.  P7.21 Light sources are free from mercury  I				╫	╫		
P7.6 Plastic parts are free from metal inlays or have inlays that can be removed with commonly available tools.  P7.6 Labels are easily separable. (This requirement does not apply to safety/regulatory labels).  P7.7 Upgrading can be done e.g. with processor, memory, cards or drives  P7.8 Upgrading can be done e.g. with processor, memory, cards or drives  P7.9 Spare parts are available after end of production for: years  P7.10 Service is available after end of production for: years  Material and substance requirements  P7.11 Portic cover/housing material type: ABS  Material type: PC+ABS  Ma				╫	╫		
P7.6° Labels are easily separable. (This requirement does not apply to safety/regulatory labels).  Product lifetime  P7.7° Upgrading can be done e.g. with processor, memory, cards or drives  P7.8° Upgrading can be done using commonly available tools  P7.9. Spare parts are available after end of production for: years    Naterial and substance requirements   P7.110				+	╫		
P7.7* Upgrading can be done e.g. with processor, memory, cards or drives  P7.8* Upgrading can be done using commonly available tools  P7.9. Spare parts are available after end of production for: years  P7.10 Service is available after end of production for: years  P7.11* Product cover/housing material type: Material and substance requirements  P7.12 Electrical cable insulation material of power cables are halogen free (including PVC). (See Note 1)  P7.13 Electrical cable insulation material of signal cables are halogen free (including PVC). (See Note 1)  P7.14 All cover/housing plastic parts >25g are halogen free. (See Note 1)  P7.15 All printed circuit boards (without components) >25g are halogen free. (See Note 2)  P7.16 Flame retarded plastic parts >25g in covers / housings are marked according ISO 1043-4:  Marking: FR/40)  P7.17 Alt 1  Chemical specifications of flame retardants in printed circuit boards (without components):  TBBPA (additive) . TBBPA (reactive) . Other; chemical name: . CAS #:  Alt. 2  Chemical specifications of flame retardants in printed circuit boards (without components) >25g according ISO 1043-4:  P7.18 Alt. 1  Flame retarded plastic parts >25g contain the following flame retardant substances/preparations in concentrations above 0.1%:  Comment. No legal limits exist, this is a market requirement.  1. Chemical name: , CAS #:  2. Chemical name: , CAS #:  3. Chemical name: , CAS #:  4.1. 2  Chemical specifications of flame retardants in plastic parts >25g according ISO 1043-4:  P7.19 Of total plastic parts' weight >25g, recycled material content is %.  P7.20 Chemical specifications of flame retardants in plastic parts >25g according ISO 1043-4:  P7.19 Of total plastic parts' weight >25g, picobased material content is %.  P7.20 If total plastic parts weight >25g, picobased material content is %.  P7.21 Light sources are free from mercury Immercury content per lamp: mg  P8 Batteries				₩	╫		
P7.7°   Upgrading can be done e.g. with processor, memory, cards or drives	F1.0						
P7.8' Upgrading can be done using commonly available tools P7.9. Spare parts are available after end of production for: years P7.10 Service is available after end of production for: years P7.11 Product cover/housing material type: Material and substance requirements P7.11 Product cover/housing material type: Material type: PC+ABS Material type: Clectrical cable insulation material of power cables are halogen free (including PVC). (See Note 1) P7.13 Electrical cable insulation material of signal cables are halogen free (including PVC). (See Note 1) P7.14 All cover/housing plastic parts >25g are halogen free. (See Note 1) P7.15 All printed circuit boards (without components) >25g are halogen free. (See Note 2) P7.16 Flame retarded plastic parts >25g in covers / housings are marked according ISO 1043-4: Marking: FR(40) P7.17 Alt 1. Chemical specifications of flame retardants in printed circuit boards >25g (without components): TBBPA (additive), TBBPA (reactive), Other; chemical name:, CAS #: Alt . 2 Chemical specifications of flame retardants in printed circuit boards (without components) >25g according	P7 7*						
P7.9. Spare parts are available after end of production for: years    P7.10   Service is available after end of production for: years				╬	<del> </del>		
P7.10 Service is available after end of production for: years    Material and substance requirements					<del> </del>		
P7.11 Product cover/housing material type: Material pye: PC+ABS Material type: ABS P7.12 Electrical cable insulation material of gional cables are halogen free (including PVC). (See Note 1) P7.13 Electrical cable insulation material of signal cables are halogen free (including PVC). (See Note 1) P7.14 All cover/housing plastic parts >25g are halogen free. (See Note 1) P7.15 All printed circuit boards (without components) >25g are halogen free. (See Note 2) P7.16 Flame retarded plastic parts >25g in covers / housings are marked according ISO 1043-4: Marking: FR(40) P7.17 Alt .1 Chemical specifications of flame retardants in printed circuit boards >25g (without components): TBBPA (reactive) Other; chemical name: CAS #: Alt. 2 Chemical specifications of flame retardants in printed circuit boards (without components) >25g according ISO 1043-4:  P7.18 Alt. 1 Flame retarded plastic parts >25g contain the following flame retardant substances/preparations in concentrations above 0.1%: Comment: No legal limits exist, this is a market requirement.  1. Chemical name: CAS #: 2. Chemical name: CAS #: 3. Chemical name: CAS #: 3. Chemical name: CAS #: 4. CAS #: 2. Chemical specifications of flame retardants in plastic parts >25g according ISO 1043-4:  P7.19 Of total plastic parts 'weight >25g, recycled material content is %. P7.20 Of total plastic parts' weight >25g, biobased material content is %. P7.21 Light sources are free from mercury If mercury is used specify: Number of lamps: and max. mercury content per lamp: mg  P8 Batteries  Batteries Battery chemical composition: Li					Щ.		
P7.11* Product cover/housing material type: Material type: ABS	P7.10						
Material type: PC+ABS	D7 44*						
P7.12 Electrical cable insulation material of power cables are halogen free (including PVC). (See Note 1)  P7.13 Electrical cable insulation material of signal cables are halogen free (including PVC). (See Note 1)  P7.14 All cover/housing plastic parts >25g are halogen free. (See Note 1)  P7.15 All printed circuit boards (without components) >25g are halogen free. (See Note 2)  P7.16 Flame retarded plastic parts >25g in covers / housings are marked according ISO 1043-4:  P7.17 Alt. 1  Chemical specifications of flame retardants in printed circuit boards >25g (without components):  TBBPA (additive), TBBPA (reactive), Other; chemical name:, CAS #:  Alt. 2  Chemical specifications of flame retardants in printed circuit boards (without components) >25g according ISO 1043-4:  P7.18 Alt. 1  Flame retarded plastic parts >25g contain the following flame retardant substances/preparations in concentrations above 0.1%:  Comment: No legal limits exist, this is a market requirement.  1. Chemical name:, CAS #:  2. Chemical name:, CAS #:  3. Chemical name:, CAS #:  4.t. 2  Chemical specifications of flame retardants in plastic parts >25g according ISO 1043-4:  P7.19 Of total plastic parts weight >25g, recycled material content is	P7.11*						
P7.13 Electrical cable insulation material of signal cables are halogen free (including PVC). (See Note 1)  P7.14 All cover/housing plastic parts >25g are halogen free. (See Note 1)  P7.15 All printed circuit boards (without components) >25g are halogen free. (See Note 2)  P7.16 Flame retarded plastic parts >25g in covers / housings are marked according ISO 1043-4:  Marking: FR(40)  P7.17 Alt. 1 Chemical specifications of flame retardants in printed circuit boards >25g (without components):  TBBPA (additive)  , TBBPA (reactive)  , Other; chemical name: , CAS #:  Alt. 2 Chemical specifications of flame retardants in printed circuit boards (without components) >25g according ISO 1043-4:  P7.18 Alt. 1 Flame retarded plastic parts >25g contain the following flame retardant substances/preparations in concentrations above 0.1%:  Comment: No legal limits exist, this is a market requirement.  1. Chemical name: , CAS #:  2. Chemical name: , CAS #:  3. Chemical name: , CAS #:  4.tt. 2 Chemical name: , CAS #:  Chemical specifications of flame retardants in plastic parts >25g according ISO 1043-4:  P7.19 Of total plastic parts' weight >25g, recycled material content is %.  P7.20 Of total plastic parts' weight >25g, recycled material content is %.  P7.21 Light sources are free from mercury	D7 12				$\overline{}$		
P7.14 All cover/housing plastic parts >25g are halogen free. (See Note 1)  P7.15 All printed circuit boards (without components) >25g are halogen free. (See Note 2)  P7.16 Flame retarded plastic parts >25g in covers / housings are marked according ISO 1043-4:  Marking: FR(40)  P7.17 Alt. 1  Chemical specifications of flame retardants in printed circuit boards >25g (without components):  TBBPA (additive), TBBPA (reactive), Other; chemical name:, CAS #:  Alt. 2  Chemical specifications of flame retardants in printed circuit boards (without components) >25g according			<del>-  -</del>		╫		
P7.15 All printed circuit boards (without components) >25g are halogen free. (See Note 2)  P7.16 Flame retarded plastic parts >25g in covers / housings are marked according ISO 1043-4:  P7.17 Alt. 1  Chemical specifications of flame retardants in printed circuit boards >25g (without components):  TBBPA (additive), TBBPA (reactive), Other; chemical name: , CAS #:  Alt. 2  Chemical specifications of flame retardants in printed circuit boards (without components) >25g according ISO 1043-4:  P7.18 Alt. 1  Flame retarded plastic parts >25g contain the following flame retardant substances/preparations in concentrations above 0.1%:  Comment: No legal limits exist, this is a market requirement.  1. Chemical name: , CAS #:  2. Chemical name: , CAS #:  3. Chemical name: , CAS #:  4. Alt. 2  Chemical specifications of flame retardants in plastic parts >25g according ISO 1043-4:  P7.19 Of total plastic parts' weight >25g, recycled material content is %.  P7.20 Of total plastic parts' weight >25g, biobased material content is %.  P7.21 Light sources are free from mercury If mercury is used specify: Number of lamps: and max. mercury content per lamp: mg  P8 Batteries  Battery chemical composition: Li				<u> </u>	Щ.		
P7.16 Flame retarded plastic parts >25g in covers / housings are marked according ISO 1043-4:  Marking: FR(40)  P7.17 Alt. 1 Chemical specifications of flame retardants in printed circuit boards >25g (without components): TBBPA (additive)  , TBBPA (reactive)  , Other; chemical name: , CAS #:  Alt. 2 Chemical specifications of flame retardants in printed circuit boards (without components) >25g according ISO 1043-4:  P7.18 Alt. 1 Flame retarded plastic parts >25g contain the following flame retardant substances/preparations in concentrations above 0.1%: Comment: No legal limits exist, this is a market requirement.  1. Chemical name: , CAS #: 2. Chemical name: , CAS #: 3. Chemical name: , CAS #: Alt. 2 Chemical specifications of flame retardants in plastic parts >25g according ISO 1043-4:  P7.19 Of total plastic parts' weight >25g, recycled material content is %.  P7.20 Of total plastic parts' weight >25g, biobased material content is %.  P7.21 Light sources are free from mercury If mercury is used specify: Number of lamps: and max. mercury content per lamp: mg  P8. Batteries  P8.1* Batteries			<u> </u>	Щ	Щ.		
Marking: FR(40)  P7.17 Alt. 1 Chemical specifications of flame retardants in printed circuit boards >25g (without components): TBBPA (additive), TBBPA (reactive), Other; chemical name:, CAS #:  Alt. 2 Chemical specifications of flame retardants in printed circuit boards (without components) >25g according ISO 1043-4:  P7.18 Alt. 1 Flame retarded plastic parts >25g contain the following flame retardant substances/preparations in concentrations above 0.1%: Comment: No legal limits exist, this is a market requirement.  1. Chemical name:, CAS #: 2. Chemical name:, CAS #: 3. Chemical name:, CAS #: 3. Chemical name:, CAS #: 4lt. 2 Chemical specifications of flame retardants in plastic parts >25g according ISO 1043-4:  P7.19 Of total plastic parts' weight >25g, recycled material content is		, , , , , , , , , , , , , , , , , , , ,		Щ	<u>Ш</u>		
Chemical specifications of flame retardants in printed circuit boards >25g (without components):  TBBPA (additive), TBBPA (reactive), Other; chemical name:, CAS #:  Alt. 2 Chemical specifications of flame retardants in printed circuit boards (without components) >25g according    ISO 1043-4:  P7.18		Marking: FR(40)					
TBBPA (additive), TBBPA (reactive), Other; chemical name:, CAS #:  Alt. 2 Chemical specifications of flame retardants in printed circuit boards (without components) >25g according     ISO 1043-4:  P7.18 Alt. 1 Flame retarded plastic parts >25g contain the following flame retardant substances/preparations in concentrations above 0.1%: Comment: No legal limits exist, this is a market requirement.  1. Chemical name:, CAS #:, CAS #:, CAS #:, CAS #:, CAS #:	P7.17						
Alt. 2 Chemical specifications of flame retardants in printed circuit boards (without components) >25g according ISO 1043-4:  P7.18 Alt. 1 Flame retarded plastic parts >25g contain the following flame retardant substances/preparations in concentrations above 0.1%: Comment: No legal limits exist, this is a market requirement.  1. Chemical name: 2. Chemical name: 3. Chemical name: 4. CAS #: 4. C							
Chemical specifications of flame retardants in printed circuit boards (without components) >25g according ISO 1043-4:  P7.18 Alt. 1 Flame retarded plastic parts >25g contain the following flame retardant substances/preparations in concentrations above 0.1%: Comment: No legal limits exist, this is a market requirement.  1. Chemical name: , CAS #: 2. Chemical name: , CAS #: 3. Chemical name: , CAS #: 4lt. 2 Chemical specifications of flame retardants in plastic parts >25g according ISO 1043-4:  P7.19 Of total plastic parts' weight >25g, recycled material content is %.  P7.20 Of total plastic parts' weight >25g, biobased material content is %.  P7.21 Light sources are free from mercury If mercury is used specify: Number of lamps: and max. mercury content per lamp: mg  P8 Batteries  P8.1* Battery chemical composition: Li		TBBPA (additive), TBBPA (reactive), Other; chemical name: , CAS #:					
ISO 1043-4:  P7.18 Alt. 1 Flame retarded plastic parts >25g contain the following flame retardant substances/preparations in concentrations above 0.1%: Comment: No legal limits exist, this is a market requirement.  1. Chemical name: , CAS #: 2. Chemical name: , CAS #: 3. Chemical name: , CAS #: 4lt. 2 Chemical specifications of flame retardants in plastic parts >25g according ISO 1043-4:  P7.19 Of total plastic parts' weight >25g, recycled material content is %. P7.20 Of total plastic parts' weight >25g, biobased material content is %. P7.21 Light sources are free from mercury If mercury is used specify: Number of lamps: and max. mercury content per lamp: mg  P8 Batteries  P8.1* Battery chemical composition: Li		Alt. 2					
P7.18 Alt. 1 Flame retarded plastic parts >25g contain the following flame retardant substances/preparations in concentrations above 0.1%: Comment: No legal limits exist, this is a market requirement.  1. Chemical name: , CAS #: 2. Chemical name: , CAS #: 3. Chemical name: , CAS #: Alt. 2 Chemical specifications of flame retardants in plastic parts >25g according ISO 1043-4:  P7.19 Of total plastic parts' weight >25g, recycled material content is %. P7.20 Of total plastic parts' weight >25g, biobased material content is %. P7.21 Light sources are free from mercury If mercury is used specify: Number of lamps: and max. mercury content per lamp: mg  P8 Batteries  Battery chemical composition: Li		Chemical specifications of flame retardants in printed circuit boards (without components) >25g according					
Flame retarded plastic parts >25g contain the following flame retardant substances/preparations in concentrations above 0.1%: Comment: No legal limits exist, this is a market requirement.  1. Chemical name: , CAS #: 2. Chemical name: , CAS #: 3. Chemical name: , CAS #: Alt. 2 Chemical specifications of flame retardants in plastic parts >25g according ISO 1043-4:  P7.19 Of total plastic parts' weight >25g, recycled material content is %.  P7.20 Of total plastic parts' weight >25g, biobased material content is %. P7.21 Light sources are free from mercury If mercury is used specify: Number of lamps: and max. mercury content per lamp: mg  P8 Batteries  P8.1* Battery chemical composition: Li		ISO 1043-4:					
concentrations above 0.1%: Comment: No legal limits exist, this is a market requirement.  1. Chemical name: , CAS #: 2. Chemical name: , CAS #: 3. Chemical name: , CAS #: 4lt. 2 Chemical specifications of flame retardants in plastic parts >25g according ISO 1043-4:  P7.19 Of total plastic parts' weight >25g, recycled material content is %.  P7.20 Of total plastic parts' weight >25g, biobased material content is %.  P7.21 Light sources are free from mercury If mercury is used specify: Number of lamps: and max. mercury content per lamp: mg  P8 Batteries  P8.1* Battery chemical composition: Li	P7.18						
Comment: No legal limits exist, this is a market requirement.  1. Chemical name: , CAS #: 2. Chemical name: , CAS #: 3. Chemical name: , CAS #: 4. CAS #: 6.							
1. Chemical name: , CAS #: 2. Chemical name: , CAS #: 3. Chemical name: , CAS #: Alt. 2 Chemical specifications of flame retardants in plastic parts >25g according ISO 1043-4:  P7.19 Of total plastic parts' weight >25g, recycled material content is %.  P7.20 Of total plastic parts' weight >25g, biobased material content is %.  P7.21 Light sources are free from mercury If mercury is used specify: Number of lamps: and max. mercury content per lamp: mg  P8 Batteries  P8.1* Battery chemical composition: Li							
2. Chemical name: , CAS #: 3. Chemical name: , CAS #:  Alt. 2		Commont. No logar minto exist, this is a market requirement.					
3. Chemical name: , CAS #:  Alt. 2 Chemical specifications of flame retardants in plastic parts >25g according ISO 1043-4:  P7.19 Of total plastic parts' weight >25g, recycled material content is %.  P7.20 Of total plastic parts' weight >25g, biobased material content is %.  P7.21 Light sources are free from mercury If mercury is used specify: Number of lamps: and max. mercury content per lamp: mg  P8 Batteries  P8.1* Battery chemical composition: Li		1. Chemical name: , CAS #:					
Alt. 2 Chemical specifications of flame retardants in plastic parts >25g according ISO 1043-4:  P7.19 Of total plastic parts' weight >25g, recycled material content is %.  P7.20 Of total plastic parts' weight >25g, biobased material content is %.  P7.21 Light sources are free from mercury If mercury is used specify: Number of lamps: and max. mercury content per lamp: mg  P8 Batteries  P8.1* Battery chemical composition: Li							
Chemical specifications of flame retardants in plastic parts >25g according ISO 1043-4:  P7.19 Of total plastic parts' weight >25g, recycled material content is %.  P7.20 Of total plastic parts' weight >25g, biobased material content is %.  P7.21 Light sources are free from mercury If mercury is used specify: Number of lamps: and max. mercury content per lamp: mg  P8 Batteries  P8.1* Battery chemical composition: Li		3. Chemical name: , CAS #:					
Chemical specifications of flame retardants in plastic parts >25g according ISO 1043-4:  P7.19 Of total plastic parts' weight >25g, recycled material content is %.  P7.20 Of total plastic parts' weight >25g, biobased material content is %.  P7.21 Light sources are free from mercury If mercury is used specify: Number of lamps: and max. mercury content per lamp: mg  P8 Batteries  P8.1* Battery chemical composition: Li		Alt 2					
P7.19 Of total plastic parts' weight >25g, recycled material content is %.  P7.20 Of total plastic parts' weight >25g, biobased material content is %.  P7.21 Light sources are free from mercury If mercury is used specify: Number of lamps: and max. mercury content per lamp: mg  P8 Batteries  P8.1* Battery chemical composition: Li				Ш			
P7.20 Of total plastic parts' weight >25g, biobased material content is %.  P7.21 Light sources are free from mercury  If mercury is used specify: Number of lamps: and max. mercury content per lamp: mg  P8 Batteries  P8.1* Battery chemical composition: Li		The state of the s					
P7.21 Light sources are free from mercury  If mercury is used specify: Number of lamps: and max. mercury content per lamp: mg  P8 Batteries  P8.1* Battery chemical composition: Li		1 1 0 0, 7	_				
If mercury is used specify: Number of lamps: and max. mercury content per lamp: mg  P8 Batteries  P8.1* Battery chemical composition: Li							
P8     Batteries       P8.1*     Battery chemical composition: Li	P7.21						
P8.1* Battery chemical composition: <i>Li</i>	DΩ						
	P8.2	Batteries meet the requirements of the following voluntary program/s:			∺		

Note 1 For cables, covers & housing plastic parts and plastic packaging materials in this standard; halogens include fluorine, chlorine, bromine, and iodine.

Note 2 In accordance with JPCA-ES-01; printed wiring boards must not contain more than 0.09% by weight (900ppm) of chlorine or bromine.

Model number *	imageRUNNER ADVANCE 4225i EQ80		
Issue date *	2020/11/10	Logo	

Product	Product environmental attributes - Market requirements (continued) Requirement met							t met	
Item							Ye	s No	n.a.
P9	Energy consump								
9.1 For the product the following power levels or energy consumptions have been measured:									
Energy m	ode *	Power level at 100 V AC	Power level at 115 V AC	Power level at 230 V AC		Reference / Stan and test method		modes	
Max		W	W	1500 W		Canon's Own S	tandard		
Printing(	Average)	W	W	619 W		Canon's Own S	tandard		$+ \overline{\Box}$
StandBy		W	W	<b>62.5</b> W		Canon's Own S	tandard		$\overline{\Box}$
LowPowe	er	W	W	<b>38.4</b> W		Canon's Own S	tandard		$\Box$
Sleep		W	W	0.59 W		Canon's Own S	tandard		
		W	W	W					
charger p	power supply / lugged in the wall disconnected from	W	W	W					
PTEC * Typical E	nergy Consumptior	W	W	W					
TEC * Typical E	nergy Consumptior	kWh/week	kWh/week	0.3654 kWh/w	reek	TEC			
Default tir	ne to enter energy	save mode: 1 minutes	}			<u> </u>			
P9.2*		the energy save functio		ne product.			$\triangleright$	1 $\square$	$\overline{}$
		the energy requiremen			n/s·				
	ENERGY STAR® Others specify:		ne or the renowing	rolamary program	.,, 0.			] [] ] []	
P10	Emissions								
	Noise emission -	Declared according to	ISO 9296						
P10.1		Mode description		Declared		Declared	A-weighted		
				A-weighted sound power		sound pressure	level $L_{p\mathrm{Am}}$ (dE	3)	
				level $L_{WAd}$ (B)	Оре	rator position 🔀	Bystander posi	tions X	Ī
				icver $E_{WAd}$ (B)		Desktop	(only if produ		
						or Desk side	operator a	ttended)	1
	Idle '	StandBy		* Not Detect			ct / Not Detect		┪╓╸
		,							
	Operation *	Print		* 6.6		52	2/50		
	Other mode								
	Measured according	ng to: 🔀 ISO7779 🗌	ECMA-74						1
D10.2	The product mosts		(only if not covered				stance m)		
F 10.2	P10.2 The product meets the acoustic noise requirements of the following voluntary program/s:								
P10.3*	Chemical emissions from printing products  1.3* Test serfermed according to 50MA 200 (100 (150 2000)) standard V at her profit.								
P10.4									
1 10.4	• •		•	one 0.047 T\/	00 4	60			
P10.5		ne <loq(=0.24) fo<="" of="" requirements="" stylen="" td="" the=""><td></td><td></td><td>OC 1.</td><td>et for :</td><td></td><td>1 <math>\square</math></td><td></td></loq(=0.24)>			OC 1.	et for :		1 $\square$	
	2.1011110di 0111100101		Dust 🔀	Ozone		Styrene	a E	لــا لا	
1			Benzene 🔀	TVO		Styrono [			
Electromagnetic emissions									
P10.6		meets the requirement	for low frequency e	lectromagnetic fie	elds of	f the following volu	intary	1	
	program/s:		. ,				-		<u>~_</u> V

Model number *	imageRUNNER ADVANCE 4225i EQ80		
Issue date *	2020/11/10	Logo	

Produc	Product environmental attributes - Market requirements (continued)					
Item		Yes	No	n.a.		
P11	Consumable materials for printing products					
P11.1*	A Safety Data Sheet (SDS) is available for the ink/toner preparation, even if not legally required (see P4.3).	$\boxtimes$				
P11.2*	Paper containing post-consumer recycled fibers can be used, provided that it meets the requirements of EN12281.					
P11.3*	2-sided (duplex) printing/copying is an integrated product function.	$\boxtimes$				
P12	Ergonomics for computing products					
P12.1*	The display meets the ergonomic requirements of ISO 9241-307 for visual display technologies.			$\boxtimes$		
P12.2*	The physical input device meets the requirements of ISO 9995 and ISO 9241-410.			$\boxtimes$		
P13	Packaging and documentation					
P13.1*	Product packaging material type(s): Wooden Pallet Product packaging material type(s): Corrugated Cardboard Product packaging material type(s): EPS, LD-PE  weight (kg): 14.0 weight (kg): 7.0 weight (kg): 2.2					
P13.2*	Product plastic packaging is halogen free (including PVC). (See Note 1)	$\square$				
P13.3*	Specify media for user and product documentation (tick box):  Electronic					
P13.4*	For paper user and product documentation, please specify contained percentage of post-consumer recycled fiber. $0\%$					
P14	Additional information					
P1.1	Product on this declaration comply with EU PoHS Directive (2011/65/EU)					
	The current EU RoHS Directive restricts the use of following substances					
	Lead					
	Mercury					
	Cadmium					
	Hexavalent Chromium					
	Polybrominated biphenyls (PBB)					
	Polybrominated diphenyl ethers (PBDE)					
	Note: This is based on knowledge as of the date of this document					
P4.2	http://canon-europe.com/about_us/sustainabilty/business/reach_customer_statement/					
	Related to REACH Article 33 – Information about substances in articles is available					
P10.1	Sound Power Level (LpA)					
	Bystander position					
	Active (BW) (front, right, back, left): 48 / 50 / 47 / 49 dB					
	Standby : Not available					
	Operator position:					
	Active (BW) : 52 dB					
	Standby : 30 dB					

## NOTE

Additional lines may be inserted to declare further items, by positioning the cursor at the far right of the row and hitting the <Enter> key.

Note 1 For cables, covers & housing plastic parts and plastic packaging materials in this standard; halogens include fluorine, chlorine, bromine, and iodine.

## Legal references Europe Annex B

Reference	Declaration item
2002/95/EC (ROHS Directive)	P1.1, P4.1
76/769/EEC (Marketing and Use Directive)	P1.6, P1.8, P4.2
amendment 89/677/EEC	P1.4
amendment 1999/77/EC	P1.2
amendment 2003/3/EC	P1.7
amendment 94/27/EEC	P1.9
Regulation (EC) No. 2037/2000, 2038/2000, 2039/2000	P1.3
Norwegian regulation relating to restrictions on the use of certain dangerous chemicals 20.12.2002	P1.5
2006/66/EC (Battery and accumulators Directive)	P2.1, P2.2, P2,3, P3.4, P8.1
2006/95/EC (Low Voltage Directive)	P3.1, 3.4
2004/108/EEC (New EMC Directive)	P3.2, 3.4
1999/5/EC (R&TTE Directive)	P3.3, 3.4
"REACH" Regulation (1907/2006), annex VII	P4.2
1999/45/EC (Dangerous Preparations Directive)	P4.3
2001/58/EC (Directive on Safety Data Sheets)	P4.3
2004/12/EC (Directive on packaging and packaging waste)	P5.1
(97/129/EC) (Commission Decision on Identification System for Packaging Materials	P5.2
2037/2000/EC Regulation on Substances that Deplete the Ozone Layer	P5.3
2002/96/EC (WEEE directive)	P3.4, P6.1