

Ecma/TC38-TG3/2015/025 (Rev. 1 – 15 April 2015)

## Annex B1 - Product environmental attributes Imaging equipment

The declaration may be published only when all rows and/or fields marked with \* are filled-in (n.a. for not applicable). Additional information regarding each item may be found under P15.

| Brand *                                 | Canon                        | Logo  |
|---|------------------------------|-------|
| Company name *                          | Canon Europe Limited         |       |
| Contact information *<br>e-mail address | environment@canon-europe.com | Canon |
| Internet site *                         | www.canon-europe.com         |       |
| Additional information                  |                              |       |

| The company declares (based on product specification or test results based obtained from sample testing), that the product |  |  |  |  |  |  |  |
|--|--|--|--|--|--|--|--|
| conforms to the statements given in this declaration.  |  |  |  |  |  |  |  |
| Type of product *  | Printer  |  |  |  |  |  |  |
| Commercial name *  | PIXMA  |  |  |  |  |  |  |
| Model number *   | TS3150 series  |  |  |  |  |  |  |
| Issue date *   | date * 2017/10/05  |  |  |  |  |  |  |
| Intended market *  | 🗌 Global 🔀 Europe 🗌 Asia, Pacific & Japan 🗌 Americas 🗌 Other |  |  |  |  |  |  |
| Additional information   |  |  |  |  |  |  |  |

This is an uncontrolled copy when in printed form. Please refer to the contact information for the latest version.

## About Annex B1

Annex B1 reflects Product environmental attributes relevant for Imaging products. The following items from the ECMA-370 Main body are not shown in the template:

P9.1 PTEC, ETEC and display resolution P12.1-P12.2 Ergonomic requirements.

| Model n  | umber *                                 | TS3150 series Logo   | •           | 1.0.1     |           |
|----------|---|--|-------------|-----------|-----------|
| lssue da | ite *                                   | 2017/10/05   | Ca          |           | )11       |
| Produc   | t environ                               | mental attributes - Legal requirements   | Require     |           | met       |
| Item     |   |  | Yes         | No        | n.a.      |
| P1       |   | bus substances and preparations  |             |           |           |
| P1.1*    |   | do comply with the current European RoHS Directive. (See legal reference and NOTE B1)  |             |           |           |
| P1.2*    | Commer                                  | a do not contain Asbestos (see legal reference).<br>nt: Legal reference has no maximum concentration value.  |             |           |           |
| P1.3*    | hydrobro<br>trichloroe                  | do not contain Ozone Depleting Substances: Chlorofluorocarbons (CFC),<br>mofluorocarbons (HBFC), hydrochlorofluorcarbons (HCFC), Halons, carbontetrachloride, 1,1,1-<br>ethane, methyl bromide (see legal reference). Comment: Legal reference has no maximum<br>ation values.                                       |             |           |           |
| P1.4*    |   | do not contain more than; 0,005% polychlorinated biphenyl (PCB), 0,005% polychlorinated (PCT) in preparations (see legal reference).   | $\square$   |           |           |
| P1.5*    | Products<br>chain co                    | do not contain more than 0,1% short chain chloroparaffins (SCCP) with 10-13 carbon atoms in t ntaining at least 48% per mass of chlorine in the SCCP (see legal reference).  |             |           |           |
| P1.6*    | (see lega                               | h direct and prolonged skin contact do not release nickel in concentrations above 0,5 μg/cm²/we<br>al reference).<br>nt: Max limit in legal reference when tested according to EN1811:2011-5.  | ek 🗌        |           |           |
| P1.7*    |   | Article 33 information about substances in articles is available at (add URL or mail contact):<br>ww.canon-europe.com/about_us/sustainability/business/reach_customer_statement/   | $\boxtimes$ |           |           |
| P2       | Batterie                                | S  |             |           |           |
| P2.1*    |   | duct contains a battery or an accumulator, the battery/accumulator is labeled with the disposal Information on proper disposal is provided in user manual. (See legal reference)   |             |           | $\square$ |
| P2.2*    | Batteries                               | jal  |             | $\square$ |           |
| P2.3*    | Batteries                               | and accumulators are readily removable. (See legal reference)  |             |           | $\square$ |
| P3       | Conform                                 | nity verification & Eco design (ErP)   |             |           |           |
| P3.1*    | The proc<br>The Dec<br><u>http://ww</u> | duct is CE-marked to show conformance with applicable legal requirements (see legal reference).<br>laration of Conformity can be requested at (add link or e-mail address):<br><a href="http://www.canon-europe.com/ce-documentation/">www.canon-europe.com/ce-documentation/</a>                                    |             |           |           |
| P3.2*    |   | luct complies with the Eco design requirements for energy-related products,<br>al reference).  | $\square$   |           |           |
|          | Required                                | l information is; given in item P15 or added to this document,   | $\square$   |           |           |
|          |   | available at (add URL): <u>http://www.canon-europe.com/printers/</u>   |             |           |           |
| P4       | Consum                                  | able materials   |             |           |           |
| P4.1*    |   | o conductor (drum, belt etc.) is used in the product, it does not contain cadmium max 0,01% (see erence and NOTE B1).  | ;           |           | $\square$ |
| P4.2*    | If ink/ton                              | er is used in the product, it does not contain cadmium max 0,1% by weight (see legal reference).   |             |           |           |
| P4.3*    | are Com<br>applicab                     | /toner formulation/preparation is classified as hazardous or contains a substance for which there<br>munity workplace exposure limits, the product/packaging is adequately labeled according to<br>le regulations and a Safety Data Sheet (SDS) in accordance with these requirements is available<br>al reference). | $\square$   |           |           |
| P5       |   | packaging  |             |           |           |
| P5.1*    | Packagii                                | ing and packaging components do not contain more than 0,01% lead, mercury, cadmium a nt chromium by weight of these together.  | and 🔀       |           |           |
| P5.2*    | The pac                                 | caging materials are marked with abbreviations and numbers indicating the nature of the material<br>e legal reference).  | l(s) 🔀      |           |           |
| P5.3*    | The pro<br>Protocol<br>Commer           | duct packaging material is free from ozone depleting substances as specified in the Montr<br>(see legal reference).<br>nt: Legal reference has no maximum concentration values.  | eal 🔀       |           |           |
| P6       | Treatme                                 | nt information   |             |           |           |
| P6.1*    | Informati                               | on for recyclers/treatment facilities is available (see legal reference).  | $\boxtimes$ |           |           |

NOTE B1 Restriction applies to the homogeneous material, unless other specified and expressed in weight %. Stating "Yes" means that the product is compliant with the mandatory requirements.

| Model n       | umber *  | TS3150 series Logo  | 0             |          |          |  |  |  |
|---------------|--|---|---------------|----------|----------|--|--|--|
| Issue da      | te *   | 2017/10/05  | Cano          |          |          |  |  |  |
|               | Environn   | mental attributes - Market requirements (See General NOTE GN below)<br>nental conscious design  | Requir        |          |          |  |  |  |
| Item          | *=mandatory to fill in. Additional information regarding each item may be found under P14. Yes No n.a.   |   |               |          |          |  |  |  |
| P7            | Design   | nbly, recycling   |               |          |          |  |  |  |
| P7.1*         |  | t have to be treated separately are easily separable  |               |          |          |  |  |  |
| P7.2*         | Parts that have to be treated separately are easily separable Image: Control of the separately are easily separable   Plastic materials in covers/housing have no surface coating. Image: Control of the separately are easily separable   |   |               |          |          |  |  |  |
| P7.3*         |  | arts > 100 g consist of one material or of easily separable materials.  |               |          | <u> </u> |  |  |  |
| P7.4*         | -  | arts > 25 g have material codes according to ISO 11469 referring ISO 1043-4.  |               | <u> </u> | <u> </u> |  |  |  |
| P7.5          | -  | arts are free from metal inlays or have inlays that can be removed with commonly available tools.   |               | <u> </u> | <u> </u> |  |  |  |
| P7.6*         | -  |   |               | <u> </u> | <u> </u> |  |  |  |
| P7.0          |  | e easily separable. (This requirement does not apply to safety/regulatory labels).  |               |          |          |  |  |  |
| P7.7*         | Product  | g can be done e.g. with processor, memory, cards or drives  |               |          |          |  |  |  |
| P7.8*         |  | g can be done using commonly available tools  |               | <u> </u> |          |  |  |  |
| P7.9.         |  |   |               |          |          |  |  |  |
|               |  |   |               |          | <u> </u> |  |  |  |
| P7.10         |  | s available after end of production for: years  |               |          |          |  |  |  |
| P7.11*        |  | and substance requirements<br>cover/housing material type (e.g. plastics, metal, aluminum):   |               |          |          |  |  |  |
| F7.11         |  |   |               |          |          |  |  |  |
| P7.12         | Material type:   Material type:     Insulation materials of external electrical cables are PVC free.   Image: Comparison of the second |   |               |          |          |  |  |  |
| P7.13         | Insulation materials of internal electrical cables are PVC free.   |   |               |          |          |  |  |  |
| P7.14         | External plastic casing/cover parts > 25 g contain no more than 0,1% weight (1000 ppm) bromine and 0,1%<br>weight (1000 ppm) chlorine attributable to brominated flame retardants, chlorinated flame retardants, and<br>polyvinyl chloride or 0,3% weight (3000 ppm) bromine and 0,3% weight (3000 ppm) chlorine in parts  |   |               |          |          |  |  |  |
| P7.15         | containing more than 25% post-consumer recycled content.       Printed circuit boards, PCBs (without components) are low halogen: all PCBs > 25 g are low  |   |               |          |          |  |  |  |
| P7.16         |  | as defined in IEC 61249-2-21. (See NOTE B2)   |               |          |          |  |  |  |
| F7.10         | Flame retarded plastic parts > 25 g in covers / housings are marked according ISO 1043-4:  |   |               |          |          |  |  |  |
| P7.17         | <u>Alt. 1:</u> Chemical specifications of flame retardants in printed circuit boards > 25 g (without components):<br>TBBPA (additive) , TBBPA (reactive) (See NOTE B3), Other; chemical name: , CAS #:   |   |               |          |          |  |  |  |
|               | Alt. 2: Chemical specifications of flame retardants in printed circuit boards (without components) > 25 g  |   |               |          |          |  |  |  |
| P7.18         | Alt. 1: Flame retarded plastic parts > 25 g contain the following flame retardant substances/preparations in concentrations above 0,1%:       1. Chemical name:     , CAS #:       (See NOTE B4)   |   |               |          |          |  |  |  |
|               |  | cal name: , CAS #: "<br>cal name: , CAS #: "  | _             | _        | _        |  |  |  |
| <b>D7</b> ( 2 |  | nemical specifications of flame retardants in plastic parts > 25 g according ISO 1043-4:  | <u>     Ц</u> | <u> </u> | <u> </u> |  |  |  |
| P7.19         | assigned   | parts > 25 g, flame retardant substances/preparations above 0,1% are used which have been<br>the following Risk phrases; and Hazard statements:   |               |          |          |  |  |  |
|               |  | ce(s) for these classifications is/are found at (add URL(s)): , (See NOTE B5)   |               |          |          |  |  |  |
| P7.20*        | lf YES; a<br>a) Of te  | umer recycled plastic material content is used in the product (See NOTE B6):<br>t least one of the two alternatives below shall be answered;<br>otal plastic parts' weight > 25 g, the postconsumer recycled plastic material content (calculated as<br>rentage of total plastic by weight) is %. | a             |          |          |  |  |  |
|               | or   | weight of recycled material is 6.40 g.  |               |          |          |  |  |  |

GENERAL NOTE Standard references should direct to the latest version of a standard. If an older version of a standard is used, section P15 shall be used for explanation.

NOTE B2 IEC 61249-2-21 defines maximum limits of 900 ppm for each of the substances chlorine and bromine and a maximum limit of 1500ppm of these substances combined. The standard does not address fluorine, iodine and astatine which are included in the group of halogens.

NOTE B3 and B4 A Guidance document on Chemical substances is available; see <a href="http://www.ecma-international.org/publications/standards/Ecma-370.htm">http://www.ecma-international.org/publications/standards/Ecma-370.htm</a>

NOTE B5 If a certain substance has been assigned a certain risk phrases / hazard statement in the referenced source, this does not necessarily mean the substance has been tested for all of the hazards referred to by a certain customer.

NOTE B6 Applies to a product containing plastic parts whose combined weight exceeds 100 g with the exception of printed circuit boards, cables, connectors and electronic components and bio-based plastic material.

| Model num  | ber *                 | TS3150 se                      | eries   |                                   |  | Logo   | 0                                |       |
|--|-----------------------|--------------------------------|---|-----------------------------------|--|--|----------------------------------|-------|
| Issue date '   | *                     | 2017/10/05                     | 5   |                                   |  |  | Can                              | OT    |
| Product e  | nvironn               | nental attr                    | ibutes - Market ree                               | quirements (cont                  | inued)   |  | Requirem                         | ent m |
| ltem   |                       |                                |   |                                   |  |  | Yes                              | No n. |
|  |                       |                                | ance requirements (o                              |                                   |  |  |                                  |       |
| P7.21* Biobased plastic material content is used in the product (See NOTE B7): |                       |                                |   |                                   |  |  |                                  |       |
|  | a) Of t<br>tota<br>or | otal plastic<br>I plastic by v |   | the biobased plastic              | vered;<br>material content (calcu                  | lated as a perce                                 | entage of                        |       |
| P7.22*   | Light sou             | irces are fre                  | e from mercury, i.e. le<br>becify: Number of lamp | ss than 0,1 mg/lamp               | o.<br>num mercury content pe                       | er lamp:   | mg                               |       |
| P8   | Batteries             | 5                              |   |                                   |  |  |                                  |       |
| P8.1*  | Battery c             | hemical con                    | nposition:  |                                   |  |  |                                  |       |
| P9   | Energy of             | consumptio                     | on (See NOTE B8)                                  |                                   |  |  |                                  |       |
| P9.1   | For the p             | product the f                  | ollowing power levels                             | or energy consumpt                | ions are reported:                                 |  |                                  |       |
| Energy mod   | le *                  |                                | Power level at<br>100 V AC                        | Power level at<br>115 V AC        | Power level at 230 V AC                            | Reference/S<br>modes and t                       |                                  | rgy   |
| Sleep mode<br>STAR® Ope<br>(OM) produc   | erational             |                                | W   | W                                 | 0.82 W   | OM mode in ENERGY ST<br>Program for Imaging Equi |                                  |       |
| Standby/off<br>ENERGY S<br>Mode (OM)   | mode for<br>TAR Ope   | erational                      | W   | W                                 | 0.23 W   |  | ENERGY STAR<br>Imaging Equipment |       |
| TEC value for TEC product  | or ENER               |                                | kWh/week  | kWh/week                          | kWh/week   |  |                                  |       |
| (TEC= Typic  | cal Energ             | у                              |   |                                   |  |  |                                  |       |
|  |                       |                                | W   | W                                 | W  |  |                                  |       |
|  |                       |                                | W   | W                                 | W  |  |                                  |       |
|  |                       |                                | W   | W                                 | W  |  |                                  |       |
|  |                       |                                | W   | W                                 | W  |  |                                  |       |
|  |                       |                                | W   | W                                 | W  |  |                                  |       |
|  |                       |                                | W   | W                                 | W  |  |                                  |       |
| <u> </u>   |                       |                                |   |                                   |  |  |                                  |       |
|  |                       |                                | y Level (International I                          | miclency Marking P                |  |  |                                  |       |
| Print/Scan S   | Speed *               | : 8                            | 3.0 images per minute                             |                                   |  | ISO/IEC 247                                      | 734                              |       |
| Default time   | to enter              | energy save                    | e mode: minute                                    | es                                |  |  |                                  | Γ     |
| P9.2*  | Informati             | on about the                   | e energy save function                            | n is provided with the            | e product.   |  | $\square$                        | n ř   |
|  | Emissio               |                                |   |                                   | •  |  |                                  |       |
|  |                       |                                | eclared according to                              | SO 9296 (See NOT                  | E B9)  |  |                                  |       |
| P10.1  | Mode                  | Mo                             | ode description                                   |                                   | Statistical upper limit A-v<br><sub>WA,c</sub> (B) | veighted sound                                   | power level,                     |       |
| F  | Idle                  | *                              |   | *                                 |  |  |                                  |       |
|  | Operatio              | n *o                           | peration mode in ECM                              | /A-74 *                           | 5.8  |  |                                  | f     |
|  | Other mo              |                                |   |                                   |  |  |                                  |       |
|  | Measure               | d according                    |   | ECMA-74<br>(only if not covered b |  |  |                                  |       |

NOTE B7 The following is to be excluded from the calculation of percentage: printed circuit boards, labels, cables, connectors and electronic components and postconsumer recycled plastic.

NOTE B8 A Guidance document on Energy Efficiency is available; see <u>http://www.ecma-international.org/publications/standards/Ecma-370.htm</u>

NOTE B9 A Guidance document on Acoustic Noise is available; see <u>http://www.ecma-international.org/publications/standards/Ecma-370.htm</u>

| Model nu     | imber *   | TS3150 series  |   |                     |  |               | Logo   | •       |             |             |      |
|--------------|---|--|---|---------------------|--|---------------|--|---------|-------------|-------------|------|
| Issue date * |   | 2017/10/05   |   |                     |  |               |  | Ca      | 11          | 0           | 1    |
|              |   |  |   |                     |  |               |  |         |             |             |      |
|              | environ   | mental attributes  | - Market ree                                    | quirements          | (continued)                                      |               |  |         |             | ment        |      |
| Item         |   |  |   |                     |  |               |  | Y       | Yes         | No          | n.a. |
| P10.2*       |   | al emissions from  |   |                     |  | aion Dotoo fr | om Flootropio                                      |         |             |             |      |
| P10.2        | Test performed according to ECMA-328 Determination of Chemical Emission Rates from Electronic                                   |  |   |                     |  |               |  |         |             |             |      |
| P10.3        | Typical   | emission rate (opera   | ition phase) is                                 | (mg/h):             |  |               |  |         |             |             |      |
|              | Electrop  | photographic devices   | : Ozone   | Dust                | Styrene  | Benzene       | TVOC   |         |             |             |      |
|              | Ink devi  | 0 1  |   | Dust                | Styrene  | Benzene       | TVOC   |         |             |             |      |
|              |   | ompliance with maxi  |   |                     | abels to be decla                                | red in P14.   |  |         |             |             |      |
| P11          |   | nable materials for  |   |                     |  |               |  |         |             |             |      |
| P11.1*       |   | y Data Sheet (SDS)   |   |                     |  |               | • •  |         | $\boxtimes$ |             |      |
| P11.2*       | Paper o<br>EN 122   | containing post-cons<br>81.                                    | umer recycle                                    | d fibers can        | be used, provide                                 | ed that it me | ets the requirem                                   | ents of | $\boxtimes$ |             |      |
| P11.3*       | 2-sided   | (duplex) printing/cop  | ying is an inte                                 | grated produc       | ct function.                                     |               |  |         |             | $\boxtimes$ |      |
| P11.4*       | The pro   | duct is delivered to e   | end-user with o                                 | default auto-d      | uplex enabled.                                   |               |  |         |             | $\boxtimes$ |      |
| P13          | Packaging and documentation   |  |   |                     |  |               |  |         |             |             |      |
| P13.1*       | Product   | packaging material<br>packaging material<br>packaging material | type(s): EPS                                    | weig                | weight (kg):<br>ht (kg): 0.103<br>ht (kg): 0.029 | 0.804         |  |         |             |             |      |
| P13.2*       |   | plastic primary pack   |   |                     |  |               |  |         | $\bowtie$   |             |      |
| P13.3*       |   | duct primary corrug  |   | d packaging,<br>0 % | specify the con-                                 | tained percer | ntage of minimur                                   |         |             |             |      |
| P13.4*       |   | media for user and phic $\boxed{X}$ , Paper $\boxed{X}$ , C    |   | entation (tick      | box):  |               |  |         |             |             |      |
| P13.5        | (Please only complete this item if paper documentation used)<br>User and product documentation on paper media is chlorine-free: |  |   |                     |  |               |  |         |             |             |      |
|              | Totally chlorine-free   |  |   |                     |  |               |  |         |             |             |      |
| P14          | Volunta   | ary programs:  |   |                     |  |               |  |         |             |             |      |
| P14.1        | The pro   | duct meets the requ  | rements of the                                  | e following vol     | untary program(s                                 | s):           |  |         |             |             |      |
|              | ENERG<br>Eco-lab<br>Eco-lab   |  | Criteria vers<br>Criteria vers<br>Criteria vers | ion:                | Date:<br>Date:<br>Date:                          | Pro           | duct category:<br>duct category:<br>duct category: |         |             |             |      |
| P15          |   | nal information (Se  |   |                     |  |               |  |         |             |             |      |
|              |   |  | ,   |                     |  |               |  |         |             |             |      |
|              |   |  |   |                     |  |               |  |         |             |             |      |
|              |   |  |   |                     |  |               |  |         |             |             |      |

NOTE B10 A Guidance document on Chemical Emissions is available; see <a href="http://www.ecma-international.org/publications/standards/Ecma-370.htm">http://www.ecma-international.org/publications/standards/Ecma-370.htm</a>

NOTE B11 Additional lines may be inserted to declare further items, by positioning the cursor at the far right of the row and hitting the <Enter> key.

## Legal references Europe Annex B1

| Reference  | Declaration item             |
|--|------------------------------|
| Directive 2011/65/EU (RoHS Directive) *<br>* Specific exemptions apply for certain products and<br>applications.   | P1.1, P4.1                   |
| (EC) 1907/2006(REACH, Annex XVII   | P1.2, P1.4, P1.6, P1.7, P4.2 |
| Regulation (EC) No. 2037/2000, 2038/2000, 2039/2000,<br>(Marketing and use of Ozone layer depleting<br>substances)   | P1.3, 5.3                    |
| Norwegian regulation relating to restrictions on the use of certain dangerous chemicals 20.12.2002   | P1.5                         |
| "REACH" Regulation (1907/2006), annex VII  | P1.10                        |
| Directive 2013/56/EC (Battery and accumulators<br>Directive) *<br>* These provisions shall not apply where, for safety,<br>performance, medical or data integrity reasons, continuity of<br>power supply is necessary and requires a permanent<br>connection between the appliance and the battery or<br>accumulator.            | P2.1, P2.2, P2,3, P8.1       |
| Directive 2006/95/EC (Low Voltage Directive)   | P3.1                         |
| Directive 2004/108/EC (EMC Directive)  | P3.1                         |
| Directive 1999/5/EC (R&TTE Directive)  | P3.1                         |
| Regulation (EC) 801/2013 amending Regulation (EC)<br>No 1275/2008 with regard to ecodesign requirements for<br>standby, off mode electric power consumption of<br>electrical and electronic household and office<br>equipment, and amending Regulation (EC) No 642/2009<br>with regard to ecodesign requirements for televisions | P3.1, P3.2                   |
| Regulation (EC) 1907/2006 (REACH Regulation),<br>Article 31, annex II)   | P4.3                         |
| Regulation (EC) 1272/2008 (CLP Regulation)   | P4.3, P7.19                  |
| Directive 2004/12/EC ( Packaging Directive)  | P5.1                         |
| Decision 97/129/EC (Secondary packaging legislation)   | P5.2                         |
| Directive 2012/19/EU (WEEE directive)  | P6.1                         |