

A HIGH-SPEED, HIGH-VOLUME VERSATILE PRINTER WITH ROBUST SECURITY



i-SENSYS LBP361dw

The Canon i-SENSYS LBP361dw is a single-function, black and white A4 printer ideal for maximising productivity for busy workgroups



**BOOST
PRODUCTIVITY**



**ROBUST
SECURITY**



**VERSATILE
PRINTING**



CONNECTIVITY

Boost productivity

Seamlessly input media types and produce large volumes of documents with optional additional paper cassettes which have a maximum capacity of 4,300 sheets. Save time with single sided print speeds of 61ppm, and duplex print speeds of 50ipm and refocus your energies elsewhere

Versatile Printing

With up to six different optional paper tray and pedestal configurations, the LBP361dw can operate as a standard desk top, or become a large free standing work station. With a variety of supported media sizes, it can be tailored for any workgroups

Robust security

Ensure your documents and devices are protected from virus or hacking threats with 360-degree security. Features include encrypted secure print, verify system at start up, and network protection

Connectivity

Connect with Wi-Fi as standard, and pair easily with Wi-Fi direct. Driverless cloud printing is also possible with native support for Universal Print by Microsoft

Canon

TECHNICAL SPECIFICATIONS

PRINTER ENGINE

Print speed	Single sided : Up to 61 ppm (A4) Up to 100 ppm (A5-Landscape) Double sided : Up to 50.9 ipm (A4)
Printing method	Monochrome laser beam printing
Print quality	Up to 1200 x 1200 dpi
Warm-up time	Print ready message shown: Approx. 2 seconds or less from power on
First Page Out Time	Mono; approx. 4.9 seconds
Recommended Monthly Print Volume	3,000 - 16,000 pages per month
Duty cycle	Max. 275,000 pages per month ¹
Print margins	5 mm-top, bottom, left and right
Advanced printing features	Secure Print Print from USB memory key (JPEG/TIFF/PDF/XPS) Barcode Print ² iOS: AirPrint, Canon PRINT Business app Android; Mopria certified, Canon Print Service Plug-in, Canon PRINT Business app Microsoft Universal Print

MEDIA HANDLING

Paper input (Standard)	550-sheet cassette 100-sheet multi-purpose tray
Paper input (Option)	550-sheet cassette x 4 (Paper Feeder PF-J1) 2,000-sheet cassette (Paper Deck Unit PD-H1) 75-sheet envelope cassettes (Envelope Feeder EF-B1)
Maximum paper input capacity	4,300-sheets
Paper output	500-sheet
Media types	Multi-Purpose Tray: Plain paper, Recycled paper, Heavy Paper, Thin paper, Colour paper, Coated paper, Pre-punched, Letterhead, Post card, Envelope Cassette: Plain paper, Recycled paper, Heavy Paper, Thin paper, Label, Colour paper, Coated paper, Pre-punched, Letterhead
Media sizes	Cassette (Standard): A4, A5, A5 (Landscape), A6, B5, B6, Legal, Letter, Executive, Statement, OFFICIO, B-OFFICIO, M-OFFICIO, GLTR, ILGL, GLGL, Foolscap, Custom sizes: Min. 99 x 148 mm Max. 216.0 x 355.6 mm. Multi-purpose tray: A4, A5, A5 (Landscape), A6, B5, B6, Legal, Letter, Executive, Statement, OFFICIO, B-OFFICIO, M-OFFICIO, GLTR, ILGL, GLGL, Foolscap, Index, Envelope (COM10, No10, Monarch, C5, DL), Custom sizes: Min. 76.2 x 127 mm Max. 216.0 x 355.6 mm. Cassette (Optional): A4, A5, A5 (Landscape), A6, B5, B6, Legal, Letter, Executive, Statement, OFFICIO, B-OFFICIO, M-OFFICIO, GLTR, ILGL, GLGL, Foolscap, Custom sizes: Min. 99 x 148 mm Max. 216.0 x 355.6 mm Envelope Feeder (Optional): Envelope (COM10, No10, Monarch, C5, DL)
Media weights	Cassette (standard and optional): 60 to 135 g/m ² Envelope Feeder (Optional): 80 to 100 g/m ² Multi-purpose tray: 60 to 199 g/m ²
Double sided printing	Automatic Cassette: A4, A5, B5, Legal, Letter, Executive, OFFICIO, B-OFFICIO, M-OFFICIO, GLTR, ILGL, GLGL, Foolscap, F4A, 16K Custom size - Min. 148 x 210 mm Max. 216 x 355.6 mm 60 to 120 g/m ²

GENERAL FEATURES

Power requirements	220-240V (±10%) 50/60Hz (±2Hz)
Power consumption	Maximum: Approx. 1500W or less Active: Approx. 771.49W or less Standby: Approx. 13.69W or less Sleep: Approx. 1.0W or less Typical Electricity Consumption (TEC): 0.61 kWh/week ³ For detailed information relating to Lot26 regulation, please go to: http://www.canon-europe.com/For_Work/Lot26/index.aspxeurope.com/For_Work/Lot26/index.aspx

Noise level

	Sound power ⁵ Active: Simplex 70 dB or less Duplex 71 dB or less Standby: Inaudible ¹⁰ Sound pressure ³ Active: 55 dB or less Standby: Inaudible ¹⁰ 430 mm x 465 mm x 370 mm Approx. 22 kg Temperature: 10 to 30°C (50 to 86°F) Humidity 20 to 80% RH (no condensation) 5 Line LCD, 5 LED (Online, Ready, Message, Job and Energy saver), Buttons, 10-key numeric keypad
--	---

Dimensions (W x D x H)

Weight

Operating environment

Control panel

CONTROLLER

Processor Speed

Memory

Storage

Printer Languages

FonTS

Interface and connectivity

Network Protocol

Software and Printer Management

Operating Systems Compatibility

CONSUMABLES

All-in-One cartridges

ACCESSORIES/OPTIONS

Items

1.6GHz x 2

2GB

32GB eMMC (available space 15GB)

UFRII (Ultra Fast Rendering), PCL5e⁴, PCL6, Adobe® PostScript³

93 PCL fonts (93 Roman, 10 Bitmap fonts, 2 OCR fonts)

Andalé Mono WT J/K/S/T (Japanese, Korean, Simplified and Traditional Chinese)¹⁵

Barcode Fonts ^{*2}

136 PostScript fonts

USB 2.0 Hi-Speed, 10BASE-T/
100BASE-TX/1000Base-T, Wireless 802.11b/g/n, Wireless Direct Connection

Print:

TCP/IP (LPD/Port9100/IPP/IPPS/FTP/WSD)

Management:

SNMPv1, SNMPv3 (IPv4, IPv6)

Security: TLS1.3, IPSec, IP/Mac address filtering, IEEE802.1X, SNMPv3, SSL (HTTPS, IPPS), Dual Network Support

Security (wireless):

Infrastructure Mode:

WEP(64/128 bit), WPA-PSK(TKIP/AES), WPA2-PSK(TKIP/AES), WPA3-SAE (AES), WPA-EAP (AES), WPA2-EAP (AES), WPA3-EAP (AES)

Access Point Mode:

WPA2-PSK(AES)

Wi-Fi Direct Mode:

WPA2-PSK (AES)

Remote User Interface (RUI),

Department ID Management,

Toner Status Tool,

iW Enterprise Management Console: Server-based software for centralised management of a fleet of devices

eMaintenance: embedded RDS allows remote eMaintenance services such as meter capture, automatic consumables management and remote diagnostics.

Content Delivery System: Server platform enables automatic firmware update to the device.

Windows® 11 / Windows® 10 / Windows® 8.1 / Server® 2022 / Server® 2019 / Server® 2016 / Server® 2012R2 / Server® 2012 / Mac OS X version 10.12 & up
Linux®⁶

Standard: Cartridge 073 (27,000 pages)⁸

Paper Feeder PF-J1 (550-sheet cassette) x 4

Paper Deck Unit PD-H1 (2,000-sheet cassette deck)

Envelope Feeder EF-B1 (Envelope feeder cassette)

Barcode Printing Kit-D1 (Enables barcode printing capability)

PCL Font Set-A1 (Enables Unicode printing capability on SAP and supports Andalé font)

User Maintenance Kit-D1 (Regular maintenance kit including fixing unit/transfer roller/pick-up roller)

Notes:

¹ Duty cycle is defined as the maximum number of printed pages for a single peak month. Any usage above the recommended duty cycle may decrease the life of the product

² Accessory - Barcode Printing Kit-D1 - is required

³ Declared noise emission in accordance with ISO 9296

⁴ A Canon PCL5e driver is not supplied, however PCL5e commands are supported on the device.

⁵ Accessory - PCL FONT SET-A1E - is required

⁶ Web distribution only. Driver will be available in 2H, 2022

⁷ Based on ISO/IEC 19752

⁸ Printer ships with 11,500 pages starter cartridge

⁹ As per US ENERGY STAR® version 3.0.

¹⁰ Inaudible means that the emission sound pressure level for a bystander is lower than absolute standard for background noise in accordance with ISO 7779

A HIGH-SPEED, HIGH-VOLUME VERSATILE PRINTER WITH ROBUST SECURITY

The Canon i-SENSYS LBP361dw is a single-function, black and white A4 printer ideal for maximising productivity in small and medium sized organisations.



PRODUCT DETAILS:

PRODUCT NAME	Mercury Code	EAN Code
i-SENSYS LBP361dw	5644C008AA	4549292198560

ACCESSORIES:

PRODUCT NAME	Mercury Code	EAN Code
PAPER FEEDER PF-J1	5694C001AA	4549292201093
PAPER DECK UNIT PD-H1	5694C002AA	4549292201109
ENVELOPE FEEDER ED-B1	5694C003AA	4549292201116
USER MAINTENANCE KIT-D1	5694C006AA	4549292201147

CONSUMABLES:

PRODUCT NAME	Mercury Code	EAN Code
Cartridge 073 Black	5724C001AA	4549292202052

Canon Inc.
canon.com

Canon Europe
canon-europe.com

English edition
© Canon Europa N.V., 2022

