

A HIGH-SPEED, HIGH-VOLUME VERSATILE PRINTER WITH ROBUST SECURITY



i-SENSYS LBP361dw

The Canon i-SENSYS LBP361dw is a single-function, black and white A4 printer ideal for maximising productivity for busy workgroups



**BOOST
PRODUCTIVITY**



**ROBUST
SECURITY**



**VERSATILE
PRINTING**



CONNECTIVITY

Boost productivity

Seamlessly input media types and produce large volumes of documents with optional additional paper cassettes which have a maximum capacity of 4,300 sheets. Save time with single sided print speeds of 61ppm, and duplex print speeds of 50ipm and refocus your energies elsewhere

Versatile Printing

With up to six different optional paper tray and pedestal configurations, the LBP361dw can operate as a standard desk top, or become a large free standing work station. With a variety of supported media sizes, it can be tailored for any workgroups

Robust security

Ensure your documents and devices are protected from virus or hacking threats with 360-degree security. Features include encrypted secure print, verify system at start up, and network protection

Connectivity

Connect with Wi-Fi as standard, and pair easily with Wi-Fi direct. Driverless cloud printing is also possible with native support for Universal Print by Microsoft

Canon

TECHNICAL SPECIFICATIONS

i-SENSYS LBP361dw

PRINTER ENGINE

| | |
|---|---|
| Print speed | Single sided : Up to 61 ppm (A4) Up to 100 ppm (A5-Landscape) Double sided : Up to 50.9 ipm (A4) |
| Printing method | Monochrome laser beam printing |
| Print quality | Up to 1200 x 1200 dpi |
| Warm-up time | Print ready message shown: Approx. 2 seconds or less from power on |
| First Page Out Time | Mono; approx. 4.9 seconds |
| Recommended Monthly Print Volume | 3,000 - 16,000 pages per month |
| Duty cycle | Max. 275,000 pages per month ¹ |
| Print margins | 5 mm-top, bottom, left and right |
| Advanced printing features | Secure Print Print from USB memory key (JPEG/TIFF/PDF/XPS) Barcode Print ² iOS: AirPrint, Canon PRINT Business app Android; Mopria certified, Canon Print Service Plug-in, Canon PRINT Business app Microsoft Universal Print |

MEDIA HANDLING

| | |
|-------------------------------------|---|
| Paper input (Standard) | 550-sheet cassette 100-sheet multi-purpose tray |
| Paper input (Option) | 550-sheet cassette x 4 (Paper Feeder PF-J1) 2,000-sheet cassette (Paper Deck Unit PD-H1) 75-sheet envelope cassettes (Envelope Feeder EF-B1) |
| Maximum paper input capacity | 4,300-sheets |
| Paper output | 500-sheet |
| Media types | Multi-Purpose Tray: Plain paper, Recycled paper, Heavy Paper, Thin paper, Colour paper, Coated paper, Pre-punched, Letterhead, Post card, Envelope Cassette: Plain paper, Recycled paper, Heavy Paper, Thin paper, Label, Colour paper, Coated paper, Pre-punched, Letterhead |
| Media sizes | Cassette (Standard): A4, A5, A5 (Landscape), A6, B5, B6, Legal, Letter, Executive, Statement, OFFICIO, B-OFFICIO, M-OFFICIO, GLTR, ILGL, GLGL, Foolscap, Custom sizes: Min. 99 x 148 mm Max. 216.0 x 355.6 mm. Multi-purpose tray: A4, A5, A5 (Landscape), A6, B5, B6, Legal, Letter, Executive, Statement, OFFICIO, B-OFFICIO, M-OFFICIO, GLTR, ILGL, GLGL, Foolscap, Index, Envelope (COM10, No10, Monarch, C5, DL), Custom sizes: Min. 76.2 x 127 mm Max. 216.0 x 355.6 mm. Cassette (Optional): A4, A5, A5 (Landscape), A6, B5, B6, Legal, Letter, Executive, Statement, OFFICIO, B-OFFICIO, M-OFFICIO, GLTR, ILGL, GLGL, Foolscap, Custom sizes: Min. 99 x 148 mm Max. 216.0 x 355.6 mm Envelope Feeder (Optional): Envelope (COM10, No10, Monarch, C5, DL) |
| Media weights | Cassette (standard and optional): 60 to 135 g/m ² Envelope Feeder (Optional): 80 to 100 g/m ² Multi-purpose tray: 60 to 199 g/m ² |
| Double sided printing | Automatic Cassette: A4, A5, B5, Legal, Letter, Executive, OFFICIO, B-OFFICIO, M-OFFICIO, GLTR, ILGL, GLGL, Foolscap, F4A, 16K Custom size - Min. 148 x 210 mm Max. 216 x 355.6 mm 60 to 120 g/m ² |

GENERAL FEATURES

| | |
|---------------------------|--|
| Power requirements | 220-240V (±10%) 50/60Hz (±2Hz) |
| Power consumption | Maximum: Approx. 1500W or less Active: Approx. 771.49W or less Standby: Approx. 13.69W or less Sleep: Approx. 1.0W or less Typical Electricity Consumption (TEC): 0.61 kWh/week ³ For detailed information relating to Lot26 regulation, please go to: http://www.canon-europe.com/For_Work/Lot26/index.aspxeurope.com/For_Work/Lot26/index.aspx |

Noise level

| | |
|--|---|
| | Sound power ⁵ Active: Simplex 70 dB or less Duplex 71 dB or less Standby: Inaudible ¹⁰ Sound pressure ³ Active: 55 dB or less Standby: Inaudible ¹⁰ 430 mm x 465 mm x 370 mm Approx. 22 kg Temperature: 10 to 30°C (50 to 86°F) Humidity 20 to 80% RH (no condensation) 5 Line LCD, 5 LED (Online, Ready, Message, Job and Energy saver), Buttons, 10-key numeric keypad |
|--|---|

Dimensions (W x D x H)

Weight

Operating environment

Control panel

CONTROLLER

Processor Speed

Memory

Storage

Printer Languages

FonTS

Interface and connectivity

Network Protocol

Software and Printer Management

Operating Systems Compatibility

CONSUMABLES

All-in-One cartridges

ACCESSORIES/OPTIONS

Items

1.6GHz x 2

2GB

32GB eMMC (available space 15GB)

UFRII (Ultra Fast Rendering), PCL5e⁴, PCL6, Adobe® PostScript³

93 PCL fonts (93 Roman, 10 Bitmap fonts, 2 OCR fonts)

Andalé Mono WT J/K/S/T (Japanese, Korean, Simplified and Traditional Chinese)¹⁵

Barcode Fonts ^{*2}

136 PostScript fonts

USB 2.0 Hi-Speed, 10BASE-T/
100BASE-TX/1000Base-T, Wireless 802.11b/g/n, Wireless Direct Connection

Print:

TCP/IP (LPD/Port9100/IPP/IPPS/FTP/WSD)

Management:

SNMPv1, SNMPv3 (IPv4, IPv6)

Security: TLS1.3, IPsec, IP/Mac address filtering, IEEE802.1X, SNMPv3, SSL (HTTPS, IPPS), Dual Network Support

Security (wireless):

Infrastructure Mode:

WEP(64/128 bit), WPA-PSK(TKIP/AES), WPA2-PSK(TKIP/AES), WPA3-SAE (AES), WPA-EAP (AES), WPA2-EAP (AES), WPA3-EAP (AES)

Access Point Mode:

WPA2-PSK(AES)

Wi-Fi Direct Mode:

WPA2-PSK (AES)

Remote User Interface (RUI),

Department ID Management,

Toner Status Tool,

iW Enterprise Management Console: Server-based software for centralised management of a fleet of devices

eMaintenance: embedded RDS allows remote eMaintenance services such as meter capture, automatic consumables management and remote diagnostics.

Content Delivery System: Server platform enables automatic firmware update to the device.

Windows[®] 11 / Windows[®] 10 / Windows[®] 8.1 / Server[®] 2022 / Server[®] 2019 / Server[®] 2016 / Server[®] 2012R2 / Server[®] 2012 / Mac OS X version 10.12 & up
Linux[®]

Standard: Cartridge 073 (27,000 pages)⁸

Paper Feeder PF-J1 (550-sheet cassette) x 4

Paper Deck Unit PD-H1 (2,000-sheet cassette deck)

Envelope Feeder EF-B1 (Envelope feeder cassette)

Barcode Printing Kit-D1 (Enables barcode printing capability)

PCL Font Set-A1 (Enables Unicode printing capability on SAP and supports Andalé font)

User Maintenance Kit-D1 (Regular maintenance kit including fixing unit/transfer roller/pick-up roller)

Notes:

¹ Duty cycle is defined as the maximum number of printed pages for a single peak month. Any usage above the recommended duty cycle may decrease the life of the product

² Accessory - Barcode Printing Kit-D1 - is required

³ Declared noise emission in accordance with ISO 9296

⁴ A Canon PCL5e driver is not supplied, however PCL5e commands are supported on the device.

⁵ Accessory - PCL FONT SET-A1E - is required

⁶ Web distribution only. Driver will be available in 2H, 2022

⁷ Based on ISO/IEC 19752

⁸ Printer ships with 11,500 pages starter cartridge

⁹ As per US ENERGY STAR[®] version3.0.

¹⁰ Inaudible means that the emission sound pressure level for a bystander is lower than absolute standard for background noise in accordance with ISO 7779

A HIGH-SPEED, HIGH-VOLUME VERSATILE PRINTER WITH ROBUST SECURITY

The Canon i-SENSYS LBP361dw is a single-function, black and white A4 printer ideal for maximising productivity in small and medium sized organisations.



PRODUCT DETAILS:

| PRODUCT NAME | Mercury Code | EAN Code |
|-------------------|--------------|---------------|
| i-SENSYS LBP361dw | 5644C011AA | 8714574672687 |

ACCESSORIES:

| PRODUCT NAME | Mercury Code | EAN Code |
|-------------------------|--------------|---------------|
| PAPER FEEDER PF-J1 | 5694C001AA | 4549292201093 |
| PAPER DECK UNIT PD-H1 | 5694C002AA | 4549292201109 |
| ENVELOPE FEEDER ED-B1 | 5694C003AA | 4549292201116 |
| USER MAINTENANCE KIT-D1 | 5694C006AA | 4549292201147 |

CONSUMABLES:

| PRODUCT NAME | Mercury Code | EAN Code |
|---------------------|--------------|---------------|
| Cartridge 073 Black | 5724C001AA | 4549292202052 |

Canon Ireland
3006 Lake Drive
Citywest, Saggart
Co. Dublin, Ireland
Telephone No: 01 2052400
Facsimile No: 01 2052525
canon.ie

Canon (UK) Ltd
The Bower
4 Roundwood Avenue
Stockley Park
Uxbridge
UB11 1AF

Canon Inc.
canon.com
Canon Europe
canon-europe.com
English edition
© Canon Europa N.V., 2022

