KE

Safety Data Sheet

.....

1. Identification of the Substance/Preparation and of the Company

Product Name MORESCO-MELT TN-615Y (MORESCO-MELT TN-615Z)

Manufacturer MORESCO Corporation

Address 5-5-3, Minatojima-minamimachi, Chuo-ku, Kobe-city, Hyogo, Japan

Customer Center Tel: 81-6-6262-3385 FAX: 81-6-6262-3327

Email Address: customercenter@moresco.co.jp

Emergency phone Number Hot-Melt Sales Department Sales Section

Tel: 81-6-6262-3310 FAX: 81-6-6262-3327 Hot-Melt Sales Department Tokyo Sales Section Tel: 81-3-5537-7055 FAX: 81-3-5537-7059

Hot-Melt Manufacturing Department Technical Section

Tel: 81-791-42-2100 FAX: 81-791-43-3179

Recommended Use and

Restrictions on Use Hot-Melt Adhesive

2. Hazard Identification

GHS Classification:

Physical Hazards: Not applicable
Health Hazards: Not applicable
Environmental Hazards: Hazardous to Aquatic Environment
Not applicable

Label Elements:

Pictograms/Symbols None
Signal Ward None
Hazard Statements None

Precautionary Statements [Prevention]

None [Response] None [Storage]

None [Disposal] None

When preventive mention mentioned above is not written, take the following information into account about the prevention / response / safekeeping / disposal

1KE

3. Composition/Information on Ingredients

Distinction between Substance and Mixture: Mixture

Chemical Name/Generic Name: Synthetic Rubber-Based Hot-Melt Adhesive

Chemical Formula Not identified

Ingredient and Concentration Synthetic Rubber, Tackifier, Plasticizer, Additives >99.8%

Titanium(IV) oxide <0.2%

4. First-Aid Measures

Inhalation: In case of inhale of the steam which was heated excessively and if feeling

abnormality in a throat, remove person to fresh air and comfortable for breathing.

Get medical advice/attention.

Skin Contact: If molten product is on skin, cool off with water immediately and get medical

advice/attention.

Eye Contact: If molten product is in eye, cool off with water immediately and get medical

advice/attention.

Ingestion: Immediately get medical advice/attention..

Expected Acute and If swallowed, may suffer from diarrhea and vomiting.

Delayed Symptoms, and May cause inflammation if in eyes.

Most Important Symptoms/ May cause inflammation if on skin.

Effects: May feel unwell if mist is inhaled.

5. Fire-Fighting Measures

Suitable Extinguishing Media Use water spray, dry chemical powder, carbon dioxide, dry sand,

foam.

Unsuitable Extinguishing Media Jet water Specific Hazards None

Specific Fire-Fighting Measures Shut off the fire source.

Use water spray, dry chemical powder, carbon dioxide, dry sand,

foam.

Heated water or a molten product may be scattered when doing water

dispersion to a molten product in the case of a large-scale fire.

In this case it is effective to intercept the air with foam extinguishers.

Cool the surrounding facilities with water spray.

Prohibit entrance except the person concerned around the fire scene.

After extinguishing a fire no admittance is allowed except people involved by stretching rope and others until the inside of the product

cools off.

Special Protective Actions for Wearing protective glasses, protective clothing, and if necessary,

Fire-Fighting respiratory protective equipment, start to fight fire on the windward

side.

6. Accidental Release Measures

Personal Precautions, Protective If skin or eye contact is possible, wear protective equipment.

inhalation.

Environmental Precautions Take up as much as possible to avoid soil contamination and water

pollution.

Avoid release to the environment.

Collection/Neutralization When molted product leaks, remove it after cooling off.

If collecting molten product, wear protective equipment such as

protection glasses, protection gloves, long sleeve work clothes and so

on.

Methods and Materials for Containment Remove a nearby firing source and set up fire extinguishing machine

parts and prevent leakage by enclosing with sand or sandbag.

Prevention of Secondary Hazards Remove all the ignition sources immediately.

Report to the related organs for help.

7. Handling and Storage

Handling:

Technical Measures May burn oneself if molten product is in eye.

Wear protective equipment such as protection glasses when handle it.

May burn oneself if molten product is on skin.

Wear protective equipment such as protection gloves, long sleeve

work clothes and so on when handle it.

May feel unwell if mist is inhaled.

Wear respiratory protective equipment to avoid inhalation when

handle it.

Do not use other than an apparatus for exclusive use.

Wear protective equipment such as protection glasses, protection

gloves, long sleeve work clothes and so on when handle it.

Keep away from heat, sparks, open flames, hot surface and static

electricity.

Do not emit steam carelessly.

Be careful so that water or contaminant does not enter.

For use only for adhesive.

Local Exhaust Ventilation/

Refer to '8. Exposure Controls/Personal Protection'.

Full Ventilation System

Avoiding Contact Refer to '10. Stability and Reactivity'.

Precautions for Safe Handling. Obtain special instructions before use.

Do not handle until all safety precautions have been read and

understood.

Do not press an empty container. It may explode under pressure.

Do not drink.

Keep out of reach of children.

Hygienic Precautions: Wash hands thoroughly after handling.

Regularly inspect protective equipment according to the inspection

table of protective equipment.

Do not eat, drink or smoke when using this product.

Storage:

Technical Measures Keep away from heat, sparks, open flames, hot surface and static

electricity.

Incompatible Materials Refer to '10. Stability and Reactivity'.

Conditions for Safe Storage Protect from sunlight.

Store in a well-ventilated and cool-dark place.

Materials for Containers/Packaging When replacing the container, use a box, a film, the paper that made

mold release processing. Otherwise it may not come off.

Exposure Controls/Personal Protection 8.

Permissible Concentration (Exposure Limit, a biological exposure index)

3mg/m³ (mineral oil mist) 1) Japan Society for Occupational Health (2010):

TWA 5mg/ m³ (mineral oil mist) ²⁾ ACGIH (2010):

TWA 10mg/m³ (Titanium(IV) oxide)²⁾

Standards for Allowable Density of Hazardous Substances in Labor Operation Air: Not established

Engineering Controls: Desirable to use a hot melt applicator that have a direct vent type.

When mist and vapors are produced, seal off sources or provide local exhaust

ventilation.

Personal Protective Equipment

Respiratory Protection: If necessary, wear appropriate respiratory protection. Hand Protection: If necessary, wear heat-resistant protective gloves. Eye Protection: If necessary, wear protection glasses side shields.

Skin and Body Protection: If necessary, wear long sleeve work clothes and work shoes.

Physical and Chemical Properties

Physical State:

Solid Appearance Color White

Odor Slight resin odor

ı. 13, 2 1KE

pH Not applicable
Melting/Freezing Point Not applicable

Boiling Point Not applicable

Flash Point 210° C (Min)

Explosive Range (Explosive Limits) No data available

Vapor Pressure No data available
Vapor Density (air=1) No data available

Specific Gravity (Density) 0.98 g/cm³ (15°C) Solubility Insoluble in water

Partition Coefficient: n-octanol/water No data available
Auto-ignition Temperature No data available

Softening point 88 °C

Volatility None (at room temperatures)

.....

10. Stability and Reactivity

Stability Stable under normal conditions.

Possibility of Hazardous Reactions No data available (Hazardous reactions will not occur under normal

use).

Conditions to Avoid No data available (Hazardous reactions will not occur under normal

use).

Incompatible Materials Strong oxidizer

Hazardous Decomposition Products None

11. Toxicological Information

Acute Toxicity:

Oral No information classified into Acute toxicity (oral) as a mixture.

Dermal No information classified into Acute toxicity (Dermal) as a mixture.

Inhalation No information classified into Acute toxicity (Inhalation) as a

mixture.

Skin Corrosion/Irritation No information classified into Skin Corrosion/Irritation as a mixture.

Serious Eye Damage/Eye Irritation No information classified into Serious Eye Damage/Eye Irritation as

a mixture.

Respiratory or Skin Sensitization No information classified into Respiratory or Skin Sensitization as a

mixture.

Germ Cell Mutagenicity No information classified into Germ Cell Mutagenicity as a mixture.

Carcinogenicity No information classified into Carcinogenicity as a mixture.

Reproductive Toxicity No information classified into Reproductive Toxicity as a mixture.

STOT/Systemic Toxicity - No information classified into STOT/Systemic Toxicity-Single

Single Exposure Exposure as a mixture.

KE

STOT/Systemic Toxicity - No information classified into STOT/Systemic Toxicity- Repeated

Repeated Exposure Exposure as a mixture.

Aspiration Hazard Aspiration Hazard is classified in Classification Not Possible as a

mixture.

12. Ecological Information

Ecotoxicity No information classified into Aquatic Toxicity as a mixture.

Persistence and Degradability

Bioaccumulative Potential

Mobility in Soil

No information available

No information available

Hazardous to the ozone layer

No information available

Other Adverse Effects

No information available

No information available

13. Disposal Considerations

Environmental Criteria

Waste Residues Dispose the waste according to national and local regulations.

Do not dump.

Contaminated Containers

Contaminated or empty container/packaging are to be disposed according to

and Packaging

national and local regulations.

14. Transport Information

International Regulation Not applicable
UN Classification Not applicable

Special Precautions: Load the containers in a manner that they are certain not to result in direct

sunlight exposure, damage, corrosion, leak, while being transported.

Load the containers in manner that they are not to fall apart while being

transport.

Do not place heavy load on top of the container.

15. Regulatory Information

No Information

16. Other Information

References: 1) Recommendation of Occupational Exposure Limits by Japan Society for Occupational Health

2) Thresholds limit values for chemical substances and physical agents and biological exposure

indices. ACGIH

•SDS of raw materials

1. As evaluations on hazards are not necessary satisfactory, special attention should be paid for use.

2. This SDS, summarizing matters to be attended to, is required for proper use of the product and is intended for normal use.

- 3. Referring to this SDS, properly use and handle this product on the user's own responsibility.
- 4. The contents of this SDS are based on information available as of today and our knowledge. The information, data, and evaluations herein are not guaranteed, and in addition, may be revised due to revision of laws or knowledge newly obtained.