# imageFORMULA R10

# QUICK AND EASY PORTABLE DOCUMENT SCANNER

## SIMPLY CONNECT AND SCAN ANYWHERE, ANYTIME!

- **Compact design**
  Take the R10 scanner with you on the go. A sleek, lightweight device, it's conveniently sized for portable use – the ideal companion for home offices, classrooms, remote workspaces and everywhere in between

- **Easy to use**
  Simply connect and scan in a matter of seconds without the need to install any driver or software applications, using Canon's unique embedded CaptureOnTouch Lite software

- **Efficient single pass scanning**
  Scan double-sided documents in one smooth motion at a speed of 12ppm, with the added efficiency of a 20-sheet feeder capacity, helping you streamline your workflow on the go

- **Speedy USB-powered scanner**
  Never worry about forgetting chargers, with a device that works with a USB cable only, minimizing hassle and reducing the time it takes to start scanning

- **Intuitive paper handling**
  Reliably scan a range of documents from A4 papers to receipts and plastic business cards. Advanced document detection features automatically adjust scan settings, so you can achieve optimal results with every scan

- **Environmentally friendly**
  Eco-friendly packaging with energy saving ultra-low power consumption

## PRODUCT RANGE

imageFORMULA R40

# Canon

## GENERAL PRODUCT INFORMATION

| | |
|---|---|
| Type | USB Powered A4 Sheetfed Portable Scanner |
| Scanning sensor unit | CMOS CIS 1 Line Sensor |
| Optical resolution | 600dpi |
| Light source | RGB LED |
| Scanning side | Front / Back / Duplex |
| Interface | USB 2.0 |
| Dimensions (WxDxH) | Tray Closed :285 (W) x 95 (D) x 40 (H)mm<br>Tray Opened: 285 (W) x 257 (D) x 174 (H)mm |
| Weight | Approx. 0.9kg |
| Power requirements | USB 2.0 bus power: 0.5A |
| Power consumption | 2.5W or less (Energy Saving Mode: 1.5W) |
| Operating environment | Temperature: 10°C to 32.5°C<br>Humidity: 25% to 80% RH |

## SCANNING SPECIFICATIONS

| | |
|---|---|
| Black and White | 12 pages per min. / 14 images per min. |
| Colour | 9 pages per min. / 10 images per min. |
| Output resolution | 150 / 200 / 300 / 400 / 600dpi |
| Output mode | Colour, Grayscale, Black and White |
| Suggested Daily Duty Cycle | Approx. 500 scans |

## DOCUMENT SPECIFICATIONS

| | |
|---|---|
| Width | 50.8 - 216mm |
| Length | 70 - 356mm |
| Thickness | 64 - 128g/m² (0.08 - 0.15mm) |
| Business card scanning | Width: 49mm<br>Length: 85mm<br>Thickness: 128-225g/ m² (0.15 - 0.3 mm) |
| Plastic card scanning | Width: 54mm<br>Length: 86mm<br>Thickness: Less than 1.4mm<br>(Embossed card can be scanned) |
| Paper separation | Separation Pad Method |
| Feeder capacity | 20-sheets |

## OTHER FEATURES

| | |
|---|---|
| - | Page Size Detection, Auto Resolution Setting, Background Smoothing, Character Emphasis, Color Dropout / Enhance Color, Deskew, Double-Feed Detection, Edge Emphasis, Image Rotation, Moiré Reduction, Pre-Scan, Prevent Bleed-Through/Remove Background, Skip Blank Page, Text Enhancement, Text Orientation Recognition, |

## BUNDLED SOFTWARE

| | |
|---|---|
| Windows | Built-in CaptureOnTouch Lite Scanning software (Windows 8.1 / 10 - 32bit/64bit) |
| Mac | Built-in CaptureOnTouch Lite Scanning software (macOS 10.12 / 10.13/ 10.14/ 10.15) |
| CONSUMABLES | Separation Pad, Feed Roller |
| ACCESSORIES | USB Cable |

**Disclaimer**

All data is based on Canon standard testing methods except where indicated.
Subject to change without notice.