

# PRO VIDEO RANGE

Showcase our fascinating world in brilliant quality. No matter what your subject is, elevate it and give it the platform it deserves to stand out with Canon's XF and XA ranges.



	XF705	XF605	XF405	XA55/XA50	XA45/XA40	XA15/XA11
	<b>4K ENG CAMCORDER</b>	<b>COMPACT 4K ENG CAMCORDER</b>	<b>COMPACT 4K ENG CAMCORDER</b>	<b>COMPACT LIGHTWEIGHT 4K CAMCORDER WITH DPAF</b>	<b>COMPACT 4K ENG CAMCORDER</b>	<b>COMPACT 4K ENG CAMCORDER</b>
	4K UHD 4:2:2 10-bit XF-HEVC Recording 12G-SDI Interface UHD H.265 IP Streaming capable*	4K UHD 4:2:2 10-bit XF-AVC Recording 12G-SDI Interface UHD H.265 IP Streaming capable*	High quality 4K lens with 15x zoom Dual Pixel CMOS AF Built in Wi-Fi for FTP Transfer	1.0-type 4K CMOS sensor High quality 4K 15x zoom lens XF-AVC and MP4 recording to SD cards	4K 20x optical zoom lens with wide angle Infrared recording capability Slow and Fast Motion recording	Advanced HD CMOS sensor Fast f/1.8-2.8 20x optical zoom lens AVCHD and MP4 recording to SD cards
<b>SENSOR</b>	1-INCH TYPE CMOS	1-INCH TYPE CMOS	1-INCH TYPE CMOS	1-INCH TYPE CMOS	1/2.3 INCH TYPE CMOS	1/2.84 INCH TYPE CMOS
<b>SENSOR SIZE (EFFECTIVE MP)</b>	8.29MP	8.29MP	8.29MP	8.29MP	8.29MP	2.91MP
<b>MAX RECORDING RESOLUTION</b>	3840 X 2160	3840 X 2160	3840 X 2160	3840 X 2160	3840 X 2160	1920 X 1080
<b>RECORDING FORMAT/DATA RATE (MAX)</b>	XF-HEVC (160Mbps) XF-AVC (45Mbps)	XF-AVC (410Mbps) HEVC (225Mbps) MP4 (150Mbps)	XF-AVC (160Mbps) MP4 (150Mbps)	XF-AVC (160Mbps) MP4 (150Mbps)	XF-AVC (160Mbps) MP4 (150Mbps)	AVCHD (28Mbps) MP4 (35Mbps)
<b>LENS FOCAL LENGTH RANGE/APERTURE</b>	25.5 to 382.5mm f/2.8	25.5 to 382.5mm f/2.8	25.5 to 382.5mm f/2.8	25.5 to 382.5mm f/2.8	29.3 - 601mm f/1.8	28.8 - 576mm f/1.8
<b>ZOOM RATIO</b>	x15 (4K UHD) x30 (FHD)	x15 (4K UHD) x30 (FHD)	x15 (4K UHD) x30 (FHD)	x15 (4K UHD) x30 (FHD)	x20 (Optical)	x20 (Optical)
<b>IMAGE STABILISATION</b>	YES	YES	YES	YES	YES	YES
<b>SAMPLING/BIT DEPTH</b>	4:2:2 10-bit (XF-HEVC) 4:2:0 8-bit (XF-AVC)	4:2:2 10-bit	4:2:0 8-bit	4:2:0 8-bit	4:2:0 8-bit	4:2:0 8-bit
<b>FRAME RATE (PAL)</b>	50.00P/25.00P	50.00P/50.00i/25.00P/24.00P	50.00P/25.00P	50.00P/50.00i/25.00P	50.00P/25.00P (50i HDMI External)	50.00P/25.00P
<b>SLOW/FAST MOTION</b>	YES	YES	YES	YES	YES	YES
<b>RECORDING MEDIA</b>	SD/SDHC/SDXC card (2 card slots)	SD/SDHC/SDXC card (2 card slots)	SD/SDHC/SDXC card (2 card slots)	SD/SDHC/SDXC card (2 card slots)	SD/SDHC/SDXC card (2 card slots)	SD/SDHC/SDXC card (2 card slots)
<b>AUDIO</b>	MPEG-4 AAC-LC (16-bit 2CH) LPCM (16-bit 4CH)	MPEG-2 AAC-LC (16-bit 2CH) LPCM (24/16-bit 4CH)	MPEG-4 AAC-LC (16-bit 2CH) LPCM (16-bit 4CH)	MPEG-4 AAC-LC (16-bit 2CH) LPCM (24-bit 4CH)	MPEG-4 AAC-LC (16-bit 2CH) LPCM (16-bit 4CH)	LPCM (16-bit 2/4CH)
<b>DUAL PIXEL XMOS AF</b>	YES	YES	YES	YES	NO	NO
<b>FOCUS ASSIST/POINTS</b>	YES	YES	YES	YES	NO	NO
<b>BUILT-IN ND FILTERS</b>	ND 1/4, ND 1/16, and ND 1/64	ND 1/4, ND 1/16, and ND 1/64	ND 1/4, ND 1/16, and ND 1/64	ND 1/4, ND 1/16, and ND 1/64	YES, GRADUATED TYPE	YES, GRADUATED TYPE
<b>SDI CONNECTORS</b>	YES 12G-SDI	YES 12G-SDI	YES 3G-SDI	YES 3G-SDI (XA55 ONLY)	YES, GRADUATED TYPE	YES 3G-SDI (XA15 ONLY)
<b>DIMENSIONS</b>	Approx.191 x 210 x 383mm (Including lens hood, not including grip belt and eye cup)	Approx. 168 x 173 x 333mm (body only (excluding grip belt) Approx. 200 x 219 x 385mm (Including lens hood, eyecup and mic holder unit)	Approx. 150 x 216 x 267mm (Including lens hood, BP-828, mic holder unit, and handle unit)	Approx. 140 x 216 x 265mm (Including lens hood, BP-820, mic holder, and handle unit)	Approx. 131 x 180 x 231mm (Including lens hood, BP-820, mic holder unit, and handle unit)	Approx. 131 x 180 x 231mm (Including lens hood, mic holder unit, and handle unit)
<b>WEIGHT</b>	Approx. 2660g	Approx. 2000g	Approx. 1670g	XA55: Approx. 970g XA50: Approx. 960g	Approx. 1120g	XA15: Approx. 1140g XA11: Approx. 1135g